

```

module: ietf-dots-telemetry
augment /ietf-signal:dots-signal/ietf-signal:message-type
  /ietf-signal:mitigation-scope/ietf-signal:scope:
    +--ro total-traffic* [unit] {dots-telemetry}?
    | +--ro unit unit
    | +--ro low-percentile-g? yang:gauge64
    | +--ro mid-percentile-g? yang:gauge64
    | +--ro high-percentile-g? yang:gauge64
    | +--ro peak-g? yang:gauge64
    +--rw total-attack-traffic* [unit] {dots-telemetry}?
    | +--rw unit unit
    | +--rw low-percentile-g? yang:gauge64
    | +--rw mid-percentile-g? yang:gauge64
    | +--rw high-percentile-g? yang:gauge64
    | +--rw peak-g? yang:gauge64
    +--ro total-attack-connection {dots-telemetry}?
    | +--ro low-percentile-c
    | | +--ro connection? yang:gauge64
    | | +--ro embryonic? yang:gauge64
    | | +--ro connection-ps? yang:gauge64
    | | +--ro request-ps? yang:gauge64
    | | +--ro partial-request-ps? yang:gauge64
    | +--ro mid-percentile-c
    | | +--ro connection? yang:gauge64
    | | +--ro embryonic? yang:gauge64
    | | +--ro connection-ps? yang:gauge64
    | | +--ro request-ps? yang:gauge64
    | | +--ro partial-request-ps? yang:gauge64
    | +--ro high-percentile-c
    | | +--ro connection? yang:gauge64
    | | +--ro embryonic? yang:gauge64
    | | +--ro connection-ps? yang:gauge64
    | | +--ro request-ps? yang:gauge64
    | | +--ro partial-request-ps? yang:gauge64
    | +--ro peak-c
    | | +--ro connection? yang:gauge64
    | | +--ro embryonic? yang:gauge64
    | | +--ro connection-ps? yang:gauge64
    | | +--ro request-ps? yang:gauge64
    | | +--ro partial-request-ps? yang:gauge64
    +--rw attack-detail* [vendor-id attack-id] {dots-telemetry}?
    | +--rw vendor-id uint32
    | +--rw attack-id uint32
    | +--rw attack-description? string
    | +--rw attack-severity? attack-severity
    | +--rw start-time? uint64
    | +--rw end-time? uint64
    | +--rw source-count
    | | +--rw low-percentile-g? yang:gauge64
    | | +--rw mid-percentile-g? yang:gauge64
    | | +--rw high-percentile-g? yang:gauge64
    | | +--rw peak-g? yang:gauge64
    +--rw top-talker
    | +--rw talker* [source-prefix]
    | | +--rw spoofed-status? boolean
    | | +--rw source-prefix inet:ip-prefix
    | | +--rw source-port-range* [lower-port]
    | | | +--rw lower-port inet:port-number
    | | | +--rw upper-port? inet:port-number
    | | +--rw source-icmp-type-range* [lower-type]
    | | | +--rw lower-type uint8
    | | | +--rw upper-type? uint8
    | | +--rw total-attack-traffic* [unit]
    | | | +--rw unit unit
    | | | +--rw low-percentile-g? yang:gauge64
    | | | +--rw mid-percentile-g? yang:gauge64
    | | | +--rw high-percentile-g? yang:gauge64
    | | | +--rw peak-g? yang:gauge64
    | +--rw total-attack-connection
    | | +--rw low-percentile-c
    | | | +--rw connection? yang:gauge64
    | | | +--rw embryonic? yang:gauge64
    | | | +--rw connection-ps? yang:gauge64
    | | | +--rw request-ps? yang:gauge64
    | | | +--rw partial-request-ps? yang:gauge64
    | | +--rw mid-percentile-c
    | | | +--rw connection? yang:gauge64
    | | | +--rw embryonic? yang:gauge64
    | | | +--rw connection-ps? yang:gauge64
    | | | +--rw request-ps? yang:gauge64
    | | | +--rw partial-request-ps? yang:gauge64
    | | +--rw high-percentile-c
    | | | +--rw connection? yang:gauge64
    | | | +--rw embryonic? yang:gauge64
    | | | +--rw connection-ps? yang:gauge64
    | | | +--rw request-ps? yang:gauge64
    | | | +--rw partial-request-ps? yang:gauge64
    | | +--rw peak-c
    | | | +--rw connection? yang:gauge64
    | | | +--rw embryonic? yang:gauge64
    | | | +--rw connection-ps? yang:gauge64
    | | | +--rw request-ps? yang:gauge64
    | | | +--rw partial-request-ps? yang:gauge64
    +--rw min-config-values
    | +--ro measurement-interval? interval
    | +--ro measurement-sample? sample
    | +--ro low-percentile? percentile
    | +--ro mid-percentile? percentile
    | +--ro high-percentile? percentile
    | +--ro server-originated-telemetry? boolean
    | +--ro telemetry-notify-interval? uint32
    +--ro max-config-values
    | +--ro measurement-interval? interval
    | +--ro measurement-sample? sample
    | +--ro low-percentile? percentile
    | +--ro mid-percentile? percentile
    | +--ro high-percentile? percentile
    | +--ro telemetry-notify-interval? uint32

```

```

module: ietf-dots-telemetry
augment-structure /ietf-signal:dots-signal/ietf-signal:message-type
  /ietf-signal:mitigation-scope/ietf-signal:scope:
    +-- (direction)? {dots-telemetry}?
    | +-- (server-to-client)
    | | +-- total-traffic* [unit]
    | | | +-- unit unit
    | | | +-- low-percentile-g? yang:gauge64
    | | | +-- mid-percentile-g? yang:gauge64
    | | | +-- high-percentile-g? yang:gauge64
    | | | +-- peak-g? yang:gauge64
    | | +-- total-attack-connection
    | | | +-- low-percentile-c
    | | | | +-- connection? yang:gauge64
    | | | | +-- embryonic? yang:gauge64
    | | | | +-- connection-ps? yang:gauge64
    | | | | +-- request-ps? yang:gauge64
    | | | | +-- partial-request-ps? yang:gauge64
    | | | +-- mid-percentile-c
    | | | | +-- connection? yang:gauge64
    | | | | +-- embryonic? yang:gauge64
    | | | | +-- connection-ps? yang:gauge64
    | | | | +-- request-ps? yang:gauge64
    | | | | +-- partial-request-ps? yang:gauge64
    | | | +-- high-percentile-c
    | | | | +-- connection? yang:gauge64
    | | | | +-- embryonic? yang:gauge64
    | | | | +-- connection-ps? yang:gauge64
    | | | | +-- request-ps? yang:gauge64
    | | | | +-- partial-request-ps? yang:gauge64
    | | | +-- peak-c
    | | | | +-- connection? yang:gauge64
    | | | | +-- embryonic? yang:gauge64
    | | | | +-- connection-ps? yang:gauge64
    | | | | +-- request-ps? yang:gauge64
    | | | | +-- partial-request-ps? yang:gauge64
    | | +-- total-attack-traffic* [unit] {dots-telemetry}?
    | | | +-- unit unit
    | | | +-- low-percentile-g? yang:gauge64
    | | | +-- mid-percentile-g? yang:gauge64
    | | | +-- high-percentile-g? yang:gauge64
    | | | +-- peak-g? yang:gauge64
    | | +-- attack-detail* [vendor-id attack-id] {dots-telemetry}?
    | | | +-- vendor-id uint32
    | | | +-- attack-id uint32
    | | | +-- attack-description? string
    | | | +-- attack-severity? attack-severity
    | | | +-- start-time? uint64
    | | | +-- end-time? uint64
    | | | +-- source-count
    | | | | +-- low-percentile-g? yang:gauge64
    | | | | +-- mid-percentile-g? yang:gauge64
    | | | | +-- high-percentile-g? yang:gauge64
    | | | | +-- peak-g? yang:gauge64
    | | +-- top-talker
    | | | +-- talker* [source-prefix]
    | | | | +-- spoofed-status? boolean
    | | | | +-- source-prefix inet:ip-prefix
    | | | | +-- source-port-range* [lower-port]
    | | | | | +-- lower-port inet:port-number
    | | | | | +-- upper-port? inet:port-number
    | | | | +-- source-icmp-type-range* [lower-type]
    | | | | | +-- lower-type uint8
    | | | | | +-- upper-type? uint8
    | | | | +-- total-attack-traffic* [unit]
    | | | | | +-- unit unit
    | | | | | +-- low-percentile-g? yang:gauge64
    | | | | | +-- mid-percentile-g? yang:gauge64
    | | | | | +-- high-percentile-g? yang:gauge64
    | | | | | +-- peak-g? yang:gauge64
    | | | +-- total-attack-connection
    | | | | +-- low-percentile-c
    | | | | | +-- connection? yang:gauge64
    | | | | | +-- embryonic? yang:gauge64
    | | | | | +-- connection-ps? yang:gauge64
    | | | | | +-- request-ps? yang:gauge64
    | | | | | +-- partial-request-ps? yang:gauge64
    | | | | +-- mid-percentile-c
    | | | | | +-- connection? yang:gauge64
    | | | | | +-- embryonic? yang:gauge64
    | | | | | +-- connection-ps? yang:gauge64
    | | | | | +-- request-ps? yang:gauge64
    | | | | | +-- partial-request-ps? yang:gauge64
    | | | | +-- high-percentile-c
    | | | | | +-- connection? yang:gauge64
    | | | | | +-- embryonic? yang:gauge64
    | | | | | +-- connection-ps? yang:gauge64
    | | | | | +-- request-ps? yang:gauge64
    | | | | | +-- partial-request-ps? yang:gauge64
    | | | | +-- peak-c
    | | | | | +-- connection? yang:gauge64
    | | | | | +-- embryonic? yang:gauge64
    | | | | | +-- connection-ps? yang:gauge64
    | | | | | +-- request-ps? yang:gauge64
    | | | | | +-- partial-request-ps? yang:gauge64
    | | +-- min-config-values
    | | | +-- measurement-interval? interval
    | | | +-- measurement-sample? sample
    | | | +-- low-percentile? percentile
    | | | +-- mid-percentile? percentile
    | | | +-- high-percentile? percentile
    | | | +-- server-originated-telemetry? boolean
    | | | +-- telemetry-notify-interval? uint32
    | | +-- max-config-values
    | | | +-- measurement-interval? interval
    | | | +-- measurement-sample? sample
    | | | +-- low-percentile? percentile
    | | | +-- mid-percentile? percentile
    | | | +-- high-percentile? percentile
    | | | +-- server-originated-telemetry? boolean
    | | | +-- telemetry-notify-interval? uint32

```

```

| +--ro supported-units
| | +--ro unit-config* [unit]
| | | +--ro unit unit-type
| | | +--ro unit-status boolean
| +--ro query-type* query-type
| +--rw telemetry* [cuid tsid]
| | +--rw cuid string
| | +--rw ccid? string
| | +--rw tsid uint32
| | +--rw (setup-type)?
|
| +--:(telemetry-config)
| | +--rw current-config
| | | +--rw measurement-interval? interval
| | | +--rw measurement-sample? sample
| | | +--rw low-percentile? percentile
| | | +--rw mid-percentile? percentile
| | | +--rw high-percentile? percentile
| | | +--rw unit-config* [unit]
| | | | +--rw unit unit-type
| | | | +--rw unit-status boolean
| | | +--rw server-originated-telemetry? boolean
| | | +--rw telemetry-notify-interval? uint32
| +--:(pipe)
| | +--rw total-pipe-capacity* [link-id unit]
| | | +--rw link-id nt:link-id
| | | +--rw capacity uint64
| | | +--rw unit unit
| +--:(baseline)
| | +--rw baseline* [id]
| | | +--rw id uint32
| | | +--rw target-prefix* inet:ip-prefix
| | | +--rw target-port-range* [lower-port]
| | | | +--rw lower-port inet:port-number
| | | | +--rw upper-port? inet:port-number
| | | +--rw target-protocol* uint8
| | | +--rw target-fqdn* inet:domain-name
| | | +--rw target-uri* inet:uri
| | | +--rw alias-name* string
| | | +--rw total-traffic-normal* [unit]
| | | | +--rw unit unit
| | | | +--rw low-percentile-g? yang:gauge64
| | | | +--rw mid-percentile-g? yang:gauge64
| | | | +--rw high-percentile-g? yang:gauge64
| | | | +--rw peak-g? yang:gauge64
| | | +--rw total-traffic-normal-per-protocol* [unit protocol]
| | | | +--rw protocol uint8
| | | | +--rw unit unit
| | | | +--rw low-percentile-g? yang:gauge64
| | | | +--rw mid-percentile-g? yang:gauge64
| | | | +--rw high-percentile-g? yang:gauge64
| | | | +--rw peak-g? yang:gauge64
| | | +--rw total-traffic-normal-per-port* [unit port]
| | | | +--rw port inet:port-number
| | | | +--rw unit unit
| | | | +--rw low-percentile-g? yang:gauge64
| | | | +--rw mid-percentile-g? yang:gauge64
| | | | +--rw high-percentile-g? yang:gauge64
| | | | +--rw peak-g? yang:gauge64
| | | +--rw total-connection-capacity* [protocol]
| | | | +--rw protocol uint8
| | | | +--rw connection? uint64
| | | | +--rw connection-client? uint64
| | | | +--rw embryonic? uint64
| | | | +--rw embryonic-client? uint64
| | | | +--rw connection-ps? uint64
| | | | +--rw connection-client-ps? uint64
| | | | +--rw request-ps? uint64
| | | | +--rw request-client-ps? uint64
| | | | +--rw partial-request-ps? uint64
| | | | +--rw partial-request-client-ps? uint64
| | | +--rw total-connection-capacity-per-port* [protocol port]
| | | | +--rw port inet:port-number
| | | | +--rw protocol uint8
| | | | +--rw connection? uint64
| | | | +--rw connection-client? uint64
| | | | +--rw embryonic? uint64
| | | | +--rw embryonic-client? uint64
| | | | +--rw connection-ps? uint64
| | | | +--rw connection-client-ps? uint64
| | | | +--rw request-ps? uint64
| | | | +--rw request-client-ps? uint64
| | | | +--rw partial-request-ps? uint64
| | | | +--rw partial-request-client-ps? uint64
| +--:(telemetry) {dots-telemetry}?
| | +--rw pre-or-ongoing-mitigation* [cuid tmid]
| | | +--rw cuid string
| | | +--rw ccid? string
| | | +--rw tmid uint32
| | | +--rw target
| | | | +--rw target-prefix* inet:ip-prefix
| | | | +--rw target-port-range* [lower-port]
| | | | | +--rw lower-port inet:port-number
| | | | | +--rw upper-port? inet:port-number
| | | | +--rw target-protocol* uint8
| | | | +--rw target-fqdn* inet:domain-name
| | | | +--rw target-uri* inet:uri
| | | | +--rw alias-name* string
| | | | +--rw mid-list* uint32
| | | +--rw total-traffic* [unit]
| | | | +--rw unit unit
| | | | +--rw low-percentile-g? yang:gauge64
| | | | +--rw mid-percentile-g? yang:gauge64
| | | | +--rw high-percentile-g? yang:gauge64
| | | | +--rw peak-g? yang:gauge64
| | | +--rw total-traffic-protocol* [unit protocol]
| | | | +--rw protocol uint8
| | | | +--rw unit unit
| | | | +--rw low-percentile-g? yang:gauge64
| | | | +--rw mid-percentile-g? yang:gauge64
| | | | +--rw high-percentile-g? yang:gauge64
| | | | +--rw peak-g? yang:gauge64
|
| | +-- high-percentile? percentile
| | +-- telemetry-notify-interval? uint32
| +-- supported-units
| | +-- unit-config* [unit]
| | | +-- unit unit-type
| | | +-- unit-status boolean
| | +-- query-type* query-type
| +-- telemetry* [cuid tsid]
| | +-- cuid string
| | +-- ccid? string
| | +-- tsid uint32
| | +-- (setup-type)?
| +--:(telemetry-config)
| | +-- current-config
| | | +-- measurement-interval? interval
| | | +-- measurement-sample? sample
| | | +-- low-percentile? percentile
| | | +-- mid-percentile? percentile
| | | +-- high-percentile? percentile
| | | +-- unit-config* [unit]
| | | | +-- unit unit-type
| | | | +-- unit-status boolean
| | | +-- server-originated-telemetry? boolean
| | | +-- telemetry-notify-interval? uint32
| +--:(pipe)
| | +-- total-pipe-capacity* [link-id unit]
| | | +-- link-id nt:link-id
| | | +-- capacity uint64
| | | +-- unit unit
| +--:(baseline)
| | +-- baseline* [id]
| | | +-- id uint32
| | | +-- target-prefix* inet:ip-prefix
| | | +-- target-port-range* [lower-port]
| | | | +-- lower-port inet:port-number
| | | | +-- upper-port? inet:port-number
| | | +-- target-protocol* uint8
| | | +-- target-fqdn* inet:domain-name
| | | +-- target-uri* inet:uri
| | | +-- alias-name* string
| | | +-- total-traffic-normal* [unit]
| | | | +-- unit unit
| | | | +-- low-percentile-g? yang:gauge64
| | | | +-- mid-percentile-g? yang:gauge64
| | | | +-- high-percentile-g? yang:gauge64
| | | | +-- peak-g? yang:gauge64
| | | +-- total-traffic-normal-per-protocol* [unit protocol]
| | | | +-- protocol uint8
| | | | +-- unit unit
| | | | +-- low-percentile-g? yang:gauge64
| | | | +-- mid-percentile-g? yang:gauge64
| | | | +-- high-percentile-g? yang:gauge64
| | | | +-- peak-g? yang:gauge64
| | | +-- total-traffic-normal-per-port* [unit port]
| | | | +-- port inet:port-number
| | | | +-- unit unit
| | | | +-- low-percentile-g? yang:gauge64
| | | | +-- mid-percentile-g? yang:gauge64
| | | | +-- high-percentile-g? yang:gauge64
| | | | +-- peak-g? yang:gauge64
| | | +-- total-connection-capacity* [protocol]
| | | | +-- protocol uint8
| | | | +-- connection? uint64
| | | | +-- connection-client? uint64
| | | | +-- embryonic? uint64
| | | | +-- embryonic-client? uint64
| | | | +-- connection-ps? uint64
| | | | +-- connection-client-ps? uint64
| | | | +-- request-ps? uint64
| | | | +-- request-client-ps? uint64
| | | | +-- partial-request-ps? uint64
| | | | +-- partial-request-client-ps? uint64
| | | +-- total-connection-capacity-per-port* [protocol port]
| | | | +-- port inet:port-number
| | | | +-- protocol uint8
| | | | +-- connection? uint64
| | | | +-- connection-client? uint64
| | | | +-- embryonic? uint64
| | | | +-- embryonic-client? uint64
| | | | +-- connection-ps? uint64
| | | | +-- connection-client-ps? uint64
| | | | +-- request-ps? uint64
| | | | +-- request-client-ps? uint64
| | | | +-- partial-request-ps? uint64
| | | | +-- partial-request-client-ps? uint64
| +--:(telemetry) {dots-telemetry}?
| | +-- pre-or-ongoing-mitigation* [cuid tmid]
| | | +-- cuid string
| | | +-- ccid? string
| | | +-- tmid uint32
| | | +-- target
| | | | +-- target-prefix* inet:ip-prefix
| | | | +-- target-port-range* [lower-port]
| | | | | +-- lower-port inet:port-number
| | | | | +-- upper-port? inet:port-number
| | | | +-- target-protocol* uint8
| | | | +-- target-fqdn* inet:domain-name
| | | | +-- target-uri* inet:uri
| | | | +-- alias-name* string
| | | | +-- mid-list* uint32
| | | +-- total-traffic* [unit]
| | | | +-- unit unit
| | | | +-- low-percentile-g? yang:gauge64
| | | | +-- mid-percentile-g? yang:gauge64
| | | | +-- high-percentile-g? yang:gauge64
| | | | +-- peak-g? yang:gauge64
| | | +-- total-traffic-protocol* [unit protocol]
| | | | +-- protocol uint8
| | | | +-- unit unit
| | | | +-- low-percentile-g? yang:gauge64
| | | | +-- mid-percentile-g? yang:gauge64
| | | | +-- high-percentile-g? yang:gauge64
| | | | +-- peak-g? yang:gauge64

```

```

-- total-traffic-port* [unit port]
+++ port inet:port-number
+++ unit unit
+++ low-percentile-g? yang:gauge64
+++ mid-percentile-g? yang:gauge64
+++ high-percentile-g? yang:gauge64
+++ peak-g? yang:gauge64
-- total-attack-traffic* [unit]
+++ protocol? uint8
+++ unit unit
+++ low-percentile-g? yang:gauge64
+++ mid-percentile-g? yang:gauge64
+++ high-percentile-g? yang:gauge64
+++ peak-g? yang:gauge64
-- total-attack-traffic-protocol* [unit protocol]
+++ protocol uint8
+++ unit unit
+++ low-percentile-g? yang:gauge64
+++ mid-percentile-g? yang:gauge64
+++ high-percentile-g? yang:gauge64
+++ peak-g? yang:gauge64
-- total-attack-traffic-port* [unit port]
+++ port inet:port-number
+++ unit unit
+++ low-percentile-g? yang:gauge64
+++ mid-percentile-g? yang:gauge64
+++ high-percentile-g? yang:gauge64
+++ peak-g? yang:gauge64
-- total-attack-connection
+++ low-percentile-1* [protocol]
| | ++ protocol uint8
| | ++ connection? yang:gauge64
| | ++ embryonic? yang:gauge64
| | ++ connection-ps? yang:gauge64
| | ++ request-ps? yang:gauge64
| | ++ partial-request-ps? yang:gauge64
+++ mid-percentile-1* [protocol]
| | ++ protocol uint8
| | ++ connection? yang:gauge64
| | ++ embryonic? yang:gauge64
| | ++ connection-ps? yang:gauge64
| | ++ request-ps? yang:gauge64
| | ++ partial-request-ps? yang:gauge64
+++ high-percentile-1* [protocol]
| | ++ protocol uint8
| | ++ connection? yang:gauge64
| | ++ embryonic? yang:gauge64
| | ++ connection-ps? yang:gauge64
| | ++ request-ps? yang:gauge64
| | ++ partial-request-ps? yang:gauge64
+++ peak-1* [protocol]
| | ++ protocol uint8
| | ++ connection? yang:gauge64
| | ++ embryonic? yang:gauge64
| | ++ connection-ps? yang:gauge64
| | ++ request-ps? yang:gauge64
| | ++ partial-request-ps? yang:gauge64
-- total-attack-connection-port
+++ low-percentile-1* [protocol port]
| | ++ port inet:port-number
| | ++ protocol uint8
| | ++ connection? yang:gauge64
| | ++ embryonic? yang:gauge64
| | ++ connection-ps? yang:gauge64
| | ++ request-ps? yang:gauge64
| | ++ partial-request-ps? yang:gauge64
+++ mid-percentile-1* [protocol port]
| | ++ port inet:port-number
| | ++ protocol uint8
| | ++ connection? yang:gauge64
| | ++ embryonic? yang:gauge64
| | ++ connection-ps? yang:gauge64
| | ++ request-ps? yang:gauge64
| | ++ partial-request-ps? yang:gauge64
+++ high-percentile-1* [protocol port]
| | ++ port inet:port-number
| | ++ protocol uint8
| | ++ connection? yang:gauge64
| | ++ embryonic? yang:gauge64
| | ++ connection-ps? yang:gauge64
| | ++ request-ps? yang:gauge64
| | ++ partial-request-ps? yang:gauge64
+++ peak-1* [protocol port]
| | ++ port inet:port-number
| | ++ protocol uint8
| | ++ connection? yang:gauge64
| | ++ embryonic? yang:gauge64
| | ++ connection-ps? yang:gauge64
| | ++ request-ps? yang:gauge64
| | ++ partial-request-ps? yang:gauge64
-- attack-detail* [vendor-id attack-id]
+++ vendor-id uint32
+++ attack-id uint32
+++ attack-description? string
+++ attack-severity? attack-severity
+++ start-time? uint64
+++ end-time? uint64
+++ source-count
| ++ low-percentile-g? yang:gauge64
| ++ mid-percentile-g? yang:gauge64
| ++ high-percentile-g? yang:gauge64
| ++ peak-g? yang:gauge64
+++ top-talker
+++ talker* [source-prefix]
| ++ spoofed-status? boolean
| ++ source-prefix inet:ip-prefix
| ++ source-port-range* [lower-port]
| | ++ lower-port inet:port-number
| | ++ upper-port? inet:port-number
| ++ source-icmp-type-range* [lower-type]
| | ++ lower-type uint8
| | ++ upper-type? uint8
| ++ total-attack-traffic* [unit]

```

```
| +-rw unit                                unit
| +-rw low-percentile-g?                  yang:gauge64
| +-rw mid-percentile-g?                  yang:gauge64
| +-rw high-percentile-g?                 yang:gauge64
| +-rw peak-g?                           yang:gauge64
+--rw total-attack-connection
+--rw low-percentile-1* [protocol]
| +-rw protocol                          uint8
| +-rw connection?                       yang:gauge64
| +-rw embryonic?                        yang:gauge64
| +-rw connection-ps?                    yang:gauge64
| +-rw request-ps?                       yang:gauge64
| +-rw partial-request-ps?               yang:gauge64
+--rw mid-percentile-1* [protocol]
| +-rw protocol                          uint8
| +-rw connection?                       yang:gauge64
| +-rw embryonic?                        yang:gauge64
| +-rw connection-ps?                    yang:gauge64
| +-rw request-ps?                       yang:gauge64
| +-rw partial-request-ps?               yang:gauge64
+--rw high-percentile-1* [protocol]
| +-rw protocol                          uint8
| +-rw connection?                       yang:gauge64
| +-rw embryonic?                        yang:gauge64
| +-rw connection-ps?                    yang:gauge64
| +-rw request-ps?                       yang:gauge64
| +-rw partial-request-ps?               yang:gauge64
+--rw peak-1* [protocol]
+--rw protocol                          uint8
+--rw connection?                       yang:gauge64
+--rw embryonic?                        yang:gauge64
+--rw connection-ps?                    yang:gauge64
+--rw request-ps?                       yang:gauge64
+--rw partial-request-ps?                yang:gauge64
```

```
| +- unit                                unit
| +- low-percentile-g?                  yang:gauge64
| +- mid-percentile-g?                  yang:gauge64
| +- high-percentile-g?                 yang:gauge64
| +- peak-g?                           yang:gauge64
+-- total-attack-connection
+-- low-percentile-1* [protocol]
| +- protocol                          uint8
| +- connection?                       yang:gauge64
| +- embryonic?                        yang:gauge64
| +- connection-ps?                    yang:gauge64
| +- request-ps?                       yang:gauge64
| +- partial-request-ps?               yang:gauge64
+-- mid-percentile-1* [protocol]
| +- protocol                          uint8
| +- connection?                       yang:gauge64
| +- embryonic?                        yang:gauge64
| +- connection-ps?                    yang:gauge64
| +- request-ps?                       yang:gauge64
| +- partial-request-ps?               yang:gauge64
+-- high-percentile-1* [protocol]
| +- protocol                          uint8
| +- connection?                       yang:gauge64
| +- embryonic?                        yang:gauge64
| +- connection-ps?                    yang:gauge64
| +- request-ps?                       yang:gauge64
| +- partial-request-ps?               yang:gauge64
+-- peak-1* [protocol]
+-- protocol                          uint8
+-- connection?                       yang:gauge64
+-- embryonic?                        yang:gauge64
+-- connection-ps?                    yang:gauge64
+-- request-ps?                       yang:gauge64
+-- partial-request-ps?                yang:gauge64
```

End of changes. 6 change blocks.

188 lines changed or deleted

192 lines changed or added

This html diff was produced by [rfcdiff 1.47](http://tools.ietf.org/tools/rfcdiff/). The latest version is available from <http://tools.ietf.org/tools/rfcdiff/>