DOTS   T. Reddy, Ed.
Internet-Draft   McAfee
Intended status: Standards Track   M. Boucadair, Ed.
Expires: ~~April 20,~~ **May 15,** 2020   Orange
                                                             P. Patil
                                                                 Cisco
                                                          A. Mortensen
                                                  Arbor Networks, Inc.
                                                             N. Teague
                                            Iron Mountain Data Centers
                                                      ~~October 18,~~
                                                   November 12, 2019

       Distributed Denial-of-Service Open Threat Signaling (DOTS) Signal
                           Channel Specification
                    draft-ietf-dots-signal-channel-38

Abstract

   This document specifies the DOTS signal channel, a protocol for
   signaling the need for protection against Distributed Denial-of-
   Service (DDoS) attacks to a server capable of enabling network
   traffic mitigation on behalf of the requesting client.

   A companion document defines the DOTS data channel, a separate
   reliable communication layer for DOTS management and configuration
   purposes.

Editorial Note (To be removed by RFC Editor)

   Please update these statements within the document with the RFC
   number to be assigned to this document:

   o "This version of this YANG module is part of RFC XXXX;"

   o "RFC XXXX: Distributed Denial-of-Service Open Threat Signaling
      (DOTS) Signal Channel Specification";

   o "| [RFCXXXX] |"

   o reference: RFC XXXX

   Please update this statement with the RFC number to be assigned to
   the following documents:

   o "RFC YYYY: Distributed Denial-of-Service Open Threat Signaling
      (DOTS) Data Channel Specification (used to be I-D.ietf-dots-data-
      channel)

   Please update TBD/TBD1/TBD2 statements with the assignments made by
   IANA to DOTS Signal Channel Protocol.

   Also, please update the "revision" date of the YANG modules.

Status of This Memo

   This Internet-Draft is submitted in full conformance with the
   provisions of BCP 78 and BCP 79.

   Internet-Drafts are working documents of the Internet Engineering
   Task Force (IETF). Note that other groups may also distribute
   working documents as Internet-Drafts. The list of current Internet-
   Drafts is at https://datatracker.ietf.org/drafts/current/.

   Internet-Drafts are draft documents valid for a maximum of six months
   and may be updated, replaced, or obsoleted by other documents at any
   time. It is inappropriate to use Internet-Drafts as reference
   material or to cite them other than as "work in progress."

   This Internet-Draft will expire on ~~April 20,~~ **May 15,** 2020.

Table of Contents

1. Introduction

    A distributed denial-of-service (DDoS) attack is a distributed
    attempt to make machines or network resources unavailable to their
    intended users. In most cases, sufficient scale for an effective
    attack can be achieved by compromising enough end-hosts and using
    those infected hosts to perpetrate and amplify the attack. The
    victim in this attack can be an application server, a host, a router,
    a firewall, or an entire network.

    Network applications have finite resources like CPU cycles, the
    number of processes or threads they can create and use, the maximum
    number of simultaneous connections they can handle, the limited
    resources of the control plane, etc. When processing network
    traffic, such applications are supposed to use these resources to
    provide the intended functionality in the most efficient manner.
    However, a DDoS attacker may be able to prevent an application from
    performing its intended task by making the application exhaust its
    finite resources.

    A TCP DDoS SYN-flood [RFC4987], for example, is a memory-exhausting
    attack while an ACK-flood is a CPU-exhausting attack. Attacks on the
    link are carried out by sending enough traffic so that the link
    becomes congested, thereby likely causing packet loss for legitimate
    traffic. Stateful firewalls can also be attacked by sending traffic
    that causes the firewall to maintain an excessive number of states
    that may jeopardize the firewall's operation overall, besides likely
    performance impacts. The firewall then runs out of memory, and can
    no longer instantiate the states required to process legitimate
    flows. Other possible DDoS attacks are discussed in [RFC4732].

    In many cases, it may not be possible for network administrators to
    determine the cause(s) of an attack. They may instead just realize
    that certain resources seem to be under attack. This document
    defines a lightweight protocol that allows a DOTS client to request
    mitigation from one or more DOTS servers for protection against
    detected, suspected, or anticipated attacks. This protocol enables
    cooperation between DOTS agents to permit a highly-automated network
    defense that is robust, reliable, and secure. Note that "secure"
    means the support of the features defined in Section 2.4 of
    [RFC8612].

    An example of a network diagram that illustrates a deployment of DOTS
    agents is shown in Figure 1. In this example, a DOTS server is

operating on the access network. A DOTS client is located on the LAN
(Local Area Network), while a DOTS gateway is embedded in the CPE
(Customer Premises Equipment).

```
   Network
   Resource          CPE router          Access network    _____
 +-----------+   +-------------+     +-------------+       /          \
 |           |___|             |_____|             |_____|  Internet  |
 |DOTS client|   | DOTS gateway|     | DOTS server |      |            |
 |           |   |             |     |             |      |            |
 +-----------+   +-------------+     +-------------+       _____/
```

             Figure 1: Sample DOTS Deployment (1)

DOTS servers can also be reachable over the Internet, as depicted in
Figure 2.

```
   Network                                         DDoS mitigation
   Resource          CPE router      _____       service
 +-----------+   +-------------+    /          \    +-------------+
 |           |___|             |___|            |___|             |
 |DOTS client|   |DOTS gateway |   | Internet   |   | DOTS server |
 |           |   |             |   |            |   |             |
 +-----------+   +-------------+    _____/    +-------------+
```

             Figure 2: Sample DOTS Deployment (2)

In typical deployments, the DOTS client belongs to a different
administrative domain than the DOTS server. For example, the DOTS
client is embedded in a firewall protecting services owned and
operated by a customer, while the DOTS server is owned and operated
by a different administrative entity (service provider, typically)
providing DDoS mitigation services. The latter might or might not
provide connectivity services to the network hosting the DOTS client.

The DOTS server may (not) be co-located with the DOTS mitigator. In
typical deployments, the DOTS server belongs to the same
administrative domain as the mitigator. The DOTS client can
communicate directly with a DOTS server or indirectly via a DOTS
gateway.

The document adheres to the DOTS architecture
[I-D.ietf-dots-architecture]. The requirements for DOTS signal
channel protocol are documented in [RFC8612]. This document
satisfies all the use cases discussed in [I-D.ietf-dots-use-cases].

This document focuses on the DOTS signal channel. This is a
companion document of the DOTS data channel specification
[I-D.ietf-dots-data-channel] that defines a configuration and a bulk
data exchange mechanism supporting the DOTS signal channel.

2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT",
"SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and
"OPTIONAL" in this document are to be interpreted as described in BCP
14 [RFC2119][RFC8174] when, and only when, they appear in all
capitals, as shown here.

(D)TLS is used for statements that apply to both Transport Layer
Security [RFC5246][RFC8446] and Datagram Transport Layer Security
[RFC6347]. Specific terms are used for any statement that applies to
either protocol alone.

The reader should be familiar with the terms defined in [RFC8612].

The meaning of the symbols in YANG tree diagrams is defined in
[RFC8340].

3. Design Overview

The DOTS signal channel is built on top of the Constrained
Application Protocol (CoAP) [RFC7252], a lightweight protocol
originally designed for constrained devices and networks. The many
features of CoAP (expectation of packet loss, support for
asynchronous Non-confirmable messaging, congestion control, small
message overhead limiting the need for fragmentation, use of minimal
resources, and support for (D)TLS) makes it a good candidate to build
the DOTS signaling mechanism from.

**DOTS clients and servers behave as CoAP endpoints. By default, a
DOTS client (or server) behaves as a CoAP client (or server).
Nevertheless, a DOTS client (or server) behaves as a CoAP server (or
client) for specific operations such as DOTS heartbeat operations
(Section 4.7).**

The DOTS signal channel is layered on existing standards (Figure 3).

```
            +---------------------+
            | DOTS Signal Channel |
            +---------------------+
            |        CoAP         |
            +----------+----------+
            |   TLS    |   DTLS   |
            +----------+----------+
```

```
                     |   TCP    |   UDP    |
                     +----------+----------+
                     |          IP         |
                     +--------------------+
```

    Figure 3: Abstract Layering of DOTS Signal Channel over CoAP over
                                (D)TLS

   In some cases, a DOTS client and server may have mutual agreement to
   use a specific port number, such as by explicit configuration or
   dynamic discovery [I-D.ietf-dots-server-discovery]. Absent such
   mutual agreement, the DOTS signal channel MUST run over port number
   TBD as defined in Section 9.1, for both UDP and TCP. In order to use
   a distinct port number (as opposed to TBD), DOTS clients and servers
   SHOULD support a configurable parameter to supply the port number to
   use.

      Note: The rationale for not using the default port number 5684
      ((D)TLS CoAP) is to avoid the discovery of services and resources
      discussed in [RFC7252] and allow for differentiated behaviors in
      environments where both a DOTS gateway and an IoT gateway (e.g.,
      Figure 3 of [RFC7452]) are co-located.

      Particularly, the use of a default port number is meant to
      simplify DOTS deployment in scenarios where no explicit IP address
      configuration is required. For example, the use of the default
      router as DOTS server aims to ease DOTS deployment within LANs (in
      which, CPEs embed a DOTS gateway as illustrated in Figures 1 and
      2) without requiring a sophisticated discovery method and
      configuration tasks within the LAN. The use of anycast is meant
      to simplify DOTS client configuration, including service
      discovery. In such anycast-based scenario, a DOTS client
      initiating a DOTS session to the DOTS server anycast address may,
      for example, be (1) redirected to the DOTS server unicast address
      to be used by the DOTS client following the procedure discussed in
      Section 4.6 or (2) relayed to a unicast DOTS server.

   The signal channel uses the "coaps" URI scheme defined in Section 6
   of [RFC7252] and the "coaps+tcp" URI scheme defined in Section 8.2 of
   [RFC8323] to identify DOTS server resources accessible using CoAP
   over UDP secured with DTLS and CoAP over TCP secured with TLS,
   respectively.

   The DOTS signal channel can be established between two DOTS agents
   prior or during an attack. The DOTS signal channel is initiated by
   the DOTS client. The DOTS client can then negotiate, configure, and
   retrieve the DOTS signal channel session behavior with its DOTS peer
   (Section 4.5). Once the signal channel is established, the DOTS
   agents may periodically send heartbeats to keep the channel active
   (Section 4.7). At any time, the DOTS client may send a mitigation
   request message (Section 4.4) to a DOTS server over the active signal
   channel. While mitigation is active (because of the higher
   likelihood of packet loss during a DDoS attack), the DOTS server
   periodically sends status messages to the client, including basic
   mitigation feedback details. Mitigation remains active until the
   DOTS client explicitly terminates mitigation, or the mitigation
   lifetime expires. Also, the DOTS server may rely on the signal
   channel session loss to trigger mitigation for pre-configured
   mitigation requests (if any).

   DOTS signaling can happen with DTLS over UDP and TLS over TCP.
   Likewise, DOTS requests may be sent using IPv4 or IPv6 transfer
   capabilities. A Happy Eyeballs procedure for DOTS signal channel is
   specified in Section 4.3.

   A DOTS client is entitled to access only to resources it creates. In
   particular, a DOTS client can not retrieve data related to mitigation
   requests created by other DOTS clients of the same DOTS client
   domain.

   Messages exchanged between DOTS agents are serialized using Concise
   Binary Object Representation (CBOR) [RFC7049], a binary encoding
   scheme designed for small code and message size. CBOR-encoded
   payloads are used to carry signal channel-specific payload messages
   which convey request parameters and response information such as
   errors. In order to allow reusing data models across protocols,
   [RFC7951] specifies the JavaScript Object Notation (JSON) encoding of
   YANG-modeled data. A similar effort for CBOR is defined in
   [I-D.ietf-core-yang-cbor].

   DOTS agents determine that a CBOR data structure is a DOTS signal
   channel object from the application context, such as from the port
   number assigned to the DOTS signal channel. The other method DOTS
   agents use to indicate that a CBOR data structure is a DOTS signal
   channel object is the use of the "application/dots+cbor" content type
   (Section 9.3).

   This document specifies a YANG module for representing DOTS
   mitigation scopes, DOTS signal channel session configuration data,
   and DOTS redirected signaling (Section 5). All parameters in the
   payload of the DOTS signal channel are mapped to CBOR types as
   specified in Table 4 (Section 6).

   In order to prevent fragmentation, DOTS agents must follow the
   recommendations documented in Section 4.6 of [RFC7252]. Refer to

Section 7.3 for more details.

DOTS agents MUST support GET, PUT, and DELETE CoAP methods. The
payload included in CoAP responses with 2.xx Response Codes MUST be
of content type "application/dots+cbor". CoAP responses with 4.xx
and 5.xx error Response Codes MUST include a diagnostic payload
(Section 5.5.2 of [RFC7252]). The Diagnostic Payload may contain
additional information to aid troubleshooting.

In deployments where multiple DOTS clients are enabled in a network
(owned and operated by the same entity), the DOTS server may detect
conflicting mitigation requests from these clients. This document
does not aim to specify a comprehensive list of conditions under
which a DOTS server will characterize two mitigation requests from
distinct DOTS clients as conflicting, nor recommend a DOTS server
behavior for processing conflicting mitigation requests. Those
considerations are implementation- and deployment-specific.
Nevertheless, the document specifies the mechanisms to notify DOTS
clients when conflicts occur, including the conflict cause
(Section 4.4).

In deployments where one or more translators (e.g., Traditional NAT
[RFC3022], CGN [RFC6888], NAT64 [RFC6146], NPTv6 [RFC6296]) are
enabled between the client's network and the DOTS server, DOTS signal
channel messages forwarded to a DOTS server MUST NOT include internal
IP addresses/prefixes and/or port numbers; external addresses/
prefixes and/or port numbers as assigned by the translator MUST be
used instead. This document does not make any recommendation about
possible translator discovery mechanisms. The following are some
(non-exhaustive) deployment examples that may be considered:

o Port Control Protocol (PCP) [RFC6887] or Session Traversal
   Utilities for NAT (STUN) [RFC5389] may be used to retrieve the
   external addresses/prefixes and/or port numbers. Information
   retrieved by means of PCP or STUN will be used to feed the DOTS
   signal channel messages that will be sent to a DOTS server.

o A DOTS gateway may be co-located with the translator. The DOTS
   gateway will need to update the DOTS messages, based upon the
   local translator's binding table.

4. DOTS Signal Channel: Messages & Behaviors

4.1. DOTS Server(s) Discovery

   This document assumes that DOTS clients are provisioned with the
   reachability information of their DOTS server(s) using any of a
   variety of means (e.g., local configuration, or dynamic means such as
   DHCP [I-D.ietf-dots-server-discovery]). The description of such
   means is out of scope of this document.

   Likewise, it is out of scope of this document to specify the behavior
   to be followed by a DOTS client to send DOTS requests when multiple
   DOTS servers are provisioned (e.g., contact all DOTS servers, select
   one DOTS server among the list). Such behavior is specified in other
   documents (e.g., [I-D.ietf-dots-multihoming]).

4.2. CoAP URIs

   The DOTS server MUST support the use of the path-prefix of "/.well-
   known/" as defined in [RFC5785] and the registered name of "dots".
   Each DOTS operation is indicated by a path-suffix that indicates the
   intended operation. The operation path (Table 1) is appended to the
   path-prefix to form the URI used with a CoAP request to perform the
   desired DOTS operation.

```
      +----------------------+---------------+-------------+
      | Operation            | Operation Path | Details     |
      +----------------------+---------------+-------------+
      | Mitigation           | /mitigate     | Section 4.4 |
      +----------------------+---------------+-------------+
      | Session configuration | /config      | Section 4.5 |
      +----------------------+---------------+-------------+
      | Heartbeat            | /hb           | Section 4.7 |
      +----------------------+---------------+-------------+
```

              Table 1: Operations and their Corresponding URIs

4.3. Happy Eyeballs for DOTS Signal Channel

   [RFC8612] mentions that DOTS agents will have to support both
   connectionless and connection-oriented protocols. As such, the DOTS
   signal channel is designed to operate with DTLS over UDP and TLS over
   TCP. Further, a DOTS client may acquire a list of IPv4 and IPv6
   addresses (Section 4.1), each of which can be used to contact the
   DOTS server using UDP and TCP. If no list of IPv4 and IPv6 addresses
   to contact the DOTS server is configured (or discovered), the DOTS
   client adds the IPv4/IPv6 addresses of its default router to the
   candidate list to contact the DOTS server.

   The following specifies the procedure to follow to select the address
   family and the transport protocol for sending DOTS signal channel
   messages.

   Such procedure is needed to avoid experiencing long connection

delays. For example, if an IPv4 path to reach a DOTS server is
functional, but the DOTS server's IPv6 path is non-functional, a
dual-stack DOTS client may experience a significant connection delay
compared to an IPv4-only DOTS client, in the same network conditions.
The other problem is that if a middlebox between the DOTS client and
DOTS server is configured to block UDP traffic, the DOTS client will
fail to establish a DTLS association with the DOTS server and, as a
consequence, will have to fall back to TLS over TCP, thereby
incurring significant connection delays.

To overcome these connection setup problems, the DOTS client attempts
to connect to its DOTS server(s) using both IPv6 and IPv4, and tries
both DTLS over UDP and TLS over TCP following a DOTS Happy Eyeballs
approach. To some extent, this approach is similar to the Happy
Eyeballs mechanism defined in [RFC8305]. The connection attempts are
performed by the DOTS client when it initializes, or in general when
it has to select an address family and transport to contact its DOTS
server. The results of the Happy Eyeballs procedure are used by the
DOTS client for sending its subsequent messages to the DOTS server.
The difference in behavior with respect to the Happy Eyeballs
mechanism [RFC8305] are listed below:

o The order of preference of the DOTS signal channel address family
   and transport protocol (most preferred first) is: UDP over IPv6,
   UDP over IPv4, TCP over IPv6, and finally TCP over IPv4. This
   order adheres to the address preference order specified in
   [RFC6724] and the DOTS signal channel preference which privileges
   the use of UDP over TCP (to avoid TCP's head of line blocking).

o The DOTS client after successfully establishing a connection MUST
   cache information regarding the outcome of each connection attempt
   for a specific time period, and it uses that information to avoid
   thrashing the network with subsequent attempts. The cached
   information is flushed when its age exceeds a specific time period
   on the order of few minutes (e.g., 10 min). Typically, if the
   DOTS client has to re-establish the connection with the same DOTS
   server within few seconds after the Happy Eyeballs mechanism is
   completed, caching avoids trashing the network especially in the
   presence of DDoS attack traffic.

o If DOTS signal channel session is established with TLS (but DTLS
   failed), the DOTS client periodically repeats the mechanism to
   discover whether DOTS signal channel messages with DTLS over UDP
   becomes available from the DOTS server, so the DOTS client can
   migrate the DOTS signal channel from TCP to UDP. Such probing
   SHOULD NOT be done more frequently than every 24 hours and MUST
   NOT be done more frequently than every 5 minutes.

When connection attempts are made during an attack, the DOTS client
SHOULD use a "Connection Attempt Delay" [RFC8305] set to 100 ms.

In reference to Figure 4, the DOTS client proceeds with the
connection attempts following the rules in [RFC8305]. In this
example, it is assumed that the IPv6 path is broken and UDP traffic
is dropped by a middlebox but has little impact to the DOTS client
because there is no long delay before using IPv4 and TCP.

```
   +-----------+                               +-----------+
   |DOTS client|                               |DOTS server|
   +-----------+                               +-----------+
        |                                            |
   T0 |--DTLS ClientHello, IPv6 ---->X               |
   T1 |--DTLS ClientHello, IPv4 ---->X               |
   T2 |--TCP SYN, IPv6-------------->X               |
   T3 |--TCP SYN, IPv4-------------------------------------->|
      |<-TCP SYNACK-----------------------------------------|
      |--TCP ACK-------------------------------------------->|
      |<------------Establish TLS Session------------------->|
      |---------------DOTS signal-------------------------->|
        |                                            |
```

 Note:
   * Retransmission messages are not shown.
   * T1-T0=T2-T1=T3-T2= Connection Attempt Delay.

            Figure 4: DOTS Happy Eyeballs (Sample Flow)

A single DOTS signal channel between DOTS agents can be used to
exchange multiple DOTS signal messages. To reduce DOTS client and
DOTS server workload, DOTS clients SHOULD re-use the (D)TLS session.

4.4. DOTS Mitigation Methods

The following methods are used by a DOTS client to request, withdraw,
or retrieve the status of mitigation requests:

PUT: DOTS clients use the PUT method to request mitigation from a
        DOTS server (Section 4.4.1). During active mitigation, DOTS
        clients may use PUT requests to carry mitigation efficacy
        updates to the DOTS server (Section 4.4.3).

GET: DOTS clients may use the GET method to subscribe to DOTS
        server status messages, or to retrieve the list of its
        mitigations maintained by a DOTS server (Section 4.4.2).

DELETE: DOTS clients use the DELETE method to withdraw a request for
        mitigation from a DOTS server (Section 4.4.4).

Mitigation request and response messages are marked as Non-
confirmable messages (Section 2.2 of [RFC7252]).

DOTS agents MUST NOT send more than one UDP datagram per round-trip
time (RTT) to the peer DOTS agent on average following the data
transmission guidelines discussed in Section 3.1.3 of [RFC8085].

Requests marked by the DOTS client as Non-confirmable messages are
sent at regular intervals until a response is received from the DOTS
server. If the DOTS client cannot maintain an RTT estimate, it MUST
NOT send more than one Non-confirmable request every 3 seconds, and
SHOULD use an even less aggressive rate whenever possible (case 2 in
Section 3.1.3 of [RFC8085]).

JSON encoding of YANG modelled data [RFC7951] is used to illustrate
the various methods defined in the following sub-sections. Also, the
examples use the Labels defined in Sections 9.6.2, 9.6.3, 9.6.4, and
9.6.5.

4.4.1. Request Mitigation

When a DOTS client requires mitigation for some reason, the DOTS
client uses the CoAP PUT method to send a mitigation request to its
DOTS server(s) (Figures 5 and 6).

If a DOTS client is entitled to solicit the DOTS service, the DOTS
server enables mitigation on behalf of the DOTS client by
communicating the DOTS client's request to a mitigator (which may be
co-located with the DOTS server) and relaying the feedback of the
thus-selected mitigator to the requesting DOTS client.

```
Header: PUT (Code=0.03)
Uri-Path: ".well-known"
Uri-Path: "dots"
Uri-Path: "mitigate"
Uri-Path: "cuid=dz6pHjaADkaFTbjr0JGBpw"
Uri-Path: "mid=123"
Content-Format: "application/dots+cbor"

{
  ...
}
```

        Figure 5: PUT to Convey DOTS Mitigation Requests

The order of the Uri-Path options is important as it defines the CoAP
resource. In particular, 'mid' MUST follow 'cuid'.

The additional Uri-Path parameters to those defined in Section 4.2
are as follows:

cuid: Stands for Client Unique Identifier. A globally unique
      identifier that is meant to prevent collisions among DOTS
      clients, especially those from the same domain. It MUST be
      generated by DOTS clients.

      For the reasons discussed in Appendix A, implementations SHOULD
      set 'cuid' using the following procedure: first, the
      Distinguished Encoding Rules (DER)-encoded Abstract Syntax
      Notation One (ASN.1) representation of the Subject Public Key
      Info (SPKI) of the DOTS client X.509 certificate [RFC5280], the
      DOTS client raw public key [RFC7250], the "Pre-Shared Key (PSK)
      identity" used by the DOTS client in the TLS 1.2
      ClientKeyExchange message, or the "identity" used by the DOTS
      client in the "pre_shared_key" TLS 1.3 extension is input to
      the SHA-256 [RFC6234] cryptographic hash. Then, the output of
      the cryptographic hash algorithm is truncated to 16 bytes;
      truncation is done by stripping off the final 16 bytes. The
      truncated output is base64url encoded (Section 5 of [RFC4648])
      with the trailing "=" removed from the encoding, and the
      resulting value used as the 'cuid'.

      The 'cuid' is intended to be stable when communicating with a
      given DOTS server, i.e., the 'cuid' used by a DOTS client
      SHOULD NOT change over time. Distinct 'cuid' values MAY be
      used by a single DOTS client per DOTS server.

      If a DOTS client has to change its 'cuid' for some reason, it
      MUST NOT do so when mitigations are still active for the old
      'cuid'. The 'cuid' SHOULD be 22 characters to avoid DOTS
      signal message fragmentation over UDP. Furthermore, if that
      DOTS client created aliases and filtering entries at the DOTS
      server by means of the DOTS data channel, it MUST delete all
      the entries bound to the old 'cuid' and re-install them using
      the new 'cuid'.

      DOTS servers MUST return 4.09 (Conflict) error code to a DOTS
      peer to notify that the 'cuid' is already in-use by another
      DOTS client. Upon receipt of that error code, a new 'cuid'
      MUST be generated by the DOTS peer (e.g., using [RFC4122]).

      Client-domain DOTS gateways MUST handle 'cuid' collision

directly and it is RECOMMENDED that 'cuid' collision is handled
directly by server-domain DOTS gateways.

DOTS gateways MAY rewrite the 'cuid' used by peer DOTS clients.
Triggers for such rewriting are out of scope.

This is a mandatory Uri-Path parameter.

mid: Identifier for the mitigation request represented with an
    integer. This identifier MUST be unique for each mitigation
    request bound to the DOTS client, i.e., the 'mid' parameter
    value in the mitigation request needs to be unique (per 'cuid'
    and DOTS server) relative to the 'mid' parameter values of
    active mitigation requests conveyed from the DOTS client to the
    DOTS server.

    In order to handle out-of-order delivery of mitigation
    requests, 'mid' values MUST increase monotonically.

    If the 'mid' value has reached 3/4 of $(2**32 - 1)$ (i.e.,
    3221225471) and no attack is detected, the DOTS client MUST
    reset 'mid' to 0 to handle 'mid' rollover. If the DOTS client
    maintains mitigation requests with pre-configured scopes, it
    MUST re-create them with the 'mid' restarting at 0.

    This identifier MUST be generated by the DOTS client.

    This is a mandatory Uri-Path parameter.

'cuid' and 'mid' MUST NOT appear in the PUT request message body
(Figure 6). The schema in Figure 6 uses the types defined in
Section 6. Note that this figure (and other similar figures
depicting a schema) are non-normative sketches of the structure of
the message.

```
   {
     "ietf-dots-signal-channel:mitigation-scope": {
       "scope": [
         {
           "target-prefix": [
             "string"
           ],
           "target-port-range": [
             {
               "lower-port": number,
               "upper-port": number
             }
           ],
           "target-protocol": [
             number
           ],
           "target-fqdn": [
             "string"
           ],
           "target-uri": [
             "string"
           ],
           "alias-name": [
             "string"
           ],
           "lifetime": number,
           "trigger-mitigation": true|false
         }
       ]
     }
   }
```

    Figure 6: PUT to Convey DOTS Mitigation Requests (Message Body
                              Schema)

The parameters in the CBOR body (Figure 6) of the PUT request are
described below:

target-prefix: A list of prefixes identifying resources under
    attack. Prefixes are represented using Classless Inter-Domain
    Routing (CIDR) notation [RFC4632].
    As a reminder, the prefix length must be less than or equal to 32
    (or 128) for IPv4 (or IPv6).

    The prefix list MUST NOT include broadcast, loopback, or multicast
    addresses. These addresses are considered as invalid values. In
    addition, the DOTS server MUST validate that target prefixes are
    within the scope of the DOTS client domain. Other validation
    checks may be supported by DOTS servers.

    This is an optional attribute.

target-port-range: A list of port numbers bound to resources under
    attack.

    A port range is defined by two bounds, a lower port number (lower-
    port) and an upper port number (upper-port). When only 'lower-
    port' is present, it represents a single port number.

    For TCP, UDP, Stream Control Transmission Protocol (SCTP)

[RFC4960], or Datagram Congestion Control Protocol (DCCP)
[RFC4340], a range of ports can be, for example, 0-1023,
1024-65535, or 1024-49151.

This is an optional attribute.

target-protocol: A list of protocols involved in an attack. Values
   are taken from the IANA protocol registry [proto_numbers].

   If 'target-protocol' is not specified, then the request applies to
   any protocol.

   This is an optional attribute.

target-fqdn: A list of Fully Qualified Domain Names (FQDNs)
   identifying resources under attack [RFC8499].

   How a name is passed to an underlying name resolution library is
   implementation- and deployment-specific. Nevertheless, once the
   name is resolved into one or multiple IP addresses, DOTS servers
   MUST apply the same validation checks as those for 'target-
   prefix'.

   The use of FQDNs may be suboptimal because:

   * It induces both an extra load and increased delays on the DOTS
      server to handle and manage DNS resolution requests.

   * It does not guarantee that the DOTS server will resolve a name
      to the same IP addresses that the DOTS client does.

   This is an optional attribute.

target-uri: A list of Uniform Resource Identifiers (URIs) [RFC3986]
   identifying resources under attack.

   The same validation checks used for 'target-fqdn' MUST be followed
   by DOTS servers to validate a target URI.

   This is an optional attribute.

alias-name: A list of aliases of resources for which the mitigation
   is requested. Aliases can be created using the DOTS data channel
   (Section 6.1 of [I-D.ietf-dots-data-channel]), direct
   configuration, or other means.

   An alias is used in subsequent signal channel exchanges to refer
   more efficiently to the resources under attack.

   This is an optional attribute.

lifetime: Lifetime of the mitigation request in seconds. The
   RECOMMENDED lifetime of a mitigation request is 3600 seconds --
   this value was chosen to be long enough so that refreshing is not
   typically a burden on the DOTS client, while still making the
   request expire in a timely manner when the client has unexpectedly
   quit. DOTS clients MUST include this parameter in their
   mitigation requests. Upon the expiry of this lifetime, and if the
   request is not refreshed, the mitigation request is removed. The
   request can be refreshed by sending the same request again.

   A lifetime of '0' in a mitigation request is an invalid value.

   A lifetime of negative one (-1) indicates indefinite lifetime for
   the mitigation request. The DOTS server MAY refuse indefinite
   lifetime, for policy reasons; the granted lifetime value is
   returned in the response. DOTS clients MUST be prepared to not be
   granted mitigations with indefinite lifetimes.

   The DOTS server MUST always indicate the actual lifetime in the
   response and the remaining lifetime in status messages sent to the
   DOTS client.

   This is a mandatory attribute.

trigger-mitigation: If the parameter value is set to 'false', DDoS
   mitigation will not be triggered for the mitigation request unless
   the DOTS signal channel session is lost.

   If the DOTS client ceases to respond to heartbeat messages, the
   DOTS server can detect that the DOTS signal channel session is
   lost. More details are discussed in Section 4.7.

   The default value of the parameter is 'true' (that is, the
   mitigation starts immediately). If 'trigger-mitigation' is not
   present in a request, this is equivalent to receiving a request
   with 'trigger-mitigation' set to 'true'.

   This is an optional attribute.

In deployments where server-domain DOTS gateways are enabled,
identity information about the origin source client domain ('cdid')
SHOULD be propagated to the DOTS server. That information is meant
to assist the DOTS server to enforce some policies such as grouping
DOTS clients that belong to the same DOTS domain, limiting the number

of DOTS requests, and identifying the mitigation scope. These
policies can be enforced per-client, per-client domain, or both.
Also, the identity information may be used for auditing and debugging
purposes.

Figure 7 shows an example of a request relayed by a server-domain
DOTS gateway.

```
  Header: PUT (Code=0.03)
  Uri-Path: ".well-known"
  Uri-Path: "dots"
  Uri-Path: "mitigate"
  Uri-Path: "cdid=7eeaf349529eb55ed50113"
  Uri-Path: "cuid=dz6pHjaADkaFTbjr0JGBpw"
  Uri-Path: "mid=123"
  Content-Format: "application/dots+cbor"

  {
    ...
  }
```

    Figure 7: PUT for DOTS Mitigation Request as Relayed by a DOTS
                              Gateway

A server-domain DOTS gateway SHOULD add the following Uri-Path
parameter:

cdid: Stands for Client Domain Identifier. The 'cdid' is conveyed by
      a server-domain DOTS gateway to propagate the source domain
      identity from the gateway's client-facing-side to the gateway's
      server-facing-side, and from the gateway's server-facing-side
      to the DOTS server. 'cdid' may be used by the final DOTS server
      for policy enforcement purposes (e.g., enforce a quota on
      filtering rules). These policies are deployment-specific.

      Server-domain DOTS gateways SHOULD support a configuration
      option to instruct whether 'cdid' parameter is to be inserted.

      In order to accommodate deployments that require enforcing per-
      client policies, per-client domain policies, or a combination
      thereof, server-domain DOTS gateways instructed to insert the
      'cdid' parameter MUST supply the SPKI hash of the DOTS client
      X.509 certificate, the DOTS client raw public key, or the hash
      of the "PSK identity" in the 'cdid', following the same rules
      for generating the hash conveyed in 'cuid', which is then used
      by the ultimate DOTS server to determine the corresponding
      client's domain. The 'cdid' generated by a server-domain
      gateway is likely to be the same as the 'cuid' except if the
      DOTS message was relayed by a client-domain DOTS gateway or the
      'cuid' was generated from a rogue DOTS client.

      If a DOTS client is provisioned, for example, with distinct
      certificates as a function of the peer server-domain DOTS
      gateway, distinct 'cdid' values may be supplied by a server-
      domain DOTS gateway. The ultimate DOTS server MUST treat those
      'cdid' values as equivalent.

      The 'cdid' attribute MUST NOT be generated and included by DOTS
      clients.

      DOTS servers MUST ignore 'cdid' attributes that are directly
      supplied by source DOTS clients or client-domain DOTS gateways.
      This implies that first server-domain DOTS gateways MUST strip
      'cdid' attributes supplied by DOTS clients. DOTS servers
      SHOULD support a configuration parameter to identify DOTS
      gateways that are trusted to supply 'cdid' attributes.

      Only single-valued 'cdid' are defined in this document. That
      is, only the first on-path server-domain DOTS gateway can
      insert a 'cdid' value. This specification does not allow
      multiple server-domain DOTS gateways, whenever involved in the
      path, to insert a 'cdid' value for each server-domain gateway.

      This is an optional Uri-Path. When present, 'cdid' MUST be
      positioned before 'cuid'.

A DOTS gateway SHOULD add the CoAP Hop-Limit Option
[I-D.ietf-core-hop-limit].

Because of the complexity to handle partial failure cases, this
specification does not allow for including multiple mitigation
requests in the same PUT request. Concretely, a DOTS client MUST NOT
include multiple entries in the 'scope' array of the same PUT
request.

FQDN and URI mitigation scopes may be thought of as a form of scope
alias, in which the addresses associated with the domain name or URI
(as resolved by the DOTS server) represent the scope of the
mitigation. Particularly, the IP addresses to which the host
subcomponent of authority component of an URI resolves represent the
'target-prefix', the URI scheme represents the 'target-protocol', the
port subcomponent of authority component of an URI represents the
'target-port-range'. If the optional port information is not present
in the authority component, the default port defined for the URI
scheme represents the 'target-port'.

In the PUT request at least one of the attributes 'target-prefix',
'target-fqdn','target-uri', or 'alias-name' MUST be present.

Attributes and Uri-Path parameters with empty values MUST NOT be
present in a request and render the entire request invalid.

Figure 8 shows a PUT request example to signal that TCP port numbers
80, 8080, and 443 used by 2001:db8:6401::1 and 2001:db8:6401::2
servers are under attack. The presence of 'cdid' indicates that a
server-domain DOTS gateway has modified the initial PUT request sent
by the DOTS client. Note that 'cdid' MUST NOT appear in the PUT
request message body.

```
  Header: PUT (Code=0.03)
  Uri-Path: ".well-known"
  Uri-Path: "dots"
  Uri-Path: "mitigate"
  Uri-Path: "cdid=7eeaf349529eb55ed50113"
  Uri-Path: "cuid=dz6pHjaADkaFTbjr0JGBpw"
  Uri-Path: "mid=123"
  Content-Format: "application/dots+cbor"

  {
    "ietf-dots-signal-channel:mitigation-scope": {
      "scope": [
        {
          "target-prefix": [
             "2001:db8:6401::1/128",
             "2001:db8:6401::2/128"
          ],
          "target-port-range": [
            {
              "lower-port": 80
            },
            {
              "lower-port": 443
            },
            {
               "lower-port": 8080
            }
          ],
          "target-protocol": [
             6
          ],
          "lifetime": 3600
        }
      ]
    }
  }
```

        Figure 8: PUT for DOTS Mitigation Request (An Example)

The corresponding CBOR encoding format for the payload is shown in
Figure 9.

```
A1                                    # map(1)
   01                                 # unsigned(1)
   A1                                 # map(1)
      02                              # unsigned(2)
      81                              # array(1)
        A3                            # map(3)
           06                         # unsigned(6)
           82                         # array(2)
              74                      # text(20)
                 323030313A6462383A363430313A3A312F313238
              74                      # text(20)
                 323030313A6462383A363430313A3A322F313238
           07                         # unsigned(7)
           83                         # array(3)
              A1                      # map(1)
                 08                   # unsigned(8)
                 18 50                # unsigned(80)
              A1                      # map(1)
                 08                   # unsigned(8)
                 19 01BB              # unsigned(443)
              A1                      # map(1)
                 08                   # unsigned(8)
                 19 1F90              # unsigned(8080)
           0A                         # unsigned(10)
           81                         # array(1)
              06                      # unsigned(6)
           0E                         # unsigned(14)
              19 0E10                 # unsigned(3600)
```

        Figure 9: PUT for DOTS Mitigation Request (CBOR)

In both DOTS signal and data channel sessions, the DOTS client MUST
authenticate itself to the DOTS server (Section 8). The DOTS server
MAY use the algorithm presented in Section 7 of [RFC7589] to derive
the DOTS client identity or username from the client certificate.
The DOTS client identity allows the DOTS server to accept mitigation
requests with scopes that the DOTS client is authorized to manage.

The DOTS server couples the DOTS signal and data channel sessions

using the DOTS client identity and optionally the 'cdid' parameter
value, so the DOTS server can validate whether the aliases conveyed
in the mitigation request were indeed created by the same DOTS client
using the DOTS data channel session. If the aliases were not created
by the DOTS client, the DOTS server MUST return 4.00 (Bad Request) in
the response.

The DOTS server couples the DOTS signal channel sessions using the
DOTS client identity and optionally the 'cdid' parameter value, and
the DOTS server uses 'mid' and 'cuid' Uri-Path parameter values to
detect duplicate mitigation requests. If the mitigation request
contains the 'alias-name' and other parameters identifying the target
resources (such as 'target-prefix', 'target-port-range', 'target-
fqdn', or 'target-uri'), the DOTS server appends the parameter values
in 'alias-name' with the corresponding parameter values in 'target-
prefix', 'target-port-range', 'target-fqdn', or 'target-uri'.

The DOTS server indicates the result of processing the PUT request
using CoAP response codes. CoAP 2.xx codes are success. CoAP 4.xx
codes are some sort of invalid requests (client errors). COAP 5.xx
codes are returned if the DOTS server is in an error state or is
currently unavailable to provide mitigation in response to the
mitigation request from the DOTS client.

Figure 10 shows an example response to a PUT request that is
successfully processed by a DOTS server (i.e., CoAP 2.xx response
codes). This version of the specification forbids 'cuid' and 'cdid'
(if used) to be returned in a response message body.

```
{
   "ietf-dots-signal-channel:mitigation-scope": {
      "scope": [
         {
            "mid": 123,
            "lifetime": 3600
         }
      ]
   }
}
```

                        Figure 10: 2.xx Response Body

If the request is missing a mandatory attribute, does not include
'cuid' or 'mid' Uri-Path options, includes multiple 'scope'
parameters, or contains invalid or unknown parameters, the DOTS
server MUST reply with 4.00 (Bad Request). DOTS agents can safely
ignore comprehension-optional parameters they don't understand
(Section 9.6.1.1).

A DOTS server that receives a mitigation request with a lifetime set
to '0' MUST reply with a 4.00 (Bad Request).

If the DOTS server does not find the 'mid' parameter value conveyed
in the PUT request in its configuration data, it MAY accept the
mitigation request by sending back a 2.01 (Created) response to the
DOTS client; the DOTS server will consequently try to mitigate the
attack. A DOTS server could reject mitigation requests when it is
near capacity or needs to rate-limit a particular client, for
example.

The relative order of two mitigation requests, having the same
'trigger-mitigation' type, from a DOTS client is determined by
comparing their respective 'mid' values. If two mitigation requests
with the same 'trigger-mitigation' type have overlapping mitigation
scopes, the mitigation request with the highest numeric 'mid' value
will override the other mitigation request. Two mitigation requests
from a DOTS client have overlapping scopes if there is a common IP
address, IP prefix, FQDN, URI, or alias-name. To avoid maintaining a
long list of overlapping mitigation requests (i.e., requests with the
same 'trigger-mitigation' type and overlapping scopes) from a DOTS
client and avoid error-prone provisioning of mitigation requests from
a DOTS client, the overlapped lower numeric 'mid' MUST be
automatically deleted and no longer available at the DOTS server.
For example, if the DOTS server receives a mitigation request which
overlaps with an existing mitigation with a higher numeric 'mid', the
DOTS server rejects the request by returning 4.09 (Conflict) to the
DOTS client. The response includes enough information for a DOTS
client to recognize the source of the conflict as described below in
the 'conflict-information' subtree with only the relevant nodes
listed:

conflict-information: Indicates that a mitigation request is
   conflicting with another mitigation request. This optional
   attribute has the following structure:

   conflict-cause: Indicates the cause of the conflict. The
      following values are defined:

      1: Overlapping targets. 'conflict-scope' provides more details
         about the conflicting target clauses.

   conflict-scope: Characterizes the exact conflict scope. It may
      include a list of IP addresses, a list of prefixes, a list of
      port numbers, a list of target protocols, a list of FQDNs, a
      list of URIs, a list of alias-names, or a 'mid'.

If the DOTS server receives a mitigation request which overlaps with
an active mitigation request, but both having distinct 'trigger-
mitigation' types, the DOTS server SHOULD deactivate (absent explicit
policy/configuration otherwise) the mitigation request with 'trigger-
mitigation' set to false. Particularly, if the mitigation request
with 'trigger-mitigation' set to false is active, the DOTS server
withdraws the mitigation request (i.e., status code is set to '7' as
defined in Table 2) and transitions the status of the mitigation
request to '8'.

Upon DOTS signal channel session loss with a peer DOTS client, the
DOTS server SHOULD withdraw (absent explicit policy/configuration
otherwise) any active mitigation requests overlapping with mitigation
requests having 'trigger-mitigation' set to false from that DOTS
client, as the loss of the session implicitly activates these
preconfigured mitigation requests and they take precedence. Note
that active-but-terminating period is not observed for mitigations
withdrawn at the initiative of the DOTS server.

DOTS clients may adopt various strategies for setting the scopes of
immediate and pre-configured mitigation requests to avoid potential
conflicts. For example, a DOTS client may tweak pre-configured
scopes so that the scope of any overlapping immediate mitigation
request will be a subset of the pre-configured scopes. Also, if an
immediate mitigation request overlaps with any of the pre-configured
scopes, the DOTS client sets the scope of the overlapping immediate
mitigation request to be a subset of the pre-configured scopes, so as
to get a broad mitigation when the DOTS signal channel collapses and
maximize the chance of recovery.

If the request is conflicting with an existing mitigation request
from a different DOTS client, the DOTS server may return 2.01
(Created) or 4.09 (Conflict) to the requesting DOTS client. If the
DOTS server decides to maintain the new mitigation request, the DOTS
server returns 2.01 (Created) to the requesting DOTS client. If the
DOTS server decides to reject the new mitigation request, the DOTS
server returns 4.09 (Conflict) to the requesting DOTS client. For
both 2.01 (Created) and 4.09 (Conflict) responses, the response
includes enough information for a DOTS client to recognize the source
of the conflict as described below:

conflict-information: Indicates that a mitigation request is
   conflicting with another mitigation request(s) from other DOTS
   client(s). This optional attribute has the following structure:

   conflict-status: Indicates the status of a conflicting mitigation
      request. The following values are defined:

      1: DOTS server has detected conflicting mitigation requests
          from different DOTS clients. This mitigation request is
          currently inactive until the conflicts are resolved.
          Another mitigation request is active.

      2: DOTS server has detected conflicting mitigation requests
          from different DOTS clients. This mitigation request is
          currently active.

      3: DOTS server has detected conflicting mitigation requests
          from different DOTS clients. All conflicting mitigation
          requests are inactive.

   conflict-cause: Indicates the cause of the conflict. The
      following values are defined:

      1: Overlapping targets. 'conflict-scope' provides more details
          about the conflicting target clauses.

      2: Conflicts with an existing accept-list. This code is
          returned when the DDoS mitigation detects source addresses/
          prefixes in the accept-listed ACLs are attacking the
          target.

      3: CUID Collision. This code is returned when a DOTS client
          uses a 'cuid' that is already used by another DOTS client.
          This code is an indication that the request has been
          rejected and a new request with a new 'cuid' is to be re-
          sent by the DOTS client (see the example shown in
          Figure 11). Note that 'conflict-status', 'conflict-scope',
          and 'retry-timer' MUST NOT be returned in the error
          response.

   conflict-scope: Characterizes the exact conflict scope. It may
      include a list of IP addresses, a list of prefixes, a list of
      port numbers, a list of target protocols, a list of FQDNs, a
      list of URIs, a list of alias-names, or references to
      conflicting ACLs (by an 'acl-name', typically
      [I-D.ietf-dots-data-channel]).

   retry-timer: Indicates, in seconds, the time after which the DOTS
      client may re-issue the same request. The DOTS server returns
      'retry-timer' only to DOTS client(s) for which a mitigation
      request is deactivated. Any retransmission of the same
      mitigation request before the expiry of this timer is likely to
      be rejected by the DOTS server for the same reasons.

```
        The retry-timer SHOULD be equal to the lifetime of the active
        mitigation request resulting in the deactivation of the
        conflicting mitigation request.

        If the DOTS server decides to maintain a state for the
        deactivated mitigation request, the DOTS server updates the
        lifetime of the deactivated mitigation request to 'retry-timer
        + 45 seconds' (that is, this mitigation request remains
        deactivated for the entire duration of 'retry-timer + 45
        seconds') so that the DOTS client can refresh the deactivated
        mitigation request after 'retry-timer' seconds, but before the
        expiry of the lifetime, and check if the conflict is resolved.

    Header: PUT (Code=0.03)
    Uri-Path: ".well-known"
    Uri-Path: "dots"
    Uri-Path: "mitigate"
    Uri-Path: "cuid=7eeaf349529eb55ed50113"
    Uri-Path: "mid=12"

    (1) Request with a conflicting 'cuid'

    {
       "ietf-dots-signal-channel:mitigation-scope": {
          "scope": [
             {
                "conflict-information": {
                  "conflict-cause": "cuid-collision"
                }
             }
          ]
       }
    }

    (2) Message body of the 4.09 (Conflict) response
      from the DOTS server

    Header: PUT (Code=0.03)
    Uri-Path: ".well-known"
    Uri-Path: "dots"
    Uri-Path: "mitigate"
    Uri-Path: "cuid=f30d281ce6b64fc5a0b91e"
    Uri-Path: "mid=12"

    (3) Request with a new 'cuid'

              Figure 11: Example of Generating a New 'cuid'
```

As an active attack evolves, DOTS clients can adjust the scope of
requested mitigation as necessary, by refining the scope of resources
requiring mitigation. This can be achieved by sending a PUT request
with a new 'mid' value that will override the existing one with
overlapping mitigation scopes.

For a mitigation request to continue beyond the initial negotiated
lifetime, the DOTS client has to refresh the current mitigation
request by sending a new PUT request. This PUT request MUST use the
same 'mid' value, and MUST repeat all the other parameters as sent in
the original mitigation request apart from a possible change to the
lifetime parameter value. In such case, the DOTS server MAY update
the mitigation request, and a 2.04 (Changed) response is returned to
indicate a successful update of the mitigation request. If this is
not the case, the DOTS server MUST reject the request with a 4.00
(Bad Request).

4.4.2. Retrieve Information Related to a Mitigation

   A GET request is used by a DOTS client to retrieve information
   (including status) of DOTS mitigations from a DOTS server.

   'cuid' is a mandatory Uri-Path parameter for GET requests.

   Uri-Path parameters with empty values MUST NOT be present in a
   request.

   The same considerations for manipulating 'cdid' parameter by server-
   domain DOTS gateways specified in Section 4.4.1 MUST be followed for
   GET requests.

   The 'c' Uri-Query option is used to control selection of
   configuration and non-configuration data nodes. Concretely, the 'c'
   (content) parameter and its permitted values defined in the following
   table [I-D.ietf-core-comi] can be used to retrieve non-configuration
   data (attack mitigation status), configuration data, or both. The
   DOTS server MAY support this optional filtering capability. It can
   safely ignore it if not supported. If the DOTS client supports the
   optional filtering capability, it SHOULD use "c=n" query (to get back
   only the dynamically changing data) or "c=c" query (to get back the
   static configuration values) when the DDoS attack is active to limit
   the size of the response.

      +-------+---+
      | Value | Description |
      +-------+---+
```

```
    | c     | Return only configuration descendant data nodes     |
    | n     | Return only non-configuration descendant data nodes |
    | a     | Return all descendant data nodes                    |
    +-------+-----------------------------------------------------+
```

The DOTS client can use Block-wise transfer [RFC7959] to get the list
of all its mitigations maintained by a DOTS server, it can send
Block2 Option in a GET request with NUM = 0 to aid in limiting the
size of the response. If the representation of all the active
mitigation requests associated with the DOTS client does not fit
within a single datagram, the DOTS server MUST use the Block2 Option
with NUM = 0 in the GET response. The Size2 Option may be conveyed
in the response to indicate the total size of the resource
representation. The DOTS client retrieves the rest of the
representation by sending additional GET requests with Block2 Options
containing NUM values greater than zero. The DOTS client MUST adhere
to the block size preferences indicated by the DOTS server in the
response. If the DOTS server uses the Block2 Option in the GET
response and the response is for a dynamically changing resource
(e.g., "c=n" or "c=a" query), the DOTS server MUST include the ETag
Option in the response. The DOTS client MUST include the same ETag
value in subsequent GET requests to retrieve the rest of the
representation.

The following examples illustrate how a DOTS client retrieves active
mitigation requests from a DOTS server. In particular:

o Figure 12 shows the example of a GET request to retrieve all DOTS
   mitigation requests signaled by a DOTS client.

o Figure 13 shows the example of a GET request to retrieve a
   specific DOTS mitigation request signaled by a DOTS client. The
   configuration data to be reported in the response is formatted in
   the same order as was processed by the DOTS server in the original
   mitigation request.

These two examples assume the default of "c=a"; that is, the DOTS
client asks for all data to be reported by the DOTS server.

```
  Header: GET (Code=0.01)
  Uri-Path: ".well-known"
  Uri-Path: "dots"
  Uri-Path: "mitigate"
  Uri-Path: "cuid=dz6pHjaADkaFTbjr0JGBpw"
  Observe: 0
```

        Figure 12: GET to Retrieve all DOTS Mitigation Requests

```
  Header: GET (Code=0.01)
  Uri-Path: ".well-known"
  Uri-Path: "dots"
  Uri-Path: "mitigate"
  Uri-Path: "cuid=dz6pHjaADkaFTbjr0JGBpw"
  Uri-Path: "mid=12332"
  Observe: 0
```

     Figure 13: GET to Retrieve a Specific DOTS Mitigation Request

If the DOTS server does not find the 'mid' Uri-Path value conveyed in
the GET request in its configuration data for the requesting DOTS
client, it MUST respond with a 4.04 (Not Found) error response code.
Likewise, the same error MUST be returned as a response to a request
to retrieve all mitigation records (i.e., 'mid' Uri-Path is not
defined) of a given DOTS client if the DOTS server does not find any
mitigation record for that DOTS client. As a reminder, a DOTS client
is identified by its identity (e.g., client certificate, 'cuid') and
optionally the 'cdid'.

Figure 14 shows a response example of all active mitigation requests
associated with the DOTS client as maintained by the DOTS server.
The response indicates the mitigation status of each mitigation
request.

```
{
  "ietf-dots-signal-channel:mitigation-scope": {
    "scope": [
      {
        "mid": 12332,
        "mitigation-start": "1507818434",
        "target-prefix": [
            "2001:db8:6401::1/128",
            "2001:db8:6401::2/128"
        ],
        "target-protocol": [
          17
        ],
        "lifetime": 1756,
        "status": "attack-successfully-mitigated",
        "bytes-dropped": "134334555",
        "bps-dropped": "43344",
        "pkts-dropped": "333334444",
        "pps-dropped": "432432"
      },
      {
        "mid": 12333,
```

```
            "mitigation-start": "1507818393",
            "target-prefix": [
                "2001:db8:6401::1/128",
                "2001:db8:6401::2/128"
            ],
            "target-protocol": [
              6
            ],
            "lifetime": 1755,
            "status": "attack-stopped",
            "bytes-dropped": "0",
            "bps-dropped": "0",
            "pkts-dropped": "0",
            "pps-dropped": "0"
          }
        ]
      }
    }
```

                    Figure 14: Response Body to a GET Request

   The mitigation status parameters are described below:

   mitigation-start: Mitigation start time is expressed in seconds
      relative to 1970-01-01T00:00Z in UTC time (Section 2.4.1 of

      [RFC7049]). The CBOR encoding is modified so that the leading tag
      1 (epoch-based date/time) MUST be omitted.

      This is a mandatory attribute when an attack mitigation is active.
      Particularly, 'mitigation-start' is not returned for a mitigation
      with 'status' code set to 8.

   lifetime: The remaining lifetime of the mitigation request, in
      seconds.

      This is a mandatory attribute.

   status: Status of attack mitigation. The various possible values of
      'status' parameter are explained in Table 2.

      This is a mandatory attribute.

   bytes-dropped: The total dropped byte count for the mitigation
      request since the attack mitigation is triggered. The count wraps
      around when it reaches the maximum value of unsigned integer64.

      This is an optional attribute.

   bps-dropped: The average number of dropped bytes per second for the
      mitigation request since the attack mitigation is triggered. This
      average SHOULD be over five-minute intervals (that is, measuring
      bytes into five-minute buckets and then averaging these buckets
      over the time since the mitigation was triggered).

      This is an optional attribute.

   pkts-dropped: The total number of dropped packet count for the
      mitigation request since the attack mitigation is triggered. The
      count wraps around when it reaches the maximum value of unsigned
      integer64.

      This is an optional attribute.

   pps-dropped: The average number of dropped packets per second for
      the mitigation request since the attack mitigation is triggered.
      This average SHOULD be over five-minute intervals (that is,
      measuring packets into five-minute buckets and then averaging
      these buckets over the time since the mitigation was triggered).

      This is an optional attribute.

```
      +-----------+-----------------------------------------------------+
      | Parameter | Description                                         |
      |     Value |                                                     |
      +-----------+-----------------------------------------------------+
      |         1 | Attack mitigation setup is in progress (e.g.,       |
      |           | changing the network path to redirect the inbound   |
      |           | traffic to a DOTS mitigator).                       |
      +-----------+-----------------------------------------------------+
      |         2 | Attack is being successfully mitigated (e.g., traffic |
      |           | is redirected to a DDoS mitigator and attack traffic |
      |           | is dropped).                                        |
      +-----------+-----------------------------------------------------+
      |         3 | Attack has stopped and the DOTS client can withdraw  |
      |           | the mitigation request. This status code will be    |
      |           | transmitted for immediate mitigation requests till  |
      |           | the mitigation is withdrawn or the lifetime expires. |
      |           | For mitigation requests with pre-configured scopes  |
      |           | (i.e., 'trigger-mitigation' set to 'false'), this   |
      |           | status code will be transmitted 4 times and then    |
      |           | transition to "8".                                  |
      +-----------+-----------------------------------------------------+
      |         4 | Attack has exceeded the mitigation provider         |
      |           | capability.                                         |
```

```
+-----------+-----------------------------------------------------+
|         5 | DOTS client has withdrawn the mitigation request and|
|           | the mitigation is active but terminating.           |
+-----------+-----------------------------------------------------+
|         6 | Attack mitigation is now terminated.                |
+-----------+-----------------------------------------------------+
|         7 | Attack mitigation is withdrawn (by the DOTS server).|
|           | If a mitigation request with 'trigger-mitigation' set|
|           | to false is withdrawn because it overlaps with an   |
|           | immediate mitigation request, this status code will |
|           | be transmitted 4 times and then transition to "8" for|
|           | the mitigation request with pre-configured scopes.  |
+-----------+-----------------------------------------------------+
|         8 | Attack mitigation will be triggered for the         |
|           | mitigation request only when the DOTS signal channel|
|           | session is lost.                                    |
+-----------+-----------------------------------------------------+
```

                    Table 2: Values of 'status' Parameter

4.4.2.1. DOTS Servers Sending Mitigation Status

   The Observe Option defined in [RFC7641] extends the CoAP core
   protocol with a mechanism for a CoAP client to "observe" a resource
   on a CoAP server: The client retrieves a representation of the
   resource and requests this representation be updated by the server as
   long as the client is interested in the resource. DOTS
   implementations MUST use the Observe Option for both 'mitigate' and
   'config' (Section 4.2).

   A DOTS client conveys the Observe Option set to '0' in the GET
   request to receive asynchronous notifications of attack mitigation
   status from the DOTS server.

   Unidirectional mitigation notifications within the bidirectional
   signal channel enables asynchronous notifications between the agents.
   [RFC7641] indicates that (1) a notification can be sent in a
   Confirmable or a Non-confirmable message, and (2) the message type
   used is typically application-dependent and may be determined by the
   server for each notification individually. For DOTS server
   application, the message type MUST always be set to Non-confirmable
   even if the underlying COAP library elects a notification to be sent
   in a Confirmable message. This overrides the behavior defined in
   Section 4.5 of [RFC7641] to send a Confirmable message instead of a
   Non-confirmable message at least every 24 hour for the following
   reasons: First, the DOTS signal channel uses a heartbeat mechanism to
   determine if the DOTS client is alive. Second, Confirmable messages
   are not suitable during an attack.

   Due to the higher likelihood of packet loss during a DDoS attack, the
   DOTS server periodically sends attack mitigation status to the DOTS
   client and also notifies the DOTS client whenever the status of the
   attack mitigation changes. If the DOTS server cannot maintain an RTT
   estimate, it MUST NOT send more than one asynchronous notification
   every 3 seconds, and SHOULD use an even less aggressive rate whenever
   possible (case 2 in Section 3.1.3 of [RFC8085]).

   When conflicting requests are detected, the DOTS server enforces the
   corresponding policy (e.g., accept all requests, reject all requests,
   accept only one request but reject all the others, ...). It is
   assumed that this policy is supplied by the DOTS server administrator
   or it is a default behavior of the DOTS server implementation. Then,
   the DOTS server sends notification message(s) to the DOTS client(s)
   at the origin of the conflict (refer to the conflict parameters
   defined in Section 4.4.1). A conflict notification message includes
   information about the conflict cause, scope, and the status of the
   mitigation request(s). For example,

   o A notification message with 'status' code set to '7 (Attack
      mitigation is withdrawn)' and 'conflict-status' set to '1' is sent
      to a DOTS client to indicate that an active mitigation request is
      deactivated because a conflict is detected.

   o A notification message with 'status' code set to '1 (Attack
      mitigation is in progress)' and 'conflict-status' set to '2' is
      sent to a DOTS client to indicate that this mitigation request is
      in progress, but a conflict is detected.

   Upon receipt of a conflict notification message indicating that a
   mitigation request is deactivated because of a conflict, a DOTS
   client MUST NOT resend the same mitigation request before the expiry
   of 'retry-timer'. It is also recommended that DOTS clients support
   means to alert administrators about mitigation conflicts.

   A DOTS client that is no longer interested in receiving notifications
   from the DOTS server can simply "forget" the observation. When the
   DOTS server sends the next notification, the DOTS client will not
   recognize the token in the message and thus will return a Reset
   message. This causes the DOTS server to remove the associated entry.
   Alternatively, the DOTS client can explicitly deregister itself by
   issuing a GET request that has the Token field set to the token of
   the observation to be cancelled and includes an Observe Option with
   the value set to '1' (deregister). The latter is RECOMMENDED.

   Figure 15 shows an example of a DOTS client requesting a DOTS server

to send notifications related to a mitigation request. Note that for
mitigations with pre-configured scopes (i.e., 'trigger-mitigation'
set to 'false'), the state will need to transition from 3 (attack-
stopped) to 8 (attack-mitigation-signal-loss).

```
+-----------+                           +-----------+
|DOTS client|                           |DOTS server|
+-----------+                           +-----------+
      |                                       |
      |  GET /<mid>                           |
      |  Token: 0x4a                          | Registration
      |  Observe: 0                           |
      +-------------------------------------->|
      |                                       |
      |  2.05 Content                         |
      |  Token: 0x4a                          | Notification of
      |  Observe: 12                          | the current state
      |  status: "attack-mitigation-in-progress" |
      |                                       |
      |<--------------------------------------+
      |  2.05 Content                         |
      |  Token: 0x4a                          | Notification upon
      |  Observe: 44                          | a state change
      |  status: "attack-successfully-mitigated" |
      |                                       |
      |<--------------------------------------+
      |  2.05 Content                         |
      |  Token: 0x4a                          | Notification upon
      |  Observe: 60                          | a state change
      |  status: "attack-stopped"             |
      |<--------------------------------------+
      |                                       |
                      ...
```

          Figure 15: Notifications of Attack Mitigation Status

4.4.2.2. DOTS Clients Polling for Mitigation Status

   The DOTS client can send the GET request at frequent intervals
   without the Observe Option to retrieve the configuration data of the
   mitigation request and non-configuration data (i.e., the attack
   status). DOTS clients MAY be configured with a policy indicating the
   frequency of polling DOTS servers to get the mitigation status. This
   frequency MUST NOT be more than one UDP datagram per RTT as discussed
   in Section 3.1.3 of [RFC8085].

   If the DOTS server has been able to mitigate the attack and the
   attack has stopped, the DOTS server indicates as such in the status.
   In such case, the DOTS client recalls the mitigation request by
   issuing a DELETE request for this mitigation request (Section 4.4.4).

   A DOTS client SHOULD react to the status of the attack as per the
   information sent by the DOTS server rather than performing its own
   detection that the attack has been mitigated. This ensures that the
   DOTS client does not recall a mitigation request prematurely because
   it is possible that the DOTS client does not sense the DDoS attack on
   its resources, but the DOTS server could be actively mitigating the
   attack because the attack is not completely averted.

4.4.3. Efficacy Update from DOTS Clients

   While DDoS mitigation is in progress, due to the likelihood of packet
   loss, a DOTS client MAY periodically transmit DOTS mitigation
   efficacy updates to the relevant DOTS server. A PUT request is used
   to convey the mitigation efficacy update to the DOTS server. This
   PUT request is treated as a refresh of the current mitigation.

   The PUT request used for efficacy update MUST include all the
   parameters used in the PUT request to carry the DOTS mitigation
   request (Section 4.4.1) unchanged apart from the 'lifetime' parameter
   value. If this is not the case, the DOTS server MUST reject the
   request with a 4.00 (Bad Request).

   The If-Match Option (Section 5.10.8.1 of [RFC7252]) with an empty
   value is used to make the PUT request conditional on the current
   existence of the mitigation request. If UDP is used as transport,
   CoAP requests may arrive out-of-order. For example, the DOTS client
   may send a PUT request to convey an efficacy update to the DOTS
   server followed by a DELETE request to withdraw the mitigation
   request, but the DELETE request arrives at the DOTS server before the
   PUT request. To handle out-of-order delivery of requests, if an If-
   Match Option is present in the PUT request and the 'mid' in the
   request matches a mitigation request from that DOTS client, the
   request is processed by the DOTS server. If no match is found, the
   PUT request is silently ignored by the DOTS server.

   An example of an efficacy update message, which includes an If-Match
   Option with an empty value, is depicted in Figure 16.

```
   Header: PUT (Code=0.03)
   Uri-Path: ".well-known"
   Uri-Path: "dots"
   Uri-Path: "mitigate"
   Uri-Path: "cuid=dz6pHjaADkaFTbjr0JGBpw"
   Uri-Path: "mid=123"
```

```
      If-Match:
      Content-Format: "application/dots+cbor"

      {
       "ietf-dots-signal-channel:mitigation-scope": {
         "scope": [
           {
             "target-prefix": [
               "2001:db8:6401::1/128",
               "2001:db8:6401::2/128"
             ],
             "target-port-range": [
               {
                 "lower-port": 80
               },
               {
                 "lower-port": 443
               },
               {
                  "lower-port": 8080
               }
             ],
             "target-protocol": [
               6
             ],
             "attack-status": "under-attack"
           }
         ]
       }
      }
```

                   Figure 16: An Example of Efficacy Update

      The 'attack-status' parameter is a mandatory attribute when
      performing an efficacy update. The various possible values contained
      in the 'attack-status' parameter are described in Table 3.

      +-----------+---+
      | Parameter | Description |
      | value | |
      +-----------+---+
      | 1 | The DOTS client determines that it is still under |
      | | attack. |
      +-----------+---+
      | 2 | The DOTS client determines that the attack is |
      | | successfully mitigated (e.g., attack traffic is not |
      | | seen). |
      +-----------+---+

                   Table 3: Values of 'attack-status' Parameter

      The DOTS server indicates the result of processing a PUT request
      using CoAP response codes. The response code 2.04 (Changed) is
      returned if the DOTS server has accepted the mitigation efficacy
      update. The error response code 5.03 (Service Unavailable) is
      returned if the DOTS server has erred or is incapable of performing
      the mitigation. As specified in [RFC7252], 5.03 uses Max-Age option
      to indicate the number of seconds after which to retry.

4.4.4. Withdraw a Mitigation

      DELETE requests are used to withdraw DOTS mitigation requests from
      DOTS servers (Figure 17).

      'cuid' and 'mid' are mandatory Uri-Path parameters for DELETE
      requests.

      The same considerations for manipulating 'cdid' parameter by DOTS
      gateways, as specified in Section 4.4.1, MUST be followed for DELETE
      requests. Uri-Path parameters with empty values MUST NOT be present
      in a request.

```
        Header: DELETE (Code=0.04)
        Uri-Path: ".well-known"
        Uri-Path: "dots"
        Uri-Path: "mitigate"
        Uri-Path: "cuid=dz6pHjaADkaFTbjr0JGBpw"
        Uri-Path: "mid=123"
```

                     Figure 17: Withdraw a DOTS Mitigation

      If the DELETE request does not include 'cuid' and 'mid' parameters,
      the DOTS server MUST reply with a 4.00 (Bad Request).

      Once the request is validated, the DOTS server immediately
      acknowledges a DOTS client's request to withdraw the DOTS signal
      using 2.02 (Deleted) response code with no response payload. A 2.02
      (Deleted) Response Code is returned even if the 'mid' parameter value
      conveyed in the DELETE request does not exist in its configuration
      data before the request.

      If the DOTS server finds the 'mid' parameter value conveyed in the
      DELETE request in its configuration data for the DOTS client, then to
      protect against route or DNS flapping caused by a DOTS client rapidly
      removing a mitigation, and to dampen the effect of oscillating

attacks, the DOTS server MAY allow mitigation to continue for a
limited period after acknowledging a DOTS client's withdrawal of a
mitigation request. During this period, the DOTS server status
messages SHOULD indicate that mitigation is active but terminating
(Section 4.4.2).

The initial active-but-terminating period SHOULD be sufficiently long
to absorb latency incurred by route propagation. The active-but-
terminating period SHOULD be set by default to 120 seconds. If the
client requests mitigation again before the initial active-but-
terminating period elapses, the DOTS server MAY exponentially
increase (the base of the exponent is 2) the active-but-terminating
period up to a maximum of 300 seconds (5 minutes).

Once the active-but-terminating period elapses, the DOTS server MUST
treat the mitigation as terminated, as the DOTS client is no longer
responsible for the mitigation.

If a mitigation is triggered due to a signal channel loss, the DOTS
server relies upon normal triggers to stop that mitigation
(typically, receipt of a valid DELETE request, expiry of the
mitigation lifetime, or scrubbing the traffic to the attack target).
In particular, the DOTS server MUST NOT consider the signal channel
recovery as a trigger to stop the mitigation.

4.5. DOTS Signal Channel Session Configuration

A DOTS client can negotiate, configure, and retrieve the DOTS signal
channel session behavior with its DOTS peers. The DOTS signal
channel can be used, for example, to configure the following:

a. Heartbeat interval (heartbeat-interval): DOTS agents regularly
    send heartbeats to each other after mutual authentication is
    successfully completed in order to keep the DOTS signal channel
    open. Heartbeat messages are exchanged between DOTS agents every
    'heartbeat-interval' seconds to detect the current status of the
    DOTS signal channel session.

b. Missing heartbeats allowed (missing-hb-allowed): This variable
    indicates the maximum number of consecutive heartbeat messages
    for which a DOTS agent did not receive a response before
    concluding that the session is disconnected or defunct.

c. Acceptable signal loss ratio: Maximum retransmissions,
    retransmission timeout value, and other message transmission
    parameters for the DOTS signal channel.

When the DOTS signal channel is established over a reliable transport
(e.g., TCP), there is no need for the reliability mechanisms provided
by CoAP over UDP since the underlying TCP connection provides
retransmissions and deduplication [RFC8323]. As a reminder, CoAP
over reliable transports does not support Confirmable or Non-
confirmable message types. As such, the transmission-related
parameters (missing-hb-allowed and acceptable signal loss ratio) are
negotiated only for DOTS over unreliable transports.

The same or distinct configuration sets may be used during times when
a mitigation is active ('mitigating-config') and when no mitigation
is active ('idle-config'). This is particularly useful for DOTS
servers that might want to reduce heartbeat frequency or cease
heartbeat exchanges when an active DOTS client has not requested
mitigation. If distinct configurations are used, DOTS agents MUST
follow the appropriate configuration set as a function of the
mitigation activity (e.g., if no mitigation request is active (also
referred to as 'idle' time), 'idle-config'-related values must be
followed). Additionally, DOTS agents MUST automatically switch to
the other configuration upon a change in the mitigation activity
(e.g., if an attack mitigation is launched after an 'idle' time, the
DOTS agent switches from 'idle-config' to 'mitigating-config'-related
values).

The specification allows for a flexible retry configuration when an
unreliable transport is in use. For example, a server may be tweaked
to return the following configuration to be used when a mitigation is
active:

o a 'max-retransmit' set to '1' together with a higher 'missing-hb-
   allowed' value (e.g., 34) and a default 'ack-timeout' set to 2
   seconds. This configuration implies more frequent heartbeats in a
   given time span when a loss is encountered.

o a lower 'missing-hb-allowed' (e.g., 7) value but delegate the
   retransmission (with exponential back-off) to the underlying CoAP
   library by setting 'max-retransmit' to a high value (e.g., 3).
   When a loss is encountered, this configuration implies less
   frequent heartbeats compared to the previous bullet.

o a higher 'ack-timeout' value (e.g., 10 seconds), a 'max-
   retransmit' set to '1', and a 'missing-hb-allowed' value set to 7.
   Compared to the previous bullet, this configuration reduces by 50%
   the number of required heartbeats from the first transmission of a
   heartbeat message to the time when the DOTS agent gives up.

o etc.

CoAP Requests and responses are indicated for reliable delivery by
marking them as Confirmable messages. DOTS signal channel session
configuration requests and responses are marked as Confirmable
messages. As explained in Section 2.1 of [RFC7252], a Confirmable
message is retransmitted using a default timeout and exponential
back-off between retransmissions, until the DOTS server sends an
Acknowledgement message (ACK) with the same Message ID conveyed from
the DOTS client.

Message transmission parameters are defined in Section 4.8 of
[RFC7252]. The DOTS server can either piggyback the response in the
acknowledgement message or, if the DOTS server cannot respond
immediately to a request carried in a Confirmable message, it simply
responds with an Empty Acknowledgement message so that the DOTS
client can stop retransmitting the request. Empty Acknowledgement
messages are explained in Section 2.2 of [RFC7252]. When the
response is ready, the server sends it in a new Confirmable message
which in turn needs to be acknowledged by the DOTS client (see
Sections 5.2.1 and 5.2.2 of [RFC7252]). Requests and responses
exchanged between DOTS agents during 'idle' time are marked as
Confirmable messages.

> Implementation Note: A DOTS client that receives a response in a
> Confirmable message may want to clean up the message state right
> after sending the ACK. If that ACK is lost and the DOTS server
> retransmits the Confirmable message, the DOTS client may no longer
> have any state that would help it correlate this response: from
> the DOTS client's standpoint, the retransmission message is
> unexpected. The DOTS client will send a Reset message so it does
> not receive any more retransmissions. This behavior is normal and
> not an indication of an error (see Section 5.3.2 of [RFC7252] for
> more details).

4.5.1. Discover Configuration Parameters

A GET request is used to obtain acceptable (e.g., minimum and maximum
values) and current configuration parameters on the DOTS server for
DOTS signal channel session configuration. This procedure occurs
between a DOTS client and its immediate peer DOTS server. As such,
this GET request MUST NOT be relayed by a DOTS gateway.

Figure 18 shows how to obtain ~~acceptable~~ configuration parameters ~~for~~ **that** the DOTS ~~server.~~
server will find acceptable.

```
  Header: GET (Code=0.01)
  Uri-Path: ".well-known"
  Uri-Path: "dots"
  Uri-Path: "config"
```

Figure 18: GET to Retrieve Configuration

The DOTS server in the 2.05 (Content) response conveys the current,
minimum, and maximum attribute values acceptable by the DOTS server
(Figure 19).

```
{
  "ietf-dots-signal-channel:signal-config": {
    "mitigating-config": {
      "heartbeat-interval": {
        "max-value": number,
        "min-value": number,
        "current-value": number
      },
      "missing-hb-allowed": {
        "max-value": number,
        "min-value": number,
        "current-value": number
      },
      "max-retransmit": {
        "max-value": number,
        "min-value": number,
        "current-value": number
      },
      "ack-timeout": {
        "max-value-decimal": "string",
        "min-value-decimal": "string",
        "current-value-decimal": "string"
      },
      "ack-random-factor": {
        "max-value-decimal": "string",
        "min-value-decimal": "string",
        "current-value-decimal": "string"
      }
    },
    "idle-config": {
      "heartbeat-interval": {
        "max-value": number,
        "min-value": number,
        "current-value": number
      },
      "missing-hb-allowed": {
        "max-value": number,
        "min-value": number,
        "current-value": number
      },
```

```
          "max-retransmit": {
            "max-value": number,
            "min-value": number,
            "current-value": number
          },
          "ack-timeout": {
            "max-value-decimal": "string",
            "min-value-decimal": "string",
            "current-value-decimal": "string"
          },
          "ack-random-factor": {
            "max-value-decimal": "string",
            "min-value-decimal": "string",
            "current-value-decimal": "string"
          }
        }
      }
   }
}
```

               Figure 19: GET Configuration Response Body Schema

   The parameters in Figure 19 are described below:

   mitigating-config: Set of configuration parameters to use when a
      mitigation is active. The following parameters may be included:

      heartbeat-interval: Time interval in seconds between two
         consecutive heartbeat messages.

         '0' is used to disable the heartbeat mechanism.

         This is an optional attribute.

      missing-hb-allowed: Maximum number of consecutive heartbeat
         messages for which the DOTS agent did not receive a response
         before concluding that the session is disconnected.

         This is an optional attribute.

      max-retransmit: Maximum number of retransmissions for a message
         (referred to as MAX_RETRANSMIT parameter in CoAP).

         This is an optional attribute.

      ack-timeout: Timeout value in seconds used to calculate the
         initial retransmission timeout value (referred to as
         ACK_TIMEOUT parameter in CoAP).

         This is an optional attribute.

      ack-random-factor: Random factor used to influence the timing of
         retransmissions (referred to as ACK_RANDOM_FACTOR parameter in
         CoAP).

         This is an optional attribute.

   idle-config: Set of configuration parameters to use when no
      mitigation is active. This attribute has the same structure as
      'mitigating-config'.

   Figure 20 shows an example of acceptable and current configuration
   parameters on a DOTS server for DOTS signal channel session
   configuration. The same acceptable configuration is used during
   mitigation and idle times.

```
{
   "ietf-dots-signal-channel:signal-config": {
     "mitigating-config": {
       "heartbeat-interval": {
         "max-value": 240,
         "min-value": 15,
         "current-value": 30
       },
       "missing-hb-allowed": {
         "max-value": 9,
         "min-value": 3,
         "current-value": 5
       },
       "max-retransmit": {
         "max-value": 15,
         "min-value": 2,
         "current-value": 3
       },
       "ack-timeout": {
         "max-value-decimal": "30.00",
         "min-value-decimal": "1.00",
         "current-value-decimal": "2.00"
       },
       "ack-random-factor": {
         "max-value-decimal": "4.00",
         "min-value-decimal": "1.10",
         "current-value-decimal": "1.50"
       }
     },
```

```
        "idle-config": {
          "heartbeat-interval": {
            "max-value": 240,
            "min-value": 15,
            "current-value": 30
          },
          "missing-hb-allowed": {
            "max-value": 9,
            "min-value": 3,
            "current-value": 5
          },
          "max-retransmit": {
            "max-value": 15,
            "min-value": 2,
            "current-value": 3
          },
          "ack-timeout": {
            "max-value-decimal": "30.00",
            "min-value-decimal": "1.00",
            "current-value-decimal": "2.00"
          },
          "ack-random-factor": {
            "max-value-decimal": "4.00",
            "min-value-decimal": "1.10",
            "current-value-decimal": "1.50"
          }
        }
      }
    }
```

                Figure 20: Example of a Configuration Response Body

4.5.2. Convey DOTS Signal Channel Session Configuration

   A PUT request (Figures 21 and 22) is used to convey the configuration
   parameters for the signal channel (e.g., heartbeat interval, maximum
   retransmissions). Message transmission parameters for CoAP are
   defined in Section 4.8 of [RFC7252]. The RECOMMENDED values of
   transmission parameter values are ack-timeout (2 seconds), max-
   retransmit (3), ack-random-factor (1.5). In addition to those
   parameters, the RECOMMENDED specific DOTS transmission parameter
   values are 'heartbeat-interval' (30 seconds) and 'missing-hb-allowed'
   ~~(5).~~
   (15).

      Note: heartbeat-interval should be tweaked to also assist DOTS
      messages for NAT traversal (SIG-011 of [RFC8612]). According to
      [RFC8085], ~~keepalive~~ **heartbeat** messages must not be sent more frequently
      than once every 15 seconds and should use longer intervals when
      possible. Furthermore, [RFC4787] recommends NATs to use a state
      timeout of 2 minutes or longer, but experience shows that sending
      packets every 15 to 30 seconds is necessary to prevent the
      majority of middleboxes from losing state for UDP flows. From
      that standpoint, the RECOMMENDED minimum heartbeat-interval is 15
      seconds and the RECOMMENDED maximum heartbeat-interval is 240
      seconds. The recommended value of 30 seconds is selected to
      anticipate the expiry of NAT state.

      A heartbeat-interval of 30 seconds may be considered as too chatty
      in some deployments. For such deployments, DOTS agents may
      negotiate longer heartbeat-interval values to prevent any network
      overload with too frequent ~~keepalives.~~ **heartbeats.**

      Different heartbeat intervals can be defined for 'mitigating-
      config' and 'idle-config' to reduce being too chatty during idle
      times. If there is an on-path translator between the DOTS client
      (standalone or part of a DOTS gateway) and the DOTS server, the
      'mitigating-config' heartbeat-interval has to be smaller than the
      translator session timeout. It is recommended that the 'idle-
      config' heartbeat-interval is ~~also smaller than the translator~~
~~   session timeout to prevent translator traversal issues, or~~
~~   disabled entirely. Means to discover the lifetime assigned by a~~
~~   translator are out of scope.~~

~~   Section 4.2 of [RFC7252] defines a "CoAP Ping" mechanism.~~
~~   Concretely, the DOTS agent sends an Empty Confirmable message and the~~
~~   peer DOTS agent will respond by sending a Reset message.~~

~~   When a Confirmable "CoAP Ping" is sent, and if there is no response,~~
~~   the "CoAP Ping" is retransmitted max-retransmit number of times by~~
~~   the CoAP layer using an initial timeout set to a random duration~~
~~   between ack-timeout and (ack-timeout*ack-random-factor) and~~
~~   exponential back-off between retransmissions. By choosing the~~
~~   recommended transmission parameters, the "CoAP Ping" will timeout~~
~~   after 45 seconds. If the DOTS agent does not receive any response~~
~~   from the peer DOTS agent for 'missing-hb-allowed' number of~~
~~   consecutive "CoAP Ping" Confirmable messages, it concludes that the~~
~~   DOTS signal channel session is disconnected. A DOTS client MUST NOT~~
~~   transmit a "CoAP Ping" while waiting for~~ **also smaller than** the ~~previous "CoAP Ping"~~
~~   response from~~ **translator**
      session timeout to prevent translator traversal issues, or
      disabled entirely. Means to discover the ~~same DOTS server.~~ **lifetime assigned by a**
      translator are out of scope.

   If the DOTS agent wishes to change the default values of message

transmission parameters, it SHOULD follow the guidance given in
Section 4.8.1 of [RFC7252]. The DOTS agents MUST use the negotiated
values for message transmission parameters and default values for
non-negotiated message transmission parameters.

The signal channel session configuration is applicable to a single
DOTS signal channel session between DOTS agents, so the 'cuid' Uri-
Path MUST NOT be used.

```
  Header: PUT (Code=0.03)
  Uri-Path: ".well-known"
  Uri-Path: "dots"
  Uri-Path: "config"
  Uri-Path: "sid=123"
  Content-Format: "application/dots+cbor"

  {
   ...
  }
```

         Figure 21: PUT to Convey the DOTS Signal Channel Session
                           Configuration Data

The additional Uri-Path parameter to those defined in Table 1 is as
follows:

sid: Session Identifier is an identifier for the DOTS signal channel
     session configuration data represented as an integer. This
     identifier MUST be generated by DOTS clients. 'sid' values MUST
     increase monotonically (when a new PUT is generated by a DOTS
     client to convey the configuration parameters for the signal
     channel).

     This is a mandatory attribute.

```
   {
     "ietf-dots-signal-channel:signal-config": {
       "mitigating-config": {
         "heartbeat-interval": {
           "current-value": number
         },
         "missing-hb-allowed": {
           "current-value": number
         },
         "max-retransmit": {
           "current-value": number
         },
         "ack-timeout": {
           "current-value-decimal": "string"
         },
         "ack-random-factor": {
           "current-value-decimal": "string"
         }
       },
       "idle-config": {
         "heartbeat-interval": {
           "current-value": number
         },
         "missing-hb-allowed": {
           "current-value": number
         },
         "max-retransmit": {
           "current-value": number
         },
         "ack-timeout": {
           "current-value-decimal": "string"
         },
         "ack-random-factor": {
           "current-value-decimal": "string"
         }
       }
     }
   }
```

         Figure 22: PUT to Convey the DOTS Signal Channel Session
                   Configuration Data (Message Body Schema)

The meaning of the parameters in the CBOR body (Figure 22) is defined
in Section 4.5.1.

At least one of the attributes 'heartbeat-interval', 'missing-hb-
allowed', 'max-retransmit', 'ack-timeout', and 'ack-random-factor'
MUST be present in the PUT request. Note that 'heartbeat-interval',
'missing-hb-allowed', 'max-retransmit', 'ack-timeout', and 'ack-
random-factor', if present, do not need to be provided for both
'mitigating-config', and 'idle-config' in a PUT request.

The PUT request with a higher numeric 'sid' value overrides the DOTS
signal channel session configuration data installed by a PUT request
with a lower numeric 'sid' value. To avoid maintaining a long list
of 'sid' requests from a DOTS client, the lower numeric 'sid' MUST be
automatically deleted and no longer available at the DOTS server.

Figure 23 shows a PUT request example to convey the configuration
parameters for the DOTS signal channel. In this example, the

heartbeat mechanism is disabled when no mitigation is active, while
the heartbeat interval is set to '91' when a mitigation is active.

```
  Header: PUT (Code=0.03)
  Uri-Path: ".well-known"
  Uri-Path: "dots"
  Uri-Path: "config"
  Uri-Path: "sid=123"
  Content-Format: "application/dots+cbor"

  {
    "ietf-dots-signal-channel:signal-config": {
      "mitigating-config": {
        "heartbeat-interval": {
          "current-value": 91
        },
        "missing-hb-allowed": {
          "current-value": 3
        },
        "max-retransmit": {
          "current-value": 3
        },
        "ack-timeout": {
          "current-value-decimal": "2.00"
        },
        "ack-random-factor": {
          "current-value-decimal": "1.50"
        }
      },
      "idle-config": {
        "heartbeat-interval": {
          "current-value": 0
        },
        "max-retransmit": {
          "current-value": 3
        },
        "ack-timeout": {
          "current-value-decimal": "2.00"
        },
        "ack-random-factor": {
          "current-value-decimal": "1.50"
        }
      }
    }
  }
```

           Figure 23: PUT to Convey the Configuration Parameters

The DOTS server indicates the result of processing the PUT request
using CoAP response codes:

o If the request is missing a mandatory attribute, does not include
   a 'sid' Uri-Path, or contains one or more invalid or unknown
   parameters, 4.00 (Bad Request) MUST be returned in the response.

o If the DOTS server does not find the 'sid' parameter value
   conveyed in the PUT request in its configuration data and if the
   DOTS server has accepted the configuration parameters, then a
   response code 2.01 (Created) MUST be returned in the response.

o If the DOTS server finds the 'sid' parameter value conveyed in the
   PUT request in its configuration data and if the DOTS server has
   accepted the updated configuration parameters, 2.04 (Changed) MUST
   be returned in the response.

o If any of the 'heartbeat-interval', 'missing-hb-allowed', 'max-
   retransmit', 'target-protocol', 'ack-timeout', and 'ack-random-
   factor' attribute values are not acceptable to the DOTS server,
   4.22 (Unprocessable Entity) MUST be returned in the response.
   Upon receipt of this error code, the DOTS client SHOULD retrieve
   the maximum and minimum attribute values acceptable to the DOTS
   server (Section 4.5.1).

   The DOTS client may re-try and send the PUT request with updated
   attribute values acceptable to the DOTS server.

A DOTS client may issue a GET message with 'sid' Uri-Path parameter
to retrieve the negotiated configuration. The response does not need
to include 'sid' in its message body.

4.5.3. Configuration Freshness and Notifications

Max-Age Option (Section 5.10.5 of [RFC7252]) SHOULD be returned by a
DOTS server to associate a validity time with a configuration it
sends. This feature allows the update of the configuration data if a
change occurs at the DOTS server side. For example, the new
configuration may instruct a DOTS client to cease heartbeats or
reduce heartbeat frequency.

It is NOT RECOMMENDED to return a Max-Age Option set to 0.

Returning a Max-Age Option set to 2**32-1 is equivalent to
associating an infinite lifetime with the configuration.

If a non-zero value of Max-Age Option is received by a DOTS client,

it MUST issue a GET request with 'sid' Uri-Path parameter to retrieve
the current and acceptable configuration before the expiry of the
value enclosed in the Max-Age option. This request is considered by
the client and the server as a means to refresh the configuration
parameters for the signal channel. When a DDoS attack is active,
refresh requests MUST NOT be sent by DOTS clients and the DOTS server
MUST NOT terminate the (D)TLS session after the expiry of the value
returned in Max-Age Option.

If Max-Age Option is not returned in a response, the DOTS client
initiates GET requests to refresh the configuration parameters each
60 seconds (Section 5.10.5 of [RFC7252]). To prevent such overload,
it is RECOMMENDED that DOTS servers return a Max-Age Option in GET
responses. Considerations related to which value to use and how such
value is set, are implementation- and deployment-specific.

If an Observe Option set to 0 is included in the configuration
request, the DOTS server sends notifications of any configuration
change (Section 4.2 of [RFC7641]).

If a DOTS server detects that a misbehaving DOTS client does not
contact the DOTS server after the expiry of Max-Age and retrieve the
signal channel configuration data, it MAY terminate the (D)TLS
session. A (D)TLS session is terminated by the receipt of an
authenticated message that closes the connection (e.g., a fatal alert
(Section 6 of [RFC8446])).

4.5.4. Delete DOTS Signal Channel Session Configuration

   A DELETE request is used to delete the installed DOTS signal channel
   session configuration data (Figure 24).

      Header: DELETE (Code=0.04)
      Uri-Path: ".well-known"
      Uri-Path: "dots"
      Uri-Path: "config"
      Uri-Path: "sid=123"

                     Figure 24: Delete Configuration

   The DOTS server resets the DOTS signal channel session configuration
   back to the default values and acknowledges a DOTS client's request
   to remove the DOTS signal channel session configuration using 2.02
   (Deleted) response code.

   Upon bootstrapping or reboot, a DOTS client MAY send a DELETE request
   to set the configuration parameters to default values. Such a
   request does not include any 'sid'.

4.6. Redirected Signaling

   Redirected DOTS signaling is discussed in detail in Section 3.2.2 of
   [I-D.ietf-dots-architecture].

   If a DOTS server wants to redirect a DOTS client to an alternative
   DOTS server for a signal session, then the response code 5.03
   (Service Unavailable) will be returned in the response to the DOTS
   client.

   The DOTS server can return the error response code 5.03 in response
   to a request from the DOTS client or convey the error response code
   5.03 in a unidirectional notification response from the DOTS server.

   The DOTS server in the error response conveys the alternate DOTS
   server's FQDN, and the alternate DOTS server's IP address(es) values
   in the CBOR body (Figure 25).

   {
     "ietf-dots-signal-channel:redirected-signal": {
       "alt-server": "string",
       "alt-server-record": [
          "string"
        ]
   }

          Figure 25: Redirected Server Error Response Body Schema

   The parameters are described below:

   alt-server: FQDN of an alternate DOTS server.

      This is a mandatory attribute.

   alt-server-record: A list of IP addresses of an alternate DOTS
      server.

      This is an optional attribute.

   The DOTS server returns the Time to live (TTL) of the alternate DOTS
   server in a Max-Age Option. That is, the time interval that the
   alternate DOTS server may be cached for use by a DOTS client. A Max-
   Age Option set to 2**32-1 is equivalent to receiving an infinite TTL.
   This value means that the alternate DOTS server is to be used until
   the alternate DOTS server redirects the traffic with another 5.03
   response which encloses an alternate server.

A Max-Age Option set to '0' may be returned for redirecting
mitigation requests. Such value means that the redirection applies
only for the mitigation request in progress. Returning short TTL in
a Max-Age Option may adversely impact DOTS clients on slow links.
Returning short values should be avoided under such conditions.

If the alternate DOTS server TTL has expired, the DOTS client MUST
use the DOTS server(s), that was provisioned using means discussed in
Section 4.1. This fall back mechanism is triggered immediately upon
expiry of the TTL, except when a DDoS attack is active.

Requests issued by misbehaving DOTS clients which do not honor the
TTL conveyed in the Max-Age Option or react to explicit re-direct
messages can be rejected by DOTS servers.

Figure 26 shows a 5.03 response example to convey the DOTS alternate
server 'alt-server.example' together with its IP addresses
2001:db8:6401::1 and 2001:db8:6401::2.

```
{
  "ietf-dots-signal-channel:redirected-signal": {
    "alt-server": "alt-server.example",
    "alt-server-record": [
       "2001:db8:6401::1",
       "2001:db8:6401::2"
     ]
}
```

          Figure 26: Example of Redirected Server Error Response Body

When the DOTS client receives 5.03 response with an alternate server
included, it considers the current request as failed, but SHOULD try
re-sending the request to the alternate DOTS server. During a DDoS
attack, the DNS server may be the target of another DDoS attack,
alternate DOTS server's IP addresses conveyed in the 5.03 response
help the DOTS client skip DNS lookup of the alternate DOTS server, at
the cost of trusting the first DOTS server to provide accurate
information. The DOTS client can then try to establish a UDP or a
TCP session with the alternate DOTS server. The DOTS client MAY
implement a method to construct IPv4-embedded IPv6 addresses
[RFC6052]; this is required to handle the scenario where an IPv6-only
DOTS client communicates with an IPv4-only alternate DOTS server.

If the DOTS client has been redirected to a DOTS server to which it
has already communicated with within the last five (5) minutes, it
MUST ignore the redirection and try to contact other DOTS servers
listed in the local configuration or discovered using dynamic means
such as DHCP or SRV procedures [I-D.ietf-dots-server-discovery]. It
is RECOMMENDED that DOTS clients support means to alert
administrators about redirect loops.

4.7. Heartbeat Mechanism

To provide an indication of signal health and distinguish an 'idle'
signal channel from a 'disconnected' or 'defunct' session, the DOTS
agent sends a heartbeat over the signal channel to maintain its half
of the channel (also, aligned with the "consents" recommendation in
Section 6 of [RFC8085]). The DOTS agent similarly expects a
heartbeat from its peer DOTS agent, and may consider a session
terminated in the prolonged absence of a peer agent heartbeat.
Concretely, while the communication between the DOTS agents is
otherwise quiescent, the DOTS client will probe the DOTS server to
ensure it has maintained cryptographic state and vice versa. Such
probes can also keep firewalls and/or stateful translators bindings
alive. This probing reduces the frequency of establishing a new
handshake when a DOTS signal needs to be conveyed to the DOTS server.

**Implementation Note: Given that CoAP roles can be multiplexed over
the same session as discussed in [RFC7252] and already supported
by CoAP implementations, both the DOTS client and server can send
DOTS heartbeat requests.**

**The DOTS Heartbeat mechanism uses non-confirmable GET requests
(Figure 27) with an expected 2.03 response (Figure 28). The GET
request used for DOTS heartbeat MUST NOT have a 'cuid', 'cdid,' or
'mid' Uri-Path. Such GET requests MUST NOT be relayed by DOTS
gateways.**

```
     Header: GET (Code=0.01)
     Uri-Path: ".well-known"
     Uri-Path: "dots"
     Uri-Path: "hb"
```

        Figure 27: GET to Check Peer DOTS Agent is Responding

```
     Header: (Code=2.03)
```

              Figure 28: Response to a Heartbeat Request

DOTS servers MAY trigger their heartbeat requests immediately after
receiving heartbeat probes from peer DOTS clients. As a reminder, it
is the responsibility of DOTS clients to ensure that on-path
translators/firewalls are maintaining a binding so that the same
external IP address and/or port number is retained for the DOTS

signal channel session.

Under normal traffic conditions (i.e., no attack is ongoing), if a DOTS agent does not receive any response from the peer DOTS agent for 'missing-hb-allowed' number of consecutive heartbeat messages, it concludes that the DOTS signal channel session is disconnected. The DOTS client MUST then try to resume the (D)TLS session.

In case of a massive DDoS attack that saturates the incoming link(s) to the DOTS client, all traffic from the DOTS server to the DOTS client will likely be dropped, although the DOTS server receives heartbeat requests in addition to DOTS messages sent by the DOTS client. In this scenario, DOTS clients MUST behave differently to handle message transmission and DOTS signal channel session liveliness during link saturation:

   The DOTS client MUST NOT consider the DOTS signal channel session terminated even after a maximum 'missing-hb-allowed' threshold is reached. The DOTS client SHOULD keep on using the current DOTS signal channel session to send heartbeat requests over it, so that the DOTS server knows the DOTS client has not disconnected the DOTS signal channel session.

   After the maximum 'missing-hb-allowed' threshold is reached, the DOTS client SHOULD try to resume the (D)TLS session. The DOTS client SHOULD send mitigation requests over the current DOTS signal channel session, and in parallel, for example, try to resume the (D)TLS session or use 0-RTT mode in DTLS 1.3 to piggyback the mitigation request in the ClientHello message.

   As soon as the link is no longer saturated, if traffic from the DOTS server reaches the DOTS client over the current DOTS signal channel session, the DOTS client can stop (D)TLS session resumption or if (D)TLS session resumption is successful then disconnect the current DOTS signal channel session.

If the DOTS server receives traffic from the peer DOTS client (e.g., peer DOTS client initiated heartbeats) but maximum 'missing-hb-allowed' threshold is reached, the DOTS server MUST NOT consider the DOTS signal channel session disconnected. The DOTS server MUST keep on using the current DOTS signal channel session so that the DOTS client can send mitigation requests over the current DOTS signal channel session. In this case, the DOTS server can identify the DOTS client is under attack and the inbound link to the DOTS client (domain) is saturated. Furthermore, if the DOTS server does not receive a mitigation request from the DOTS client, it implies the DOTS client has not detected the attack or, if an attack mitigation is in progress, it implies the applied DDoS mitigation actions are not yet effective to handle the DDoS attack volume.

If the DOTS server does not receive any traffic from the peer DOTS client during the time span required to exhaust the maximum 'missing-hb-allowed' threshold, the DOTS server concludes the session is disconnected. The DOTS server can then trigger pre-configured mitigation requests for this DOTS client (if any).

In DOTS over ~~UDP, heartbeat messages MUST be exchanged between the DOTS agents using the "CoAP Ping" mechanism defined in Section 4.2 of [RFC7252].~~

~~In DOTS over~~ TCP, ~~heartbeat messages MUST be exchanged between the DOTS agents using the Ping and Pong messages specified in Section 5.4 of [RFC8323]. That is, the DOTS agent sends a Ping message and~~ the ~~peer DOTS agent would respond by sending a single Pong message. The~~ sender of a ~~Ping~~ **DOTS heartbeat** message has to allow up to 'heartbeat-interval' seconds when waiting for a ~~Pong~~ **heartbeat** reply. When a failure is detected by a DOTS client, it proceeds with the session recovery following the same approach as the one used for unreliable transports.

5. DOTS Signal Channel YANG Modules

   This document defines a YANG [RFC7950] module for DOTS mitigation scope, DOTS signal channel session configuration data, and DOTS redirection signaling.

   This YANG module (ietf-dots-signal-channel) defines the DOTS client interaction with the DOTS server as seen by the DOTS client. A DOTS server is allowed to update the non-configurable 'ro' entities in the responses. This YANG module is not intended to be used via NETCONF/ RESTCONF for DOTS server management purposes; such module is out of the scope of this document. It serves only to provide a data model and encoding, but not a management data model.

   A companion YANG module is defined to include a collection of types defined by IANA: "iana-dots-signal-channel" (Section 5.2).

5.1. Tree Structure

   This document defines the YANG module "ietf-dots-signal-channel" (Section 5.3), which has the following tree structure. A DOTS signal message can be a mitigation, a configuration, or a redirect message.

```
module: ietf-dots-signal-channel
    +--rw dots-signal
       +--rw (message-type)?
```

```
                 +--:(mitigation-scope)
                 |  +--rw scope* [cuid mid]
                 |     +--rw cdid?                 string
                 |     +--rw cuid                  string
                 |     +--rw mid                   uint32
                 |     +--rw target-prefix*        inet:ip-prefix
                 |     +--rw target-port-range*    [lower-port]
                 |     |  +--rw lower-port    inet:port-number
                 |     |  +--rw upper-port?   inet:port-number
                 |     +--rw target-protocol*      uint8
                 |     +--rw target-fqdn*          inet:domain-name
                 |     +--rw target-uri*           inet:uri
                 |     +--rw alias-name*           string
                 |     +--rw lifetime?             int32
                 |     +--rw trigger-mitigation?   boolean
                 |     +--ro mitigation-start?     uint64
                 |     +--ro status?               iana-signal:status
                 |     +--ro conflict-information
                 |     |  +--ro conflict-status?   iana-signal:conflict-status
                 |     |  +--ro conflict-cause?    iana-signal:conflict-cause
                 |     |  +--ro retry-timer?       uint32
                 |     |  +--ro conflict-scope
                 |     |     +--ro target-prefix*        inet:ip-prefix
                 |     |     +--ro target-port-range*    [lower-port]
                 |     |     |  +--ro lower-port    inet:port-number
                 |     |     |  +--ro upper-port?   inet:port-number
                 |     |     +--ro target-protocol*      uint8
                 |     |     +--ro target-fqdn*          inet:domain-name
                 |     |     +--ro target-uri*           inet:uri
                 |     |     +--ro alias-name*           string
                 |     |     +--ro acl-list* [acl-name]
                 |     |     |  +--ro acl-name
                 |     |     |  |     -> /ietf-data:dots-data/dots-client/acls/
                 |     |     |  |        acl/name
                 |     |     |  +--ro acl-type?
                 |     |     |        -> /ietf-data:dots-data/dots-client/acls/
                 |     |     |           acl/type
                 |     |     +--ro mid?                  -> ../../../mid
                 |     +--ro bytes-dropped?        yang:zero-based-counter64
                 |     +--ro bps-dropped?          yang:gauge64
                 |     +--ro pkts-dropped?         yang:zero-based-counter64
                 |     +--ro pps-dropped?          yang:gauge64
                 |     +--rw attack-status?        iana-signal:attack-status
                 +--:(signal-config)
                 |  +--rw sid                 uint32
                 |  +--rw mitigating-config
                 |  |  +--rw heartbeat-interval
                 |  |  |  +--ro max-value?       uint16
                 |  |  |  +--ro min-value?       uint16
                 |  |  |  +--rw current-value?   uint16
                 |  |  +--rw missing-hb-allowed
                 |  |  |  +--ro max-value?       uint16
                 |  |  |  +--ro min-value?       uint16
                 |  |  |  +--rw current-value?   uint16
                 |  |  +--rw max-retransmit
                 |  |  |  +--ro max-value?       uint16
                 |  |  |  +--ro min-value?       uint16
                 |  |  |  +--rw current-value?   uint16
                 |  |  +--rw ack-timeout
                 |  |  |  +--ro max-value-decimal?       decimal64
                 |  |  |  +--ro min-value-decimal?       decimal64
                 |  |  |  +--rw current-value-decimal?   decimal64
                 |  |  +--rw ack-random-factor
                 |  |     +--ro max-value-decimal?       decimal64
                 |  |     +--ro min-value-decimal?       decimal64
                 |  |     +--rw current-value-decimal?   decimal64
                 |  +--rw idle-config
                 |     +--rw heartbeat-interval
                 |     |  +--ro max-value?       uint16
                 |     |  +--ro min-value?       uint16
                 |     |  +--rw current-value?   uint16
                 |     +--rw missing-hb-allowed
                 |     |  +--ro max-value?       uint16
                 |     |  +--ro min-value?       uint16
                 |     |  +--rw current-value?   uint16
                 |     +--rw max-retransmit
                 |     |  +--ro max-value?       uint16
                 |     |  +--ro min-value?       uint16
                 |     |  +--rw current-value?   uint16
                 |     +--rw ack-timeout
                 |     |  +--ro max-value-decimal?       decimal64
                 |     |  +--ro min-value-decimal?       decimal64
                 |     |  +--rw current-value-decimal?   decimal64
                 |     +--rw ack-random-factor
                 |        +--ro max-value-decimal?       decimal64
                 |        +--ro min-value-decimal?       decimal64
                 |        +--rw current-value-decimal?   decimal64
                 +--:(redirected-signal)
                    +--ro alt-server           string
                    +--ro alt-server-record*   inet:ip-address
```

5.2. IANA DOTS Signal Channel YANG Module

```
   <CODE BEGINS> file "iana-dots-signal-channel@2019-01-17.yang"
   module iana-dots-signal-channel {
```

```
        yang-version 1.1;
        namespace "urn:ietf:params:xml:ns:yang:iana-dots-signal-channel";
        prefix iana-signal;

        organization
          "IANA";
        contact
          "Internet Assigned Numbers Authority

           Postal: ICANN
                12025 Waterfront Drive, Suite 300
                Los Angeles, CA  90094-2536
                United States of America
           Tel:    +1 310 301 5800
           <mailto:iana@iana.org>";
        description
          "This module contains a collection of YANG data types defined
           by IANA and used for DOTS signal channel protocol.

           Copyright (c) 2019 IETF Trust and the persons identified as
           authors of the code.  All rights reserved.

           Redistribution and use in source and binary forms, with or
           without modification, is permitted pursuant to, and subject
           to the license terms contained in, the Simplified BSD License
           set forth in Section 4.c of the IETF Trust's Legal Provisions
           Relating to IETF Documents
           (http://trustee.ietf.org/license-info).

           This version of this YANG module is part of RFC XXXX; see
           the RFC itself for full legal notices.";

        revision 2019-01-17 {
          description
            "Initial revision.";
          reference
            "RFC XXXX: Distributed Denial-of-Service Open Threat
                       Signaling (DOTS) Signal Channel Specification";
        }

        typedef status {
          type enumeration {
            enum attack-mitigation-in-progress {
              value 1;
              description
                "Attack mitigation setup is in progress (e.g., changing
                 the network path to re-route the inbound traffic
                 to DOTS mitigator).";
            }
            enum attack-successfully-mitigated {
              value 2;
              description
                "Attack is being successfully mitigated (e.g., traffic
                 is redirected to a DDoS mitigator and attack
                 traffic is dropped or blackholed).";
            }
            enum attack-stopped {
              value 3;
              description
                "Attack has stopped and the DOTS client can
                 withdraw the mitigation request.";
            }
            enum attack-exceeded-capability {
              value 4;
              description
                "Attack has exceeded the mitigation provider
                 capability.";
            }
            enum dots-client-withdrawn-mitigation {
              value 5;
              description
                "DOTS client has withdrawn the mitigation
                 request and the mitigation is active but
                 terminating.";
            }
            enum attack-mitigation-terminated {
              value 6;
              description
                "Attack mitigation is now terminated.";
            }
            enum attack-mitigation-withdrawn {
              value 7;
              description
                "Attack mitigation is withdrawn.";
            }
            enum attack-mitigation-signal-loss {
              value 8;
              description
                "Attack mitigation will be triggered
                 for the mitigation request only when
                 the DOTS signal channel session is lost.";
            }
          }
          description
            "Enumeration for status reported by the DOTS server.";
```

```
      }
      typedef conflict-status {
        type enumeration {
          enum request-inactive-other-active {
            value 1;
            description
              "DOTS Server has detected conflicting mitigation
               requests from different DOTS clients.
               This mitigation request is currently inactive
               until the conflicts are resolved. Another
               mitigation request is active.";

          }
          enum request-active {
            value 2;
            description
              "DOTS Server has detected conflicting mitigation
               requests from different DOTS clients.
               This mitigation request is currently active.";
          }
          enum all-requests-inactive {
            value 3;
            description
              "DOTS Server has detected conflicting mitigation
               requests from different DOTS clients.  All
               conflicting mitigation requests are inactive.";
          }
        }
        description
          "Enumeration for conflict status.";
      }

      typedef conflict-cause {
        type enumeration {
          enum overlapping-targets {
            value 1;
            description
              "Overlapping targets. conflict-scope provides
               more details about the exact conflict.";
          }
          enum conflict-with-acceptlist {
            value 2;
            description
              "Conflicts with an existing accept-list.

               This code is returned when the DDoS mitigation
               detects that some of the source addresses/prefixes
               listed in the accept-list ACLs are actually
               attacking the target.";
          }
          enum cuid-collision {
            value 3;
            description
              "Conflicts with the cuid used by another
               DOTS client.";
          }
        }
        description
          "Enumeration for conflict causes.";
      }
      typedef attack-status {
        type enumeration {
          enum under-attack {
            value 1;
            description
              "The DOTS client determines that it is still under
               attack.";
          }
          enum attack-successfully-mitigated {
            value 2;
            description
              "The DOTS client determines that the attack is
               successfully mitigated.";
          }
        }
        description
          "Enumeration for attack status codes.";
      }
    }
    <CODE ENDS>
```

5.3. IETF DOTS Signal Channel YANG Module

   This module uses the common YANG types defined in [RFC6991] and types
   defined in [I-D.ietf-dots-data-channel].

```
   <CODE BEGINS> file "ietf-dots-signal-channel@2019-01-17.yang"
   module ietf-dots-signal-channel {
     yang-version 1.1;
     namespace "urn:ietf:params:xml:ns:yang:ietf-dots-signal-channel";
     prefix signal;

     import ietf-inet-types {
       prefix inet;
```

```
                  reference "Section 4 of RFC 6991";
              }
              import ietf-yang-types {
                prefix yang;
                reference "Section 3 of RFC 6991";
              }
              import ietf-dots-data-channel {
                prefix ietf-data;
                reference
                  "RFC YYYY: Distributed Denial-of-Service Open Threat Signaling
                            (DOTS) Data Channel Specification";
              }
              import iana-dots-signal-channel {
                prefix iana-signal;

              }

              organization
                "IETF DDoS Open Threat Signaling (DOTS) Working Group";
              contact
                "WG Web:    <https://datatracker.ietf.org/wg/dots/>
                 WG List:   <mailto:dots@ietf.org>

                 Editor:    Konda, Tirumaleswar Reddy
                            <mailto:TirumaleswarReddy_Konda@McAfee.com>

                 Editor:    Mohamed Boucadair
                            <mailto:mohamed.boucadair@orange.com>

                 Author:    Prashanth Patil
                            <mailto:praspati@cisco.com>

                 Author:    Andrew Mortensen
                            <mailto:amortensen@arbor.net>

                 Author:    Nik Teague
                            <mailto:nteague@verisign.com>";
              description
                "This module contains YANG definition for the signaling
                 messages exchanged between a DOTS client and a DOTS server.

                 Copyright (c) 2019 IETF Trust and the persons identified as
                 authors of the code.  All rights reserved.

                 Redistribution and use in source and binary forms, with or
                 without modification, is permitted pursuant to, and subject
                 to the license terms contained in, the Simplified BSD License
                 set forth in Section 4.c of the IETF Trust's Legal Provisions
                 Relating to IETF Documents
                 (http://trustee.ietf.org/license-info).

                 This version of this YANG module is part of RFC XXXX; see
                 the RFC itself for full legal notices.";

              revision 2019-01-17 {
                description
                  "Initial revision.";
                reference
                  "RFC XXXX: Distributed Denial-of-Service Open Threat
                            Signaling (DOTS) Signal Channel Specification";
              }

              /*
               * Groupings
               */

              grouping mitigation-scope {
                description
                  "Specifies the scope of the mitigation request.";
                list scope {
                  key "cuid mid";
                  description
                    "The scope of the request.";
                  leaf cdid {
                    type string;
                    description
                      "The cdid should be included by a server-domain
                       DOTS gateway to propagate the client domain
                       identification information from the
                       gateway's client-facing-side to the gateway's
                       server-facing-side, and from the gateway's
                       server-facing-side to the DOTS server.

                       It may be used by the final DOTS server
                       for policy enforcement purposes.";
                  }
                  leaf cuid {
                    type string;
                    description
                      "A unique identifier that is
                       generated by a DOTS client to prevent
                       request collisions.  It is expected that the
                       cuid will remain consistent throughout the
                       lifetime of the DOTS client.";
                  }
```

```
            leaf mid {
              type uint32;
              description
                "Mitigation request identifier.

                 This identifier must be unique for each mitigation
                 request bound to the DOTS client.";
            }
            uses ietf-data:target;
            leaf-list alias-name {
              type string;
              description
                "An alias name that points to a resource.";
            }
            leaf lifetime {
              type int32;
              units "seconds";
              default "3600";
              description
                "Indicates the lifetime of the mitigation request.

                 A lifetime of '0' in a mitigation request is an
                 invalid value.

                 A lifetime of negative one (-1) indicates indefinite
                 lifetime for the mitigation request.";
            }
            leaf trigger-mitigation {
              type boolean;
              default "true";
              description
                "If set to 'false', DDoS mitigation will not be
                 triggered unless the DOTS signal channel
                 session is lost.";
            }
            leaf mitigation-start {
              type uint64;
              config false;
              description
                "Mitigation start time is represented in seconds
                 relative to 1970-01-01T00:00:00Z in UTC time.";
            }
            leaf status {
              type iana-signal:status;
              config false;
              description
                "Indicates the status of a mitigation request.
                 It must be included in responses only.";
            }
            container conflict-information {
              config false;
              description
                "Indicates that a conflict is detected.
                 Must only be used for responses.";
              leaf conflict-status {
                type iana-signal:conflict-status;
                description
                  "Indicates the conflict status.";
              }
              leaf conflict-cause {
                type iana-signal:conflict-cause;
                description
                  "Indicates the cause of the conflict.";
              }
              leaf retry-timer {
                type uint32;
                units "seconds";
                description
                  "The DOTS client must not re-send the
                   same request that has a conflict before the expiry of
                   this timer.";
              }
              container conflict-scope {
                description
                  "Provides more information about the conflict scope.";
                uses ietf-data:target {
                  when "../conflict-cause = 'overlapping-targets'";
                }
                leaf-list alias-name {
                  when "../../conflict-cause = 'overlapping-targets'";
                  type string;
                  description
                    "Conflicting alias-name.";
                }
                list acl-list {
                  when "../../conflict-cause = 'conflict-with-acceptlist'";
                  key "acl-name";
                  description
                    "List of conflicting ACLs as defined in the DOTS data
                     channel.  These ACLs are uniquely defined by
                     cuid and acl-name.";
                  leaf acl-name {
                    type leafref {
                      path "/ietf-data:dots-data/ietf-data:dots-client/"
                        + "ietf-data:acls/ietf-data:acl/ietf-data:name";
```

```
                    }
                    description
                      "Reference to the conflicting ACL name bound to
                       a DOTS client.";
                  }
                  leaf acl-type {
                    type leafref {
                      path "/ietf-data:dots-data/ietf-data:dots-client/"
                          + "ietf-data:acls/ietf-data:acl/ietf-data:type";
                    }
                    description
                      "Reference to the conflicting ACL type bound to
                       a DOTS client.";
                  }
                }
                leaf mid {
                  when "../../conflict-cause = 'overlapping-targets'";
                  type leafref {
                    path "../../../mid";
                  }
                  description
                    "Reference to the conflicting 'mid' bound to
                     the same DOTS client.";
                }
              }
            }
          }
          leaf bytes-dropped {
            type yang:zero-based-counter64;
            units "bytes";
            config false;
            description
              "The total dropped byte count for the mitigation
               request since the attack mitigation is triggered.
               The count wraps around when it reaches the maximum value
               of counter64 for dropped bytes.";
          }
          leaf bps-dropped {
            type yang:gauge64;
            config false;
            description
              "The average number of dropped bits per second for
               the mitigation request since the attack
               mitigation is triggered. This should be over
               five-minute intervals (that is, measuring bytes
               into five-minute buckets and then averaging these
               buckets over the time since the mitigation was
               triggered).";
          }
          leaf pkts-dropped {
            type yang:zero-based-counter64;
            config false;
            description
              "The total number of dropped packet count for the
               mitigation request since the attack mitigation is
               triggered.  The count wraps around when it reaches
               the maximum value of counter64 for dropped packets.";
          }
          leaf pps-dropped {
            type yang:gauge64;
            config false;
            description
              "The average number of dropped packets per second
               for the mitigation request since the attack
               mitigation is triggered. This should be over
               five-minute intervals (that is, measuring packets
               into five-minute buckets and then averaging these
               buckets over the time since the mitigation was
               triggered).";
          }
          leaf attack-status {
            type iana-signal:attack-status;
            description
              "Indicates the status of an attack as seen by the
               DOTS client.";
          }
        }
      }
    }

    grouping config-parameters {
      description
        "Subset of DOTS signal channel session configuration.";
      container heartbeat-interval {
        description
          "DOTS agents regularly send heartbeats to each other
           after mutual authentication is successfully
           completed in order to keep the DOTS signal channel
           open.";
        leaf max-value {
          type uint16;
          units "seconds";
          config false;
          description
            "Maximum acceptable heartbeat-interval value.";
        }
        leaf min-value {
```

```
              type uint16;
              units "seconds";
              config false;
              description
                "Minimum acceptable heartbeat-interval value.";
            }
            leaf current-value {
              type uint16;
              units "seconds";
              default "30";
              description
                "Current heartbeat-interval value.

                 '0' means that heartbeat mechanism is deactivated.";
            }
          }
          container missing-hb-allowed {
            description
              "Maximum number of missing heartbeats allowed.";
            leaf max-value {
              type uint16;
              config false;
              description
                "Maximum acceptable missing-hb-allowed value.";
            }
            leaf min-value {
              type uint16;
              config false;
              description
                "Minimum acceptable missing-hb-allowed value.";
            }
            leaf current-value {
              type uint16;
              default "5"; "15";
              description
                "Current missing-hb-allowed value.";
            }
          }
          container max-retransmit {
            description
              "Maximum number of retransmissions of a Confirmable
               message.";
            leaf max-value {
              type uint16;
              config false;
              description
                "Maximum acceptable max-retransmit value.";
            }
            leaf min-value {
              type uint16;
              config false;
              description
                "Minimum acceptable max-retransmit value.";
            }
            leaf current-value {
              type uint16;
              default "3";
              description
                "Current max-retransmit value.";
            }
          }
          container ack-timeout {
            description
              "Initial retransmission timeout value.";
            leaf max-value-decimal {
              type decimal64 {
                fraction-digits 2;
              }
              units "seconds";
              config false;
              description
                "Maximum ack-timeout value.";
            }
            leaf min-value-decimal {
              type decimal64 {
                fraction-digits 2;
              }
              units "seconds";
              config false;
              description
                "Minimum ack-timeout value.";
            }
            leaf current-value-decimal {
              type decimal64 {
                fraction-digits 2;
              }
              units "seconds";
              default "2";
              description
                "Current ack-timeout value.";
            }
          }
          container ack-random-factor {
            description
              "Random factor used to influence the timing of
```

```
                retransmissions.";
            leaf max-value-decimal {
              type decimal64 {
                fraction-digits 2;
              }
              config false;
              description
                "Maximum acceptable ack-random-factor value.";
            }
            leaf min-value-decimal {
              type decimal64 {
                fraction-digits 2;
              }
              config false;
              description
                "Minimum acceptable ack-random-factor value.";
            }
            leaf current-value-decimal {
              type decimal64 {
                fraction-digits 2;
              }
              default "1.5";
              description
                "Current ack-random-factor value.";
            }
          }
        }

        grouping signal-config {
          description
            "DOTS signal channel session configuration.";
          leaf sid {
            type uint32;
            mandatory true;
            description
              "An identifier for the DOTS signal channel
               session configuration data.";
          }
          container mitigating-config {
            description
              "Configuration parameters to use when a mitigation
               is active.";
            uses config-parameters;
          }
          container idle-config {
            description
              "Configuration parameters to use when no mitigation
               is active.";
            uses config-parameters;
          }
        }

        grouping redirected-signal {
          description
            "Grouping for the redirected signaling.";
          leaf alt-server {
            type string;
            config false;
            mandatory true;
            description
              "FQDN of an alternate server.";
          }
          leaf-list alt-server-record {
            type inet:ip-address;
            config false;
            description
              "List of records for the alternate server.";

          }
        }

        /*
         * Main Container for DOTS Signal Channel
         */

        container dots-signal {
          description
            "Main container for DOTS signal message.

             A DOTS signal message can be a mitigation, a configuration,
             or a redirected signal message.";
          choice message-type {
            description
              "Can be a mitigation, a configuration, or a redirect
               message.";
            case mitigation-scope {
              description
                "Mitigation scope of a mitigation message.";
              uses mitigation-scope;
            }
            case signal-config {
              description
                "Configuration message.";
              uses signal-config;
            }
```

```
                case redirected-signal {
                  description
                    "Redirected signaling.";
                  uses redirected-signal;
                }
              }
            }
          }
        }
        <CODE ENDS>
```

6. YANG/JSON Mapping Parameters to CBOR

   All parameters in the payload of the DOTS signal channel MUST be
   mapped to CBOR types as shown in Table 4 and are assigned an integer
   key to save space.

   o Note: Implementers must check that the mapping output provided by
      their YANG-to-CBOR encoding schemes is aligned with the content of
      Table 4. For example, some CBOR and JSON types for enumerations
      and the 64-bit quantities can differ depending on the encoder
      used.

   The CBOR key values are divided into two types: comprehension-
   required and comprehension-optional. DOTS agents can safely ignore
   comprehension-optional values they don't understand, but cannot
   successfully process a request if it contains comprehension-required
   values that are not understood. The 4.00 response SHOULD include a
   diagnostic payload describing the unknown comprehension-required CBOR
   key values. The initial set of CBOR key values defined in this
   specification are of type comprehension-required.

Parameter Name	YANG Type	CBOR Key	CBOR Major Type & Information	JSON Type
ietf-dots-signal-cha nnel:mitigation-scope	container	1	5 map	Object
scope	list	2	4 array	Array
cdid	string	3	3 text string	String
cuid	string	4	3 text string	String
mid	uint32	5	0 unsigned	Number
target-prefix	leaf-list inet: ip-prefix	6	4 array 3 text string	Array String
target-port-range	list	7	4 array	Array
lower-port	inet: port-number	8	0 unsigned	Number
upper-port	inet: port-number	9	0 unsigned	Number
target-protocol	leaf-list uint8	10	4 array 0 unsigned	Array Number
target-fqdn	leaf-list inet: domain-name	11	4 array 3 text string	Array String
target-uri	leaf-list inet:uri	12	4 array 3 text string	Array String
alias-name	leaf-list string	13	4 array 3 text string	Array String
lifetime	int32	14	0 unsigned 1 negative	Number Number
mitigation-start	uint64	15	0 unsigned	String
status	enumeration	16	0 unsigned	String
conflict-information	container	17	5 map	Object
conflict-status	enumeration	18	0 unsigned	String
conflict-cause	enumeration	19	0 unsigned	String
retry-timer	uint32	20	0 unsigned	Number
conflict-scope	container	21	5 map	Object
acl-list	list	22	4 array	Array
acl-name	leafref	23	3 text string	String
acl-type	leafref	24	3 text string	String
bytes-dropped	yang:zero- based- counter64	25	0 unsigned	String
bps-dropped	yang:gauge64	26	0 unsigned	String
pkts-dropped	yang:zero- based- counter64	27	0 unsigned	String
pps-dropped	yang:gauge64	28	0 unsigned	String
attack-status	enumeration	29	0 unsigned	String
ietf-dots-signal- channel:signal-config	container	30	5 map	Object
sid	uint32	31	0 unsigned	Number
mitigating-config	container	32	5 map	Object
heartbeat-interval	container	33	5 map	Object
max-value	uint16	34	0 unsigned	Number
min-value	uint16	35	0 unsigned	Number
current-value	uint16	36	0 unsigned	Number
missing-hb-allowed	container	37	5 map	Object
max-retransmit	container	38	5 map	Object
ack-timeout	container	39	5 map	Object
ack-random-factor	container	40	5 map	Object
max-value-decimal	decimal64	41	6 tag 4 [-2, integer]	String
min-value-decimal	decimal64	42	6 tag 4	

```
|                     |             |     |    | [-2, integer]| String |
| current-value-decimal| decimal64  | 43  | 6 tag 4      |        |
|                     |             |     |    | [-2, integer]| String |
| idle-config         | container   | 44  | 5 map        | Object |
| trigger-mitigation  | boolean     | 45  | 7 bits 20    | False  |
|                     |             |     | 7 bits 21    | True   |
| ietf-dots-signal-cha|             |     |              |        |
|nnel:redirected-signal| container  | 46  | 5 map        | Object |
| alt-server          | string      | 47  | 3 text string| String |
| alt-server-record   | leaf-list   | 48  | 4 array      | Array  |
|                     | inet:       |     |              |        |
|                     |  ip-address |     | 3 text string| String |
+---------------------+-------------+-----+--------------+--------+
```

    Table 4: CBOR Key Values Used in DOTS Signal Channel Messages & Their
             Mappings to JSON and YANG

7. (D)TLS Protocol Profile and Performance Considerations
7.1. (D)TLS Protocol Profile

    This section defines the (D)TLS protocol profile of DOTS signal
    channel over (D)TLS and DOTS data channel over TLS.

    There are known attacks on (D)TLS, such as man-in-the-middle and
    protocol downgrade attacks. These are general attacks on (D)TLS and,
    as such, they are not specific to DOTS over (D)TLS; refer to the
    (D)TLS RFCs for discussion of these security issues. DOTS agents
    MUST adhere to the (D)TLS implementation recommendations and security
    considerations of [RFC7525] except with respect to (D)TLS version.
    Since DOTS signal channel encryption relying upon (D)TLS is virtually
    a green-field deployment, DOTS agents MUST implement only (D)TLS 1.2
    or later.

    When a DOTS client is configured with a domain name of the DOTS
    server, and connects to its configured DOTS server, the server may
    present it with a PKIX certificate. In order to ensure proper
    authentication, a DOTS client MUST verify the entire certification
    path per [RFC5280]. Additionally, the DOTS client MUST use [RFC6125]
    validation techniques to compare the domain name with the certificate
    provided. Certification authorities that issue DOTS server
    certificates SHOULD support the DNS-ID and SRV-ID identifier types.
    DOTS server SHOULD prefer the use of DNS-ID and SRV-ID over CN-ID
    identifier types in certificate requests (as described in Section 2.3
    of [RFC6125]) and the wildcard character '*' SHOULD NOT be included
    in the presented identifier. DOTS doesn't use URI-IDs for server
    identity verification.

    A key challenge to deploying DOTS is the provisioning of DOTS
    clients, including the distribution of keying material to DOTS
    clients to enable the required mutual authentication of DOTS agents.
    Enrollment over Secure Transport (EST) [RFC7030] defines a method of
    certificate enrollment by which domains operating DOTS servers may
    provide DOTS clients with all the necessary cryptographic keying
    material, including a private key and a certificate to authenticate
    themselves.   One deployment option is DOTS clients behave as EST
    clients for certificate enrollment from an EST server provisioned by
    the mitigation provider. This document does not specify which EST or
    other mechanism the DOTS client uses to achieve initial enrollment.

    The Server Name Indication (SNI) extension [RFC6066] defines a
    mechanism for a client to tell a (D)TLS server the name of the server
    it wants to contact. This is a useful extension for hosting
    environments where multiple virtual servers are reachable over a
    single IP address. The DOTS client may or may not know if it is
    interacting with a DOTS server in a virtual server hosting
    environment, so the DOTS client SHOULD include the DOTS server FQDN
    in the SNI extension.

    Implementations compliant with this profile MUST implement all of the
    following items:

    o DTLS record replay detection (Section 3.3 of [RFC6347]) or an
       equivalent mechanism to protect against replay attacks.

    o DTLS session resumption without server-side state to resume
       session and convey the DOTS signal.

    o At least one of raw public keys [RFC7250] or PSK handshake
       [RFC4279] with (EC)DHE key exchange which reduces the size of the
       ServerHello, and can be used by DOTS agents that cannot obtain
       certificates.

    Implementations compliant with this profile SHOULD implement all of
    the following items to reduce the delay required to deliver a DOTS
    signal channel message:

    o TLS False Start [RFC7918] which reduces round-trips by allowing
       the TLS client's second flight of messages (ChangeCipherSpec) to
       also contain the DOTS signal. TLS False Start is formally defined
       for use with TLS, but the same technique is applicable to DTLS as
       well.

    o Cached Information Extension [RFC7924] which avoids transmitting
       the server's certificate and certificate chain if the client has
       cached that information from a previous TLS handshake.
```

Compared to UDP, DOTS signal channel over TCP requires an additional
round-trip time (RTT) of latency to establish a TCP connection. DOTS
implementations are encouraged to implement TCP Fast Open [RFC7413]
to eliminate that RTT.

7.2. (D)TLS 1.3 Considerations

   TLS 1.3 provides critical latency improvements for connection
   establishment over TLS 1.2. The DTLS 1.3 protocol
   [I-D.ietf-tls-dtls13] is based upon the TLS 1.3 protocol and provides
   equivalent security guarantees. (D)TLS 1.3 provides two basic
   handshake modes the DOTS signal channel can take advantage of:

   o A full handshake mode in which a DOTS client can send a DOTS
      mitigation request message after one round trip and the DOTS
      server immediately responds with a DOTS mitigation response. This
      assumes no packet loss is experienced.

   o 0-RTT mode in which the DOTS client can authenticate itself and
      send DOTS mitigation request messages in the first message, thus
      reducing handshake latency. 0-RTT only works if the DOTS client
      has previously communicated with that DOTS server, which is very
      likely with the DOTS signal channel.

      The DOTS client has to establish a (D)TLS session with the DOTS
      server during 'idle' time and share a PSK.

      During a DDoS attack, the DOTS client can use the (D)TLS session
      to convey the DOTS mitigation request message and, if there is no
      response from the server after multiple retries, the DOTS client
      can resume the (D)TLS session in 0-RTT mode using PSK.

      DOTS servers that support (D)TLS 1.3 MAY allow DOTS clients to
      send early data (0-RTT). DOTS clients MUST NOT send "CoAP Ping"
      as early data; such messages MUST be rejected by DOTS servers.
      Section 8 of [RFC8446] discusses some mechanisms to implement to
      limit the impact of replay attacks on 0-RTT data. If the DOTS
      server accepts 0-RTT, it MUST implement one of these mechanisms to
      prevent replay at the TLS layer. A DOTS server can reject 0-RTT
      by sending a TLS HelloRetryRequest.

      The DOTS signal channel messages sent as early data by the DOTS
      client are idempotent requests. As a reminder, the Message ID
      (Section 3 of [RFC7252]) is changed each time a new CoAP request
      is sent, and the Token (Section 5.3.1 of [RFC7252]) is randomized
      in each CoAP request. The DOTS server(s) MUST use the Message ID
      and the Token in the DOTS signal channel message to detect replay
      of early data at the application layer, and accept 0-RTT data at
      most once from the same DOTS client. This anti-replay defense
      requires sharing the Message ID and the Token in the 0-RTT data
      between DOTS servers in the DOTS server domain. DOTS servers do
      not rely on transport coordinates to identify DOTS peers. As
      specified in Section 4.4.1, DOTS servers couple the DOTS signal
      channel sessions using the DOTS client identity and optionally the
      'cdid' parameter value. Furthermore, 'mid' value is monotonically
      increased by the DOTS client for each mitigation request,
      attackers replaying mitigation requests with lower numeric 'mid'
      values and overlapping scopes with mitigation requests having
      higher numeric 'mid' values will be rejected systematically by the
      DOTS server. Likewise, 'sid' value is monotonically increased by
      the DOTS client for each configuration request (Section 4.5.2),
      attackers replaying configuration requests with lower numeric
      'sid' values will be rejected by the DOTS server if it maintains a
      higher numeric 'sid' value for this DOTS client.

      Owing to the aforementioned protections, all DOTS signal channel
      requests are safe to transmit in TLS 1.3 as early data. Refer to
      [I-D.boucadair-dots-earlydata] for more details.

      A simplified TLS 1.3 handshake with 0-RTT DOTS mitigation request
      message exchange is shown in Figure 27. **29.**

```
           DOTS Client                                DOTS Server

           ClientHello
           (0-RTT DOTS signal message)
                                    -------->
                                                          ServerHello
                                                  {EncryptedExtensions}
                                                             {Finished}
                                    <--------   [DOTS signal message]
           (end_of_early_data)
           {Finished}              -------->
           [DOTS signal message]   <------->   [DOTS signal message]

      Note that:
           () Indicates messages protected 0-RTT keys
           {} Indicates messages protected using handshake keys
           [] Indicates messages protected using 1-RTT keys

            Figure 27: **29:** A Simplified TLS 1.3 Handshake with 0-RTT
```

7.3. DTLS MTU and Fragmentation

To avoid DOTS signal message fragmentation and the subsequent
decreased probability of message delivery, DOTS agents MUST ensure
that the DTLS record fit within a single datagram. As a reminder,
DTLS handles fragmentation and reassembly only for handshake messages
and not for the application data (Section 4.1.1 of [RFC6347]). If
the PMTU cannot be discovered, DOTS agents MUST assume a PMTU of 1280
bytes, as IPv6 requires that every link in the Internet have an MTU
of 1280 octets or greater as specified in [RFC8200]. If IPv4 support
on legacy or otherwise unusual networks is a consideration and the
PMTU is unknown, DOTS implementations MAY assume on a PMTU of 576
bytes for IPv4 datagrams, as every IPv4 host must be capable of
receiving a packet whose length is equal to 576 bytes as discussed in
[RFC0791] and [RFC1122].

The DOTS client must consider the amount of record expansion expected
by the DTLS processing when calculating the size of CoAP message that
fits within the path MTU. Path MTU MUST be greater than or equal to
[CoAP message size + DTLS 1.2 overhead of 13 octets + authentication
overhead of the negotiated DTLS cipher suite + block padding]
(Section 4.1.1.1 of [RFC6347]). If the total request size exceeds
the path MTU then the DOTS client MUST split the DOTS signal into
separate messages; for example, the list of addresses in the 'target-
prefix' parameter could be split into multiple lists and each list
conveyed in a new PUT request.

Implementation Note: DOTS choice of message size parameters works
well with IPv6 and with most of today's IPv4 paths. However, with
IPv4, it is harder to safely make sure that there is no IP
fragmentation. If the IPv4 path MTU is unknown, implementations may
want to limit themselves to more conservative IPv4 datagram sizes
such as 576 bytes, as per [RFC0791].

8. Mutual Authentication of DOTS Agents & Authorization of DOTS Clients

   (D)TLS based upon client certificate can be used for mutual
   authentication between DOTS agents. If, for example, a DOTS gateway
   is involved, DOTS clients and DOTS gateways must perform mutual
   authentication; only authorized DOTS clients are allowed to send DOTS
   signals to a DOTS gateway. The DOTS gateway and the DOTS server must
   perform mutual authentication; a DOTS server only allows DOTS signal
   channel messages from an authorized DOTS gateway, thereby creating a
   two-link chain of transitive authentication between the DOTS client
   and the DOTS server.

   The DOTS server should support certificate-based client
   authentication. The DOTS client should respond to the DOTS server's
   TLS CertificateRequest message with the PKIX certificate held by the
   DOTS client. DOTS client certificate validation must be performed as
   per [RFC5280] and the DOTS client certificate must conform to the
   [RFC5280] certificate profile. If a DOTS client does not support TLS
   client certificate authentication, it must support pre-shared key
   based or raw public key based client authentication.

```
+-------------------------------------------+
|       example.com domain     +---------+  |
|                              |  AAA    |  |
|  +--------------+            | Server  |  |
|  | Application  |            +------+--+  |
|  | server       +<--------------+    ^    |
|  | (DOTS client)|               |    |    |
|  +--------------+               |    |    |
|                                 V    V    |   example.net domain
|                          +-----+----+--+  |   +---------------+
|  +--------------+        |             |  |   |               |
|  |    Guest     +<----x---->+   DOTS   +<------>+    DOTS      |
|  | (DOTS client)|        |  gateway |  |   |    server     |
|  +--------------+        |          |  |   |               |
|                          +----+-----+--+  |   +---------------+
|                               ^           |
|                               |           |
|  +---------------+            |           |
|  | DDoS detector |            |           |
|  | (DOTS client) +<------------+           |
|  +---------------+                         |
+-------------------------------------------+
```

   Figure 28: 30: Example of Authentication and Authorization of DOTS Agents

   In the example depicted in Figure 28, 30, the DOTS gateway and DOTS
   clients within the 'example.com' domain mutually authenticate. After
   the DOTS gateway validates the identity of a DOTS client, it
   communicates with the AAA server in the 'example.com' domain to
   determine if the DOTS client is authorized to request DDoS
   mitigation. If the DOTS client is not authorized, a 4.01
   (Unauthorized) is returned in the response to the DOTS client. In
   this example, the DOTS gateway only allows the application server and
   DDoS attack detector to request DDoS mitigation, but does not permit
   the user of type 'guest' to request DDoS mitigation.

   Also, DOTS gateways and servers located in different domains must
   perform mutual authentication (e.g., using certificates). A DOTS
   server will only allow a DOTS gateway with a certificate for a
   particular domain to request mitigation for that domain. In
   reference to Figure 28, 30, the DOTS server only allows the DOTS gateway
   to request mitigation for 'example.com' domain and not for other

   domains.

9. IANA Considerations

9.1. DOTS Signal Channel UDP and TCP Port Number

   IANA is requested to assign the port number TBD to the DOTS signal
   channel protocol for both UDP and TCP from the "Service Name and
   Transport Protocol Port Number Registry" available at
   https://www.iana.org/assignments/service-names-port-numbers/service-
   names-port-numbers.xhtml.

   The assignment of port number 4646 is strongly suggested, as 4646 is
   the ASCII decimal value for ".." (DOTS).

9.2. Well-Known 'dots' URI

   This document requests IANA to register the 'dots' well-known URI
   (Table 5) in the Well-Known URIs registry
   (https://www.iana.org/assignments/well-known-uris/well-known-
   uris.xhtml) as defined by [RFC5785]:

   +----------+----------------+--------------------+----------------+
   | URI | Change | Specification | Related |
   | suffix | controller | document(s) | information |
   +----------+----------------+--------------------+----------------+
   | dots | IETF | [RFCXXXX] | None |
   +----------+----------------+--------------------+----------------+

                     Table 5: 'dots' well-known URI

9.3. Media Type Registration

   This document requests IANA to register the "application/dots+cbor"
   media type in the "Media Types" registry [IANA.MediaTypes] in the
   manner described in [RFC6838], which can be used to indicate that the
   content is a DOTS signal channel object:

   o Type name: application
   o Subtype name: dots+cbor
   o Required parameters: N/A
   o Optional parameters: N/A
   o Encoding considerations: binary
   o Security considerations: See the Security Considerations section
      of [RFCXXXX]
   o Interoperability considerations: N/A
   o Published specification: [RFCXXXX]
   o Applications that use this media type: DOTS agents sending DOTS
      messages over CoAP over (D)TLS.
   o Fragment identifier considerations: N/A
   o Additional information:

         Magic number(s): N/A
         File extension(s): N/A
         Macintosh file type code(s): N/A
   o Person & email address to contact for further information:
      IESG, iesg@ietf.org
   o Intended usage: COMMON
   o Restrictions on usage: none
   o Author: See Authors' Addresses section.
   o Change controller: IESG
   o Provisional registration? No

9.4. CoAP Content-Formats Registration

   This document requests IANA to register the CoAP Content-Format ID
   for the "application/dots+cbor" media type in the "CoAP Content-
   Formats" registry [IANA.CoAP.Content-Formats] (0-255 range):

   o Media Type: application/dots+cbor
   o Encoding: -
   o Id: TBD1
   o Reference: [RFCXXXX]

9.5. CBOR Tag Registration

   This section defines the DOTS CBOR tag as another means for
   applications to declare that a CBOR data structure is a DOTS signal
   channel object. Its use is optional and is intended for use in cases
   in which this information would not otherwise be known. DOTS CBOR
   tag is not required for DOTS signal channel protocol version
   specified in this document. If present, the DOTS tag MUST prefix a
   DOTS signal channel object.

   This document requests IANA to register the DOTS signal channel CBOR
   tag in the "CBOR Tags" registry [IANA.CBOR.Tags] using the 24-255
   range:

   o CBOR Tag: TBD2 (please assign the same value as the Content-
      Format)
   o Data Item: DDoS Open Threat Signaling (DOTS) signal channel object
   o Semantics: DDoS Open Threat Signaling (DOTS) signal channel
      object, as defined in [RFCXXXX]
   o Description of Semantics: [RFCXXXX]

9.6. DOTS Signal Channel Protocol Registry

   The document requests IANA to create a new registry, entitled "DOTS
   Signal Channel Registry". The following sections define sub-
   registries.

9.6.1. DOTS Signal Channel CBOR Key Values Sub-Registry

   The document requests IANA to create a new sub-registry, entitled
   "DOTS Signal Channel CBOR Key Values".

   The structure of this sub-registry is provided in Section 9.6.1.1.
   Section 9.6.1.2 provides how the registry is initially populated with
   the values in Table 4.

9.6.1.1. Registration Template

   Parameter name:
      Parameter name as used in the DOTS signal channel.

   CBOR Key Value:
      Key value for the parameter. The key value MUST be an integer in
      the 1-65535 range. The key values of the comprehension-required
      range (0x0001 - 0x3FFF) and of the comprehension-optional range
      (0x8000 - 0xBFFF) are assigned by IETF Review (Section 4.8 of
      [RFC8126]). The key values of the comprehension-optional range
      (0x4000 - 0x7FFF) are assigned by Specification Required
      (Section 4.6 of [RFC8126]) and of the comprehension-optional range
      (0xC000 - 0xFFFF) are reserved for Private Use (Section 4.1 of
      [RFC8126]).

      Registration requests for the 0x4000 - 0x7FFF range are evaluated
      after a three-week review period on the dots-signal-reg-
      review@ietf.org mailing list, on the advice of one or more
      Designated Experts. However, to allow for the allocation of
      values prior to publication, the Designated Experts may approve
      registration once they are satisfied that such a specification
      will be published. New registration requests should be sent in
      the form of an email to the review mailing list; the request
      should use an appropriate subject (e.g., "Request to register CBOR
      Key Value for DOTS: example"). IANA will only accept new
      registrations from the Designated Experts, and will check that
      review was requested on the mailing list in accordance with these
      procedures.

      Within the review period, the Designated Experts will either
      approve or deny the registration request, communicating this
      decision to the review list and IANA. Denials should include an
      explanation and, if applicable, suggestions as to how to make the
      request successful. Registration requests that are undetermined
      for a period longer than 21 days can be brought to the IESG's
      attention (using the iesg@ietf.org mailing list) for resolution.

      Criteria that should be applied by the Designated Experts includes
      determining whether the proposed registration duplicates existing
      functionality, whether it is likely to be of general applicability
      or whether it is useful only for a single use case, and whether
      the registration description is clear. IANA must only accept
      registry updates to the 0x4000 - 0x7FFF range from the Designated
      Experts and should direct all requests for registration to the
      review mailing list. It is suggested that multiple Designated
      Experts be appointed. In cases where a registration decision
      could be perceived as creating a conflict of interest for a
      particular Expert, that Expert should defer to the judgment of the
      other Experts.

   CBOR Major Type:
      CBOR Major type and optional tag for the parameter.

   Change Controller:
      For Standards Track RFCs, list the "IESG". For others, give the
      name of the responsible party. Other details (e.g., email
      address) may also be included.

   Specification Document(s):
      Reference to the document or documents that specify the parameter,
      preferably including URIs that can be used to retrieve copies of
      the documents. An indication of the relevant sections may also be
      included but is not required.

9.6.1.2. Initial Sub-Registry Content

Parameter Name	CBOR Key Value	CBOR Major Type	Change Controller	Specification Document(s)
ietf-dots-signal-chan nel:mitigation-scope	1	5	IESG	[RFCXXXX]
scope	2	4	IESG	[RFCXXXX]
cdid	3	3	IESG	[RFCXXXX]
cuid	4	3	IESG	[RFCXXXX]
mid	5	0	IESG	[RFCXXXX]
target-prefix	6	4	IESG	[RFCXXXX]
target-port-range	7	4	IESG	[RFCXXXX]

```
      | lower-port            |   8   |   0   |    IESG     | [RFCXXXX]    |
      | upper-port            |   9   |   0   |    IESG     | [RFCXXXX]    |
      | target-protocol       |  10   |   4   |    IESG     | [RFCXXXX]    |
      | target-fqdn           |  11   |   4   |    IESG     | [RFCXXXX]    |
      | target-uri            |  12   |   4   |    IESG     | [RFCXXXX]    |
      | alias-name            |  13   |   4   |    IESG     | [RFCXXXX]    |
      | lifetime              |  14   |  0/1  |    IESG     | [RFCXXXX]    |
      | mitigation-start      |  15   |   0   |    IESG     | [RFCXXXX]    |
      | status                |  16   |   0   |    IESG     | [RFCXXXX]    |
      | conflict-information  |  17   |   5   |    IESG     | [RFCXXXX]    |
      | conflict-status       |  18   |   0   |    IESG     | [RFCXXXX]    |
      | conflict-cause        |  19   |   0   |    IESG     | [RFCXXXX]    |
      | retry-timer           |  20   |   0   |    IESG     | [RFCXXXX]    |
      | conflict-scope        |  21   |   5   |    IESG     | [RFCXXXX]    |
      | acl-list              |  22   |   4   |    IESG     | [RFCXXXX]    |
      | acl-name              |  23   |   3   |    IESG     | [RFCXXXX]    |
      | acl-type              |  24   |   3   |    IESG     | [RFCXXXX]    |
      | bytes-dropped         |  25   |   0   |    IESG     | [RFCXXXX]    |
      | bps-dropped           |  26   |   0   |    IESG     | [RFCXXXX]    |
      | pkts-dropped          |  27   |   0   |    IESG     | [RFCXXXX]    |
      | pps-dropped           |  28   |   0   |    IESG     | [RFCXXXX]    |
      | attack-status         |  29   |   0   |    IESG     | [RFCXXXX]    |
      | ietf-dots-signal-     |  30   |   5   |    IESG     | [RFCXXXX]    |
      | channel:signal-config |       |       |             |              |
      | sid                   |  31   |   0   |    IESG     | [RFCXXXX]    |
      | mitigating-config     |  32   |   5   |    IESG     | [RFCXXXX]    |
      | heartbeat-interval    |  33   |   5   |    IESG     | [RFCXXXX]    |
      | min-value             |  34   |   0   |    IESG     | [RFCXXXX]    |
      | max-value             |  35   |   0   |    IESG     | [RFCXXXX]    |
      | current-value         |  36   |   0   |    IESG     | [RFCXXXX]    |
      | missing-hb-allowed    |  37   |   5   |    IESG     | [RFCXXXX]    |
      | max-retransmit        |  38   |   5   |    IESG     | [RFCXXXX]    |
      | ack-timeout           |  39   |   5   |    IESG     | [RFCXXXX]    |
      | ack-random-factor     |  40   |   5   |    IESG     | [RFCXXXX]    |
      | min-value-decimal     |  41   | 6tag4 |    IESG     | [RFCXXXX]    |
      | max-value-decimal     |  42   | 6tag4 |    IESG     | [RFCXXXX]    |
      | current-value-        |  43   | 6tag4 |    IESG     | [RFCXXXX]    |
      |  decimal              |       |       |             |              |
      | idle-config           |  44   |   5   |    IESG     | [RFCXXXX]    |
      | trigger-mitigation    |  45   |   7   |    IESG     | [RFCXXXX]    |
      | ietf-dots-signal-chan |  46   |   5   |    IESG     | [RFCXXXX]    |
      | nel:redirected-signal |       |       |             |              |
      | alt-server            |  47   |   3   |    IESG     | [RFCXXXX]    |
      | alt-server-record     |  48   |   4   |    IESG     | [RFCXXXX]    |
      +-----------------------+-------+-------+-------------+--------------+
```

        Table 6: Initial DOTS Signal Channel CBOR Key Values Registry

9.6.2. Status Codes Sub-Registry

   The document requests IANA to create a new sub-registry, entitled
   "DOTS Signal Channel Status Codes". Codes in this registry are used
   as valid values of 'status' parameter.

   The registry is initially populated with the following values:

```
   +-----+--------------------------------+--------------+-----------+
   | Cod | Label                          | Description  | Reference |
   |  e  |                                |              |           |
   +-----+--------------------------------+--------------+-----------+
   |  1  | attack-mitigation-in-progress  | Attack       | [RFCXXXX] |
   |     |                                | mitigation   |           |
   |     |                                | setup is in  |           |
   |     |                                | progress     |           |
   |     |                                | (e.g.,       |           |
   |     |                                | changing the |           |
   |     |                                | network path |           |
   |     |                                | to redirect  |           |
   |     |                                | the inbound  |           |
   |     |                                | traffic to a |           |
   |     |                                | DOTS         |           |
   |     |                                | mitigator).  |           |
   |  2  | attack-successfully-mitigated  | Attack is    | [RFCXXXX] |
   |     |                                | being        |           |
   |     |                                | successfully |           |
   |     |                                | mitigated    |           |
   |     |                                | (e.g.,       |           |
   |     |                                | traffic is   |           |
   |     |                                | redirected   |           |
   |     |                                | to a DDoS    |           |
   |     |                                | mitigator    |           |
   |     |                                | and attack   |           |
   |     |                                | traffic is   |           |
   |     |                                | dropped).    |           |
   |  3  | attack-stopped                 | Attack has   | [RFCXXXX] |
   |     |                                | stopped and  |           |
   |     |                                | the DOTS     |           |
   |     |                                | client can   |           |
   |     |                                | withdraw the |           |
   |     |                                | mitigation   |           |
   |     |                                | request.     |           |
   |  4  | attack-exceeded-capability     | Attack has   | [RFCXXXX] |
   |     |                                | exceeded the |           |
   |     |                                | mitigation   |           |
   |     |                                | provider     |           |
```

```
    |     |                                | capability. |           |
    |  5  | dots-client-withdrawn-mitigation | DOTS client | [RFCXXXX] |
    |     |                                | has         |           |
    |     |                                | withdrawn   |           |
    |     |                                | the         |           |
    |     |                                | mitigation  |           |
    |     |                                | request and |           |
    |     |                                | the         |           |
    |     |                                | mitigation  |           |
    |     |                                | is active   |           |
    |     |                                | but         |           |
    |     |                                | terminating.|           |
    |  6  | attack-mitigation-terminated   | Attack      | [RFCXXXX] |
    |     |                                | mitigation  |           |
    |     |                                | is now      |           |
    |     |                                | terminated. |           |
    |  7  | attack-mitigation-withdrawn    | Attack      | [RFCXXXX] |
    |     |                                | mitigation  |           |
    |     |                                | is          |           |
    |     |                                | withdrawn.  |           |
    |  8  | attack-mitigation-signal-loss  | Attack      | [RFCXXXX] |
    |     |                                | mitigation  |           |
    |     |                                | will be     |           |
    |     |                                | triggered   |           |
    |     |                                | for the     |           |
    |     |                                | mitigation  |           |
    |     |                                | request only|           |
    |     |                                | when the    |           |
    |     |                                | DOTS signal |           |
    |     |                                | channel     |           |
    |     |                                | session is  |           |
    |     |                                | lost.       |           |
    +-----+--------------------------------+-------------+-----------+
```

   New codes can be assigned via Standards Action [RFC8126].

9.6.3. Conflict Status Codes Sub-Registry

   The document requests IANA to create a new sub-registry, entitled
   "DOTS Signal Channel Conflict Status Codes". Codes in this registry
   are used as valid values of 'conflict-status' parameter.

   The registry is initially populated with the following values:

```
    +------+-----------------------------+---------------+-----------+
    | Code | Label                       | Description   | Reference |
    +------+-----------------------------+---------------+-----------+
    |  1   | request-inactive-other-active | DOTS server | [RFCXXXX] |
    |      |                             | has detected  |           |
    |      |                             | conflicting   |           |
    |      |                             | mitigation    |           |
    |      |                             | requests from |           |
    |      |                             | different DOTS|           |
    |      |                             | clients. This |           |
    |      |                             | mitigation    |           |
    |      |                             | request is    |           |
    |      |                             | currently     |           |
    |      |                             | inactive until|           |
    |      |                             | the conflicts |           |
    |      |                             | are resolved. |           |
    |      |                             | Another       |           |
    |      |                             | mitigation    |           |
    |      |                             | request is    |           |
    |      |                             | active.       |           |
    |  2   | request-active              | DOTS server   | [RFCXXXX] |
    |      |                             | has detected  |           |
    |      |                             | conflicting   |           |
    |      |                             | mitigation    |           |
    |      |                             | requests from |           |
    |      |                             | different DOTS|           |
    |      |                             | clients. This |           |
    |      |                             | mitigation    |           |
    |      |                             | request is    |           |
    |      |                             | currently     |           |
    |      |                             | active.       |           |
    |  3   | all-requests-inactive       | DOTS server   | [RFCXXXX] |
    |      |                             | has detected  |           |
    |      |                             | conflicting   |           |
    |      |                             | mitigation    |           |
    |      |                             | requests from |           |
    |      |                             | different DOTS|           |
    |      |                             | clients. All  |           |
    |      |                             | conflicting   |           |
    |      |                             | mitigation    |           |
    |      |                             | requests are  |           |
    |      |                             | inactive.     |           |
    +------+-----------------------------+---------------+-----------+
```

   New codes can be assigned via Standards Action [RFC8126].

9.6.4. Conflict Cause Codes Sub-Registry

   The document requests IANA to create a new sub-registry, entitled
   "DOTS Signal Channel Conflict Cause Codes". Codes in this registry
   are used as valid values of 'conflict-cause' parameter.

The registry is initially populated with the following values:

Code	Label	Description	Reference
1	overlapping-targets	Overlapping targets.	[RFCXXXX]
2	conflict-with-acceptlist	Conflicts with an existing accept-list. This code is returned when the DDoS mitigation detects source addresses/prefixes in the accept-listed ACLs are attacking the target.	[RFCXXXX]
3	cuid-collision	CUID Collision. This code is returned when a DOTS client uses a 'cuid' that is already used by another DOTS client.	[RFCXXXX]

New codes can be assigned via Standards Action [RFC8126].

9.6.5. Attack Status Codes Sub-Registry

The document requests IANA to create a new sub-registry, entitled "DOTS Signal Channel Attack Status Codes". Codes in this registry are used as valid values of 'attack-status' parameter.

The registry is initially populated with the following values:

Code	Label	Description	Reference
1	under-attack	The DOTS client determines that it is still under attack.	[RFCXXXX]
2	attack-successfully-mitigated	The DOTS client determines that the attack is successfully mitigated.	[RFCXXXX]

New codes can be assigned via Standards Action [RFC8126].

9.7. DOTS Signal Channel YANG Modules

This document requests IANA to register the following URIs in the "ns" subregistry within the "IETF XML Registry" [RFC3688]:

     URI: urn:ietf:params:xml:ns:yang:ietf-dots-signal-channel
     Registrant Contact: The IESG.
     XML: N/A; the requested URI is an XML namespace.

     URI: urn:ietf:params:xml:ns:yang:iana-dots-signal-channel
     Registrant Contact: IANA.
     XML: N/A; the requested URI is an XML namespace.

This document requests IANA to register the following YANG modules in the "YANG Module Names" subregistry [RFC7950] within the "YANG Parameters" registry.

     Name: ietf-dots-signal-channel
     Namespace: urn:ietf:params:xml:ns:yang:ietf-dots-signal-channel
     Maintained by IANA: N
     Prefix: signal
     Reference: RFC XXXX

     Name: iana-dots-signal-channel
     Namespace: urn:ietf:params:xml:ns:yang:iana-dots-signal-channel
     Maintained by IANA: Y
     Prefix: iana-signal
     Reference: RFC XXXX

This document defines the initial version of the IANA-maintained iana-dots-signal-channel YANG module. IANA is requested to add this note:

   Status, conflict status, conflict cause, and attack status values
   must not be directly added to the iana-dots-signal-channel YANG
   module. They must instead be respectively added to the "DOTS

        Status Codes", "DOTS Conflict Status Codes", "DOTS Conflict Cause
        Codes", and "DOTS Attack Status Codes" registries.

     When a 'status', 'conflict-status', 'conflict-cause', or 'attack-
     status' value is respectively added to the "DOTS Status Codes", "DOTS
     Conflict Status Codes", "DOTS Conflict Cause Codes", or "DOTS Attack
     Status Codes" registry, a new "enum" statement must be added to the
     iana-dots-signal-channel YANG module. The following "enum"
     statement, and substatements thereof, should be defined:

     "enum":   Replicates the label from the registry.

     "value":   Contains the IANA-assigned value corresponding to the
                    'status', 'conflict-status', 'conflict-cause', or
                    'attack-status'.

     "description": Replicates the description from the registry.

     "reference":   Replicates the reference from the registry and add the
                    title of the document.

     When the iana-dots-signal-channel YANG module is updated, a new
     "revision" statement must be added in front of the existing revision
     statements.

     IANA is requested to add this note to "DOTS Status Codes", "DOTS
     Conflict Status Codes", "DOTS Conflict Cause Codes", and "DOTS Attack
     Status Codes" registries:

        When this registry is modified, the YANG module iana-dots-signal-
        channel must be updated as defined in [RFCXXXX].

  10. Security Considerations

     High-level DOTS security considerations are documented in [RFC8612]
     and [I-D.ietf-dots-architecture].

     Authenticated encryption MUST be used for data confidentiality and
     message integrity. The interaction between the DOTS agents requires
     Datagram Transport Layer Security (DTLS) or Transport Layer Security
     (TLS) with a cipher suite offering confidentiality protection, and
     the guidance given in [RFC7525] MUST be followed to avoid attacks on
     (D)TLS. The (D)TLS protocol profile used for the DOTS signal channel
     is specified in Section 7.

     If TCP is used between DOTS agents, an attacker may be able to inject
     RST packets, bogus application segments, etc., regardless of whether
     TLS authentication is used. Because the application data is TLS
     protected, this will not result in the application receiving bogus
     data, but it will constitute a DoS on the connection. This attack
     can be countered by using TCP-AO [RFC5925]. Although not widely
     adopted, if TCP-AO is used, then any bogus packets injected by an
     attacker will be rejected by the TCP-AO integrity check and therefore
     will never reach the TLS layer.

     An attack vector that can be achieved if the 'cuid' is guessable is a
     misbehaving DOTS client from within the client's domain which uses
     the 'cuid' of another DOTS client of the domain to delete or alter
     active mitigations. For this attack vector to happen, the
     misbehaving client needs to pass the security validation checks by
     the DOTS server, and eventually the checks of a client-domain DOTS
     gateway.

     A similar attack can be achieved by a compromised DOTS client which
     can sniff the TLS 1.2 handshake, use the client certificate to
     identify the 'cuid' used by another DOTS client. This attack is not
     possible if algorithms such as version 4 Universally Unique
     IDentifiers (UUIDs) in Section 4.4 of [RFC4122] are used to generate
     the 'cuid' because such UUIDs are not a deterministic function of the
     client certificate. Likewise, this attack is not possible with TLS
     1.3 because most of the TLS handshake is encrypted and the client
     certificate is not visible to eavesdroppers.

     A compromised DOTS client can collude with a DDoS attacker to send
     mitigation request for a target resource, gets the mitigation
     efficacy from the DOTS server, and conveys the mitigation efficacy to
     the DDoS attacker to possibly change the DDoS attack strategy.
     Obviously, signaling an attack by the compromised DOTS client to the
     DOTS server will trigger attack mitigation. This attack can be
     prevented by monitoring and auditing DOTS clients to detect
     misbehavior and to deter misuse, and by only authorizing the DOTS
     client to request mitigation for specific target resources (e.g., an
     application server is authorized to request mitigation for its IP
     addresses but a DDoS mitigator can request mitigation for any target
     resource in the network). Furthermore, DOTS clients are typically
     co-located on network security services (e.g., firewall) and a
     compromised security service potentially can do a lot more damage to
     the network.

     Rate-limiting DOTS requests, including those with new 'cuid' values,
     from the same DOTS client defends against DoS attacks that would
     result in varying the 'cuid' to exhaust DOTS server resources. Rate-
     limit policies SHOULD be enforced on DOTS gateways (if deployed) and
     DOTS servers.

In order to prevent leaking internal information outside a client-
domain, DOTS gateways located in the client-domain SHOULD NOT reveal
the identification information that pertains to internal DOTS clients
(e.g., source IP address, client's hostname) unless explicitly
configured to do so.

DOTS servers MUST verify that requesting DOTS clients are entitled to
trigger actions on a given IP prefix. That is, only actions on IP
resources that belong to the DOTS client' domain MUST be authorized
by a DOTS server. The exact mechanism for the DOTS servers to
validate that the target prefixes are within the scope of the DOTS
client domain is deployment-specific.

The presence of DOTS gateways may lead to infinite forwarding loops,
which is undesirable. To prevent and detect such loops, this
document uses the Hop-Limit Option.

When FQDNs are used as targets, the DOTS server MUST rely upon DNS
privacy enabling protocols (e.g., DNS over TLS [RFC7858] or DoH
[RFC8484]) to prevent eavesdroppers from possibly identifying the
target resources protected by the DDoS mitigation service, and means
to ensure the target FQDN resolution is authentic (e.g., DNSSEC
[RFC4034]).

CoAP-specific security considerations are discussed in Section 11 of
[RFC7252], while CBOR-related security considerations are discussed
in Section 8 of [RFC7049].

11. Contributors

   The following individuals have contributed to this document:

   o Jon Shallow, NCC Group, Email: jon.shallow@nccgroup.trust

   o Mike Geller, Cisco Systems, Inc. 3250 Florida 33309 USA, Email:
      mgeller@cisco.com

   o Robert Moskowitz, HTT Consulting Oak Park, MI 42837 United States,
      Email: rgm@htt-consult.com

   o Dan Wing, Email: dwing-ietf@fuggles.com

12. Acknowledgements

   Thanks to Christian Jacquenet, Roland Dobbins, Roman Danyliw, Michael
   Richardson, Ehud Doron, Kaname Nishizuka, Dave Dolson, Liang Xia,
   Gilbert Clark, Xialiang Frank, Jim Schaad, Klaus Hartke, Nesredien
   Suleiman, Stephen Farrell, and Yoshifumi Nishida for the discussion
   and comments.

   The authors would like to give special thanks to Kaname Nishizuka and
   Jon Shallow for their efforts in implementing the protocol and
   performing interop testing at IETF Hackathons.

   Thanks to the core WG for the recommendations on Hop-Limit and
   redirect signaling.

   Special thanks to Benjamin Kaduk for the detailed AD review.

   Thanks to Alexey Melnikov, Adam Roach, Suresh Krishnan, Mirja
   Kuehlewind, and Alissa Cooper for the review.

13. References

13.1. Normative References

   [I-D.ietf-core-hop-limit]
              Boucadair, M., K, R., and J. Shallow, "Constrained
              Application Protocol (CoAP) Hop-Limit Option", draft-ietf-
              core-hop-limit-07 (work in progress), October 2019.

   [RFC0791] Postel, J., "Internet Protocol", STD 5, RFC 791,
              DOI 10.17487/RFC0791, September 1981,
              <https://www.rfc-editor.org/info/rfc791>.

   [RFC1122] Braden, R., Ed., "Requirements for Internet Hosts -
              Communication Layers", STD 3, RFC 1122,
              DOI 10.17487/RFC1122, October 1989,
              <https://www.rfc-editor.org/info/rfc1122>.

   [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
              Requirement Levels", BCP 14, RFC 2119,
              DOI 10.17487/RFC2119, March 1997,
              <https://www.rfc-editor.org/info/rfc2119>.

   [RFC3688] Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688,
              DOI 10.17487/RFC3688, January 2004,
              <https://www.rfc-editor.org/info/rfc3688>.

   [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform
              Resource Identifier (URI): Generic Syntax", STD 66,
              RFC 3986, DOI 10.17487/RFC3986, January 2005,
              <https://www.rfc-editor.org/info/rfc3986>.

   [RFC4279] Eronen, P., Ed. and H. Tschofenig, Ed., "Pre-Shared Key

                    Ciphersuites for Transport Layer Security (TLS)",
                    RFC 4279, DOI 10.17487/RFC4279, December 2005,
                    <https://www.rfc-editor.org/info/rfc4279>.

     [RFC4632]   Fuller, V. and T. Li, "Classless Inter-domain Routing
                    (CIDR): The Internet Address Assignment and Aggregation
                    Plan", BCP 122, RFC 4632, DOI 10.17487/RFC4632, August
                    2006, <https://www.rfc-editor.org/info/rfc4632>.

     [RFC4648]   Josefsson, S., "The Base16, Base32, and Base64 Data
                    Encodings", RFC 4648, DOI 10.17487/RFC4648, October 2006,
                    <https://www.rfc-editor.org/info/rfc4648>.

     [RFC5246]   Dierks, T. and E. Rescorla, "The Transport Layer Security
                    (TLS) Protocol Version 1.2", RFC 5246,
                    DOI 10.17487/RFC5246, August 2008,
                    <https://www.rfc-editor.org/info/rfc5246>.

     [RFC5280]   Cooper, D., Santesson, S., Farrell, S., Boeyen, S.,
                    Housley, R., and W. Polk, "Internet X.509 Public Key
                    Infrastructure Certificate and Certificate Revocation List
                    (CRL) Profile", RFC 5280, DOI 10.17487/RFC5280, May 2008,
                    <https://www.rfc-editor.org/info/rfc5280>.

     [RFC5785]   Nottingham, M. and E. Hammer-Lahav, "Defining Well-Known
                    Uniform Resource Identifiers (URIs)", RFC 5785,
                    DOI 10.17487/RFC5785, April 2010,
                    <https://www.rfc-editor.org/info/rfc5785>.

     [RFC6066]   Eastlake 3rd, D., "Transport Layer Security (TLS)
                    Extensions: Extension Definitions", RFC 6066,
                    DOI 10.17487/RFC6066, January 2011,
                    <https://www.rfc-editor.org/info/rfc6066>.

     [RFC6125]   Saint-Andre, P. and J. Hodges, "Representation and
                    Verification of Domain-Based Application Service Identity
                    within Internet Public Key Infrastructure Using X.509
                    (PKIX) Certificates in the Context of Transport Layer
                    Security (TLS)", RFC 6125, DOI 10.17487/RFC6125, March
                    2011, <https://www.rfc-editor.org/info/rfc6125>.

     [RFC6347]   Rescorla, E. and N. Modadugu, "Datagram Transport Layer
                    Security Version 1.2", RFC 6347, DOI 10.17487/RFC6347,
                    January 2012, <https://www.rfc-editor.org/info/rfc6347>.

     [RFC6991]   Schoenwaelder, J., Ed., "Common YANG Data Types",
                    RFC 6991, DOI 10.17487/RFC6991, July 2013,
                    <https://www.rfc-editor.org/info/rfc6991>.

     [RFC7049]   Bormann, C. and P. Hoffman, "Concise Binary Object
                    Representation (CBOR)", RFC 7049, DOI 10.17487/RFC7049,
                    October 2013, <https://www.rfc-editor.org/info/rfc7049>.

     [RFC7250]   Wouters, P., Ed., Tschofenig, H., Ed., Gilmore, J.,
                    Weiler, S., and T. Kivinen, "Using Raw Public Keys in
                    Transport Layer Security (TLS) and Datagram Transport
                    Layer Security (DTLS)", RFC 7250, DOI 10.17487/RFC7250,
                    June 2014, <https://www.rfc-editor.org/info/rfc7250>.

     [RFC7252]   Shelby, Z., Hartke, K., and C. Bormann, "The Constrained
                    Application Protocol (CoAP)", RFC 7252,
                    DOI 10.17487/RFC7252, June 2014,
                    <https://www.rfc-editor.org/info/rfc7252>.

     [RFC7525]   Sheffer, Y., Holz, R., and P. Saint-Andre,
                    "Recommendations for Secure Use of Transport Layer
                    Security (TLS) and Datagram Transport Layer Security
                    (DTLS)", BCP 195, RFC 7525, DOI 10.17487/RFC7525, May
                    2015, <https://www.rfc-editor.org/info/rfc7525>.

     [RFC7641]   Hartke, K., "Observing Resources in the Constrained
                    Application Protocol (CoAP)", RFC 7641,
                    DOI 10.17487/RFC7641, September 2015,
                    <https://www.rfc-editor.org/info/rfc7641>.

     [RFC7918]   Langley, A., Modadugu, N., and B. Moeller, "Transport
                    Layer Security (TLS) False Start", RFC 7918,
                    DOI 10.17487/RFC7918, August 2016,
                    <https://www.rfc-editor.org/info/rfc7918>.

     [RFC7924]   Santesson, S. and H. Tschofenig, "Transport Layer Security
                    (TLS) Cached Information Extension", RFC 7924,
                    DOI 10.17487/RFC7924, July 2016,
                    <https://www.rfc-editor.org/info/rfc7924>.

     [RFC7950]   Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language",
                    RFC 7950, DOI 10.17487/RFC7950, August 2016,
                    <https://www.rfc-editor.org/info/rfc7950>.

     [RFC7959]   Bormann, C. and Z. Shelby, Ed., "Block-Wise Transfers in
                    the Constrained Application Protocol (CoAP)", RFC 7959,
                    DOI 10.17487/RFC7959, August 2016,
                    <https://www.rfc-editor.org/info/rfc7959>.

     [RFC8085]   Eggert, L., Fairhurst, G., and G. Shepherd, "UDP Usage

                   Guidelines", BCP 145, RFC 8085, DOI 10.17487/RFC8085,
                   March 2017, <https://www.rfc-editor.org/info/rfc8085>.

     [RFC8126]   Cotton, M., Leiba, B., and T. Narten, "Guidelines for
                   Writing an IANA Considerations Section in RFCs", BCP 26,
                   RFC 8126, DOI 10.17487/RFC8126, June 2017,
                   <https://www.rfc-editor.org/info/rfc8126>.

     [RFC8174]   Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC
                   2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174,
                   May 2017, <https://www.rfc-editor.org/info/rfc8174>.

     [RFC8200]   Deering, S. and R. Hinden, "Internet Protocol, Version 6
                   (IPv6) Specification", STD 86, RFC 8200,
                   DOI 10.17487/RFC8200, July 2017,
                   <https://www.rfc-editor.org/info/rfc8200>.

     [RFC8305]   Schinazi, D. and T. Pauly, "Happy Eyeballs Version 2:
                   Better Connectivity Using Concurrency", RFC 8305,
                   DOI 10.17487/RFC8305, December 2017,
                   <https://www.rfc-editor.org/info/rfc8305>.

     [RFC8323]   Bormann, C., Lemay, S., Tschofenig, H., Hartke, K.,
                   Silverajan, B., and B. Raymor, Ed., "CoAP (Constrained
                   Application Protocol) over TCP, TLS, and WebSockets",
                   RFC 8323, DOI 10.17487/RFC8323, February 2018,
                   <https://www.rfc-editor.org/info/rfc8323>.

     [RFC8446]   Rescorla, E., "The Transport Layer Security (TLS) Protocol
                   Version 1.3", RFC 8446, DOI 10.17487/RFC8446, August 2018,
                   <https://www.rfc-editor.org/info/rfc8446>.

  13.2. Informative References

     [I-D.boucadair-dots-earlydata]
                   Boucadair, M. and R. K, "Using Early Data in DOTS", draft-
                   boucadair-dots-earlydata-00 (work in progress), January
                   2019.

     [I-D.ietf-core-comi]
                   Veillette, M., Stok, P., Pelov, A., Bierman, A., and I.
                   Petrov, "CoAP Management Interface", draft-ietf-core-
                   comi-08 (work in progress), September 2019.

     [I-D.ietf-core-yang-cbor]
                   Veillette, M., Petrov, I., and A. Pelov, "CBOR Encoding of
                   Data Modeled with YANG", draft-ietf-core-yang-cbor-11
                   (work in progress), September 2019.

     [I-D.ietf-dots-architecture]
                   Mortensen, A., K, R., Andreasen, F., Teague, N., and R.
                   Compton, "Distributed-Denial-of-Service Open Threat
                   Signaling (DOTS) Architecture", draft-ietf-dots-
                   architecture-14 (work in progress), May 2019.

     [I-D.ietf-dots-data-channel]
                   Boucadair, M. and R. K, "Distributed Denial-of-Service
                   Open Threat Signaling (DOTS) Data Channel Specification",
                   draft-ietf-dots-data-channel-31 (work in progress), July
                   2019.

     [I-D.ietf-dots-multihoming]
                   Boucadair, M., K, R., and W. Pan, "Multi-homing Deployment
                   Considerations for Distributed-Denial-of-Service Open
                   Threat Signaling (DOTS)", draft-ietf-dots-multihoming-02
                   (work in progress), July 2019.

     [I-D.ietf-dots-server-discovery]
                   Boucadair, M. and R. K, "Distributed-Denial-of-Service
                   Open Threat Signaling (DOTS) Agent Discovery", draft-ietf-
                   dots-server-discovery-05 (work in progress), August 2019.

     [I-D.ietf-dots-use-cases]
                   Dobbins, R., Migault, D., Moskowitz, R., Teague, N., Xia,
                   L., and K. Nishizuka, "Use cases for DDoS Open Threat
                   Signaling", draft-ietf-dots-use-cases-20 (work in
                   progress), September 2019.

     [I-D.ietf-tls-dtls13]
                   Rescorla, E., Tschofenig, H., and N. Modadugu, "The
                   Datagram Transport Layer Security (DTLS) Protocol Version
                   1.3", draft-ietf-tls-dtls13-32 draft-ietf-tls-dtls13-33 (work in progress), July October
                   2019.

     [IANA.CBOR.Tags]
                   IANA, "Concise Binary Object Representation (CBOR) Tags",
                   <http://www.iana.org/assignments/cbor-tags/cbor-
                   tags.xhtml>.

     [IANA.CoAP.Content-Formats]
                   IANA, "CoAP Content-Formats",
                   <http://www.iana.org/assignments/core-parameters/core-
                   parameters.xhtml#content-formats>.

     [IANA.MediaTypes]

                 IANA, "Media Types",
                 <http://www.iana.org/assignments/media-types>.

     [proto_numbers]
                 "IANA, "Protocol Numbers"", 2011,
                 <http://www.iana.org/assignments/protocol-numbers>.

     [RFC3022]   Srisuresh, P. and K. Egevang, "Traditional IP Network
                 Address Translator (Traditional NAT)", RFC 3022,
                 DOI 10.17487/RFC3022, January 2001,
                 <https://www.rfc-editor.org/info/rfc3022>.

     [RFC4034]   Arends, R., Austein, R., Larson, M., Massey, D., and S.
                 Rose, "Resource Records for the DNS Security Extensions",
                 RFC 4034, DOI 10.17487/RFC4034, March 2005,
                 <https://www.rfc-editor.org/info/rfc4034>.

     [RFC4122]   Leach, P., Mealling, M., and R. Salz, "A Universally
                 Unique IDentifier (UUID) URN Namespace", RFC 4122,
                 DOI 10.17487/RFC4122, July 2005,
                 <https://www.rfc-editor.org/info/rfc4122>.

     [RFC4340]   Kohler, E., Handley, M., and S. Floyd, "Datagram
                 Congestion Control Protocol (DCCP)", RFC 4340,
                 DOI 10.17487/RFC4340, March 2006,
                 <https://www.rfc-editor.org/info/rfc4340>.

     [RFC4732]   Handley, M., Ed., Rescorla, E., Ed., and IAB, "Internet
                 Denial-of-Service Considerations", RFC 4732,
                 DOI 10.17487/RFC4732, December 2006,
                 <https://www.rfc-editor.org/info/rfc4732>.

     [RFC4787]   Audet, F., Ed. and C. Jennings, "Network Address
                 Translation (NAT) Behavioral Requirements for Unicast
                 UDP", BCP 127, RFC 4787, DOI 10.17487/RFC4787, January
                 2007, <https://www.rfc-editor.org/info/rfc4787>.

     [RFC4960]   Stewart, R., Ed., "Stream Control Transmission Protocol",
                 RFC 4960, DOI 10.17487/RFC4960, September 2007,
                 <https://www.rfc-editor.org/info/rfc4960>.

     [RFC4987]   Eddy, W., "TCP SYN Flooding Attacks and Common
                 Mitigations", RFC 4987, DOI 10.17487/RFC4987, August 2007,
                 <https://www.rfc-editor.org/info/rfc4987>.

     [RFC5389]   Rosenberg, J., Mahy, R., Matthews, P., and D. Wing,
                 "Session Traversal Utilities for NAT (STUN)", RFC 5389,
                 DOI 10.17487/RFC5389, October 2008,
                 <https://www.rfc-editor.org/info/rfc5389>.

     [RFC5925]   Touch, J., Mankin, A., and R. Bonica, "The TCP
                 Authentication Option", RFC 5925, DOI 10.17487/RFC5925,
                 June 2010, <https://www.rfc-editor.org/info/rfc5925>.

     [RFC6052]   Bao, C., Huitema, C., Bagnulo, M., Boucadair, M., and X.
                 Li, "IPv6 Addressing of IPv4/IPv6 Translators", RFC 6052,
                 DOI 10.17487/RFC6052, October 2010,
                 <https://www.rfc-editor.org/info/rfc6052>.

     [RFC6146]   Bagnulo, M., Matthews, P., and I. van Beijnum, "Stateful
                 NAT64: Network Address and Protocol Translation from IPv6
                 Clients to IPv4 Servers", RFC 6146, DOI 10.17487/RFC6146,
                 April 2011, <https://www.rfc-editor.org/info/rfc6146>.

     [RFC6234]   Eastlake 3rd, D. and T. Hansen, "US Secure Hash Algorithms
                 (SHA and SHA-based HMAC and HKDF)", RFC 6234,
                 DOI 10.17487/RFC6234, May 2011,
                 <https://www.rfc-editor.org/info/rfc6234>.

     [RFC6296]   Wasserman, M. and F. Baker, "IPv6-to-IPv6 Network Prefix
                 Translation", RFC 6296, DOI 10.17487/RFC6296, June 2011,
                 <https://www.rfc-editor.org/info/rfc6296>.

     [RFC6724]   Thaler, D., Ed., Draves, R., Matsumoto, A., and T. Chown,
                 "Default Address Selection for Internet Protocol Version 6
                 (IPv6)", RFC 6724, DOI 10.17487/RFC6724, September 2012,
                 <https://www.rfc-editor.org/info/rfc6724>.

     [RFC6838]   Freed, N., Klensin, J., and T. Hansen, "Media Type
                 Specifications and Registration Procedures", BCP 13,
                 RFC 6838, DOI 10.17487/RFC6838, January 2013,
                 <https://www.rfc-editor.org/info/rfc6838>.

     [RFC6887]   Wing, D., Ed., Cheshire, S., Boucadair, M., Penno, R., and
                 P. Selkirk, "Port Control Protocol (PCP)", RFC 6887,
                 DOI 10.17487/RFC6887, April 2013,
                 <https://www.rfc-editor.org/info/rfc6887>.

     [RFC6888]   Perreault, S., Ed., Yamagata, I., Miyakawa, S., Nakagawa,
                 A., and H. Ashida, "Common Requirements for Carrier-Grade
                 NATs (CGNs)", BCP 127, RFC 6888, DOI 10.17487/RFC6888,
                 April 2013, <https://www.rfc-editor.org/info/rfc6888>.

     [RFC7030]   Pritikin, M., Ed., Yee, P., Ed., and D. Harkins, Ed.,
                 "Enrollment over Secure Transport", RFC 7030,

                     DOI 10.17487/RFC7030, October 2013,
                     <https://www.rfc-editor.org/info/rfc7030>.

     [RFC7413]   Cheng, Y., Chu, J., Radhakrishnan, S., and A. Jain, "TCP
                 Fast Open", RFC 7413, DOI 10.17487/RFC7413, December 2014,
                 <https://www.rfc-editor.org/info/rfc7413>.

     [RFC7452]   Tschofenig, H., Arkko, J., Thaler, D., and D. McPherson,
                 "Architectural Considerations in Smart Object Networking",
                 RFC 7452, DOI 10.17487/RFC7452, March 2015,
                 <https://www.rfc-editor.org/info/rfc7452>.

     [RFC7589]   Badra, M., Luchuk, A., and J. Schoenwaelder, "Using the
                 NETCONF Protocol over Transport Layer Security (TLS) with
                 Mutual X.509 Authentication", RFC 7589,
                 DOI 10.17487/RFC7589, June 2015,
                 <https://www.rfc-editor.org/info/rfc7589>.

     [RFC7858]   Hu, Z., Zhu, L., Heidemann, J., Mankin, A., Wessels, D.,
                 and P. Hoffman, "Specification for DNS over Transport
                 Layer Security (TLS)", RFC 7858, DOI 10.17487/RFC7858, May
                 2016, <https://www.rfc-editor.org/info/rfc7858>.

     [RFC7951]   Lhotka, L., "JSON Encoding of Data Modeled with YANG",
                 RFC 7951, DOI 10.17487/RFC7951, August 2016,
                 <https://www.rfc-editor.org/info/rfc7951>.

     [RFC8340]   Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams",
                 BCP 215, RFC 8340, DOI 10.17487/RFC8340, March 2018,
                 <https://www.rfc-editor.org/info/rfc8340>.

     [RFC8484]   Hoffman, P. and P. McManus, "DNS Queries over HTTPS
                 (DoH)", RFC 8484, DOI 10.17487/RFC8484, October 2018,
                 <https://www.rfc-editor.org/info/rfc8484>.

     [RFC8499]   Hoffman, P., Sullivan, A., and K. Fujiwara, "DNS
                 Terminology", BCP 219, RFC 8499, DOI 10.17487/RFC8499,
                 January 2019, <https://www.rfc-editor.org/info/rfc8499>.

     [RFC8612]   Mortensen, A., Reddy, T., and R. Moskowitz, "DDoS Open
                 Threat Signaling (DOTS) Requirements", RFC 8612,
                 DOI 10.17487/RFC8612, May 2019,
                 <https://www.rfc-editor.org/info/rfc8612>.

Appendix A. CUID Generation

   The document recommends the use of SPKI to generate the 'cuid'. This
   design choice is motivated by the following reasons:

   o SPKI is globally unique.

   o It is deterministic.

   o It allows to avoid extra cycles that may be induced by 'cuid'
      collision.

   o DOTS clients do not need to store the 'cuid' in a persistent
      storage.

   o It allows to detect compromised DOTS clients that do not adhere to
      the 'cuid' generation algorithm.

Authors' Addresses

   Tirumaleswar Reddy (editor)
   McAfee, Inc.
   Embassy Golf Link Business Park
   Bangalore, Karnataka 560071
   India

   Email: kondtir@gmail.com

   Mohamed Boucadair (editor)
   Orange
   Rennes 35000
   France

   Email: mohamed.boucadair@orange.com
   Prashanth Patil
   Cisco Systems, Inc.

   Email: praspati@cisco.com

   Andrew Mortensen
   Arbor Networks, Inc.
   2727 S. State St
   Ann Arbor, MI 48104
   United States

   Email: andrew@moretension.com

   Nik Teague
   Iron Mountain Data Centers
   United Kingdom

      Email: nteague@ironmountain.co.uk