```
module ietf-dots-signal-channel {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-dots-signal-channel";
  prefix signal;

  import ietf-inet-types {
    prefix inet;
    reference
      "Section 4 of RFC 6991";
  }
  import ietf-yang-types {
    prefix yang;
    reference
      "Section 3 of RFC 6991";
  }
  import ietf-dots-data-channel {
    prefix ietf-data;
    reference
      "RFC 8783: Distributed Denial-of-Service Open Threat Signaling
                 (DOTS) Data Channel Specification";
  }
  import iana-dots-signal-channel {
    prefix iana-signal;
  }
  import ietf-yang-structure-ext {
    prefix sx;
    reference
      "RFC 8791: YANG Data Structure Extensions";
  }

  organization
    "IETF DDoS Open Threat Signaling (DOTS) Working Group";
  contact
    "WG Web:   <https://datatracker.ietf.org/wg/dots/>
     WG List:  <mailto:dots&ietf.org>

     Editor:  Konda, Tirumaleswar Reddy.K
              <mailto:TirumaleswarReddy_Konda&McAfee.com>

     Editor:  Mohamed Boucadair
              <mailto:mohamed.boucadair&orange.com>

     Author:  Prashanth Patil
              <mailto:praspati&cisco.com>
              <mailto:praspati@cisco.com>

     Author:  Andrew Mortensen
              <mailto:amortensen&arbor.net>

     Author:  Nik Teague
              <mailto:nteague&ironmountain.co.uk>";
  description
```

```
     "This module contains YANG definition for the signaling
      messages exchanged between a DOTS client and a DOTS server.

      Copyright (c) 2020 IETF Trust and the persons identified as
      authors of the code.  All rights reserved.

      Redistribution and use in source and binary forms, with or
      without modification, is permitted pursuant to, and subject
      to the license terms contained in, the Simplified BSD License
      set forth in Section 4.c of the IETF Trust's Legal Provisions
      Relating to IETF Documents
      (http://trustee.ietf.org/license-info).

      This version of this YANG module is part of RFC 8782; see
      the RFC itself for full legal notices.";

   revision 2020-07-02 {
     description
       "Updated revision.";
     reference
       "RFC xxxx: xxx";
   }
   revision 2020-05-28 {
     description
       "Initial revision.";
     reference
       "RFC 8782: Distributed Denial-of-Service Open Threat
                  Signaling (DOTS) Signal Channel Specification";
   }

   /*
    * Groupings
    */

   grouping mitigation-scope {
     description
       "Specifies the scope of the mitigation request.";
     list scope {
       key "cuid mid"; "mid";
       description
         "The scope of the request.";
       leaf cdid {
         type string;
         description
           "The cdid should be included by a server-domain
            DOTS gateway to propagate the client domain
            identification information from the
            gateway's client-facing side to the gateway's
            server-facing side, and from the gateway's
            server-facing side to the DOTS server.

            It may be used by the final DOTS server
            for policy enforcement purposes.";
```

```
        }
        leaf cuid {
          type string;
          description
            "A unique identifier that is
            generated by a DOTS client to prevent
            request collisions.  It is expected that the
            cuid will remain consistent throughout the
            lifetime of the DOTS client.";
        }
        leaf mid {
          type uint32;
          description
            "Mitigation request identifier.

             This identifier must be unique for each mitigation
             request bound to the DOTS client.";
        }
        uses ietf-data:target;
        leaf-list alias-name {
          type string;
          description
            "An alias name that points to a resource.";
        }
        leaf lifetime {
          type int32;
          units "seconds";
          default "3600";
          description
            "Indicates the lifetime of the mitigation request.

             A lifetime of '0' in a mitigation request is an
             invalid value.

             A lifetime of negative one (-1) indicates indefinite
             lifetime for the mitigation request.";
        }
        leaf trigger-mitigation {
          type boolean;
          default "true";
          description
            "If set to 'false', DDoS mitigation will not be
             triggered unless the DOTS signal channel
             session is lost.";
        }
        choice direction {
          description
            "xxx.";
          case server-to-client {
            description
              "xx.";
            leaf mitigation-start {
              type uint64;
```

```
              config false;
                  description
                    "Mitigation start time is represented in seconds
                     relative to 1970-01-01T00:00:00Z in UTC time.";
              }
            leaf status {
              type iana-signal:status;
              config false;
                  description
                    "Indicates the status of a mitigation request.
                     It must be included in responses only.";
              }
            container conflict-information {
              config false;
                  description
                    "Indicates that a conflict is detected.
                     Must only be used for responses.";
                leaf conflict-status {
                  type iana-signal:conflict-status;
                  description
                    "Indicates the conflict status.";
                }
                leaf conflict-cause {
                  type iana-signal:conflict-cause;
                  description
                    "Indicates the cause of the conflict.";
                }
                leaf retry-timer {
                  type uint32;
                  units "seconds";
                  description
                    "The DOTS client must not resend the
                     same request that has a conflict before the expiry of
                     this timer.";
                }
                container conflict-scope {
                  description
                    "Provides more information about the conflict scope.";
                  uses ietf-data:target {
                    when "/dots-signal/scope/conflict-information/"
                        + "conflict-cause = 'overlapping-targets'";
                  }
                  leaf-list alias-name {
                    when "../../conflict-cause = 'overlapping-targets'";
                    type string;
                    description
                      "Conflicting alias-name.";
                  }
                  list acl-list {
                    when "../../conflict-cause = 'conflict-with-acceptlist'";
                    key "acl-name";
                    description
                      "List of conflicting ACLs as defined in the DOTS data
```

```
                     channel.  These ACLs are uniquely defined by
                     cuid and acl-name.";
                leaf acl-name {
                  type leafref {
                    path "/ietf-data:dots-data/ietf-data:dots-client/"
                       + "ietf-data:acls/ietf-data:acl/ietf-data:name";
                  }
                  description
                    "Reference to the conflicting ACL name bound to
                     a DOTS client.";
                }
                leaf acl-type {
                  type leafref {
                    path "/ietf-data:dots-data/ietf-data:dots-client/"
                       + "ietf-data:acls/ietf-data:acl/ietf-data:type";
                  }
                  description
                    "Reference to the conflicting ACL type bound to
                     a DOTS client.";
                }
              }
              leaf mid {
                when "../../conflict-cause = 'overlapping-targets'";
                type leafref {
                  path "../../../mid";
                }
                description
                  "Reference to the conflicting 'mid' bound to
                   the same DOTS client.";
              }
            }
          }
          leaf bytes-dropped {
            type yang:zero-based-counter64;
            units "bytes";
            config false;
            description
              "The total dropped byte count for the mitigation
               request since the attack mitigation was triggered.
               The count wraps around when it reaches the maximum value
               of counter64 for dropped bytes.";
          }
          leaf bps-dropped {
            type yang:gauge64;
            config false;
            description
              "The average number of dropped bits per second for
               the mitigation request since the attack
               mitigation was triggered.  This should be over
               five-minute intervals (that is, measuring bytes
               into five-minute buckets and then averaging these
               buckets over the time since the mitigation was
               triggered).";
```

```
            }
            leaf pkts-dropped {
              type yang:zero-based-counter64;
          config false;
                description
                  "The total number of dropped packet count for the
                   mitigation request since the attack mitigation was
                   triggered.  The count wraps around when it reaches
                   the maximum value of counter64 for dropped packets.";
            }
            leaf pps-dropped {
              type yang:gauge64;
          config false;
                description
                  "The average number of dropped packets per second
                   for the mitigation request since the attack
                   mitigation was triggered.  This should be over
                   five-minute intervals (that is, measuring packets
                   into five-minute buckets and then averaging these
                   buckets over the time since the mitigation was
                   triggered).";
            }
            leaf attack-status {
              type iana-signal:attack-status;
              description
                "Indicates the status of an attack as seen by the
                 DOTS client.";
            }
          }
        }
      }
    }

    grouping config-parameters {
      description
        "Subset of DOTS signal channel session configuration.";
      container heartbeat-interval {
        description
          "DOTS agents regularly send heartbeats to each other
           after mutual authentication is successfully
           completed in order to keep the DOTS signal channel
           open.";
        choice direction {
          description
            "xxx.";
          case server-to-client {
            description
              "xx.";
            leaf max-value {
              type uint16;
              units "seconds";
          config false;
                description
```

```
              "Maximum acceptable heartbeat-interval value.";
          }
          leaf min-value {
            type uint16;
            units "seconds";
        config false;
            description
              "Minimum acceptable heartbeat-interval value.";
          }
        }
      }
      leaf current-value {
        type uint16;
        units "seconds";
        default "30";
        description
          "Current heartbeat-interval value.

           '0' means that heartbeat mechanism is deactivated.";
      }
    }
    container missing-hb-allowed {
      description
        "Maximum number of missing heartbeats allowed.";
      choice direction {
        description
          "xxx.";
        case server-to-client {
          description
            "xx.";
          leaf max-value {
            type uint16;
        config false;
            description
              "Maximum acceptable missing-hb-allowed value.";
          }
          leaf min-value {
            type uint16;
        config false;
            description
              "Minimum acceptable missing-hb-allowed value.";
          }
        }
      }
      leaf current-value {
        type uint16;
        default "15";
        description
          "Current missing-hb-allowed value.";
      }
    }
    container probing-rate {
      description
```

```
            "The limit for sending Non-confirmable messages with
             no response.";
          choice direction {
            description
              "xxx.";
            case server-to-client {
              description
                "xx.";
              leaf max-value {
                type uint16;
                units "byte/second";
            config false;
                description
                  "Maximum acceptable probing-rate value.";
              }
              leaf min-value {
                type uint16;
                units "byte/second";
            config false;
                description
                  "Minimum acceptable probing-rate value.";
              }
            }
          }
          leaf current-value {
            type uint16;
            units "byte/second";
            default "5";
            description
              "Current probing-rate value.";
          }
        }
        container max-retransmit {
          description
            "Maximum number of retransmissions of a Confirmable
             message.";
          choice direction {
            description
              "xxx.";
            case server-to-client {
              description
                "xx.";
              leaf max-value {
                type uint16;
            config false;
                description
                  "Maximum acceptable max-retransmit value.";
              }
              leaf min-value {
                type uint16;
            config false;
                description
                  "Minimum acceptable max-retransmit value.";
```

```
        }
      }
    }
    leaf current-value {
      type uint16;
      default "3";
      description
        "Current max-retransmit value.";
    }
  }
  container ack-timeout {
    description
      "Initial retransmission timeout value.";
    choice direction {
      description
        "xxx.";
      case server-to-client {
        description
          "xx.";
        leaf max-value-decimal {
          type decimal64 {
            fraction-digits 2;
          }
          units "seconds";
      config false;
          description
            "Maximum ack-timeout value.";
        }
        leaf min-value-decimal {
          type decimal64 {
            fraction-digits 2;
          }
          units "seconds";
      config false;
          description
            "Minimum ack-timeout value.";
        }
      }
    }
    leaf current-value-decimal {
      type decimal64 {
        fraction-digits 2;
      }
      units "seconds";
      default "2";
      description
        "Current ack-timeout value.";
    }
  }
  container ack-random-factor {
    description
      "Random factor used to influence the timing of
       retransmissions.";
```

```
      choice direction {
        description
          "xxx.";
        case server-to-client {
          description
            "xx.";
          leaf max-value-decimal {
            type decimal64 {
              fraction-digits 2;
            }
      config false;
            description
              "Maximum acceptable ack-random-factor value.";
          }
          leaf min-value-decimal {
            type decimal64 {
              fraction-digits 2;
            }
      config false;
            description
              "Minimum acceptable ack-random-factor value.";
          }
        }
      }
      leaf current-value-decimal {
        type decimal64 {
          fraction-digits 2;
        }
        default "1.5";
        description
          "Current ack-random-factor value.";
      }
    }
  }

  grouping signal-config {
    description
      "DOTS signal channel session configuration.";
    leaf sid {
      type uint32;
      mandatory true;
      description
        "An identifier for the DOTS signal channel
         session configuration data.";
    }
    container mitigating-config {
      description
        "Configuration parameters to use when a mitigation
         is active.";
      uses config-parameters;
    }
    container idle-config {
      description
```

```
              "Configuration parameters to use when no mitigation
               is active.";
          uses config-parameters;
        }
      }

      grouping redirected-signal {
        description
          "Grouping for the redirected signaling.";
        choice direction {
          description
            "xxx.";
          case server-to-client {
            description
              "xx.";
            leaf alt-server {
              type string;
          config false;
              mandatory true;
              description
                "FQDN of an alternate server.";
            }
            leaf-list alt-server-record {
              type inet:ip-address;
          config false;
              description
                "List of records for the alternate server.";
            }
          }
        }
      }

      /*
       * Main Container for DOTS Signal Channel
       */

      container dots-signal
      sx:structure "dots-signal" {
        description
          "Main container for DOTS signal message.

           A DOTS signal message can be a mitigation, a configuration,
           or a redirected signal message.";
        choice message-type {
          description
            "Can be a mitigation, a configuration, or a redirect
             message.";
          case mitigation-scope {
            description
              "Mitigation scope of a mitigation message.";
            uses mitigation-scope;
          }
          case signal-config {
```

```
            description
              "Configuration message.";
            uses signal-config;
          }
          case redirected-signal {
            description
              "Redirected signaling.";
            uses redirected-signal;
          }
          case heartbeat {
            description
              "DOTS heartbeats.";
            leaf peer-hb-status {
              type boolean;
              mandatory true;
              description
                "Indicates whether a DOTS agent receives heartbeats
                 from its peer.  The value is set to 'true' if the
                 DOTS agent is receiving heartbeat messages
                 from its peer.";
            }
          }
        }
      }
    }
```