



Business Message Documentation

Application Type	Application Business Message (ABM)
M3 version	BE15
M3 Business Message	PDS - Purchase Delivery Schedule
Message Direction	Outbound
Message Application	ABM PurchaseDeliverySchedule Show 1

Map name	M3BE15_PDS_Out_ABM_PurchaseDeliverySchedule_Show_1
----------	--

Source file	ABM_PurchaseDeliverySchedule_Show_1_MIG_v1.pdf
Created	2013-09-03 15:56



Introduction

This document is a Message Implementation Guideline (MIG) for a business message used in Infor's enterprise application, M3. It defines in detail the collaboration logic between the business message and the M3 system.

The MIG supplied by Infor is based on the business functionality in M3.

The business message format is Extensible Markup Language (XML). XML is a standard developed by the World Wide Web Consortium (W3C). "Element" in this document refers to an XML element. The business message is divided into "message parts"; a message part is a logical unit within the business message, for example, a header, an address or details/lines. Within each message part each element can have up to four parents. The message part, the parents and the element define the XPath for the element. Structural levels for the message's object and process (for example "PurchaseOrder" and "Show") are only shown in the XPaths in this document.

This document consists of two major sections: Elements Used and Element Documentation. The section Elements Used provides an overall view of all elements used in this MIG. The section Element Documentation provides detailed specifications of each and every element implemented in the business message. The element information is presented in the order in which the elements are defined in the business message.



Elements Used

This section contains a summary of all elements used in this message application, that is, the elements that have documentation attached. The XPaths for these elements are provided relative to the message parts. The elements are listed in message structure order



Elements Used

MessagePart

GeneralMessageHeader

MessageIdentification/MessageObject
MessageIdentification/MessageMethod
MessageIdentification/MessageVersion
MessageIdentification/MessageIdentityNumber
MessageLanguage/Language/Code
MessageLanguage/Language/Description
MessageDate/DateAndTime/Date
MessageDate/DateAndTime/Time
MessageDate/DateAndTime/GMTOffset
MessageDate/DateAndTime/DateFormat
MessageDate/DateAndTime/TimeFormat
MessageFunction/MessageFunctionIndicator
MessageStatus/MessageStatusIndicator
ApplicationMessage/Identity
ApplicationMessage/SeverityCode
ApplicationMessage/Text
ApplicationMessage/LanguageCode



Elements Used

MessagePart	Show/Address
	SAK2
	SAK3
	SNAM
	SAD1
	SAD2
	SAD3
	SAD4
	VAK2
	VAK3
	VNAM
	VAD1
	VAD2
	VAD3
	VAD4
	INAM
	IAD1
	IAD2
	IAD3
	IAD4
	DAK2
	DAK3
	DNAM
	DAD1
	DAD2
	DAD3
	DAD4



Elements Used

MessagePart	Show/Detail
	Item/PNLI
	Item/PNLS
	Item/ITNO
	Item/SITE
	Item/CODT
	Item/CFQA
	Item/PUUN
	Item/ITDS
	Item/EACD
	Item/FACI
	Item/WHLO
	Item/POTC
	Item/PUST
	Item/PUSL
	Item/SUNO
	Item/PRCS
	Item/SUFI
	Item/PITD
	Item/PITT
	Item/SORN
	Item/PUPR
	Item/ODI1
	Item/ODI2
	Item/ODI3
	Item/CPPR
	Item/CFD1
	Item/CFD2
	Item/CFD3
	Item/PPUN
	Item/PUCD
	Item/CPUC
	Item/LNAM
	Item/PTCD
	Item/DWDT
	Item/ORQA
	Item/ADQA
	Item/TNQA
	Item/RVQA
	Item/RCDT
	Item/CAQA



Elements Used

MessagePart	Show/Detail
	Item/RJQA
	Item/SDQA
	Item/IVQA
	Item/IDAT
	Item/PLPN
	Item/PLPS
	Item/PURC
	Item/BUYE
	Item/GRMT
	Item/PACT
	Item/TXID
	Item/ECVE
	Item/OURR
	Item/OURT
	Item/VTCD
	Item/ATNR
	Item/RORC
	Item/RORN
	Item/RORL
	Item/RORX
	CumQuantity/IRTY
	CumQuantity/INRF
	CumQuantity/CUML
	CumQuantity/WHLO
	CumQuantity/ADID
	CumQuantity/DLSP
	CumQuantity/MOYE
	CumQuantity/AGNO
	CumQuantity/CQCF
	CumQuantity/CQCA
	CumQuantity/CUMD
	CumQuantity/POPN
	CumQuantity/ALWT
	CumQuantity/ALWQ
	CumQuantity/CUFD
	CumQuantity/CUMR
	CumQuantity/CUAY
	DeliveryNote/PRCS
	DeliveryNote/SUFI
	DeliveryNote/REPN



Elements Used

MessagePart	Show/Detail
	DeliveryNote/PUNO
	DeliveryNote/PNLI
	DeliveryNote/PNLS
	DeliveryNote/RCDT
	DeliveryNote/RPQA
	DeliveryNote/PUUN
	DeliveryNote/SUDO
	Demand/DSPN
	Demand/WHLO
	Demand/ITNO
	Demand/PUNO
	Demand/PNLI
	Demand/PNLS
	Demand/VDDT
	Demand/ORQA
	Demand/PRQA
	Demand/LEDT
	Demand/RGTM
	Demand/PLPN
	Demand/PLPS
	Demand/FPLP
	Demand/FDAT
	Demand/CMCO
	Demand/MEDC
	Demand/RSIN



Elements Used

MessagePart	Show/Header
	CONO
	PUNO
	DONR
	DOVA
	DATE
	PUDT
	DWDT
	LEDT
	CONM
	REVN
	RENM
	SUNO
	CSCD
	BUYE
	CUCD
	TXCU
	TXPY
	TXMO
	TXDL
	TXAF
	TXPA
	TXHA
	YRE1
	PHNO
	TFNO
	REVV
	REMK
	REV1
	COAM
	DIVI
	FACI
	WHLO
	ORTY
	LNCD
	TEPY
	MODL
	TEDL
	TEAF
	TEPA
	RFID



Elements Used

MessagePart	Show/Header
	TEL1
	HAFE
	POTC
	PYAD
	MTDP
	MTWP
	OURR
	OURT
	PRSU
	AGNT



Elements Used

MessagePart	Show/TextLine
	LNCD
	TXID
	TYTR
	TXVR
	TXCC
	TXEI
	LINO
	TX60



Element Documentation

This section is based on the same structure as the section Elements Used, but here you see all the available descriptions, statuses (conditional or mandatory), repeats (0, 1, 2 etc. or unbounded), data types (alphanumeric, numeric, date etc.) and data lengths. There is a page break for every message part. Parents' attributes are only shown when the parents change. This section also includes M3 application documentation and the XPath for the element, which specifies the position of the element in the message structure.

M3 application documentation consists of three sections: M3 Application Description, M3 Application Data Translation and M3 Application Specification.

M3 Application Description

This section provides a general description in “business process language” and describes how the element is used in relation to the M3 logic, for example, which M3 data is used.

M3 Application Data Translation

This section specifies whether or not the data can be translated between M3 and the message. Data translation is used, for example, to translate unit of measure (“STK” to “PCS”) and currency codes (“PND” to “GBP”). Data translations are managed by the M3 program “Business Message Data Translation. Display” (CRS881) and the program “Business Message Data. Translate” (CRS882). The key used in (CRS881) for the element’s data translation is provided.

M3 Application Specification

This section contains the specification that constitutes the base for the business message. It describes whether the element uses data from or transfers data to a M3 API, uses calculated data and/or fixed data. It also describes how and when to make the M3 API calls, which input and output fields to use, etc. Additional information may also be given, such as conditions or notes to clarify specific logic used. Taken together, the sections M3 Application Description and M3 Application Specification define the functionality of the business message.

MessagePart		Repeat		Description
GeneralMessageHeader		M	1	General message header
Parent1	MessageIdentification	M	1	Message identification
Element	MessageObject	M		Message object
XPath: <i>PurchaseDeliverySchedule_Show_1/GeneralMessageHeader/MessageIdentification/MessageObject</i>				
Parent1	MessageIdentification	M	1	Message identification
Element	MessageMethod	M		Message method
XPath: <i>PurchaseDeliverySchedule_Show_1/GeneralMessageHeader/MessageIdentification/MessageMethod</i>				
Parent1	MessageIdentification	M	1	Message identification
Element	MessageVersion	M		Message version
XPath: <i>PurchaseDeliverySchedule_Show_1/GeneralMessageHeader/MessageIdentification/MessageVersion</i>				
Parent1	MessageIdentification	M	1	Message identification
Element	MessageIdentityNumber	M		MessageIdentityNumber
XPath: <i>PurchaseDeliverySchedule_Show_1/GeneralMessageHeader/MessageIdentification/MessageIdentityNumber</i>				
Parent2	MessageLanguage	M	1	MessageLanguage
Parent1	Language	M	1	Language
Element	Code	M		Code
XPath: <i>PurchaseDeliverySchedule_Show_1/GeneralMessageHeader/MessageLanguage/Language/Code</i>				
Parent2	MessageLanguage	M	1	MessageLanguage
Parent1	Language	M	1	Language
Element	Description	C		Description
XPath: <i>PurchaseDeliverySchedule_Show_1/GeneralMessageHeader/MessageLanguage/Language/Description</i>				
Parent2	MessageDate	M	1	Message Date
Parent1	DateAndTime	C	1	DateAndTime
Element	Date	M		Date
XPath: <i>PurchaseDeliverySchedule_Show_1/GeneralMessageHeader/MessageDate/DateAndTime/Date</i>				

MessagePart		Repeat		Description
GeneralMessageHeader		M	1	General message header
Parent2	MessageDate	M	1	Message Date
Parent1	DateAndTime	C	1	DateAndTime
Element	Time	C		Time

XPath: *PurchaseDeliverySchedule_Show_1/GeneralMessageHeader/MessageDate/DateAndTime/Time*

Parent2	MessageDate	M	1	Message Date
Parent1	DateAndTime	C	1	DateAndTime
Element	GMTOffset	C		GMTOffset

XPath: *PurchaseDeliverySchedule_Show_1/GeneralMessageHeader/MessageDate/DateAndTime/GMTOffset*

Parent2	MessageDate	M	1	Message Date
Parent1	DateAndTime	C	1	DateAndTime
Element	DateFormat	C		Date format

XPath: *PurchaseDeliverySchedule_Show_1/GeneralMessageHeader/MessageDate/DateAndTime/DateFormat*

Parent2	MessageDate	M	1	Message Date
Parent1	DateAndTime	C	1	DateAndTime
Element	TimeFormat	C		Time format

XPath: *PurchaseDeliverySchedule_Show_1/GeneralMessageHeader/MessageDate/DateAndTime/TimeFormat*

Parent1	MessageFunction	C	1	Message function
Element	MessageFunctionIndicator	C		Message function indicator

XPath: *PurchaseDeliverySchedule_Show_1/GeneralMessageHeader/MessageFunction/MessageFunctionIndicator*

Parent1	MessageStatus	C	1	Message status
Element	MessageStatusIndicator	C		Message status indicator

XPath: *PurchaseDeliverySchedule_Show_1/GeneralMessageHeader/MessageStatus/MessageStatusIndicator*

Parent1	ApplicationMessage	C	unbounded	Application message
Element	Identity	M		Identity

XPath: *PurchaseDeliverySchedule_Show_1/GeneralMessageHeader/ApplicationMessage/Identity*



MessagePart		Repeat		Description
GeneralMessageHeader		M	1	General message header
Parent1	ApplicationMessage	C	unbounded	Application message
Element	SeverityCode	C		Severity code
XPath: <i>PurchaseDeliverySchedule_Show_1/GeneralMessageHeader/ApplicationMessage/SeverityCode</i>				
Parent1	ApplicationMessage	C	unbounded	Application message
Element	Text	M		Text
XPath: <i>PurchaseDeliverySchedule_Show_1/GeneralMessageHeader/ApplicationMessage/Text</i>				
Parent1	ApplicationMessage	C	unbounded	Application message
Element	LanguageCode	M		Language code
XPath: <i>PurchaseDeliverySchedule_Show_1/GeneralMessageHeader/ApplicationMessage/LanguageCode</i>				



MessagePart		Repeat	Description
Show/Address		C 1	Purchase delivery schedule address
Element	SAK2	C a 3	Supplier address key 2

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: SAK2

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/SAK2*

Element	SAK3	C a 3	Supplier address key 3
---------	------	-------	------------------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: SAK3

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/SAK3*

Element	SNAM	C a 36	Supplier name
---------	------	--------	---------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: SNAM

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/SNAM*

Element	SAD1	C a 36	Supplier Address line 1
---------	------	--------	-------------------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: SAD1

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/SAD1*

Element	SAD2	C a 36	Supplier Address line 2
---------	------	--------	-------------------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: SAD2

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/SAD2*

Element	SAD3	C a 36	Supplier Address line 3
---------	------	--------	-------------------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: SAD3

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/SAD3*



MessagePart		Repeat	Description
Show/Address		C 1	Purchase delivery schedule address
Element	SAD4	C a 36	Supplier Address line 4

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: SAD4

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/SAD4*

Element	VAK2	C a 3	Via Goods Receiver address key 2
---------	------	-------	----------------------------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: VAK2

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/VAK2*

Element	VAK3	C a 3	Via Goods Receiver address key 3
---------	------	-------	----------------------------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: VAK3

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/VAK3*

Element	VNAM	C a 36	Via Goods Receiver Name
---------	------	--------	-------------------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: VNAM

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/VNAM*

Element	VAD1	C a 36	Via Goods Receiver Address line 1
---------	------	--------	-----------------------------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: VAD1

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/VAD1*

Element	VAD2	C a 36	Via Goods Receiver Address line 2
---------	------	--------	-----------------------------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: VAD2

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/VAD2*



MessagePart		Repeat	Description
Show/Address		C 1	Purchase delivery schedule address
Element	VAD3	C a 36	Via Goods Receiver Address line 3

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: VAD3

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/VAD3*

Element	VAD4	C a 36	Via Goods Receiver Address line 4
---------	------	--------	-----------------------------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: VAD4

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/VAD4*

Element	INAM	C a 36	Invoice Receiver name
---------	------	--------	-----------------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: INAM

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/INAM*

Element	IAD1	C a 36	Invoice Receiver Address line 1
---------	------	--------	---------------------------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: IAD1

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/IAD1*

Element	IAD2	C a 36	Invoice Receiver Address line 2
---------	------	--------	---------------------------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: IAD2

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/IAD2*

Element	IAD3	C a 36	Invoice Receiver Address line 3
---------	------	--------	---------------------------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: IAD3

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/IAD3*



MessagePart		Repeat	Description
Show/Address		C 1	Purchase delivery schedule address
Element	IAD4	C a 36	Invoice Receiver Address line 4

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: IAD4

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/IAD4*

Element	DAK2	C a 3	Delivery address key 2
---------	------	-------	------------------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: DAK2

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/DAK2*

Element	DAK3	C a 3	Delivery address key 3
---------	------	-------	------------------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: DAK3

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/DAK3*

Element	DNAM	C a 36	Delivery Receiver name
---------	------	--------	------------------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: DNAM

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/DNAM*

Element	DAD1	C a 36	Delivery Address line 1
---------	------	--------	-------------------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: DAD1

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/DAD1*

Element	DAD2	C a 36	Delivery Address line 2
---------	------	--------	-------------------------

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: DAD2

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/DAD2*



MessagePart		Repeat		Description
Show/Address		C	1	Purchase delivery schedule address
Element	DAD3	C	a 36	Delivery Address line 3

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: GetAddressesResponse Field: DAD3

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/DAD3*

Element	DAD4	C	a 36	Delivery Address line 4
M3 Application Description:				
M3 Application Specification:				
API data MI program: PPS200MI Transaction: GetAddressesResponse Field: DAD4				
XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Address/DAD4</i>				



MessagePart		Repeat	Description
Show/Detail		C unbou	Purchase delivery schedule detail

Parent1	Item	M 1	Purchase delivery schedule item
Element	PNLI	C n 3	Purchase order line

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: PNLI

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/PNLI*

Parent1	Item	M 1	Purchase delivery schedule item
Element	PNLS	C n 3	Purchase order line subnumber

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: PNLS

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/PNLS*

Parent1	Item	M 1	Purchase delivery schedule item
Element	ITNO	C a 15	Item number

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: ITNO

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/ITNO*

Parent1	Item	M 1	Purchase delivery schedule item
Element	SITE	C a 30	Supplier item number

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: SITE

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/SITE*

Parent1	Item	M 1	Purchase delivery schedule item
Element	CODT	C d 10	Confirmed delivery date

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: CODT

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/CODT*



MessagePart		Repeat	Description
Show/Detail		C unbou	Purchase delivery schedule detail
Parent1	Item	M 1	Purchase delivery schedule item
Element	CFQA	C n 17	Confirmed quantity
M3 Application Description:			
M3 Application Specification:			
API data MI program: PPS200MI Transaction: LstLine_Record Field: CFQA			
XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/CFQA</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	PUUN	C a 3	Purchase order U/M
M3 Application Description:			
M3 Application Specification:			
API data MI program: PPS200MI Transaction: LstLine_Record Field: PUUN			
XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/PUUN</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	ITDS	C a 30	Name
M3 Application Description:			
M3 Application Specification:			
API data MI program: PPS200MI Transaction: LstLine_Record Field: ITDS			
XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/ITDS</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	EACD	C n 13	EAN code
M3 Application Description:			
M3 Application Specification:			
API data MI program: PPS200MI Transaction: LstLine_Record Field: EACD			
XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/EACD</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	FACI	C a 3	Facility
M3 Application Description:			
M3 Application Specification:			
API data MI program: PPS200MI Transaction: LstLine_Record Field: FACI			
XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/FACI</i>			



MessagePart		Repeat	Description
Show/Detail		C unbou	Purchase delivery schedule detail

Parent1	Item	M 1	Purchase delivery schedule item
Element	WHLO	C a 3	Warehouse

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: WHLO

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/WHLO*

Parent1	Item	M 1	Purchase delivery schedule item
Element	POTC	C a 2	Purchase order category

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: POTC

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/POTC*

Parent1	Item	M 1	Purchase delivery schedule item
Element	PUST	C a 2	Highest status - purchase order

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: PUST

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/PUST*

Parent1	Item	M 1	Purchase delivery schedule item
Element	PUSL	C a 2	Lowest status - purchase order

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: PUSL

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/PUSL*

Parent1	Item	M 1	Purchase delivery schedule item
Element	SUNO	C a 10	Supplier number

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: SUNO

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/SUNO*



MessagePart		Repeat	Description
Show/Detail		C unbou	Purchase delivery schedule detail
Parent1	Item	M 1	Purchase delivery schedule item
Element	PRCS	C a 3	Service process
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: PRCS XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/PRCS</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	SUFI	C a 20	Service
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: SUFI XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/SUFI</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	PITD	C a 30	Purchase order item name
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: PITD XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/PITD</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	PITT	C a 60	Purchase order item description
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: PITT XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/PITT</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	SORN	C a 20	Supplier order number
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: SORN XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/SORN</i>			



MessagePart		Repeat	Description
Show/Detail		C unbou	Purchase delivery schedule detail

Parent1	Item	M 1	Purchase delivery schedule item
Element	PUPR	C n 17	Purchase price

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: PUPR

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/PUPR*

Parent1	Item	M 1	Purchase delivery schedule item
Element	ODI1	C n 7	Discount 1

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: ODI1

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/ODI1*

Parent1	Item	M 1	Purchase delivery schedule item
Element	ODI2	C n 7	Discount 2

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: ODI2

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/ODI2*

Parent1	Item	M 1	Purchase delivery schedule item
Element	ODI3	C n 7	Discount 3

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: ODI3

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/ODI3*

Parent1	Item	M 1	Purchase delivery schedule item
Element	CPPR	C n 17	Confirmed purchase price

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: CPPR

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/PPR*

MessagePart		Repeat	Description
Show/Detail		C	unbou Purchase delivery schedule detail
Parent1	Item	M 1	Purchase delivery schedule item
Element	CFD1	C n 7	Confirmed discount 1
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: CFD1 XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/CFD1</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	CFD2	C n 7	Confirmed discount 2
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: CFD2 XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/CFD2</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	CFD3	C n 7	Confirmed discount 3
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: CFD3 XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/CFD3</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	PPUN	C a 3	Purchase price U/M
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: PPUN XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/PPUN</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	PUCD	C n 5	Purchase price quantity
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: PUCD XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/PUCD</i>			



MessagePart		Repeat	Description
Show/Detail		C unbou	Purchase delivery schedule detail

Parent1	Item	M 1	Purchase delivery schedule item
Element	CPUC	C n 5	Confirmed purchase price quantity

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: CPUC

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/CPUC*

Parent1	Item	M 1	Purchase delivery schedule item
Element	LNAM	C n 17	Line amount - order currency

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: LNAM

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/LNAM*

Parent1	Item	M 1	Purchase delivery schedule item
Element	PTCD	C n 1	Purchase price text

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: PTCD

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/PTCD*

Parent1	Item	M 1	Purchase delivery schedule item
Element	DWDT	C d 10	Requested delivery date

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: DWDT

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/DWDT*

Parent1	Item	M 1	Purchase delivery schedule item
Element	ORQA	C n 17	Ordered quantity - alternate U/M

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: ORQA

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/ORQA*



MessagePart		Repeat	Description
Show/Detail		C unbou	Purchase delivery schedule detail
Parent1	Item	M 1	Purchase delivery schedule item
Element	ADQA	C n 17	Advised quantity alternate U/M
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: ADQA XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/ADQA</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	TNQA	C n 17	Transport notified quantity
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: TNQA XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/TNQA</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	RVQA	C n 17	Received quantity
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: RVQA XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/RVQA</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	RCDT	C d 10	Receipt date
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: RCDT XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/RCDT</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	CAQA	C n 17	Approved quantity - alternate U/M
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: CAQA XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/CAQA</i>			



MessagePart		Repeat	Description
Show/Detail		C unbou	Purchase delivery schedule detail

Parent1	Item	M 1	Purchase delivery schedule item
Element	RJQA	C n 17	Rejected quantity

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: RJQA

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/RJQA*

Parent1	Item	M 1	Purchase delivery schedule item
Element	SDQA	C n 17	Stored quantity

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: SDQA

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/SDQA*

Parent1	Item	M 1	Purchase delivery schedule item
Element	IVQA	C n 17	Invoiced quantity - alternate U/M

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: IVQA

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/IVQA*

Parent1	Item	M 1	Purchase delivery schedule item
Element	IDAT	C d 10	Invoice date

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: IDAT

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/IDAT*

Parent1	Item	M 1	Purchase delivery schedule item
Element	PLPN	C n 7	Order proposal number

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: PLPN

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/PLPN*



MessagePart		Repeat	Description
Show/Detail		C unbou	Purchase delivery schedule detail
Parent1	Item	M 1	Purchase delivery schedule item
Element	PLPS	C n 3	Subnumber - order proposal
M3 Application Description:			
M3 Application Specification:			
API data MI program: PPS200MI Transaction: LstLine_Record Field: PLPS			
XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/PLPS</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	PURC	C a 10	Requisition by
M3 Application Description:			
M3 Application Specification:			
API data MI program: PPS200MI Transaction: LstLine_Record Field: PURC			
XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/PURC</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	BUYE	C a 10	Buyer
M3 Application Description:			
M3 Application Specification:			
API data MI program: PPS200MI Transaction: LstLine_Record Field: BUYE			
XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/BUYE</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	GRMT	C a 3	Goods receiving method
M3 Application Description:			
M3 Application Specification:			
API data MI program: PPS200MI Transaction: LstLine_Record Field: GRMT			
XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/GRMT</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	PACT	C a 6	Packaging
M3 Application Description:			
M3 Application Specification:			
API data MI program: PPS200MI Transaction: LstLine_Record Field: PACT			
XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/PACT</i>			



MessagePart		Repeat	Description
Show/Detail		C unbou	Purchase delivery schedule detail

Parent1	Item	M 1	Purchase delivery schedule item
Element	TXID	C n 13	Text identity

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: TXID

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/TXID*

Parent1	Item	M 1	Purchase delivery schedule item
Element	ECVE	C a 4	Revision number

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: ECVE

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/ECVE*

Parent1	Item	M 1	Purchase delivery schedule item
Element	OURR	C a 10	Our reference number

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: OURR

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/OURR*

Parent1	Item	M 1	Purchase delivery schedule item
Element	OURT	C a 1	Reference type

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: OURT

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/OURT*

Parent1	Item	M 1	Purchase delivery schedule item
Element	VTCD	C n 2	VAT code

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLine_Record Field: VTCD

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/VTCD*

MessagePart		Repeat	Description
Show/Detail		C	unbou Purchase delivery schedule detail
Parent1	Item	M 1	Purchase delivery schedule item
Element	ATNR	C n 17	Attribute number
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: ATNR XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/ATNR</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	RORC	C n 1	Reference order category
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: RORC XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/RORC</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	RORN	C a 10	Reference order number
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: RORN XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/RORN</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	RORL	C n 6	Reference order line
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: RORL XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/RORL</i>			
Parent1	Item	M 1	Purchase delivery schedule item
Element	RORX	C n 3	Line suffix
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLine_Record Field: RORX XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Item/RORX</i>			



MessagePart		Repeat	Description
Show/Detail		C unbou	Purchase delivery schedule detail

Parent1	CumQuantity	C unbounded	
Element	IRTY	C n 1	Internal reference type

M3 Application Description:

M3 Application Specification:

API data MI program: MMS072MI Transaction: LstCumulative_Record Field: IRTY

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/CumQuantity/IRTY*

Parent1	CumQuantity	C unbounded	
Element	INRF	C a 10	Internal reference

M3 Application Description:

M3 Application Specification:

API data MI program: MMS072MI Transaction: LstCumulative_Record Field: INRF

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/CumQuantity/INRF*

Parent1	CumQuantity	C unbounded	
Element	CUML	C n 2	Cumulative level

M3 Application Description:

M3 Application Specification:

API data MI program: MMS072MI Transaction: LstCumulative_Record Field: CUML

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/CumQuantity/CUML*

Parent1	CumQuantity	C unbounded	
Element	WHLO	C a 3	Warehouse

M3 Application Description:

M3 Application Specification:

API data MI program: MMS072MI Transaction: LstCumulative_Record Field: WHLO

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/CumQuantity/WHLO*

Parent1	CumQuantity	C unbounded	
Element	ADID	C a 6	Address number

M3 Application Description:

M3 Application Specification:

API data MI program: MMS072MI Transaction: LstCumulative_Record Field: ADID

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/CumQuantity/ADID*



MessagePart		Repeat	Description
Show/Detail		C unbou	Purchase delivery schedule detail
Parent1	CumQuantity	C unbounded	
Element	DLSP	C a 12	Delivery specification
M3 Application Description: M3 Application Specification: API data MI program: MMS072MI Transaction: LstCumulative_Record Field: DLSP XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/CumQuantity/DLSP</i>			
Parent1	CumQuantity	C unbounded	
Element	MOYE	C a 15	Model/year
M3 Application Description: M3 Application Specification: API data MI program: MMS072MI Transaction: LstCumulative_Record Field: MOYE XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/CumQuantity/MOYE</i>			
Parent1	CumQuantity	C unbounded	
Element	AGNO	C a 7	Blanket agreement number
M3 Application Description: M3 Application Specification: API data MI program: MMS072MI Transaction: LstCumulative_Record Field: AGNO XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/CumQuantity/AGNO</i>			
Parent1	CumQuantity	C unbounded	
Element	CQCF	C n 17	Cumulative quantity
M3 Application Description: M3 Application Specification: API data MI program: MMS072MI Transaction: LstCumulative_Record Field: CQCF XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/CumQuantity/CQCF</i>			
Parent1	CumQuantity	C unbounded	
Element	CQCA	C n 17	Cumulative quantity Alternate U/M
M3 Application Description: M3 Application Specification: API data MI program: MMS072MI Transaction: LstCumulative_Record Field: CQCA XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/CumQuantity/CQCA</i>			



MessagePart		Repeat	Description
Show/Detail		C unbou	Purchase delivery schedule detail

Parent1	CumQuantity	C unbounded	
Element	CUMD	C d 10	Cumulative calculation date

M3 Application Description:

M3 Application Specification:

API data MI program: MMS072MI Transaction: LstCumulative_Record Field: CUMD

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/CumQuantity/CUMD*

Parent1	CumQuantity	C unbounded	
Element	POPN	C a 30	Alias number

M3 Application Description:

M3 Application Specification:

API data MI program: MMS072MI Transaction: LstCumulative_Record Field: POPN

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/CumQuantity/POPN*

Parent1	CumQuantity	C unbounded	
Element	ALWT	C n 2	Alias category

M3 Application Description:

M3 Application Specification:

API data MI program: MMS072MI Transaction: LstCumulative_Record Field: ALWT

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/CumQuantity/ALWT*

Parent1	CumQuantity	C unbounded	
Element	ALWQ	C a 4	Alias qualifier

M3 Application Description:

M3 Application Specification:

API data MI program: MMS072MI Transaction: LstCumulative_Record Field: ALWQ

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/CumQuantity/ALWQ*

Parent1	CumQuantity	C unbounded	
Element	CUFD	C d 10	Cumulative from date

M3 Application Description:

M3 Application Specification:

API data MI program: MMS072MI Transaction: LstCumulative_Record Field: CUFD

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/CumQuantity/CUFD*



MessagePart		Repeat	Description
Show/Detail		C unbou	Purchase delivery schedule detail
Parent1	CumQuantity	C unbounded	
Element	CUMR	C n 1	Deduct returns
M3 Application Description: M3 Application Specification: API data MI program: MMS072MI Transaction: LstCumulative_Record Field: CUMR XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/CumQuantity/CUMR</i>			
Parent1	CumQuantity	C unbounded	
Element	CUAY	C n 1	Year to year cumulative calculation
M3 Application Description: M3 Application Specification: API data MI program: MMS072MI Transaction: LstCumulative_Record Field: CUAY XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/CumQuantity/CUAY</i>			
Parent1	DeliveryNote	C unbounded	Delivery schedule receive
Element	PRCS	C a 3	Service process
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLatestDel_Record Field: PRCS XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/DeliveryNote/PRCS</i>			
Parent1	DeliveryNote	C unbounded	Delivery schedule receive
Element	SUFI	C a 20	Service
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLatestDel_Record Field: SUFI XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/DeliveryNote/SUFI</i>			
Parent1	DeliveryNote	C unbounded	Delivery schedule receive
Element	REPN	C n 10	Receiving number
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLatestDel_Record Field: REPN XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/DeliveryNote/REPN</i>			



MessagePart		Repeat	Description
Show/Detail		C	unbou Purchase delivery schedule detail
Parent1	DeliveryNote	C	unbounded Delivery schedule receive
Element	PUNO	C a 7	Purchase order number

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLatestDel_Record Field: PUNO

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/DeliveryNote/PUNO*



MessagePart		Repeat	Description
Show/Detail		C unbou	Purchase delivery schedule detail
Parent1	DeliveryNote	C unbounded	Delivery schedule receive
Element	PNLI	C n 3	Purchase order line
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLatestDel_Record Field: PNLI XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/DeliveryNote/PNLI</i>			
Parent1	DeliveryNote	C unbounded	Delivery schedule receive
Element	PNLS	C n 3	Purchase order line subnumber
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLatestDel_Record Field: PNLS XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/DeliveryNote/PNLS</i>			
Parent1	DeliveryNote	C unbounded	Delivery schedule receive
Element	RCDT	C d 10	Receipt date
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLatestDel_Record Field: RCDT XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/DeliveryNote/RCDT</i>			
Parent1	DeliveryNote	C unbounded	Delivery schedule receive
Element	RPQA	C n 17	Reported quantity in alternative unit
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLatestDel_Record Field: RPQA XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/DeliveryNote/RPQA</i>			
Parent1	DeliveryNote	C unbounded	Delivery schedule receive
Element	PUUN	C a 3	Purchase order U/M
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstLatestDel_Record Field: PUUN XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/DeliveryNote/PUUN</i>			



MessagePart		Repeat	Description
Show/Detail		C unbou	Purchase delivery schedule detail

Parent1	DeliveryNote	C unbounded	Delivery schedule receive
Element	SUDO	C a 20	Delivery note number

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstLatestDel_Record Field: SUDO

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/DeliveryNote/SUDO*

Parent1	Demand	M unbounded	Purchase delivery schedule demand
Element	DSPN	C n 11	Printout number - delivery schedule

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstDelSchLine_Record Field: DSPN

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Demand/DSPN*

Parent1	Demand	M unbounded	Purchase delivery schedule demand
Element	WHLO	C a 3	Warehouse

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstDelSchLine_Record Field: WHLO

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Demand/WHLO*

Parent1	Demand	M unbounded	Purchase delivery schedule demand
Element	ITNO	C a 15	Item number

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstDelSchLine_Record Field: ITNO

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Demand/ITNO*

Parent1	Demand	M unbounded	Purchase delivery schedule demand
Element	PUNO	C a 7	Purchase order number

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstDelSchLine_Record Field: PUNO

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Demand/PUNO*

MessagePart		Repeat	Description
Show/Detail		C	unbou Purchase delivery schedule detail
Parent1	Demand	M unbounded	Purchase delivery schedule demand
Element	PNLI	C n 3	Purchase order line
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstDelSchLine_Record Field: PNLI XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Demand/PNLI</i>			
Parent1	Demand	M unbounded	Purchase delivery schedule demand
Element	PNLS	C n 3	Purchase order line subnumber
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstDelSchLine_Record Field: PNLS XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Demand/PNLS</i>			
Parent1	Demand	M unbounded	Purchase delivery schedule demand
Element	VDDT	C d 10	Valid delivery date
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstDelSchLine_Record Field: VDDT XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Demand/VDDT</i>			
Parent1	Demand	M unbounded	Purchase delivery schedule demand
Element	ORQA	C n 17	Ordered quantity - alternate U/M
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstDelSchLine_Record Field: ORQA XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Demand/ORQA</i>			
Parent1	Demand	M unbounded	Purchase delivery schedule demand
Element	PRQA	C n 17	Printed quantity
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstDelSchLine_Record Field: PRQA XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Demand/PRQA</i>			



MessagePart		Repeat	Description
Show/Detail		C unbou	Purchase delivery schedule detail

Parent1	Demand	M unbounded	Purchase delivery schedule demand
Element	LEDT	C d 10	First printout date

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstDelSchLine_Record Field: LEDT

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Demand/LEDT*

Parent1	Demand	M unbounded	Purchase delivery schedule demand
Element	RGTM	C n 6	Entry time

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstDelSchLine_Record Field: RGTM

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Demand/RGTM*

Parent1	Demand	M unbounded	Purchase delivery schedule demand
Element	PLPN	C n 7	Planned order

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstDelSchLine_Record Field: PLPN

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Demand/PLPN*

Parent1	Demand	M unbounded	Purchase delivery schedule demand
Element	PLPS	C n 3	Subnumber - planned order

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstDelSchLine_Record Field: PLPS

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Demand/PLPS*

Parent1	Demand	M unbounded	Purchase delivery schedule demand
Element	FPLP	C n 1	From planned order

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstDelSchLine_Record Field: FPLP

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Demand/FPLP*



MessagePart		Repeat	Description
Show/Detail		C unbounded	Purchase delivery schedule detail

Parent1 Demand M unbounded Purchase delivery schedule demand

Element FDAT C d 10 From date

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstDelSchLine_Record Field: FDAT

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Demand/FDAT*

Parent1 Demand M unbounded Purchase delivery schedule demand

Element CMCO C a 2 Communication code

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstDelSchLine_Record Field: CMCO

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Demand/CMCO*

Parent1 Demand M unbounded Purchase delivery schedule demand

Element MEDC C a 10 Media

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstDelSchLine_Record Field: MEDC

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Demand/MEDC*

Parent1 Demand M unbounded Purchase delivery schedule demand

Element RSIN C n 1 Delivery status indicator

M3 Application Description:

M3 Application Specification:

API data MI program: PPS200MI Transaction: LstDelSchLine_Record Field: RSIN

XPath: *PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Detail/Demand/RSIN*



MessagePart		Repeat		Description
Show/Header		M	1	Purchase delivery schedule header
Element	CONO	C	n 3	Company
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: CONO XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/CONO</i>				
Element	PUNO	C	a 7	Purchase order number
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: PUNO XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/PUNO</i>				
Element	DONR	C	a 3	Document number
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: DONR XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/DONR</i>				
Element	DOVA	C	a 2	Document variant
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: DOVA XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/DOVA</i>				
Element	DATE	C	d 10	Entry date
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: DATE XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/DATE</i>				
Element	PUDT	C	d 10	Order date
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: PUDT XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/PUDT</i>				



MessagePart		Repeat		Description
Show/Header		M	1	Purchase delivery schedule header
Element	DWDT	C	d 10	Requested delivery date
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: DWDT XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/DWDT</i>				
Element	LEDT	C	d 10	First printout date
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: LEDT XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/LEDT</i>				
Element	CONM	C	a 36	Company name
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: CONM XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/CONM</i>				
Element	REVN	C	a 2	Revision number
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: REVN XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/REVN</i>				
Element	RENM	C	a 36	Name of user responsible
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: RENM XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/RENM</i>				
Element	SUNO	C	a 10	Supplier number
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: SUNO XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/SUNO</i>				



MessagePart		Repeat	Description
Show/Header		M 1	Purchase delivery schedule header
Element	CSCD	C a 3	Country
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: CSCD XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/CSCD</i>			
Element	BUYE	C a 10	Buyer
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: BUYE XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/BUYE</i>			
Element	CUCD	C a 3	Currency
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: CUCD XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/CUCD</i>			
Element	TXCU	C a 15	Currency name
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: TXCU XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/TXCU</i>			
Element	TXPY	C a 15	Terms of Payment name
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: TXPY XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/TXPY</i>			
Element	TXMO	C a 15	Delivery Mode name
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: TXMO XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/TXMO</i>			



MessagePart		Repeat		Description
Show/Header		M	1	Purchase delivery schedule header
Element	TXDL	C	a 15	Terms of Delivery name
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: TXDL XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/TXDL</i>				
Element	TXAF	C	a 15	Terms of Freight name
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: TXAF XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/TXAF</i>				
Element	TXPA	C	a 15	Terms of Packaging name
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: TXPA XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/TXPA</i>				
Element	TXHA	C	a 15	Harbor or airport name
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: TXHA XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/TXHA</i>				
Element	YRE1	C	a 36	Your reference
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: YRE1 XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/YRE1</i>				
Element	PHNO	C	a 16	Telephone number
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: PHNO XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/PHNO</i>				



MessagePart		Repeat		Description
Show/Header		M	1	Purchase delivery schedule header
Element	TFNO	C	a 16	Facsimile transmission number
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: TFNO XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/TFNO</i>				
Element	REVV	C	n 15	Revision amount
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: REVV XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/REVV</i>				
Element	REMK	C	a 30	Remark
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: REMK XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/REMK</i>				
Element	REV1	C	n 15	Amount before revision
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: REV1 XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/REV1</i>				
Element	COAM	C	n 17	Total order cost
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: COAM XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/COAM</i>				
Element	DIVI	C	a 3	Division
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: DIVI XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/DIVI</i>				



MessagePart		Repeat	Description
Show/Header		M 1	Purchase delivery schedule header
Element	FACI	C a 3	Facility
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: FACI XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/FACI</i>			
Element	WHLO	C a 3	Warehouse
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: WHLO XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/WHLO</i>			
Element	ORTY	C a 3	Order type
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: ORTY XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/ORTY</i>			
Element	LNCD	C a 2	Language
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: LNCD XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/LNCD</i>			
Element	TEPY	C a 3	Payment terms
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: TEPY XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/TEPY</i>			
Element	MODL	C a 3	Delivery method
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: MODL XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/MODL</i>			



MessagePart		Repeat		Description
Show/Header		M	1	Purchase delivery schedule header
Element	TEDL	C	a 3	Delivery terms
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: TEDL XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/TEDL</i>				
Element	TEAF	C	a 3	Freight terms
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: TEAF XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/TEAF</i>				
Element	TEPA	C	a 3	Packaging terms
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: TEPA XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/TEPA</i>				
Element	RFID	C	a 10	Reference
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: RFID XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/RFID</i>				



MessagePart		Repeat		Description
Show/Header		M	1	Purchase delivery schedule header
Element	TEL1	C	a 36	Terms text
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: TEL1 XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/TEL1</i>				
Element	HAFE	C	a 6	Harbor or airport
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: HAFE XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/HAFE</i>				
Element	POTC	C	a 2	Purchase order category
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: POTC XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/POTC</i>				
Element	PYAD	C	a 3	Our invoicing address
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: PYAD XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/PYAD</i>				
Element	MTDP	C	n 1	Multiple delivery addresses
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: MTDP XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/MTDP</i>				
Element	MTWP	C	n 1	Multiple warehouses
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: MTWP XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/MTWP</i>				



MessagePart		Repeat		Description
Show/Header		M	1	Purchase delivery schedule header
Element	OURR	C	a 10	Our reference number
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: OURR XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/OURR</i>				
Element	OURT	C	a 1	Reference type
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: OURT XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/OURT</i>				
Element	PRSU	C	a 10	Payee
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: PRSU XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/PRSU</i>				
Element	AGNT	C	a 10	Agent
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: GetHeadResponse Field: AGNT XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/Header/AGNT</i>				



MessagePart		Repeat	Description
Show/TextLine		C unbou	Purchase delivery schedule text - head
Element	LNCD	C a 2	Language
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstHeadTxt_Record Field: LNCD XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/TextLine/LNCD</i>			
Element	TXID	C n 13	Text identity
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstHeadTxt_Record Field: TXID XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/TextLine/TXID</i>			
Element	TYTR	C a 1	Transaction type
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstHeadTxt_Record Field: TYTR XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/TextLine/TYTR</i>			
Element	TXVR	C a 10	Text block
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstHeadTxt_Record Field: TXVR XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/TextLine/TXVR</i>			
Element	TXCC	C a 2	Text control code
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstHeadTxt_Record Field: TXCC XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/TextLine/TXCC</i>			
Element	TXEI	C n 1	External/internal text
M3 Application Description: M3 Application Specification: API data MI program: PPS200MI Transaction: LstHeadTxt_Record Field: TXEI XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/TextLine/TXEI</i>			



MessagePart		Repeat	Description
Show/TextLine		C unbou	Purchase delivery schedule text - head
Element	LINO	C n 3	Line number
M3 Application Description:			
M3 Application Specification:			
API data MI program: PPS200MI Transaction: LstHeadTxt_Record Field: LINO			
XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/TextLine/LINO</i>			
Element	TX60	C a 60	Text
M3 Application Description:			
M3 Application Specification:			
API data MI program: PPS200MI Transaction: LstHeadTxt_Record Field: TX60			
XPath: <i>PurchaseDeliverySchedule_Show_1/PurchaseDeliverySchedule/Show/TextLine/TX60</i>			



END