



Business Message Documentation

Application Type	EDI Business Message (EBM)
M3 version	BE15
M3 Business Message	DDI - Delivery Demand Instraction
Message Direction	Inbound
Message Application	Ford GSEC X12 862 2002

Map name	M3BE15_DDI_In_Ford_GSEC_X12_862_2002
----------	---

Source file	M3BE15_DDI_In_Ford_GSEC_X12_862_2002_MIG_v1.pdf
Created	2013-06-13 15:40



Introduction

This document is a Message Implementation Guideline (MIG) for an EDI Business Message (EBM) used in Infor's enterprise application, M3. It defines in detail the collaboration logic between an EDI message specification and the M3 system. This logic is implemented in an EBM, which is a component in the M3 EDI solution.

The MIG supplied by Infor is usually based on a standard MIG from an EDI implementation standardization organization such as EANCOM, Odette or VICS, and is a subset of the standard MIG, based on the business functionality in M3.

This document consists of two major sections: Elements Used and Element Documentation. The section Elements Used provides an overall view of all EDI elements used in this MIG. The section Element Documentation provides detailed specifications of each and every group, segment, composite and element implemented in the EBM. The element information is presented in the order in which the elements are defined in the standard EDI message.



Elements Used

This section contains a summary of all elements used in this message application, that is, the elements that have documentation attached. Group number, segment name, composite name (if applicable), element name and description are provided for these elements. The elements are listed in message structure order.

Group	Segment	Composite /Element	Element	Description
0 M 1				
	BSS M 1			BSS - Beginning Segment for Shipping Schedule
			0127 M	127 - Reference Number
			0353 M	353 - Transaction Set Purpose Code
			0373 M	373 - Date
			0675 M	675 - Forecast Type Qualifier
			0676 C	676 - Forecast Quantity Qualifier
	GS C 1			Functional Group Header
			0480 M	Version/Release Indicator ID Code
	ST M 1			ST - Transaction Set Header
			0143 M	143 - Transaction Set Identifier Code
1 C 200				Loop Id N1
	N1 C 1			N1 - Name
			0067 C	67 - Identification Code
			0098 M	98 - Entity Identifier Code
	N2 C 2			N2 - Additional Name Information
			0093 M	93 - Name
	N3 C 1			N3 - Address Information
			0166 M	166 - Address Information

Group	Segment	Composite /Element	Element	Description
1 C 200				Loop Id N1
	N4 C 1			N4 - Geographic Location
			0019 C	19 - City Name
			0026 C	26 - Country Code
			0116 C	116 - Postal Code
2 C 10000				Loop Id LIN
	LIN M 1			LIN - Item Identification Detail
			0234 M	234 - Product/ Service ID
			0235 M	235 - Product/ Service ID Qualifier
	REF C 12			REF - Reference Numbers
			0127 C	127 - Reference Number
			0128 M	128 - Reference Number Qualifier
	TD1 C 1			TD1 - Carrier Details (Quantity and Weight)
			0080 C	80 - Lading Quantity
			0103 C	103 - Packaging Code
	UNT M 1			UNT - Unit Detail
			0355 M	355 - Unit of Measurement Code
3 C 100				Loop Id FST
	FST C 1			FST - Forecast Schedule
			0337 C	337 - Time
			0373 M	373 - Date
			0380 M	380 - Quantity

Group	Segment	Composite /Element	Element	Description
3 C 100				Loop Id FST
	FST C 1		0680 M	FST - Forecast Schedule 680 - Forecast Qualifier
4 C 24				Loop Id JIT
	JIT C 1		0337 M	JIT - Just-In-Time Schedule 337 - Time
			0380 M	380 - Quantity
5 C 10				Loop Id SHP
	REF C 12		0127 C	REF - Reference Numbers 127 - Reference Number
			0128 M	128 - Reference Number Qualifier
	SHP C 1		0373 C	SHP - Shipped/Received Information 373 - Date
			0374 C	374 - Date/Time Qualifier
			0380 C	380 - Quantity
			0673 C	673 - Quantity Qualifier



Element Documentation

This section is based on the same structure as the section Elements Used, but here you see all the available descriptions, sequence numbers (in the complete message) for segments and elements (within parentheses). It also includes M3 application documentation and the XPath for the corresponding XML element (XML is one of the technologies that is used for EBM applications), which specifies the position of the element in the message structure. M3 application documentation, as well as the corresponding XPath, can exist on a group, segment, composite and/or element level. Most common is the element level.

M3 application documentation consists of three sections: M3 Application Description, M3 Application Data Translation and M3 Application Specification.

M3 application documentation consists of three sections: M3 Application Description, M3 Application Data Translation and M3 Application Specification.

M3 Application Description

This section provides a general description in “business process language” and describes how the element is used in relation to the M3 logic, for example, which qualifiers are used and which M3 data is used.

M3 Application Data Translation

This section specifies whether or not the data can be translated between M3 and the message. Data translation is used, for example, to translate unit of measure ("STK" to "PCS"), currency codes ("PND" to "GBP") and qualifiers ("BY" to "BU"). Data translations are managed by the M3 program "Business Message Data Translation. Display" (CRS881) and the program "Business Message Data. Translate" (CRS882). The key used in (CRS881) for the element's data translation is provided.

M3 Application Specification

This section contains the specification that constitutes the base for the EBM. It describes whether the element uses data from or transfers data to a M3 API, uses calculated data and/or fixed data. It also describes how and when to make the M3 API calls, which input and output fields to use, etc. Additional information may also be given, such as conditions or notes to clarify specific logic used.

Taken together, the sections M3 Application Description and M3 Application Specification define the functionality of the EBM.

Group: 0	M 1	Segment Group: 0
Segment: BSS	M 1	BSS - Beginning Segment for Shipping Schedule
0127	M AN 30	127 - Reference Number
	M3 Application Description Reference identification as Delivery schedule	
	M3 Application Specification API dataMI program: RSS110MI Transaction: AddHeader Field: DPNR	
	XPath <i>X12862/BSS/e02_0127</i>	
0353	M AN 2	353 - Transaction Set Purpose Code
	M3 Application Description '00' = Original '05' = Replacement of the original 862	
	M3 Application Specification Condition e01_0353 equals "00" API dataMI program: RSS110MI Transaction: AddHeader Field: RSAC = 2 API dataMI program: RSS110MI Transaction: AddItem Field: RSAC = 2	
	Condition e01_0353 equals "05" API dataMI program: RSS110MI Transaction: AddHeader Field: RSAC = 1 API dataMI program: RSS110MI Transaction: AddItem Field: RSAC = 1	
	XPath <i>X12862/BSS/e01_0353</i>	
0373	M AN 6	373 - Date
	M3 Application Description Date as Date generated	
	M3 Application Specification API dataMI program: RSS110MI Transaction: AddHeader Field: GEDT	
	XPath <i>X12862/BSS/e03_0373</i>	

Group: 0	M 1	Segment Group: 0
Segment: BSS	M 1	BSS - Beginning Segment for Shipping Schedule
0373	M AN 6	373 - Date
	M3 Application Description Date as Finish date	
	M3 Application Specification API dataMI program: RSS110MI Transaction: AddHeader Field: ENDT	
	XPath <i>X12862/BSS/e06_0373</i>	
	M3 Application Description Date as Start date	
	M3 Application Specification API dataMI program: RSS110MI Transaction: AddHeader Field: EXDT	
	XPath <i>X12862/BSS/e05_0373</i>	
0675	M AN 2	675 - Forecast Type Qualifier
	M3 Application Description Schedule Type Qualifier as Date type	
	M3 Application Specification Condition: e04_0675 equals "DL" API dataMI program: RSS110MI Transaction: AddHeader Field: DTTP = "1"	
	Condition: e04_0675 equals "SH" API dataMI program: RSS110MI Transaction: AddHeader Field: DTTP = "3"	
	XPath <i>X12862/BSS/e04_0675</i>	
0676	C AN 1	676 - Forecast Quantity Qualifier
	M3 Application Description 'A' = Actual discrete quantities 'C' = Cumulative quantities	
	M3 Application Specification Fixed data: "A" o "C"	
	XPath <i>X12862/BSS/e11_0676</i>	



Group: 0	M 1	Segment Group: 0
Segment: GS 0480	C 1 M AN 12 M3 Application Description Version/release as Version and Release M3 Application Specification API dataMI program: RSS110MITransaction: AddHeader Field: E0xx Note: Substring the first three characters. API dataMI program: RSS110MITransaction: AddHeader Field: E0xx Note: Substring from position 4 to 6. XPath <i>X12862/GS/e08_0480</i>	Functional Group Header Version/Release Indicator ID Code
Segment: ST 0143	M 1 M AN 3 M3 Application Description Transaction set identifier code as Message type M3 Application Specification API dataMI program: RSS110MI Transaction: AddHeader Field: E065 XPath <i>X12862/ST/e01_0143</i>	ST - Transaction Set Header 143 - Transaction Set Identifier Code



Group: 1	C 200	Segment Group: 1
Segment: N1	C 1	N1 - Name
0067	C AN 17	67 - Identification Code
	M3 Application Description Identification code as Address coded	
	M3 Application Specification API dataMI program: RSS110MI Transaction: AddAddress Field: CDEA	
	Condition: e01_0098 equals "ST" API dataMI program: RSS110MI Transaction: AddAddress Field: ADRT = "10"	
	Condition: e01_0098 equals "BY" API call: RSS110MI/GetPartner Input field CONO: CONO Input field PAAL: e04_0067	
	API call: RSS110MI/AddHeader Input field CONO: CONO Input field DIVI: DIVI Input field E0IO: "I" Input field E0PA: E0PA, output from GetPartner or e04_0067 if NOK from GetPartner. Input field DPMA: "1" Input field EDFR: Envelope/Properties/identity	
	XPath X12862/LOOP_N1_g001/N1/e04_0067	
0098	M AN 2	98 - Entity Identifier Code
	M3 Application Description 'BY' = Buying party 'ST' = Ship to	
	M3 Application Specification Fixed data: "BY" or "ST"	
	XPath X12862/LOOP_N1_g001/N1/e01_0098	

Group: 1	C 200	Segment Group: 1
Segment: N2 0093	C 2 M AN 35 M3 Application Description Name as Company name M3 Application Specification Condition: e01_0098 equals "ST" API dataMI program: RSS110MI Transaction: AddAddress Field: CONM XPath X12862/LOOP_N1_g001/N2/e01_0093	N2 - Additional Name Information 93 - Name
Segment: N3 0166	C 1 M AN 35 M3 Application Description Address information as Address line 1 M3 Application Specification Condition: e01_0098 equals "ST" API dataMI program: RSS110MI Transaction: AddAddress Field: ADR1 XPath X12862/LOOP_N1_g001/N3/e01_0166 M3 Application Description Address information as Address line 2 M3 Application Specification Condition: e01_0098 equals "ST" API dataMI program: RSS110MI Transaction: AddAddress Field: ADR2 XPath X12862/LOOP_N1_g001/N3/e02_0166	N3 - Address Information 166 - Address Information
Segment: N4 0019	C 1 C AN 19 M3 Application Description City name as Address line 4 M3 Application Specification Condition: e01_0098 equals "ST" API dataMI program: RSS110MI Transaction: AddAddress Field: ADR4 XPath X12862/LOOP_N1_g001/N4/e01_0019	N4 - Geographic Location 19 - City Name



Group: 1	C 200	Segment Group: 1
Segment: N4 0026	C 1 C AN 2 M3 Application Description Country code as Country M3 Application Specification Condition: e01_0098 equals "ST" API dataMI program: RSS110MI Transaction: AddAddress Field: CSCD API call: RSS110MI/AddAddress Input field CONO: CONO Input field DIVI: DIVI Input field ODPN: ODPN, output from AddHeader. Input field ODPI: ODPI, output from AddItem. M3 Data Translation Message standard: "X12" Version: "2002" Message: "862" Parent elements: "g001/N1" Data element: "e04_0026" Movex table: "OOHEAD" Movex field: "OACSCD" XPath X12862/LOOP_N1_g001/N4/e04_0026	N4 - Geographic Location 26 - Country Code
0116	C AN 9 M3 Application Description Postal code as Postal code M3 Application Specification Condition: e01_0098 equals "ST" API dataMI program: RSS110MI Transaction: AddAddress Field: PONO XPath X12862/LOOP_N1_g001/N4/e03_0116	116 - Postal Code



Group: 2	C 10000	Segment Group: 2
Segment: LIN 0234	M 1 M AN 30 M3 Application Description 'BP' = Buyer part number as Alias number 'DR' = Drawing revision number as Partner's engineering change order no 'PO' = Code identifying the buyer's PO as Customer's order number M3 Application Specification Condition: e02_0235 equals "BP" API dataMI program: RSS110MI Transaction: AddItem Field: POPN API dataMI program: RSS110MI Transaction: AddItem Field: ALWT = "06" Condition: e02_0235 equals "DR" API dataMI program: RSS110MI Transaction: AddItem Field: RSEC Condition: e02_0235 equals "PO" API dataMI program: RSS110MI Transaction: AddItem Field: CUOR XPath X12862/LOOP_LIN_g002/LIN/e03_0234 XPath X12862/LOOP_LIN_g002/LIN/e05_0234 XPath X12862/LOOP_LIN_g002/LIN/e07_0234 XPath X12862/LOOP_LIN_g002/LIN/e09_0234 XPath X12862/LOOP_LIN_g002/LIN/e11_0234 XPath X12862/LOOP_LIN_g002/LIN/e13_0234 XPath X12862/LOOP_LIN_g002/LIN/e15_0234 XPath X12862/LOOP_LIN_g002/LIN/e17_0234	LIN - Item Identification Detail 234 - Product/Service ID

Group: 2	C 1000	Segment Group: 2
Segment: LIN 0234	M 1 M AN 30 M3 Application Description 'BP' = Buyer part number as Alias number 'DR' = Drawing revision number as Partner's engineering change order no 'PO' = Code identifying the buyer's PO as Customer's order number M3 Application Specification Condition: e02_0235 equals "BP" API dataMI program: RSS110MI Transaction: AddItem Field: POPN API dataMI program: RSS110MI Transaction: AddItem Field: ALWT = "06" Condition: e02_0235 equals "DR" API dataMI program: RSS110MI Transaction: AddItem Field: RSEC Condition: e02_0235 equals "PO" API dataMI program: RSS110MI Transaction: AddItem Field: CUOR XPath X12862/LOOP_LIN_g002/LIN/e19_0234 XPath X12862/LOOP_LIN_g002/LIN/e21_0234 XPath X12862/LOOP_LIN_g002/LIN/e23_0234 XPath X12862/LOOP_LIN_g002/LIN/e25_0234 XPath X12862/LOOP_LIN_g002/LIN/e27_0234 XPath X12862/LOOP_LIN_g002/LIN/e29_0234 XPath X12862/LOOP_LIN_g002/LIN/e31_0234	LIN - Item Identification Detail 234 - Product/Service ID

Group: 2	C 10000	Segment Group: 2
Segment: LIN	M 1	LIN - Item Identification Detail
0235	M AN 2	235 - Product/Service ID Qualifier
	M3 Application Description	
	'BP' = Buyer part number	
	'DR' = Drawing revision number	
	'PO' = Code identifying the buyer's PO	
	M3 Application Specification	
	Fixed data: "BP" or "DR" or "PO"	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e02_0235	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e04_0235	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e06_0235	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e08_0235	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e10_0235	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e12_0235	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e14_0235	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e16_0235	



Group: 2	C 10000	Segment Group: 2
Segment: LIN	M 1	LIN - Item Identification Detail
0235	M AN 2	235 - Product/Service ID Qualifier
	M3 Application Description	
	'BP' = Buyer part number	
	'DR' = Drawing revision number	
	'PO' = Code identifying the buyer's PO	
	M3 Application Specification	
	Fixed data: "BP" or "DR" or "PO"	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e18_0235	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e20_0235	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e22_0235	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e24_0235	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e26_0235	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e28_0235	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e30_0235	



Group: 2	C 1000	Segment Group: 2
Segment: REF	C 12	REF - Reference Numbers
0127	C AN 30	127 - Reference Number
	M3 Application Description	
	'DK' = Dock number as Address coded	
	'LF' = The assembly line feed location or the deliver to internal stock location as Address coded	
	M3 Application Specification	
	Condition: e01_0128 equals "DK"	
	API dataMI program: RSS110MI Transaction: AddAddress Field: CDEA	
	API call: RSS110MI/AddAddress	
	Input field CONO: CONO	
	Input field DIVI: DIVI	
	Input field ODPN: ODPN, Note: Output from AddHeader	
	Input field ODPI: ODPI, Note: Output from AddItem	
	Input field ADRT: "11"	
	Condition: e01_0128 equals "LF"	
	API dataMI program: RSS110MI Transaction: AddAddress Field: CDEA	
	API call: RSS110MI/AddAddress	
	Input field CONO: CONO	
	Input field DIVI: DIVI	
	Input field ODPN: ODPN, Note: Output from AddHeader	
	Input field ODPI: ODPI, Note: Output from AddItem	
	Input field ADRT: "12"	
	XPath	
	<i>X12862/LOOP_LIN_g002/REF/e02_0127</i>	
0128	M AN 2	128 - Reference Number Qualifier
	M3 Application Description	
	'DK' = Dock number	
	'LF' = The assembly line feed location or the deliver to internal stock location	
	M3 Application Specification	
	Fixed data: "DK" or "LF"	
	XPath	
	<i>X12862/LOOP_LIN_g002/REF/e01_0128</i>	

Group: 2	C 1000	Segment Group: 2
Segment: TD1	C 1	TD1 - Carrier Details (Quantity and Weight)
0080	C NO 7	80 - Lading Quantity
	M3 Application Description Lading quantity as Number of packages	
	M3 Application Specification API dataMI program: RSS110MI Transaction: UpdItem Field: AMKO	
	API call: RSS110MI/UpdItem Input field CONO: CONO Input field DIVI: DIVI Input field ODPN: ODPN Input field ODPI: ODPI	
	XPath <i>X12862/LOOP_LIN_g002/TD1/e02_0080</i>	
0103	C AN 5	103 - Packaging Code
	M3 Application Description Packaging code as Customer's packaging identity	
	M3 Application Specification API dataMI program: RSS110MI Transaction: UpdItem Field: CUPA	
	XPath <i>X12862/LOOP_LIN_g002/TD1/e01_0103</i>	
Segment: UNT	M 1	UNT - Unit Detail
0355	M AN 2	355 - Unit of Measurement Code
	M3 Application Description Unit or basis for measurement code as Unit of measure	
	M3 Application Specification API dataMI program: RSS110MI Transaction: AddItem Field: UNIT	
	M3 Data Translation Message standard: "X12" Version: "2002" Message: "862" Parent elements: "g002/UNT" Data element: "e01_0355" Movex table: "ORSITM" Movex field: "RBUNIT"	
	XPath <i>X12862/LOOP_LIN_g002/UNT/e01_0355</i>	



Group: 3	C 100	Segment Group: 3
Segment: FST 0337	C 1 C AN 4 M3 Application Description Time as Requested delivery time M3 Application Specification API dataMI program: RSS110MI Transaction: AddInstruction Field: RLTM Note: Format HHMM received. XPath <i>X12862/LOOP_LIN_g002/LOOP_FST_g003/FST/e07_0337</i>	FST - Forecast Schedule 337 - Time
0373	M AN 6 M3 Application Description Date as Requested delivery date M3 Application Specification API dataMI program: RSS110MI Transaction: AddInstruction Field: RLDT XPath <i>X12862/LOOP_LIN_g002/LOOP_FST_g003/FST/e04_0373</i>	373 - Date
0380	M N 10 M3 Application Description Quantity as Requested quantity or Cumulative quantity M3 Application Specification Condition: BSS/676 equals "A" API dataMI program: RSS110MI Transaction: SndInstruction Field: DEMQ Condition: BSS/676 equals "C" API dataMI program: RSS110MI Transaction: SndInstruction Field: CQCF XPath <i>X12862/LOOP_LIN_g002/LOOP_FST_g003/FST/e01_0380</i>	380 - Quantity

Group: 3	C 100	Segment Group: 3
Segment: FST 0680	C 1 M AN 1 M3 Application Description 'C' = Firm M3 Application Specification Condition e02_0680 equals "C" API dataMI program: RSS110MI Transaction: AddInstruction Field: RSIN = "1" XPath X12862/LOOP_LIN_g002/LOOP_FST_g003/FST/e02_0680	FST - Forecast Schedule 680 - Forecast Qualifier
Group: 4	C 24	Segment Group: 4
Segment: JIT 0337	C 1 M AN 4 M3 Application Description Time of requirement as Requested delivery time M3 Application Specification API dataMI program: RSS110MI Transaction: AddInstruction Field: RLTM Note: Time format received = HHMM API call: RSS110MI/AddInstruction Input field CONO: CONO Input field DIVI: DIVI Input field ODPN: ODPN, Note: Output from AddHeader. Input field ODPI: ODPI, Note: Output from AddItem. XPath X12862/LOOP_LIN_g002/LOOP_FST_g003/LOOP_JIT_g004/JIT/e02_0337	JIT - Just-In-Time Schedule 337 - Time
0380	M N 10 M3 Application Description Quantity required as Requested quantity M3 Application Specification API dataMI program: RSS110MI Transaction: AddInstruction Field: DEMQ XPath X12862/LOOP_LIN_g002/LOOP_FST_g003/LOOP_JIT_g004/JIT/e01_0380	380 - Quantity



Group: 4	C 24	Segment Group: 4
Segment: JIT	C 1	JIT - Just-In-Time Schedule
Group: 5	C 10	Segment Group: 5
Segment: REF	C 12	REF - Reference Numbers
0127	C AN 30	127 - Reference Number
	M3 Application Description 'SI' = Shipper's identifying number for shipment as Delivery note number	
	M3 Application Specification Condition: e01_0128 equals "SI" API dataMI program: RSS110MI Transaction: AddDeliveryNote Field: DNNO API call: RSS110MI/AddDeliveryNote Input field CONO: CONO Input field DIVI: DIVI Input field ODPN: ODPN Input field ODPI: ODPI Note: No API call if no DNNO received.	
	XPath X12862/LOOP_LIN_g002/LOOP_SHP_g005/REF/e02_0127	
0128	M AN 2	128 - Reference Number Qualifier
	M3 Application Description 'SI' = Shipper's identifying number for shipment	
	M3 Application Specification Fixed data: "SI"	
	XPath X12862/LOOP_LIN_g002/LOOP_SHP_g005/REF/e01_0128	



Group: 5	C 10	Segment Group: 5
Segment: SHP	C 1	SHP - Shipped/Received Information
0373	C AN 6	373 - Date
	M3 Application Description Date as Cumulative calculation date	
	M3 Application Specification Condition: e01_0673 equals "02" Condition: e03_0374 equals "011" API dataMI program: RSS110MI Transaction: AddCumQuantity Field: CUMD	
	 Condition: e01_0673 equals "02" Condition: e03_0374 equals "050" API dataMI program: RSS110MI Transaction: AddCumQuantity Field: CUMD	
	 API call: RSS110MI/AddCumQuantity Input field CONO: CONO Input field DIVI: DIVI Input field ODPN: ODPN Input field ODPI: ODPI Input field CUMT: "1"	
	XPath X12862/LOOP_LIN_g002/LOOP_SHP_g005/SHP/e06_0373	



Group: 5	C 10	Segment Group: 5
Segment: SHP	C 1	SHP - Shipped/Received Information
0373	C AN 6	373 - Date
	M3 Application Description	
	Date as Cumulative from date or Delivery note date or Receipt date	
	M3 Application Specification	
	Condition: e01_0673 equals "01"	
	Condition: e03_0374 equals "011"	
	API dataMI program: RSS110MI Transaction: AddDeliveryNote Field: DNDT	
	Condition: e01_0673 equals "01"	
	Condition: e03_0374 equals "050"	
	API dataMI program: RSS110MI Transaction: AddDeliveryNote Field: RCDT	
	Condition: e01_0673 equals "02"	
	Condition: e03_0374 equals "011"	
	API dataMI program: RSS110MI Transaction: AddCumQuantity Field: CUFD	
	Condition: e01_0673 equals "02"	
	Condition: e03_0374 equals "050"	
	API dataMI program: RSS110MI Transaction: AddCumQuantity Field: CUFD	
	XPath	
	X12862/LOOP_LIN_g002/LOOP_SHP_g005/SHP/e04_0373	
0374	C AN 3	374 - Date/Time Qualifier
	M3 Application Description	
	'011' = Shipped	
	'050' = Received	
	M3 Application Specification	
	Fixed data: "011" or "050"	
	XPath	
	X12862/LOOP_LIN_g002/LOOP_SHP_g005/SHP/e03_0374	



Group: 5	C 10	Segment Group: 5
Segment: SHP	C 1	SHP - Shipped/Received Information
0380	C N 10	380 - Quantity
	M3 Application Description '01' = Discrete quantity as Receipt quantity '02' = Cumulative quantity as Cumulative quantity	
	M3 Application Specification Condition: e01_0673 equals "01" API dataMI program: RSS110MI Transaction: AddDeliveryNote Field: RCQT	
	Condition: e01_0673 equals "02" API dataMI program: RSS110MI Transaction: AddCumQuantity Field: CQCF	
	XPath <i>X12862/LOOP_LIN_g002/LOOP_SHP_g005/SHP/e02_0380</i>	
0673	C AN 2	673 - Quantity Qualifier
	M3 Application Description '01' = Discrete quantity '02' = Cumulative quantity	
	M3 Application Specification Fixed data: "01" or "02"	
	XPath <i>X12862/LOOP_LIN_g002/LOOP_SHP_g005/SHP/e01_0673</i>	