



Business Message Documentation

Application Type	EDI Business Message (EBM)
M3 version	BE15
M3 Business Message	DDI - Delivery Demand Instrauction
Message Direction	Inbound
Message Application	X12 862 4010

Map name	M3BE15_DDI_In_X12_862_4010
----------	-----------------------------------

Source file	M3BE15_DDI_In_X12_862_4010_MIG_v1.pdf
Created	2013-06-13 15:40



Introduction

This document is a Message Implementation Guideline (MIG) for an EDI Business Message (EBM) used in Infor's enterprise application, M3. It defines in detail the collaboration logic between an EDI message specification and the M3 system. This logic is implemented in an EBM, which is a component in the M3 EDI solution.

The MIG supplied by Infor is usually based on a standard MIG from an EDI implementation standardization organization such as EANCOM, Odette or VICS, and is a subset of the standard MIG, based on the business functionality in M3.

This document consists of two major sections: Elements Used and Element Documentation. The section Elements Used provides an overall view of all EDI elements used in this MIG. The section Element Documentation provides detailed specifications of each and every group, segment, composite and element implemented in the EBM. The element information is presented in the order in which the elements are defined in the standard EDI message.



Elements Used

This section contains a summary of all elements used in this message application, that is, the elements that have documentation attached. Group number, segment name, composite name (if applicable), element name and description are provided for these elements. The elements are listed in message structure order.

Group	Segment	Composite /Element	Element	Description
0 M 1				
	BSS M 1			BSS - Beginning Segment for Shipping Schedule/ Production Sequence
			0127 M	Reference Identification
			0353 M	Transaction Set Purpose Code
			0373 M	Date
			0675 M	Schedule Type Qualifier
	GS C 1			Functional Group Header
			0480 M	Version/Release Indicator ID Code
	ST M 1			ST - Transaction Set Header
			0143 M	Transaction Set Identifier Code
1 C 200				Loop Id N1
	N1 C 1			N1 - Name Identification Code
			0067 C	
			0098 M	Entity Identifier Code
	N2 C 2			N2 - Additional Name Information
			0093 M	Name
	N3 C 2			N3 - Address Information
			0166 M	Address Information
	N4 C 1			N4 - Geographic Location
			0019 C	City Name
			0026 C	Country Code

Group	Segment	Composite /Element	Element	Description
1 C 200				Loop Id N1
	N4 C 1		0116 C	N4 - Geographic Location Postal Code
2 C 10000				Loop Id LIN
	LIN M 1		0234 M	LIN - Item Identification Product/Service ID
			0235 M	Product/Service ID Qualifier
	REF C 12		0127 C	REF - Reference Identification Reference Identification
			0128 M	Reference Identification Qualifier
	UIT M 1	C001 M * 0355 M		UIT - Unit Detail C001 - Composite Unit of Measure C001 - Composite Unit of Measure
3 C 100				Loop Id FST
	FST C 1		0373 M	FST - Forecast Schedule Date
			0680 M	Forecast Qualifier
4 C 96				Loop Id JIT
	JIT C 1		0337 M	JIT - Just-In-Time Schedule Time
			0380 M	Quantity



Element Documentation

This section is based on the same structure as the section Elements Used, but here you see all the available descriptions, sequence numbers (in the complete message) for segments and elements (within parentheses). It also includes M3 application documentation and the XPath for the corresponding XML element (XML is one of the technologies that is used for EBM applications), which specifies the position of the element in the message structure. M3 application documentation, as well as the corresponding XPath, can exist on a group, segment, composite and/or element level. Most common is the element level.

M3 application documentation consists of three sections: M3 Application Description, M3 Application Data Translation and M3 Application Specification.

M3 application documentation consists of three sections: M3 Application Description, M3 Application Data Translation and M3 Application Specification.

M3 Application Description

This section provides a general description in “business process language” and describes how the element is used in relation to the M3 logic, for example, which qualifiers are used and which M3 data is used.

M3 Application Data Translation

This section specifies whether or not the data can be translated between M3 and the message. Data translation is used, for example, to translate unit of measure ("STK" to "PCS"), currency codes ("PND" to "GBP") and qualifiers ("BY" to "BU"). Data translations are managed by the M3 program "Business Message Data Translation. Display" (CRS881) and the program "Business Message Data. Translate" (CRS882). The key used in (CRS881) for the element's data translation is provided.

M3 Application Specification

This section contains the specification that constitutes the base for the EBM. It describes whether the element uses data from or transfers data to a M3 API, uses calculated data and/or fixed data. It also describes how and when to make the M3 API calls, which input and output fields to use, etc. Additional information may also be given, such as conditions or notes to clarify specific logic used.

Taken together, the sections M3 Application Description and M3 Application Specification define the functionality of the EBM.

Group: 0	M 1	Segment Group: 0
Segment: BSS	M 1	BSS - Beginning Segment for Shipping Schedule/Production Sequence
0127	M AN 30	Reference Identification
	M3 Application Description Reference identification as Delivery schedule	
	M3 Application Specification API dataMI program: RSS110MI Transaction: AddHeader Field: DPNR	
	XPath <i>X12862/BSS/e02_0127</i>	
0353	M AN 2	Transaction Set Purpose Code
	M3 Application Description '00' = Original '05' = Replacement of the original 862	
	M3 Application Specification Condition e01_0353 equals "00" API dataMI program: RSS110MI Transaction: AddHeader Field: RSAC = 2 API dataMI program: RSS110MI Transaction: AddItem Field: RSAC = 2	
	Condition e01_0353 equals "05" API dataMI program: RSS110MI Transaction: AddHeader Field: RSAC = 1 API dataMI program: RSS110MI Transaction: AddItem Field: RSAC = 1	
	XPath <i>X12862/BSS/e01_0353</i>	
0373	M AN 8	Date
	M3 Application Description Date as Date generated	
	M3 Application Specification API dataMI program: RSS110MI Transaction: AddHeader Field: GEDT	
	XPath <i>X12862/BSS/e03_0373</i>	



Group: 0	M 1	Segment Group: 0
Segment: BSS	M 1	BSS - Beginning Segment for Shipping Schedule/Production Sequence
0373	M AN 8	Date
	M3 Application Description Date as Finish date	
	M3 Application Specification API dataMI program: RSS110MI Transaction: AddHeader Field: ENDT	
	XPath X12862/BSS/e06_0373	
	M3 Application Description Date as Start date	
	M3 Application Specification API dataMI program: RSS110MI Transaction: AddHeader Field: EXDT	
	XPath X12862/BSS/e05_0373	
0675	M AN 2	Schedule Type Qualifier
	M3 Application Description Schedule Type Qualifier as Date type	
	M3 Application Specification Condition: e04_0675 equals "DL" API dataMI program: RSS110MI Transaction: AddHeader Field: DTTP = "1"	
	Condition: e04_0675 equals "SH" API dataMI program: RSS110MI Transaction: AddHeader Field: DTTP = "3"	
	XPath X12862/BSS/e04_0675	



Group: 0	M 1	Segment Group: 0
Segment: GS 0480	C 1 M AN 12 M3 Application Description Version/release as Version and Release M3 Application Specification API dataMI program: RSS110MITransaction: AddHeader Field: E0xx Note: Substring the first three characters. API dataMI program: RSS110MITransaction: AddHeader Field: E0xx Note: Substring from position 4 to 6. XPath <i>X12862/GS/e08_0480</i>	Functional Group Header Version/Release Indicator ID Code
Segment: ST 0143	M 1 M AN 3 M3 Application Description Transaction set identifier code as Message type M3 Application Specification API dataMI program: RSS110MI Transaction: AddHeader Field: E065 XPath <i>X12862/ST/e01_0143</i>	ST - Transaction Set Header Transaction Set Identifier Code

Group: 1	C 200	Segment Group: 1
Segment: N1	C 1	N1 - Name
0067	C AN 80	Identification Code
	M3 Application Description Identification code as Address coded	
	M3 Application Specification API dataMI program: RSS110MI Transaction: AddAddress Field: CDEA Condition: e01_0098 equals "ST" API dataMI program: RSS110MI Transaction: AddAddress Field: ADRT = "10" Condition: e01_0098 equals "SI" API call: RSS110MI/GetPartner Input field CONO: CONO Input field PAAL: e04_0067 API call: RSS110MI/AddHeader Input field CONO: CONO Input field DIVI: DIVI Input field E0IO: "I" Input field E0PA: E0PA, output from GetPartner or e04_0067 if NOK from GetPartner. Input field DPMA: "1" Input field EDFR: Envelope/Properties/identity XPath <i>X12862/LOOP_N1_g001/N1/e04_0067</i>	
0098	M AN 3	Entity Identifier Code
	M3 Application Description 'SI' = Shipping schedule issuer 'ST' = Ship to	
	M3 Application Specification Fixed data: "SI" or "ST"	
	XPath <i>X12862/LOOP_N1_g001/N1/e01_0098</i>	



Group: 1	C 200	Segment Group: 1
Segment: N2 0093	C 2 M AN 60 M3 Application Description Name as Company name M3 Application Specification Condition: e01_0098 equals "ST" API dataMI program: RSS110MI Transaction: AddAddress Field: CONM XPath X12862/LOOP_N1_g001/N2/e01_0093	N2 - Additional Name Information Name
Segment: N3 0166	C 2 M AN 55 M3 Application Description Address information as Address line 1 M3 Application Specification Condition: e01_0098 equals "ST" API dataMI program: RSS110MI Transaction: AddAddress Field: ADR1 XPath X12862/LOOP_N1_g001/N3/e01_0166 M3 Application Description Address information as Address line 2 M3 Application Specification Condition: e01_0098 equals "ST" API dataMI program: RSS110MI Transaction: AddAddress Field: ADR2 XPath X12862/LOOP_N1_g001/N3/e02_0166	N3 - Address Information Address Information
Segment: N4 0019	C 1 C AN 30 M3 Application Description City name as Address line 4 M3 Application Specification Condition: e01_0098 equals "ST" API dataMI program: RSS110MI Transaction: AddAddress Field: ADR4 XPath X12862/LOOP_N1_g001/N4/e01_0019	N4 - Geographic Location City Name



Group: 1	C 200	Segment Group: 1
Segment: N4 0026	C 1 C AN 3 M3 Application Description Country code as Country M3 Application Specification Condition: e01_0098 equals "ST" API dataMI program: RSS110MI Transaction: AddAddress Field: CSCD API call: RSS110MI/AddAddress Input field CONO: CONO Input field DIVI: DIVI Input field ODPN: ODPN, output from AddHeader. Input field ODPI: ODPI, output from AddItem. M3 Data Translation Message standard: "X12" Version: "4010" Message: "862" Parent elements: "g001/N1" Data element: "e04_0026" Movex table: "OOHEAD" Movex field: "OACSCD" XPath X12862/LOOP_N1_g001/N4/e04_0026	N4 - Geographic Location Country Code
0116	C AN 15 M3 Application Description Postal code as Postal code M3 Application Specification Condition: e01_0098 equals "ST" API dataMI program: RSS110MI Transaction: AddAddress Field: PONO XPath X12862/LOOP_N1_g001/N4/e03_0116	Postal Code

Group: 2	C 10000	Segment Group: 2
Segment: LIN	M 1	LIN - Item Identification
0234	M AN 48	Product/Service ID
M3 Application Description		
'BP' = Buyer part number as Alias number		
'DR' = Drawing revision number as Partner's engineering change order no		
'PO' = Code identifying the buyer's PO as Customer's order number		
M3 Application Specification		
Condition: e02_0235 equals "BP"		
API dataMI program: RSS110MI Transaction: AddItem Field: POPN		
API dataMI program: RSS110MI Transaction: AddItem Field: ALWT = "06"		
Condition: e02_0235 equals "DR"		
API dataMI program: RSS110MI Transaction: AddItem Field: RSEC		
Condition: e02_0235 equals "PO"		
API dataMI program: RSS110MI Transaction: AddItem Field: CUOR		
XPath		
<i>X12862/LOOP_LIN_g002/LIN/e03_0234</i>		
XPath		
<i>X12862/LOOP_LIN_g002/LIN/e05_0234</i>		
XPath		
<i>X12862/LOOP_LIN_g002/LIN/e07_0234</i>		
XPath		
<i>X12862/LOOP_LIN_g002/LIN/e09_0234</i>		
XPath		
<i>X12862/LOOP_LIN_g002/LIN/e11_0234</i>		
XPath		
<i>X12862/LOOP_LIN_g002/LIN/e13_0234</i>		
XPath		
<i>X12862/LOOP_LIN_g002/LIN/e15_0234</i>		
XPath		
<i>X12862/LOOP_LIN_g002/LIN/e17_0234</i>		

Group: 2	C 1000	Segment Group: 2
Segment: LIN 0234	M 1 M AN 48 M3 Application Description 'BP' = Buyer part number as Alias number 'DR' = Drawing revision number as Partner's engineering change order no 'PO' = Code identifying the buyer's PO as Customer's order number M3 Application Specification Condition: e02_0235 equals "BP" API dataMI program: RSS110MI Transaction: AddItem Field: POPN API dataMI program: RSS110MI Transaction: AddItem Field: ALWT = "06" Condition: e02_0235 equals "DR" API dataMI program: RSS110MI Transaction: AddItem Field: RSEC Condition: e02_0235 equals "PO" API dataMI program: RSS110MI Transaction: AddItem Field: CUOR XPath <i>X12862/LOOP_LIN_g002/LIN/e19_0234</i> XPath <i>X12862/LOOP_LIN_g002/LIN/e21_0234</i> XPath <i>X12862/LOOP_LIN_g002/LIN/e23_0234</i> XPath <i>X12862/LOOP_LIN_g002/LIN/e25_0234</i> XPath <i>X12862/LOOP_LIN_g002/LIN/e27_0234</i> XPath <i>X12862/LOOP_LIN_g002/LIN/e29_0234</i> XPath <i>X12862/LOOP_LIN_g002/LIN/e31_0234</i>	LIN - Item Identification Product/Service ID



Group: 2	C 10000	Segment Group: 2
Segment: LIN 0235	M 1 M AN 2 M3 Application Description 'BP' = Buyer part number 'DR' = Drawing revision number 'PO' = Code identifying the buyer's PO M3 Application Specification Fixed data: "BP" or "DR" or "PO" XPath <i>X12862/LOOP_LIN_g002/LIN/e02_0235</i> XPath <i>X12862/LOOP_LIN_g002/LIN/e04_0235</i> XPath <i>X12862/LOOP_LIN_g002/LIN/e06_0235</i> XPath <i>X12862/LOOP_LIN_g002/LIN/e08_0235</i> XPath <i>X12862/LOOP_LIN_g002/LIN/e10_0235</i> XPath <i>X12862/LOOP_LIN_g002/LIN/e12_0235</i> XPath <i>X12862/LOOP_LIN_g002/LIN/e14_0235</i> XPath <i>X12862/LOOP_LIN_g002/LIN/e16_0235</i> XPath <i>X12862/LOOP_LIN_g002/LIN/e18_0235</i>	LIN - Item Identification Product/Service ID Qualifier



Group: 2	C 10000	Segment Group: 2
Segment: LIN	M 1	LIN - Item Identification
0235	M AN 2	Product/Service ID Qualifier
	M3 Application Description	
	'BP' = Buyer part number	
	'DR' = Drawing revision number	
	'PO' = Code identifying the buyer's PO	
	M3 Application Specification	
	Fixed data: "BP" or "DR" or "PO"	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e20_0235	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e22_0235	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e24_0235	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e26_0235	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e28_0235	
	XPath	
	X12862/LOOP_LIN_g002/LIN/e30_0235	

Group: 2	C 1000	Segment Group: 2
Segment: REF 0127	C 12 C AN 30 M3 Application Description 'DK' = Dock number as Address coded 'LF' = The assembly line feed location or the deliver to internal stock location as Address coded M3 Application Specification Condition: e01_0128 equals "DK" API dataMI program: RSS110MI Transaction: AddAddress Field: CDEA API call: RSS110MI/AddAddress Input field CONO: CONO Input field DIVI: DIVI Input field ODPN: ODPN, Note: Output from AddHeader Input field ODPI: ODPI, Note: Output from AddItem Input field ADRT: "11" Condition: e01_0128 equals "LF" API dataMI program: RSS110MI Transaction: AddAddress Field: CDEA API call: RSS110MI/AddAddress Input field CONO: CONO Input field DIVI: DIVI Input field ODPN: ODPN, Note: Output from AddHeader Input field ODPI: ODPI, Note: Output from AddItem Input field ADRT: "12" XPath <i>X12862/LOOP_LIN_g002/REF/e02_0127</i>	REF - Reference Identification Reference Identification
0128	M AN 3 M3 Application Description 'DK' = Dock number 'LF' = The assembly line feed location or the deliver to internal stock location M3 Application Specification Fixed data: "DK" or "LF" XPath <i>X12862/LOOP_LIN_g002/REF/e01_0128</i>	Reference Identification Qualifier

Group: 2	C 1000	Segment Group: 2
Segment: UIT	M 1	UIT - Unit Detail
C001	M	C001 - Composite Unit of Measure
** 0355	M AN 2	C001 - Composite Unit of Measure
M3 Application Description Unit of measure as Unit of measure		
M3 Application Specification API dataMI program: RSS110MI Transaction: AddItem Field: UNIT		
M3 Data Translation Message standard: "X12" Version: "4010" Message: "862" Parent elements: "g002/UIT" Data element: "e01_0355" Movex table: "OOLINE" Movex field: "OBALUN"		
XPath X12862/LOOP_LIN_g002/UIT/cmp01/e01_0355		
Group: 3	C 100	Segment Group: 3
Segment: FST	C 1	FST - Forecast Schedule
0373	M AN 8	Date
M3 Application Description Date as Requested delivery date		
M3 Application Specification API dataMI program: RSS110MI Transaction: AddInstruction Field: RLDT		
XPath X12862/LOOP_LIN_g002/LOOP_FST_g003/FST/e04_0373		
0680	M AN 1	Forecast Qualifier
M3 Application Description 'C' = Firm		
M3 Application Specification Condition e02_0680 equals "C"		
API dataMI program: RSS110MI Transaction: AddInstruction Field: RSIN = "1"		
XPath X12862/LOOP_LIN_g002/LOOP_FST_g003/FST/e02_0680		



Group: 4	C 96	Segment Group: 4
Segment: JIT 0337	C 1 M AN 8 M3 Application Description Time of requirement as Requested delivery time M3 Application Specification API dataMI program: RSS110MI Transaction: AddInstruction Field: RLTM Note: Time format received = HHMM API call: RSS110MI/AddInstruction Input field CONO: CONO Input field DIVI: DIVI Input field ODPN: ODPN, Note: Output from AddHeader. Input field ODPI: ODPI, Note: Output from AddItem. XPath <i>X12862/LOOP_LIN_g002/LOOP_FST_g003/LOOP_JIT_g004/JIT/e02_0337</i>	JIT - Just-In-Time Schedule Time
0380	M N 15 M3 Application Description Quantity required as Requested quantity M3 Application Specification API dataMI program: RSS110MI Transaction: AddInstruction Field: DEMQ XPath <i>X12862/LOOP_LIN_g002/LOOP_FST_g003/LOOP_JIT_g004/JIT/e01_0380</i>	Quantity