

KPIs and parametric analysis

RE Heat

Dr. Herena Torio



Agenda

- KPIs
 - Solar thermal (video)
 - Heat pumps
- Parametric analysis
 - Example



Characterization of Heat pump performance



Which indicator(s) you know?

 What are their main drawbacks/ limitations?



Characterization of Heat pump performance



Coefficient of performance, COP

- Easy to calculate, f(Tc, Th)
- Obtainable for some data from data sheets and manufacturer data
- → Static! Only performance at those given conditions (power, not energy!)

Heat pump efficiency ratio, η_{hp}

- Easy to infer based on manufacturers data
- Assumed to be constant (simplification) for a given heat pump

Heat pump databases:

- https://opennetzero.org/dataset/heat-pump-database
- https://www.energynetworks.org/publications/low-carbontechnologies-heat-pump-database



Characterization of Heat pump performance



Coefficient of performance, COP

- Easy to calculate, f(Tc, Th)
- Obtainable for some data from data sheets and manufacturer data
- → Static! Only performance at those given conditions (power, not energy!)

$$COP_{Carnot} = \frac{T_h}{T_h - T_c} = \frac{T_4}{T_4 - T_2}$$


$$\eta_{hp} = \frac{COP}{COP_{Carnot}}$$

$$COP_i = \frac{Q_c}{P_{el}}$$

Seasonal COP

(energy, instead of power!)

$$COP_{seas} = \frac{\sum_{t=0}^{t} Q_c}{\sum_{t=0}^{t} P_{el}}$$





Characterization of Heat pump performance



 $COP_{Carnot} = \frac{T_h}{T_h - T_c} = \frac{T_4}{T_4 - T_2}$

Coefficient of performance, COP

- Easy to calculate, f(Tc, Th)
- Obtainable for some data from data sheets and manufacturer data
- → Static! Only performance at those given conditions (power, not energy!)

c! Only performance at those given
$$\eta_{hp} = \frac{COP}{COP_{carnot}}$$

$$COP_i = \frac{Q_c}{P_{el}}$$

Seasonal COP

(energy, instead of power!)

$$COP_{seas} = \frac{\sum_{t=0}^{t} Q_c}{\sum_{t=0}^{t} P_{el}}$$

How to infer the time-based performance (other than with dynamic simulations)?




Characterization of Heat pump performance



Duration curves

- Load duration curves
- Temperature duration curves
- Resource duration curves
- Performance duration curves

Power Energy







Agenda

- KPIs
 - Solar thermal (video)
 - Heat pumps
- Parametric analysis
 - Example
 - Proposal



Definition Start Geometric parameters, Sort of simplified sensitivity analysis constants, and independent variables Check the trend on the performance of Input initial guess a system P3 and Two Calculate Tpv and Te Calculate evaporator parameters: T1, h1, P1 Source: https://doi.org/10.1016/j.solener.2021.02.006 Calculate compressor parameters: T3, h3, Wc Calculate gas cooler parameters: T_4 , h_4 , $T_{w,i}$ Update P₃ Expansion valve Update Two No $T_{w,i}$ - $T_{w,in}$ < ToleranceCold water No h₁ - h₄ < Tolerance sas cooler Yes CO_2 Calculate Performance Parameters Output: E, COP, $W_{c.}$ Q_{w} , $T_{w.o}$ Hot water End Compressor


Fig. 2. Schematic diagram of the heat pump with PV/evaporator arrangement.



Definition

Sort of simplified sensitivity analysis

- Check the trend on the performance of a system










Definition

Sort of simplified sensitivity analysis

- Check the trend on the performance of a system










Proposal

- 1. Application to your heat pump project
- 1. Calculate the COP under different conditions: Tsource, Tdemand, Gsolar...
- 2. Plot the duration curves for your varying conditions: Qdemand, Tsource,...

First step: choose only ONE variable for your parametric analysis and assume everything else to be constant

- → duration curves of two variables cannot be combined with one another!!!
- 3. Plot the duration curves for the performance of the heat pump





Proposal


- 1. Application to your heat pump project
- 1. Calculate the COP under different conditions: Tsource, Tdemand, Gsolar...
- 2. Plot the duration curves for your varying conditions: Qdemand, Tsource,...

First step: choose only ONE variable for your parametric analysis and assume everything else to be constant

→ duration curves of two variables cannot be combined with one another!!!

3. Plot the duration curves for the performance of the heat pump

Static input values, desing conditions, e.g. COP,



Estimation for annual/season al performance

Repeat for different conditions

CAUTION:

Assuming a

Simultaneity

cannot be

constant demand!

guaranteed with


duration curves!





Proposal

2. Application to your heat pump+ solar thermal project






Proposal

2. Application to your heat pump+ solar thermal project

Static input values, desing conditions, e.g. COP,

CAUTION: No demand considered so far! – only efficiencies, indep of energy flows!

→ For annual performance "estimation": typical radiation in the demand season (E.g. winter)





References

IEA 2023. Renewables 2022 Analysis and forecast to 2027. Link: https://iea.blob.core.windows.net/assets/ada7af90-e280-46c4-a577-df2e4fb44254/Renewables2022.pdf Last accessed: Oct. 2023

SHC 2022 (W.Weiss):SOLAR HEAT WORLD WIDE, Global Market Development and Trends 2022 Detailed Market Figures 2021, Link: https://www.iea-shc.org/Data/Sites/1/publications/Solar-Heat-Worldwide-2023.pdf Last accessed: Oct. 2023