

Artificial Intelligence

Intelligent Agents

Intelligent Agents

Outline

- Agents and environments
- Rationality
- Intelligence Agent
- PEAS (Performance measure, Environment, Actuators, Sensors)
- Environment types
- Agent types

Agents

- An **agent** is anything that can be viewed as **perceiving** its **environment** through **sensors** and **acting** upon that environment through **actuators**
 - Operates in an environment
 - Perceive its environment through sensors
 - Acts upon its environment through actuators/ effectors
 - Has Goals

Agents and environments

- The **agent function** maps from percept histories to actions:

$$[f: \mathcal{P}^* \rightarrow \mathcal{A}]$$

- The **agent program** runs on the physical **architecture** to produce f
- agent = architecture + program

Sensor and Effectors

- An agent perceives its environment through sensors
 - The complete set of inputs at a given time is called a percept
 - The current percept or Sequence of percepts can influence the action of an agent
- It can change the environment through actuators/ effectors
 - An operation involving an actuator is called an action
 - Action can be grouped into action sequences

Examples of Agents




Humans

senses
body parts

```
Else
  If (Len(Trim$(str1
    blnFileNext =
  Else
    ' Process data
    intColon = InStr
    If (intColon
      strName =
      strValue =
      strName = S
      Call xnNode
    End If
  End If
End If
```

Programs

keyboard, mouse, dataset
monitor, speakers, files



Robots


cameras, pads
motors, limbs

Examples of Agents (cont..)

Ex:

- **Human agent:** eyes, ears, and other organs for sensors;
 - hands, legs, mouth, and other body parts for actuators
- **Robotic agent:** cameras and infrared range finders for sensors;
 - various motors, wheels, and speakers for actuators
- **A software agent:** function (Input) as sensors
 - function as actuators (output-Screening)

Vacuum-Cleaner World



- **Percepts:** location and contents, e.g., [A,Dirty]
- **Actions:** *Left, Right, Suck, NoOp*

A vacuum-cleaner agent

Percept sequence	Action
$[A, Clean]$	<i>Right</i>
$[A, Dirty]$	<i>Suck</i>
$[B, Clean]$	<i>Left</i>
$[B, Dirty]$	<i>Suck</i>
$[A, Clean], [A, Clean]$	<i>Right</i>
$[A, Clean], [A, Dirty]$	<i>Suck</i>
\vdots	\vdots

function REFLEX-VACUUM-AGENT($[location, status]$) **returns** an action

if $status = Dirty$ **then return** *Suck*

else if $location = A$ **then return** *Right*

else if $location = B$ **then return** *Left*

What is the **right** function?

Can it be implemented in a small agent program?

Rationality

Fixed **performance measure** evaluates the **environment sequence**

- one point per square cleaned up in time T ?
- one point per clean square per time step, minus one per move?
- penalize for $> k$ dirty squares?

A **rational agent** chooses whichever action maximizes the **expected** value of the performance measure **given the percept sequence to date**

Rational \neq omniscient

- percepts may not supply all relevant information

Rational \neq clairvoyant

- action outcomes may not be as expected

Hence, rational \neq successful

Rational \Rightarrow exploration, learning, autonomy

Rationality

What is rational at any given time depends on four things:

- The performance measure that defines the criterion of success.
- The agent's prior knowledge of the environment.
- The actions that the agent can perform.
- The agent's percept sequence to date.

Rational agents

- A **rational agent** is one that does the right thing.
- For each possible percept sequence, a rational agent should select an action that is expected to maximize its performance measure, given the evidence provided by the percept sequence and whatever built-in knowledge the agent has.
- An agent's **percept sequence** is the complete history of everything the agent has ever perceived

Rational agents (cont..)

- Rationality is distinct from omniscience (all-knowing with infinite knowledge)
- Agents can perform actions in order to modify future percepts so as to obtain useful information (information gathering, exploration)

Autonomy in Agents

The **autonomy** of an agent is the extent to which its behaviour is determined by its own experience (with ability to learn and adapt)

- Extremes
 - No autonomy – ignores environment/data
 - Complete autonomy – must act randomly/no program
- Example: baby learning to crawl
- Ideal: design agents to have some autonomy
 - Possibly good to become more autonomous in time

Intelligence Agent

- Must sense
- Must act
- Must autonomous (to some extent)
- Must rational

PEAS

- **PEAS:** Performance measure, Environment, Actuators, Sensors
- Must first specify the setting for intelligent agent design
- Consider, e.g., the task of designing an automated taxi driver:
 - Performance measure
 - Environment
 - Actuators
 - Sensors

PEAS

- **The task of designing an automated taxi driver:**
 - **Performance measure:** Safe, fast, legal, comfortable trip, maximize profits
 - **Environment:** Roads, other traffic, pedestrians, customers
 - **Actuators:** Steering wheel, accelerator, brake, signal, horn
 - **Sensors:** Cameras, sonar, speedometer, GPS, odometer, engine sensors, keyboard

PEAS

Agent: Medical diagnosis system

- **Performance measure:** Healthy patient, minimize costs, lawsuits
- **Environment:** Patient, hospital, staff
- **Actuators:** Screen display (questions, tests, diagnoses, treatments, referrals)
- **Sensors:** Keyboard (entry of symptoms, findings, patient's answers)

PEAS

Agent: Part-picking robot

- **Performance measure:** Percentage of parts in correct bins
- **Environment:** Conveyor belt with parts, bins
- **Actuators:** Jointed arm and hand
- **Sensors:** Camera, joint angle sensors

PEAS

Agent: Interactive English tutor

- **Performance measure:** Maximize student's score on test
- **Environment:** Set of students
- **Actuators:** Screen display (exercises, suggestions, corrections)
- **Sensors:** Keyboard

Environments –

Accessible vs. inaccessible

- An accessible environment is one in which the agent can obtain complete, accurate, up-to-date information about the environment's state
- Most moderately complex environments (for example, the everyday physical world and the Internet) are inaccessible
- The more accessible an environment is, the simpler it is to build agents to operate in it

Environments –

Deterministic vs. non-deterministic

- A deterministic environment is one in which the next state of the environment is completely determined by the current state and the action executed by the agent.
- The physical world can to all intents and purposes be regarded as non-deterministic
- Non-deterministic environments present greater problems for the agent designer

Environments –

Episodic vs. non-episodic

- In an episodic environment, the performance of an agent is dependent on a number of discrete episodes, with no link between the performance of an agent in different scenarios
- Episodic environments are simpler from the agent developer's perspective because the agent can decide what action to perform based only on the current episode — it need not reason about the interactions between this and future episodes

Environments –

Static vs. dynamic

- A static environment is unchanged while an agent is reflecting.
- A dynamic environment is one that has other processes operating on it, and which hence changes in ways beyond the agent's control
- Other processes can interfere with the agent's actions (as in concurrent systems theory)
- The physical world is a highly dynamic environment

Environments –

Discrete vs. continuous

- An environment is discrete if there are a fixed, finite number of actions and percepts in it
 - Ex: chess game
- Continuous environments have a certain level of mismatch with computer systems
 - Ex: taxi driving
- Discrete environments could *in principle* be handled by a kind of “lookup table”

Discussion



Review Question

- Define in your own words the following terms:
 - agent, agent function, agent program, rationality, autonomy,
- For each of the following agents, develop a PEAS description of the task environment
 - Part-picking robot, Taxi Driver
- Describe the following types of the environment
 - Static vs. Dynamic
 - Deterministic vs. non-deterministic
- List 4 most complex environments in which constructing agent is very difficult.
- What is Omniscience?