

```
Last login: Fri Apr 16 08:52:36 on ttys000
jackbourne@Jacks-MacBook-Pro ~ % ls
Applications      Library           Public            gitDemo
Desktop           Movies            Splice            gitDemo.html
Documents         Music             boom              running around
Downloads         Pictures          first             super_boom
jackbourne@Jacks-MacBook-Pro ~ % git add gitDemo.html
fatal: not a git repository (or any of the parent directories): .git
jackbourne@Jacks-MacBook-Pro ~ % git status
fatal: not a git repository (or any of the parent directories): .git
jackbourne@Jacks-MacBook-Pro ~ % git init
Initialized empty Git repository in /Users/jackbourne/.git/
jackbourne@Jacks-MacBook-Pro ~ % git status
warning: could not open directory '.Trash/': Operation not permitted
warning: could not open directory 'Downloads/': Operation not permitted
On branch master
```

No commits yet

Untracked files:

(use "git add <file>..." to include in what will be committed)

```
.CFUserTextEncoding
.DS_Store
.config/
.vscode/
.zsh_history
Applications/
Desktop/
Documents/
Library/
Movies/
Music/
Pictures/
Public/
Splice/
boom/
first/
gitDemo
gitDemo.html
super_boom/
```

It took 4.68 seconds to enumerate untracked files. 'status -uno' may speed it up, but you have to be careful not to forget to add new files yourself (see 'git help status').

nothing added to commit but untracked files present (use "git add" to track)

```
jackbourne@Jacks-MacBook-Pro ~ % git add gitDemo.html
jackbourne@Jacks-MacBook-Pro ~ % git status
warning: could not open directory '.Trash/': Operation not permitted
warning: could not open directory 'Downloads/': Operation not permitted
On branch master
```

No commits yet

Changes to be committed:

(use "git rm --cached <file>..." to unstage)

```
new file:   gitDemo.html
```

Untracked files:

(use "git add <file>..." to include in what will be committed)

.CFUserTextEncoding
.DS_Store
.config/
.vscode/
.zsh_history
Applications/
Desktop/
Documents/
Library/
Movies/
Music/
Pictures/
Public/
Splice/
boom/
first/
gitDemo
super_boom/

```
jackbourne@Jacks-MacBook-Pro ~ % git commit -m "create gitDemo.html"
```

```
[master (root-commit) b419d04] create gitDemo.html
```

```
Committer: Jack Bourne <jackbourne@Jacks-MacBook-Pro.local>
```

Your name and email address were configured automatically based on your username and hostname. Please check that they are accurate. You can suppress this message by setting them explicitly. Run the following command and follow the instructions in your editor to edit your configuration file:

```
git config --global --edit
```

After doing this, you may fix the identity used for this commit with:

```
git commit --amend --reset-author
```

```
1 file changed, 0 insertions(+), 0 deletions(-)
```

```
create mode 100644 gitDemo.html
```

```
jackbourne@Jacks-MacBook-Pro ~ % git status
```

```
warning: could not open directory '.Trash/': Operation not permitted
```

```
warning: could not open directory 'Downloads/': Operation not permitted
```

```
On branch master
```

Untracked files:

(use "git add <file>..." to include in what will be committed)

.CFUserTextEncoding
.DS_Store
.config/
.vscode/
.zsh_history
Applications/
Desktop/
Documents/
Library/
Movies/
Music/
Pictures/
Public/
Splice/

```
boom/  
first/  
gitDemo  
super_boom/
```

```
nothing added to commit but untracked files present (use "git add" to track)  
jackbourne@Jacks-MacBook-Pro ~ %
```

```
[Restored 16 Apr 2021 at 10:22:40]
```

```
Last login: Fri Apr 16 09:09:00 on ttys000
```

```
jackbourne@Jacks-MacBook-Pro ~ % git status
```

```
warning: could not open directory '.Trash/': Operation not permitted
```

```
warning: could not open directory 'Downloads/': Operation not permitted
```

```
On branch master
```

```
Changes not staged for commit:
```

```
(use "git add <file>..." to update what will be committed)
```

```
(use "git restore <file>..." to discard changes in working directory)
```

```
modified:   gitDemo.html
```

```
Untracked files:
```

```
(use "git add <file>..." to include in what will be committed)
```

```
.CFUserTextEncoding
```

```
.DS_Store
```

```
.config/
```

```
.vscode/
```

```
.zsh_history
```

```
Applications/
```

```
Desktop/
```

```
Documents/
```

```
Library/
```

```
Movies/
```

```
Music/
```

```
Pictures/
```

```
Public/
```

```
Splice/
```

```
boom/
```

```
first/
```

```
gitDemo
```

```
super_boom/
```

```
no changes added to commit (use "git add" and/or "git commit -a")
```

```
jackbourne@Jacks-MacBook-Pro ~ % git add gitDemo.html
```

```
jackbourne@Jacks-MacBook-Pro ~ % git status
```

```
warning: could not open directory '.Trash/': Operation not permitted
```

```
warning: could not open directory 'Downloads/': Operation not permitted
```

```
On branch master
```

```
Changes to be committed:
```

```
(use "git restore --staged <file>..." to unstage)
```

```
modified:   gitDemo.html
```

```
Untracked files:
```

```
(use "git add <file>..." to include in what will be committed)
```

```
.CFUserTextEncoding
```

```
.DS_Store
```

```
.config/
```

```
.vscode/
```

```
.zsh_history
```

```
Applications/
```

```
Desktop/
```

```
Documents/  
Library/  
Movies/  
Music/  
Pictures/  
Public/  
Splice/  
boom/  
first/  
gitDemo  
super_boom/
```

```
jackbourne@Jacks-MacBook-Pro ~ % git commit -m "add basic html skeleton"  
[master f508ec0] add basic html skeleton  
Committer: Jack Bourne <jackbourne@Jacks-MacBook-Pro.local>  
Your name and email address were configured automatically based  
on your username and hostname. Please check that they are accurate.  
You can suppress this message by setting them explicitly. Run the  
following command and follow the instructions in your editor to edit  
your configuration file:
```

```
git config --global --edit
```

After doing this, you may fix the identity used for this commit with:

```
git commit --amend --reset-author
```

```
1 file changed, 17 insertions(+)  
jackbourne@Jacks-MacBook-Pro ~ % git status  
warning: could not open directory '.Trash/': Operation not permitted  
warning: could not open directory 'Downloads/': Operation not permitted  
On branch master  
Untracked files:
```

(use "git add <file>..." to include in what will be committed)

```
.CFUserTextEncoding  
.DS_Store  
.config/  
.vscode/  
.zsh_history  
Applications/  
Desktop/  
Documents/  
Library/  
Movies/  
Music/  
Pictures/  
Public/  
Splice/  
boom/  
first/  
gitDemo  
super_boom/
```

```
nothing added to commit but untracked files present (use "git add" to track)  
jackbourne@Jacks-MacBook-Pro ~ % git status  
warning: could not open directory '.Trash/': Operation not permitted  
warning: could not open directory 'Downloads/': Operation not permitted  
On branch master
```

Changes not staged for commit:

(use "git add <file>..." to update what will be committed)

(use "git restore <file>..." to discard changes in working directory)

modified: gitDemo.html

Untracked files:

(use "git add <file>..." to include in what will be committed)

.CFUserTextEncoding

.DS_Store

.config/

.vscode/

.zsh_history

Applications/

Desktop/

Documents/

Library/

Movies/

Music/

Pictures/

Public/

Splice/

boom/

first/

gitDemo

super_boom/

no changes added to commit (use "git add" and/or "git commit -a")

jackbourne@Jacks-MacBook-Pro ~ % git dif

git: 'dif' is not a git command. See 'git --help'.

The most similar commands are

diff

config

difftool

init

jackbourne@Jacks-MacBook-Pro ~ % git status

warning: could not open directory '.Trash/': Operation not permitted

warning: could not open directory 'Downloads/': Operation not permitted

On branch master

Changes not staged for commit:

(use "git add <file>..." to update what will be committed)

(use "git restore <file>..." to discard changes in working directory)

modified: gitDemo.html

Untracked files:

(use "git add <file>..." to include in what will be committed)

.CFUserTextEncoding

.DS_Store

.config/

.vscode/

.zsh_history

Applications/

Desktop/

Documents/

Library/

Movies/

Music/

Pictures/

```
Public/  
Splice/  
boom/  
first/  
gitDemo  
super_boom/
```

no changes added to commit (use "git add" and/or "git commit -a")

jackbourne@Jacks-MacBook-Pro ~ % git diff

diff --git a/gitDemo.html b/gitDemo.html

index e0ba07c..5bee636 100644

--- a/gitDemo.html

+++ b/gitDemo.html

@@ -11,6 +11,7 @@

<body>

<h1>heeeeelllllooooo</h1>

+ <h2>boooooooooo!</h2>

</body>

jackbourne@Jacks-MacBook-Pro ~ % clear

jackbourne@Jacks-MacBook-Pro ~ % ls

Applications	Library	Public	gitDemo
Desktop	Movies	Splice	gitDemo.html
Documents	Music	boom	running around
Downloads	Pictures	first	super_boom

jackbourne@Jacks-MacBook-Pro ~ % mkdir learn_git_again

jackbourne@Jacks-MacBook-Pro ~ % ls

Applications	Library	Public	gitDemo	super_boom
Desktop	Movies	Splice	gitDemo.html	
Documents	Music	boom	learn_git_again	
Downloads	Pictures	first	running around	

jackbourne@Jacks-MacBook-Pro ~ % cd learn_git_again

jackbourne@Jacks-MacBook-Pro learn_git_again % touch third.txt

jackbourne@Jacks-MacBook-Pro learn_git_again % ls

third.txt

jackbourne@Jacks-MacBook-Pro learn_git_again % cd ..

jackbourne@Jacks-MacBook-Pro ~ % cd lear_git_again

cd: no such file or directory: lear_git_again

jackbourne@Jacks-MacBook-Pro ~ % cd learn_git_again

jackbourne@Jacks-MacBook-Pro learn_git_again % git init

Initialized empty Git repository in /Users/jackbourne/learn_git_again/.git/

jackbourne@Jacks-MacBook-Pro learn_git_again % git add third.txt

jackbourne@Jacks-MacBook-Pro learn_git_again % git status

On branch master

No commits yet

Changes to be committed:

(use "git rm --cached <file>..." to unstage)

new file: third.txt

jackbourne@Jacks-MacBook-Pro learn_git_again % git commit -m "adding third txt"

[master (root-commit) 1b1b3db] adding third txt

Committer: Jack Bourne <jackbourne@Jacks-MacBook-Pro.local>

Your name and email address were configured automatically based

on your username and hostname. Please check that they are accurate. You can suppress this message by setting them explicitly. Run the following command and follow the instructions in your editor to edit your configuration file:

```
git config --global --edit
```

After doing this, you may fix the identity used for this commit with:

```
git commit --amend --reset-author
```

```
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 third.txt
jackbourne@Jacks-MacBook-Pro learn_git_again % git status
On branch master
nothing to commit, working tree clean
jackbourne@Jacks-MacBook-Pro learn_git_again % git log
commit 1b1b3db963b2a753ba963d0a1c7096e0ef6101dd (HEAD -> master)
Author: Jack Bourne <jackbourne@Jacks-MacBook-Pro.local>
Date:   Fri Apr 16 10:42:17 2021 +0200
```

```
adding third txt
jackbourne@Jacks-MacBook-Pro learn_git_again % touch fourth.txt
jackbourne@Jacks-MacBook-Pro learn_git_again % git add fourth.txt
jackbourne@Jacks-MacBook-Pro learn_git_again % git status
On branch master
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
        new file:   fourth.txt
```

```
jackbourne@Jacks-MacBook-Pro learn_git_again % git commit -m "adding fourth.txt"
```

```
[master a82d4e5] adding fourth.txt
Committer: Jack Bourne <jackbourne@Jacks-MacBook-Pro.local>
Your name and email address were configured automatically based
on your username and hostname. Please check that they are accurate.
You can suppress this message by setting them explicitly. Run the
following command and follow the instructions in your editor to edit
your configuration file:
```

```
git config --global --edit
```

After doing this, you may fix the identity used for this commit with:

```
git commit --amend --reset-author
```

```
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 fourth.txt
jackbourne@Jacks-MacBook-Pro learn_git_again % git status
On branch master
nothing to commit, working tree clean
jackbourne@Jacks-MacBook-Pro learn_git_again % git log
commit a82d4e5703cc0acb199f800e27694b712a8c3c75 (HEAD -> master)
Author: Jack Bourne <jackbourne@Jacks-MacBook-Pro.local>
Date:   Fri Apr 16 10:44:11 2021 +0200
```

```
adding fourth.txt
```

commit 1b1b3db963b2a753ba963d0a1c7096e0ef6101dd

Author: Jack Bourne <jackbourne@Jacks-MacBook-Pro.local>

Date: Fri Apr 16 10:42:17 2021 +0200

```
adding third txt
jackbourne@Jacks-MacBook-Pro learn_git_again % rm third.txt
jackbourne@Jacks-MacBook-Pro learn_git_again % ls
fourth.txt
jackbourne@Jacks-MacBook-Pro learn_git_again % git config --global core.pager=cat
error: invalid key: core.pager=cat
jackbourne@Jacks-MacBook-Pro learn_git_again % core.pager=cat git config
zsh: command not found: core.pager=cat
jackbourne@Jacks-MacBook-Pro learn_git_again % core.pager=cat - git config
zsh: command not found: core.pager=cat
jackbourne@Jacks-MacBook-Pro learn_git_again % git config --global core.pager 'cat'
jackbourne@Jacks-MacBook-Pro learn_git_again % git config --global
usage: git config [<options>]
```

Config file location

--global	use global config file
--system	use system config file
--local	use repository config file
--worktree	use per-worktree config file
-f, --file <file>	use given config file
--blob <blob-id>	read config from given blob object

Action

--get	get value: name [value-regex]
--get-all	get all values: key [value-regex]
--get-regexp	get values for regexp: name-regex [value-regex]
--get-urlmatch	get value specific for the URL: section[.var] URL
--replace-all	replace all matching variables: name value [value_regex]
x]	
--add	add a new variable: name value
--unset	remove a variable: name [value-regex]
--unset-all	remove all matches: name [value-regex]
--rename-section	rename section: old-name new-name
--remove-section	remove a section: name
-l, --list	list all
-e, --edit	open an editor
--get-color	find the color configured: slot [default]
--get-colorbool	find the color setting: slot [stdout-is-tty]

Type

-t, --type <>	value is given this type
--bool	value is "true" or "false"
--int	value is decimal number
--bool-or-int	value is --bool or --int
--path	value is a path (file or directory name)
--expiry-date	value is an expiry date

Other

-z, --null	terminate values with NUL byte
--name-only	show variable names only
--includes	respect include directives on lookup
--show-origin	show origin of config (file, standard input, blob, com


```
mand line)
    --default <value>          with --get, use default value when missing entry
```

```
jackbourne@Jacks-MacBook-Pro learn_git_again % git config --get-all
error: wrong number of arguments, should be from 1 to 2
usage: git config [<options>]
```

```
Config file location
    --global          use global config file
    --system          use system config file
    --local           use repository config file
    --worktree        use per-worktree config file
    -f, --file <file> use given config file
    --blob <blob-id>  read config from given blob object
```

```
Action
    --get             get value: name [value-regex]
    --get-all        get all values: key [value-regex]
    --get-regexp      get values for regexp: name-regex [value-regex]
    --get-urlmatch    get value specific for the URL: section[.var] URL
    --replace-all    replace all matching variables: name value [value_rege
```

```
x]
    --add             add a new variable: name value
    --unset           remove a variable: name [value-regex]
    --unset-all      remove all matches: name [value-regex]
    --rename-section  rename section: old-name new-name
    --remove-section  remove a section: name
    -l, --list        list all
    -e, --edit        open an editor
    --get-color       find the color configured: slot [default]
    --get-colorbool   find the color setting: slot [stdout-is-tty]
```

```
Type
    -t, --type <>    value is given this type
    --bool           value is "true" or "false"
    --int            value is decimal number
    --bool-or-int    value is --bool or --int
    --path           value is a path (file or directory name)
    --expiry-date    value is an expiry date
```

```
Other
    -z, --null       terminate values with NUL byte
    --name-only      show variable names only
    --includes       respect include directives on lookup
    --show-origin    show origin of config (file, standard input, blob, com
mand line)
    --default <value> with --get, use default value when missing entry
```

```
jackbourne@Jacks-MacBook-Pro learn_git_again %
```