



TECHNICAL UNIVERSITY OF MUNICH

**SCHOOL OF COMPUTATION, INFORMATION AND
TECHNOLOGY
INFORMATICS**

Master's Thesis in Informatics

**DRAFT - Thesis Proposal:
Something With Usability in PIX:E**

Rai Trouvain



TECHNICAL UNIVERSITY OF MUNICH

**SCHOOL OF COMPUTATION, INFORMATION AND
TECHNOLOGY
INFORMATICS**

Master's Thesis in Informatics

**DRAFT - Thesis Proposal:
Something With Usability in PIX:E**

Thesis Proposal: Irgendetwas mit Usability
in PIX:E

Author:	Rai Trouvain
Supervisor:	Prof. Dr. Georg Groh
Advisors:	Julian Geheeb M.Sc.
Submission Date:	DRAFT - 14.06.2026

Disclaimer

I confirm that this Master's thesis is my own work and I have documented all sources and material used.

(Date)

(Rai Trouvain)

Acknowledgements

The acknowledgements

Abstract

English Abstract

Zusammenfassung

German Abstract

Contents

1 Introduction	2
2 Background	3
3 Path-Based Diagrams	4
3.1 Path Selection	4
3.1.1 Functionality	4
3.1.2 Implementation	4
3.1.3 Workflow	4
3.2 Diagram Generation	5
3.2.1 Functionality	5
3.2.2 Implementation	6
3.2.3 Workflow	6
3.2.4 Limitations	6
4 Locks and Keys	7
4.1 Definition and Taxonomy	7
4.2 Creating and Visualizing Locks and Keys	7
4.3 Pathfinding with Locks and Keys	7
4.3.1 Basic Dijkstra with Locks and Keys	7
4.3.2 Fixed Keys	9
4.3.3 Soft Gates	10
4.3.4 Consumable Keys and Soft-Lock Detection	10
4.4 Bidirectional Edges and Backtracking	12
4.4.1 Example	14
4.4.2 Full Algorithm	14
4.5 Options/Settings	15
4.6 Testing	15
4.7 Limitations and Future Workflow	15
Bibliography	16

1 Introduction

2 Background

3 Path-Based Diagrams

- basic idea already present in PaceMaker: select path in statechart and visualize data along path
- main design guideline: build upon high configurability already present in the system
- following sections describe functionalities, implementation choices and workflow/usage of these features implemented in pixe

3.1 Path Selection

3.1.1 Functionality

- selection of nodes in statechart triggers calculation of path connecting them
- selected path is highlighted (visual feedback)
- path is subsequently used for diagram generation

3.1.2 Implementation

- select start + end node, optionally intermediate -> calculate path using dijkstra
- `pathsApi.ts`: to allow for different algorithms in the future (e.g. specific pathfinding for nestedness and concurrency)

3.1.3 Workflow

- selection of at least two nodes
 - Ctrl + click
- path is calculated along nodes **in order of selection**
- if path is found, the corresponding nodes are highlighted
- path can be de-selected by removing node selection (clicking anywhere)




Figure 1: Path highlighted in state chart

3.2 Diagram Generation

3.2.1 Functionality

- expandable element on statechart page
 - usability: users can hide diagrams while working on statechart
- can create multiple diagrams and remove diagrams (red because diagrams do not persist)




Figure 2: Upper section of the charts page with expandable element and UI for diagram creation

- selection of one or multiple component definitions for the y axis
- optionally selection of one component for the x axis (e.g. estimated playtime)
 - values are summed up along selected path
 - default: equal spacing




Figure 3: Selectors for components to be mapped to X/Y axes

- selected path along x axis
 - if no path selected: all nodes,  sorted



Figure 4: Diagram visualizing component along selected path




Figure 5: Diagram visualizing component across all nodes

3.2.2 Implementation

- [chartJS](#) library
- modular architecture: `PxDiagrams` as wrapper element
 - manages diagrams
 - currently: passes path (reactively), deletes diagrams
 - future work: path snapshots, different data types
- data is extracted from nodes once per diagram, switching between axis configurations is then done via different parsing configurations

3.2.3 Workflow

1. add new diagram
2. in any order:
 - select one or no component for x axis
 - select one or more component for y axis
 - select path
- changes in any of the configurations will be reflected live in the diagram

3.2.4 Limitations

- diagrams do not persist (reset when reloading page)
- only line diagrams for now
- same path selection for all diagrams

4 Locks and Keys

requirements/context:

- multiple keys possible per node
- multiple locks possible per node
- pathfinding and reachability analysis

4.1 Definition and Taxonomy

4.2 Creating and Visualizing Locks and Keys

4.3 Pathfinding with Locks and Keys

4.3.1 Basic Dijkstra with Locks and Keys

- goal: all locks assigned to edges in the path have to be unlocked by key(s) collected up to the edge in question
- inventory: track keys collected along path to determine whether encountered edges can be unlocked
 - inventory similar to [\(Aversa, Sardina, and Vassos 2015\)](#)
 - modeled via `PxKeySet` -> formally: mapping of key defs to counts
- basic form: inventory associated with a node reflects keys collected along shortest path to this node and keys made available in this node -> later extended (consumable keys)

4.3.1.1 Unlocking Function

- `canUnlock()`: given (multi-)sets of locks and keys, determine whether locks can be unlocked
 - added complexity due to an edge potentially having multiple locks, and each locks potentially being unlocked by multiple keys
 - exponential blowup, but no optimization so far as average case is expected to be less complex

given set of keys in inventory K and locks on edge L :

```
canUnlock(K, L):
  if L = ∅
    return TRUE

  unlockingKeysets = required(l1) × ... × required(ln)
```

```

if  $\exists U \in \text{unlockingKeysets}$  where  $\forall u \in U. u \in K$ :
  return TRUE
else
  return FALSE

```

4.3.1.2 Example




Figure 6: Calculation of unlocking keysets

- $I = \{X, Y\} \rightarrow \text{false}$
- $I = X, Y, Z \rightarrow \text{true}$

4.3.1.3 Full Algorithm




Figure 7: Calculation of unlocking keysets for key consumption

4.3.1.4 Example Iteration

- TODO add small example of iteration

4.3.2 Fixed Keys

- goal: fixed keys can only unlock locks on outgoing edges of the node they are assigned to

implementation:

- do not add keys to inventory of neighbors
-  add example

4.3.3 Soft Gates

- goal: soft gates **can** be passed without the corresponding key, but this should be indicated in the path highlighting

implementation:

- during pathfinding, ignore soft-gate locks
- after path has been found, re-trace it to determine whether keys are available or not
-  add example from pixe

4.3.4 Consumable Keys and Soft-Lock Detection

- goal: inventory should reflect usage of single-use keys
- variants of inventory -> idea of ‘parallel universes’
 - nodes exist in different realities if they have different inventories
 - assign each node a set of possible keysets

implementation:

- maintain set of `PxKeySets` per node
- in `canUnlock`, consider multiplicity of consumable keys
- for updating inventory of neighbor nodes: remove consumed keys from inventory
 - if there are multiple possible constellations, add multiple keysets

4.3.4.1 Pathfinding with Consumable Keys

Extending Unlocking Check

given multiset of keys in inventory K and locks on edge L :

```
canUnlock(K, L):
  if L = ∅
    return TRUE

  unlockingKeysets = required(l1) × ... × required(ln)

  if ∃ U ∈ unlockingKeysets where U ⊆ K:
    return TRUE
  else
    return FALSE
```

- note: subset of multiset




Figure 8: Calculation of unlocking keysets

- now: $I = \{X, Z\} \rightarrow \text{false}$

Removing Consumable Keys from Inventory

given inventory I containing multisets of keys K and locks on edge L :

```

canUnlock(I, L):
  if L = ∅
    return TRUE

  consumableRequirements = locks with at least one consumable key unlocking
  unlockingKeysets = required(l1) × ... × required(ln)

  updatedInventory = {}
  for K_i ∈ I:
    if ∃ U ∈ unlockingKeysets with K_i ⊆ U:
      updatedInventory.push(K_i - { key ∈ U. consumable(key) })

  return updatedInventory
  
```




Figure 9: Calculation of unlocking keysets for key consumption

- $I = \{X, X, Z\} \rightarrow \{Z\}$
- example in pixe for consumable keys

4.3.4.2 Soft-Locks

(Mawhorter and Smith 2021): >it is possible to reach the goal state from every reachable state

- here: not nodes, but **states in which nodes are visited**




Figure 10: Calculation of unlocking keysets for key consumption

implementation:

- potential soft-lock state: node unlockable with some, but not all keysets
- when removing consumed keys: remove empty keysets entirely. then, compare inventory length before and after consumption
- example in pixe for consumable keys

4.4 Bidirectional Edges and Backtracking

- goal: allow for longer/cyclic paths needed to collect keys
- another idea of parallel universes
- add citation from julians paper?

implementation:

- alternative used here: nodes are re-added to queue iff they have a different inventory assigned to them than in previous encounters -> only duplicate nodes as needed
 - for each node, maintain inventories it has been visited with
 - only re-visit with a different inventory
 - add limiting constant for revisits
 - also maintain unlocked edges




Figure 11: Calculation of unlocking keysets for key consumption

- critical path: $A - B - A - C$




Figure 12: Calculation of unlocking keysets for key consumption

4.4.1 Example

-  example screenshot from pixe

4.4.2 Full Algorithm

-  make diagram of full algorithm?

4.5 Options/Settings

-  describe pathfinding options

4.6 Testing

-  describe

4.7 Limitations and Future Workflow

- difficulty estimation
- recommendations for lock/key types ([Dormans 2017](#))
- LLM-based consistency check with descriptions

Bibliography

Davide Aversa, Sebastian Sardina, and Stavros Vassos. 2015. Path Planning with Inventory-Driven Jump-Point-Search. *Proceedings of the AAAI Conference on Artificial Intelligence and Interactive Digital Entertainment*, 11(1):2–8.

Joris Dormans. 2017. Cyclic Generation.

Ross Mawhorter and Adam Smith. 2021. Softlock Detection for Super Metroid with Computation Tree Logic. In *Proceedings of the 16th International Conference on the Foundations of Digital Games*, pages 1–10, New York, NY, USA. Association for Computing Machinery.