# Chapter 8 Security


#### A note on the use of these Powerpoint slides:

We're making these slides freely available to all (faculty, students, readers). They're in PowerPoint form so you see the animations; and can add, modify, and delete slides (including this one) and slide content to suit your needs. They obviously represent a *lot* of work on our part. In return for use, we only ask the following:

- If you use these slides (e.g., in a class) that you mention their source (after all, we'd like people to use our book!)
- If you post any slides on a www site, that you note that they are adapted from (or perhaps identical to) our slides, and note our copyright of this material.

Thanks and enjoy! JFK/KWR

© All material copyright 1996-2016 J.F Kurose and K.W. Ross, All Rights Reserved




#### Computer Networking: A Top Down Approach

7<sup>th</sup> edition Jim Kurose, Keith Ross Pearson/Addison Wesley April 2016

## Chapter 8 roadmap


- 8.1 What is network security?
- 8.2 Principles of cryptography
- 8.3 Message integrity, authentication
- 8.4 Securing e-mail
- **8.5** Securing TCP connections: SSL
- 8.6 Network layer security: IPsec
- 8.7 Securing wireless LANs
- 8.8 Operational security: firewalls and IDS

#### The language of cryptography



m plaintext message  $K_A(m)$  ciphertext, encrypted with key  $K_A(m) = K_B(K_A(m))$ 

### Symmetric key cryptography



symmetric key crypto: Bob and Alice share same (symmetric) key: K<sub>S</sub>

- e.g., key is knowing substitution pattern in mono alphabetic substitution cipher
- Q: how do Bob and Alice agree on key value?

## Simple encryption scheme

substitution cipher: substituting one thing for another

monoalphabetic cipher: substitute one letter for another

```
plaintext: abcdefghijklmnopqrstuvwxyz
ciphertext: mnbvcxzasdfghjklpoiuytrewq
```

e.g.: Plaintext: bob. i love you. alice ciphertext: nkn. s gktc wky. mgsbc

Encryption key: mapping from set of 26 letters to set of 26 letters

#### A more sophisticated encryption approach

- n substitution ciphers, M<sub>1</sub>,M<sub>2</sub>,...,M<sub>n</sub>
- cycling pattern:
  - e.g., n=4:  $M_1, M_3, M_4, M_3, M_2$ ;  $M_1, M_3, M_4, M_3, M_2$ ; ...
- for each new plaintext symbol, use subsequent substitution pattern in cyclic pattern
  - dog: d from M<sub>1</sub>, o from M<sub>3</sub>, g from M<sub>4</sub>

Encryption key: n substitution ciphers, and cyclic pattern



key need not be just n-bit pattern

#### Symmetric key crypto: DES

#### **DES: Data Encryption Standard**

- US encryption standard [NIST 1993]
- 56-bit symmetric key, 64-bit plaintext input
- block cipher with cipher block chaining
- how secure is DES?
  - DES Challenge: 56-bit-key-encrypted phrase decrypted (brute force) in less than a day
  - no known good analytic attack
- making DES more secure:
  - 3DES: encrypt 3 times with 3 different keys


## Symmetric key crypto: DES

#### **DES** operation

initial permutation

16 identical "rounds" of function application, each using different 48 bits of key

final permutation



#### **AES: Advanced Encryption Standard**

- symmetric-key NIST standard, replaced DES (Nov 2001)
- processes data in 128 bit blocks
- 128, 192, or 256 bit keys
- brute force decryption (try each key) taking I sec on DES, takes I49 trillion years for AES