MathML in htmlbag

Every formula below is presentation MathML embedded directly in the HTML source. The htmlbag selector picks up the `<math>` subtree as foreign content, hands it to the MathML reader, and the math engine renders to a single HList that flows inline with the surrounding text.

Inline math: variables and superscripts

The Pythagorean relation $a^2 + b^2 = c^2$ holds for every right triangle with legs a, b and hypotenuse c.

Single-character <mi> defaults to italic per the MathML spec; the reader auto-maps a, b, c to U+1D44E ff so the font shows them in the Mathematical Italic alphabet.

Inline math: fractions and roots

The quadratic formula $x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$ solves $ax^2 + bx + c = 0$.

Display math: big operators with limits

Gauss famously summed the first n integers:

$$\sum_{k=1}^{n} k = \frac{n(n+1)}{2}$$

display="block" routes through math.DisplayMath, which applies the bigger FractionNumeratorDisplayStyleShiftUp and centres limits above / below the sigma rather than typesetting them as scripts.

Nested scripts and indexed roots

Index-of-summation gymnastics plus an n-th root:

$$\sqrt[n]{\sum_{i=1}^{n} x_i^2} = \sigma_n$$

Multi-character identifier (function name)

Per the MathML default, multi-character `<mi>` stays upright — that's how function names render correctly:

$$\frac{d}{dx}\sin(x) = \cos(x)$$