
CS6650 Assignment 1: Design Document

Name: Boyang Li

Project repository: https://github.com/boyanglineu-prog/6650

1. Architecture



2. Major classes

Server


- `SkierServlet` handles `/resorts/*`, `/health`, and `/stats` (mapped in `web.xml`).
- `LeaderboardEndpoint` is the WebSocket endpoint. It keeps a map of sessions, and one scheduled thread pushes the leaderboard to every subscriber every 500 ms.
- `RequestStats` holds thread-safe GET and POST counters (`AtomicLong`).

Client


- `SwipeClient` is the orchestrator. It starts the subscribers, measures the round-trip time, runs the warmup and then the main phase, prints the metrics, and writes `swipe_metrics.csv`. It uses `SwipeMessage` to create the requests and `SubscribeClient` for the WebSocket side.
- `SubscribeClient` is the WebSocket client. It keeps one connection per resort.

3. Threading model (client)

Run order (main thread):



Inside each phase (warmup and main run):



- **Generator (1 dedicated thread):** creates `SwipeMessage` s and `put` s them on a bounded `LinkedBlockingQueue` (10,000 slots).
- **Sender pool (fixed thread pool):** each worker `take` s a message and sends it with a **single shared `HttpClient`**
- **Failure handling:** up to 5 retries with backoff (50 ms x 2^attempt) on connection errors or 5xx; 4xx are not retried; 10 s request timeout.
- **Phases:** (1) *RTT probe*: one cold request plus 100 sequential requests; (2) *warmup*: 32 threads x 1,000 = 32,000 swipes; (3) *main run*: 500 threads, 500,000 swipes.
- **Metrics:** counters are atomic; each swipe records `{start time, latency, status, resortID}` in a `ConcurrentLinkedQueue` , written to CSV after the run.

4. WebSocket connection management (client)

- **Subscription pool:** 10 subscribers, one per resort (1-10), connected through a 10-thread `ScheduledExecutorService` .
- **Reconnect:** `@OnClose` schedules a reconnect after 1 s. A failed connect retries with exponential backoff (1, 2, 4, ... capped at 30 s).
- **Metrics:** connections and reconnects, handshake time per resort, updates per subscriber, push latency (receive time minus `serverTimestamp`).

5. Little's Law

Throughput = L / W, where L = concurrent requests in flight and W = time per request.

- **L = 500** (one in-flight request per sender thread).
- **W = 21.0 ms**: average of 100 sequential requests.
- **Predicted maximum**: 500 / 0.0210 s = 23,864 swipes/s.
- **Measured**: 9,162 swipes/s (38% of predicted).