


SENG1110/SENG6110 Object Oriented Programming

Lecture 10 Recursion



Outline

- Recursive definitions
- Recursive Problem Solving
- Factorial example
- How recursion works
- Tracing a recursive method
- The Run-Time Stack
- Infinite Recursion and Stack Overflow
- Recursion and Iteration
- Sequential search example
- Fibonacci example

Recursive Definitions

- Recursion
 - Process of solving a problem by reducing it to simpler versions of itself.

Recursive Definitions

- Recursive algorithm:
 - Algorithm that finds the solution to a given problem by reducing the problem to smaller versions of itself.
 - Has one or more base cases.
 - Implemented using recursive methods.
- Recursive method:
 - Method that calls itself.
- Base case:
 - Case in recursive definition in which the solution is obtained directly.
 - Stops the recursion.

Recursive Problem Solving

5

- Find one or more simple cases of the problem that can be solved directly – base cases
- Find a way to make the problem smaller for a recursive solution
- Find a way to combine the partial solutions

Factorial example

7

$n! = 1$, when $n = 1$ ← base case
 $n! = n * (n - 1)!$ otherwise

```
factorial (n)
  if n == 1
    return 1
  else
    return n * factorial(n - 1)
```

Factorial example

6

- Factorial:
 - $n! = 1$, when $n = 1$
 - $n! = n * (n - 1)!$ otherwise

$$\begin{aligned} 3! &= 3 * 2! \\ &= 3 * 2 * 1! \\ &= 3 * 2 * 1 \end{aligned}$$

Factorial example

8


$n! = 1$, when $n = 1$ ← base case
 $n! = n * (n - 1)!$ otherwise

Recursive case

```
factorial (n)
  if n == 1
    return 1
  else
    return n * factorial(n - 1)
```

Factorial example

9



How Recursion Works

10

- Each call of a method generates an instance of that method
- An instance of a method contains
 - memory for each parameter
 - memory for each local variable
 - memory for the return value

Tracing a Recursive Method

11

- Recursive method:
 - Has unlimited copies of itself.
 - Every recursive call has its own:
 - Code
 - Set of parameters
 - Set of local variables

Tracing a Recursive Method

12

- After completing a recursive call:
 - Control goes back to the calling environment.
 - Recursive call must execute completely before control goes back to previous call.
 - Execution in previous call begins from point immediately following recursive call.

Recursive Factorial Method

13


```
public static int fact(int num)
{
    if (num == 1)
        return 1;
    else
        return num * fact(num - 1);
}
```

May 17
Dr. Regina Berretta



Activations Are Added Dynamically

15




May 17
Dr. Regina Berretta



Example: factorial(4)

14




May 17
Dr. Regina Berretta



Number of Activations = # Calls

16




May 17
Dr. Regina Berretta



Recursive Process Bottoms out

17




May 17
Dr. Regina Berretta



Activations Are Deallocated

19




May 17
Dr. Regina Berretta



Recursive Process Unwinds

18




May 17
Dr. Regina Berretta



Activations Are Deallocated

20



May 17
Dr. Regina Berretta



Value Returned Is in the First Activation

21

return value n 4
24 Activation record for **factorial(4)**

May 17
Dr. Regina Berretta



The Run-Time Stack

22

- To support recursive method calls, the run-time system treats memory as a *stack* of activation records
- Computing **factorial(n)** requires the allocation of *n* activation records on the stack

May 17
Dr. Regina Berretta



Infinite Recursion and Stack Overflow

23

```
int infiniteRecursion (int n) {  
    if (n == 0)  
        return 1;  
    else  
        return infiniteRecursion (n);  
}
```

The value of *n* never reaches zero, so the method is called, and records are pushed onto the stack, until the system runs out of memory.

May 17
Dr. Regina Berretta



Recursion and Iteration

24

```
int factorial (int n){  
    if n == 1  
        return 1;  
    else  
        return n * factorial (n - 1);  
}
```

```
int factorial (int n){  
    int result = 1;  
    while (n > 1){  
        result = result * n;  
        n--;  
    }  
    return result;  
}
```

Recursive methods can be translated to methods that run loops.

May 17
Dr. Regina Berretta



Memory Usage

25

```
int factorial (int n){
    int result = 1;
    while (n > 1){
        result = result * n;
        n--;
    }
    return result;
}
```

n 4
return value

result 1
n 4
return value

May 17
Dr. Regina Berthiaume

Recursive version

Iterative version



Memory Usage

27

```
int factorial (int n){
    int result = 1;
    while (n > 1){
        result = result * n;
        n--;
    }
    return result;
}
```

n 2
return value
n 3
return value
n 4
return value

result 12
n 2
return value

May 17
Dr. Regina Berthiaume

Recursive version

Iterative version



Memory Usage

26

```
int factorial (int n){
    int result = 1;
    while (n > 1){
        result = result * n;
        n--;
    }
    return result;
}
```

n 3
return value
n 4
return value

result 4
n 3
return value

May 17
Dr. Regina Berthiaume

Recursive version

Iterative version



Memory Usage

28

```
int factorial (int n){
    int result = 1;
    while (n > 1){
        result = result * n;
        n--;
    }
    return result;
}
```

n 1
return value
n 2
return value
n 3
return value
n 4
return value

result 24
n 1
return value 24

May 17
Dr. Regina Berthiaume

Recursive version

Iterative version



Sequential Search example

29

```
int find(int[] a, int target) {  
    return recursiveFind(a, target, 0);  
}
```

Top-level method
maintains interface
to clients

```
int recursiveFind(int[] a, int target, int pos) {  
    if (pos == a.length)   
        return -1;  
    else if (a[pos] == target)  
        return pos;  
    else  
        return recursiveFind(a, target, pos + 1);  
}
```

Base case 1:
not in array

Base case 2:
found target

Recursive step:
search rest of
array

May 17
Dr. Regina Berretta



Fibonacci Example

31

- The first two numbers in the series are 0 and 1.
- Each remaining number is obtained by taking the sum of the previous two numbers in the series.
- Example: 0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, ...

Definition: $\text{fib}(n) = 0$, when $n = 0$
 $\text{fib}(n) = 1$, when $n = 1$
 $\text{fib}(n) = \text{fib}(n - 1) + \text{fib}(n - 2)$ when $n > 1$

May 17
Dr. Regina Berretta



Sequential Search example

30

34	67	56	41	21	89	13
0	1	2	3	4	5	6

target 41
pos 0 (initially)

recursiveFind(a, 41, 0) ->
 recursiveFind(a, 41, 1) ->
 recursiveFind(a, 41, 2) ->
 recursiveFind(a, 41, 3) ->
 3 <-
 3 <-
 3 <-
 3 <-
Returns

May 17
Dr. Regina Berretta



Fibonacci Example

32


```
int fib (int n)  
{  
    if (n == 0)  
        return 0;  
    else if (n == 1)  
        return 1;  
    else  
        return fib (n - 1)  
            + fib (n - 2);  
}
```

May 17
Dr. Regina Berretta




Tracing `fib(4)` with a Call Tree

33




Tracing `fib(4)` with a Call Tree

35




Tracing `fib(4)` with a Call Tree

34




Tracing `fib(4)` with a Call Tree

36




Tracing `fib(4)` with a Call Tree

37




Tracing `fib(4)` with a Call Tree

39




Tracing `fib(4)` with a Call Tree

38




Tracing `fib(4)` with a Call Tree

40




Tracing `fib(4)` with a Call Tree

41




Tracing `fib(4)` with a Call Tree

43




Tracing `fib(4)` with a Call Tree

42




Tracing `fib(4)` with a Call Tree

44




Tracing $\text{fib}(4)$ with a Call Tree

45



Work Done - Stack Memory


47



Maximum number of activations = The depth of the tree

Tracing $\text{fib}(4)$ with a Call Tree

46



Fibonacci as Algorithm and Process

48

- Fibonacci generates a *tree-recursive process* (processing time grows with the size of the call tree, and memory grows with depth of tree)

Fibonacci with a Loop

49

```
int fib (int n){  
    if (n == 0)  
        return 0;  
    else if (n == 1)  
        return 1;  
    else  
        return fib (n - 1)  
            + fib (n - 2);  
}
```

```
int fib (int n){  
    int a = 1, b = 0;  
    while (n > 0){  
        int temp = a;  
        a = a + b;  
        b = temp;  
        n--;  
    }  
    return b;  
}
```

Your task

51

- Read
 - Lecture slides
 - Chapter 11
- Exercises
 - MyProgrammingLab
 - Computer lab exercises



Recursion or Iteration?

50

- Two ways to solve particular problem:
 - Iteration
 - Recursion
- Iterative control structures use looping to repeat a set of statements.
- Tradeoffs between two options:
 - Sometimes recursive solution is easier.
 - Recursive solution is often slower.