


SENG1110/SENG6110

Object Oriented Programming



Lecture 3

Flow of control – selection



Outline

- Previously...
 - Variables, expressions and operators
 - Input and output
 - The Class String
 - Documentation and Style
 - Examples
- Now...
 - Conditional statements
 - `if` and `if-else`
 - Compare – primitive x class types
 - Type boolean
 - `Switch` statement
 - Java API documentation
 - Program errors
 - Input/Output – TIO and GUI

...attention...😊

- Week 3 is THE WEEK!!!!
- It is **vital** now you start
 - to do a lot of different exercises:
 - From the book
 - Computer lab exercises
- Ask help:
 - PASS
 - Help Desk

Example - SMS cost pseudocode

```
input number_messages;  
total = 10 + 0.22*number_messages  
output total
```

Example – SMS – using TIO input/output

5

```
import java.util.*;
public class SMScost
{
    public static void main (String[] args)
    {
        Scanner console = new Scanner(System.in);

        int count;
        double cost;

        System.out.print("Input No of Messages: ");
        count = console.nextInt();
        cost = 10 + 0.22 * count;
        System.out.print("Total Cost is "+cost);
    }
}
```

Example - SMS Cost modification 1

6

- Suppose that in the SmsCost example you want to include the follow aspect: if the total cost is more than A\$50 then the user will receive a discount of 5%. How to do this?
- Using conditional statement - **if** and **if-else**

if and if-else - syntax

7

```
if (condition)
{
    statement;
    statement;
    ...;
}
```

if and if-else - syntax

8

```
if (condition)
{
    statement;
    statement;
    ...;
}
else
{
    statement;
    statement;
    ...;
}
```

if and if-else - syntax

9

- The braces may be omitted if a single statement follows the if or else

```
if (condition)
    statement;
else
    statement;
```

```
if (condition)
    statement;
else
{
    statement;
    statement;
}
```

avoid

```
if (condition)
{
    statement;
    statement;
}
else
    statement;
```

avoid

SMS cost example 1

10

- Include the follow aspect: if the total cost is more than A\$50 then the user will receive a discount of 5%. How to do this?

```
input number_messages;
total = 10 + 0.22*number_messages
if (total > 50)
{
    total = total*0.95
}
output total
```

SMS cost example 1

11

```
import java.util.*;
public class SMScost
{
    public static void main (String[] args)
    {
        Scanner console = new Scanner(System.in);
        int count;
        double cost;

        System.out.print("Input No of Messages: ");
        count = console.nextInt();
        cost = 10 + 0.22 * count;
        if (cost>50)
            cost = cost*0.95;

        System.out.print("Total Cost is "+cost);
    }
}
```

SMS cost example 1

12

```
import java.util.*;
public class SMScost
{
    public static void main (String[] args)
    {
        Scanner console = new Scanner(System.in);
        int count;
        double cost;

        System.out.print("Input No of Messages: ");
        count = console.nextInt();
        cost = 10 + 0.22 * count;
        if (cost>50)
        {
            cost = cost*0.95;
            System.out.print(" You received a 5% discount ");
        }
        System.out.print("Total Cost is "+cost);
    }
}
```

SMS cost example 2

13

- Suppose that in the SmsCost example you want to include the follow aspect:
 - if the total cost is more than A\$50 then the user will receive a 5% discount.
 - If total cost is less or equal than A\$50 then the discount will be 2%.

SMS cost example 2

14

```
input number_messages;  
totalcost = 10 + 0.22*number_messages  
if (totalcost > 50)  
    totalcost = totalcost*0.95  
else  
    totalcost = totalcost*0.98  
output totalcost
```

SMS cost example 2

15

```
import java.util.*;  
public class SMScost  
{  
    public static void main (String[] args) throws IOException  
    {  
        Scanner console = new Scanner(System.in);  
        int count;  
        double cost;  
  
        System.out.print("Input No of Messages: ");  
        count = console.nextInt();  
        cost = 10 + 0.22 * count;  
        if (cost>50)  
            cost = cost*0.95;  
        else  
            cost = cost*0.98;  
  
        System.out.print("Total Cost is "+cost);  
    }  
}
```

SMS cost example 3

16

- New customer request:
 - Change the SMS program so that it can also compute a more complicated cost formula, eg. If the number of messages is more than 50, then subsequent messages are given a 10% discount.

SMS cost example 3

17

- Pseudocode would be:

```
if (count > 50)
    cost = 10 + 0.22*50 + 0.22*(count-50)*0.9
else
    cost = 10 + 0.22 * count
```

output cost

We could alter the first formula to:

```
10 + 0.22*(50 + (count-50)*0.9)
or      21.0 + (count-50)*0.198
or even 11.1 + count*0.198
```

SMS cost example 3

18

```
import java.util.*;
public class SMScost
{
    public static void main (String[] args)
    {
        Scanner console = new Scanner(System.in);
        int count;
        double cost;

        System.out.print("Input No of Messages: ");
        count = console.nextInt();
        if (count > 50)
            cost = 10 + 0.22*50 + 0.22*(count-50)*0.9;
        else
            cost = 10 + 0.22*count;

        System.out.print("Total Cost is "+cost);
    }
}
```

Introduction to Boolean Expressions

19

- The value of a boolean expression is either

true
or
false

- Examples

```
- time < limit
- balance <= 0
```

Java comparison operators

20

Math Notation	Name	Java Notation	Java Examples
=	Equal to	==	balance == 0 answer == 'y'
≠	Not equal to	!=	income != tax answer != 'y'
>	Greater than	>	expenses > income
≥	Greater than or equal to	>=	points >= 60
<	Less than	<	pressure < max
≤	Less than or equal to	<=	expenses <= income

Compound boolean expressions

21

Name	Java Notation	Java Examples
Logical <i>and</i>	&&	(sum > min) && (sum < max)
Logical <i>or</i>		(answer == 'y') (answer == 'Y')
Logical <i>not</i>	!	!(number < 0)

Mar-17
Dr. Regina Berretta



Boolean Operators

22

- The Effect of the Boolean Operators && (and), || (or), and ! (not) on Boolean values

Value of A	Value of B	Value of A && B	Value of A B	Value of ! (A)
true	true	true	true	false
true	false	false	true	false
false	true	false	true	true
false	false	false	false	true

Mar-17
Dr. Regina Berretta



Boolean expressions - examples

23

Expression	Value	Explanation
!('A' > 'B')	true	Because 'A' > 'B' is false , !('A' > 'B') is true
!(6 <= 7)	false	Because 6 <= 7 is true , !(6 <= 7) is false .
(14 >= 5) && ('A' < 'B')	true	Because (14 >= 5) is true , ('A' < 'B') is true , and true && true is true , the expression evaluates to true .
(24 >= 35) && ('A' < 'B')	false	Because (24 >= 35) is false , ('A' < 'B') is true , and false && true is false , the expression evaluates to false .

Mar-17
Dr. Regina Berretta



Boolean expressions - examples

24

Expression	Value	Explanation
(14 >= 5) ('A' > 'B')	true	Because (14 >= 5) is true , ('A' > 'B') is false , and true false is true , the expression evaluates to true .
(24 >= 35) ('A' > 'B')	false	Because (24 >= 35) is false , ('A' > 'B') is false , and false false is false , the expression evaluates to false .
('A' <= 'a') (7 != 7)	true	Because ('A' <= 'a') is true , (7 != 7) is false , and true false is true , the expression evaluates to true .

Mar-17
Dr. Regina Berretta



Boolean expressions - examples

25

- Examples with operators

	a=1 b=2	a=1 b=4	a=1 b=3	a=6 b=2	a=6 b=4	a=6 b=3	a=5 b=2	a=5 b=3
if ((a>5) && (b<3))	F	F	F	T	F	F	F	F
if ((a>5) (b<3))	T	F	F	T	T	T	T	F
if ((a==5) && (b<3))	F	F	F	F	F	F	T	F
if ((a!=5) (b<3))	T	T	T	T	T	T	T	F
if ((a==5) && (b!=3))	F	F	F	F	F	F	T	F
if ((a!=5) (b!=3))	T	T	T	T	T	T	T	F
if ((a!=5) && (b!=3))	T	T	F	T	T	F	F	F

Mar-17
Dr. Regina Berretta



Example – swap 2 variables – Java code

27

```
import java.util.*;

public class SMSTio {

    public static void main (String[] args) {
        Scanner console = new Scanner(System.in);
        int a,b,aux;

        System.out.print("Input values to a and b ");
        a = console.nextInt();
        b = console.nextInt();
        if (a>b){
            aux=a;
            a=b;
            b=aux;
        }
        System.out.print(" a= "+a+"b="+b);
    }
}
```

Mar-17
Dr. Regina Berretta




Example – swap 2 variables

26

- Read 2 values, a and b, swap 2 variables if a is greater than b

```
input a
input b
if (a>b)
{
    aux=a;
    a=b;
    b=aux;
}
```



- What problems can occur if you don't do the right sequence of these statements?

Mar-17
Dr. Regina Berretta



Nested if

28

```
if (condition)
{
    statement;
    if (condition)
    {
        statement;
        statement;
    }
    else
    {
        statement;
        statement;
    }
}
else
{
    statement;
    statement;
}
```

Mar-17
Dr. Regina Berretta



Nested if - Example

29

- Suppose the code below to decide whether credit is approved:

```
if ( name ok )
    if ( id ok )
        if ( amount ok )
            display credit approved
        else
            display credit denied
    else
        display credit denied
else
    display credit denied
```

Nested if - Example

30

- Here is a more easily readable (and understandable) way to achieve the same thing (note the use of brackets around every Boolean expression):

```
if ( (name ok) && (id ok) && (amount ok) )
    display credit approved
else
    display credit denied
```

- How to rewrite using the boolean expression for

```
if (?????)
    display credit denied
else
    display credit approved
```

Nested if Example

31

```
if(balance > 50000.00)           //Line 1
    interestRate = 0.07;         //Line 2
else if(balance >= 25000.00)     //Line 3
    interestRate = 0.05;         //Line 4
else if(balance >= 1000.00)      //Line 5
    interestRate = 0.03;         //Line 6
else                             //Line 7
    interestRate = 0.00;         //Line 8
```

Nested if Example

32

```
if(score >= 90) System.out.println("The grade is A");
else if(score >= 80) System.out.println("The grade is B");
else if(score >= 70) System.out.println("The grade is C");
else if(score >= 60) System.out.println("The grade is D");
else System.out.println("The grade is F");
```


Nested Statements

33

- Different forms

First Form

```
if (a > b)
{
    if (c > d)
        e = f
}
else
    g = h;
```

Mar-17
Dr. Regina Berretta

Second Form

```
if (a > b)
    if (c > d)
        e = f
    else
        g = h;
```



SMS cost example 4

35

```
input count
if (count >= 0)
{
    if (count > 50)
        cost = 10 + 0.22*50 + 0.22*(count-50)*0.9
    else
        cost = 10 + 0.22 * count
}
else
{
    output error message
}
output cost
```

Mar-17
Dr. Regina Berretta



SMS cost example 4

34

- Is the previous Sms program ok?
- The program accepts negative numbers.
- How to correct this?

Mar-17
Dr. Regina Berretta



SMS cost example 4

36

```
import java.util.*;

public class SMScost {
    public static void main (String[] args){
        Scanner console = new Scanner(System.in);
        int count;
        double cost;
        System.out.print("Input No of Messages: ");
        count = console.nextInt();

        if (count >= 0)
        {
            if (count > 50)
                cost = 10 + 0.22*50 + 0.22*(count-50)*0.9;
            else
                cost = 10 + 0.22*count;
            System.out.print("Total Cost is "+cost);
        }
        else
        {
            System.out.print("Number of messages can't be negative");
        }
    }
}
```

Mar-17
Dr. Regina Berretta



Using ==

37

- == is appropriate for determining if two integers or characters have the same value.

```
if (a == 3)
```

where **a** is an integer type

- == is **not** appropriate for determining if two floating points values are equal. Use < and some appropriate tolerance instead.

```
if (abs(b - c) < epsilon)
```

where **b**, **c**, and **epsilon** are floating point types

Using ==

38

- == is not appropriate for determining if two objects have the same value.
 - if (**s1** == **s2**), where **s1** and **s2** refer to strings, determines only if s1 and s2 refer the a common memory location.
 - If **s1** and **s2** refer to strings with identical sequences of characters, but stored in different memory locations, (**s1** == **s2**) is false.

Using ==

39

- To test the equality of objects of class String, use method **equals**.

```
s1.equals(s2)
```

or

```
s2.equals(s1)
```

- To test for equality ignoring case, use method **equalsIgnoreCase**.

```
("Hello".equalsIgnoreCase("hello"))
```

equals and equalsIgnoreCase

40

- Syntax

```
String.equals(Other_String)
```

```
String.equalsIgnoreCase(Other_String)
```

Testing Strings for Equality

41

Enter two lines of text:

Java is not coffee.

Java is NOT COFFEE.

The two lines are not equal.

The two lines are not equal.

But the lines are equal, ignoring case.

Sample
screen
output

Mar-17
Dr. Regina Berretta



```
import java.util.Scanner;
public class StringEqualityDemo
{
    public static void main (String [] args)
    {
        String s1, s2;
        System.out.println ("Enter two lines of text:");
        Scanner keyboard = new Scanner (System.in);
        s1 = keyboard.nextLine ();
        s2 = keyboard.nextLine ();
        if (s1.equals(s2))
            System.out.println ("The two lines are equal.");
        else
            System.out.println ("The two lines are not equal.");
        if (s2.equals(s1))
            System.out.println ("The two lines are equal.");
        else
            System.out.println ("The two lines are not equal.");
        if (s1.equalsIgnoreCase(s2))
            System.out.println ("But the lines are equal, ignoring case.");
        else
            System.out.println ( "Lines are not equal, even ignoring case.");
    }
}
```

Mar-17
Dr. Regina Berretta



Method `compareTo`

43

- Syntax
`String_1.compareTo(String_2)`
- Method `compareTo` returns
 - a negative number if `String_1` precedes `String_2`
 - zero if the two strings are equal
 - a positive number if `String_2` precedes `String_1`.

Mar-17
Dr. Regina Berretta



Java API Documentation

44

- Java API (application programming interface) Documentation

<http://docs.oracle.com/javase/8/docs/api/>

Mar-17
Dr. Regina Berretta



The Conditional Operator

45

```
if (n1 > n2)
    max = n1;
else
    max = n2;
can be written as
max = (n1 > n2) ? n1 : n2;
```

- The `?` and `:` together are called the *conditional operator* or *ternary operator*.

The Conditional Operator

46

- The conditional operator is useful with print and println statements.

```
System.out.print("You worked " +
    (hours > 1) ? "hours" : "hour");
```

The `exit` Method

47

- Sometimes a situation arises that makes continuing the program pointless.
- A program can be terminated normally by `System.exit(0)`.

The `exit` Method

48

- Example

```
if (numberOfWinners == 0)
{
    System.out.println ("Error: Dividing by zero.");
    System.exit (0);
}
else
{
    oneShare = payoff / numberOfWinners;
    System.out.println ("Each winner will receive $"
        + oneShare);
}
```

The Type `boolean`

49

- The type `boolean` is a primitive type with only two values: `true` and `false`.
- Boolean variables can make programs more readable.

```
if (systemsAreOK)
```

instead of

```
if((temperature <= 100) && (thrust >= 12000)
    && (cabinPressure > 30) && ...)
```

Boolean Expressions and Variables

50

- Variables, constants, and expressions of type `boolean` all evaluate to either `true` or `false`.
- A boolean variable can be given the value of a boolean expression by using an assignment operator.

```
boolean isPositive = (number > 0);
...
if (isPositive) ...
```

Naming Boolean Variables

51

- Choose names such as `isPositive` or `systemsAreOk`.
- Avoid names such as `numberSign` or `systemStatus`.

Short-circuit Evaluation

52

- Sometimes only part of a boolean expression needs to be evaluated to determine the value of the entire expression.
 - If the first operand associated with an `||` is `true`, the expression is `true`.
 - If the first operand associated with an `&&` is `false`, the expression is `false`.

Short-circuit Evaluation

53

- Short-circuit evaluation is not only efficient, sometimes it is essential!
- A run-time error can result, for example, from an attempt to divide by zero.

```
if ((number != 0) && (sum/number > 5))
```

switch Structures

54

```
switch (expression)
{
    case value1: statements1
                break;
    case value2: statements2
                break;
    ...
    case valuen: statementsn
                break;
    default: statements
}
```

- Expression also known as selector
- Expression can be identifier
- Value can only be integral
- The action for each case ends with the word **break**
- Java 7 allows String expressions

switch Statement Example

55

```
switch (grade)
{
    case 'A': System.out.println("The grade is A.");
              break;
    case 'B': System.out.println("The grade is B.");
              break;
    case 'C': System.out.println("The grade is C.");
              break;
    case 'D': System.out.println("The grade is D.");
              break;
    case 'F': System.out.println("The grade is F.");
              break;
    default: System.out.println("The grade is invalid.");
}
```

The **switch** Statement - example

56

Enter number of babies: 1
Congratulations.

Enter number of babies: 3
Wow. Triplets.

Enter number of babies: 4
Unbelievable; 4 babies.

Enter number of babies: 6
I don't believe you.

Sample
screen
output

```
import java.util.Scanner;
public class MultipleBirths
{
    public static void main (String [] args)
    {
        int numberOfBabies;
        System.out.print ("Enter number of babies: ");
        Scanner keyboard = new Scanner (System.in);
        numberOfBabies = keyboard.nextInt ();
        switch (numberOfBabies)
        {
            case 1: System.out.println ("Congratulations.");
                    break;
            case 2: System.out.println ("Wow. Twins.");
                    break;
            case 3: System.out.println ("Wow. Triplets.");
                    break;
            case 4:
            case 5: System.out.print ("Unbelievable; ");
                    System.out.println (numberOfBabies + " babies.");
                    break;
            default: System.out.println ("I don't believe you.");
                    break;
        }
    }
}
Mar-17
Dr. Regina Berretta
```

57

Program Errors

58

- **Syntax errors**
 - Occur when a syntax rule is violated
 - Are detected at compile time.
 - When the Java compiler finds a syntax error, it prints an error message.
- **Example**

```
System.ot.print("Input No of Messages: ");
```

Program Errors

59

- **Run-time errors**
 - Occur when the computer is asked to do something that it considers illegal
 - Example

```
double z, x=1, y=0;
z = x/y;
```
 - An expression depends on the values contained in the variables.
 - The Java run-time environment will print a message telling us the nature of the error and where it was encountered.

Program Errors

60

- **Logic errors** (design errors or bugs)
 - Occur when we fail to express ourselves accurately.
 - The instruction is phrased properly, and thus the syntax is correct.
 - The instruction is meaningful, and thus the semantics are valid.
 - But the instruction does not do what we intended, and thus is logically incorrect.
 - Programming environments do not detect logic errors automatically.

Debugging

61

- A bug is not easy to locate.
- You can try to find the bug(s):
 - Using pencil and paper
 - Using the code, adding extra lines to the program.
 - Using tools available (we will use BlueJ soon in the computer labs)
- Determining if any of the variables deviate from their expected values will highlight the existence of a bug.
- A variables value is printed in the terminal window as follows:

```
System.out.print ("<some message>" + <variable name>);
```

Debugging

62

```
import java.util.*;
public class Value
{
    public static void main (String[] args)
    {
        Scanner console = new Scanner(System.in);
        int x,y,z;

        System.out.print("Please Enter a value for x: ");
        x = console.nextInt();
        System.out.print("Please Enter a value for y: ");
        y = console.nextInt();
        System.out.print("Please Enter a value for z: ");
        z = console.nextInt();

        y = (x+y)/z + x;
        System.out.print("y = " + y);
    }
}
```

Debugging – Example 1

63

- Let's see the logical part

```
System.out.print("Please Enter a value for x: ");
x = console.nextInt();
System.out.print("Please Enter a value for y: ");
y = console.nextInt();
System.out.print("Please Enter a value for z: ");
z = console.nextInt();

y = (x+y)/z + x;
System.out.print("y = " + y);
```

- Suppose you have

	x	y	z
	2	3	2
x+y = 5			
(x+y)/z = 2.5			
(x+y)/z + x = 4.5			

But the program gives 4. Why? How to discover what is happening?

Debugging – Example 1

64

- Modify the code

```
System.out.print("Please Enter a value for x: ");
x = console.nextInt();
System.out.print("Please Enter a value for y: ");
y = console.nextInt();
System.out.print("Please Enter a value for z: ");
z = console.nextInt();

int a = x+y;
System.out.print("a = "+a); -> 5 -> ok

a = a/z; -> 2 -> not ok! What is the problem?
```

- x, y and z need to be **double** and not **int**


Debugging

65

- Many times it is very difficult to find the bug(s).
- You need to examine the code very carefully.
- First step
 - Suppose you have different inputs, then follow the code and determine the expected outputs.
- Second step
 - Run the code, and print the results in each step. See if the program matches with your first step.

GUI - JOptionPane

- An example of GUI – Graphic User Interface



simple GUI

67

```
import javax.swing.JOptionPane
```

- Input

```
String_Variable = JOptionPane.showInputDialog  
(String_Expression);
```
- Output

```
JOptionPane.showMessageDialog  
(null, String_Expression);
```
- The the input and output is **ALWAYS** a String. So you need to convert (ex.: Integer.parseInt)
- `System.exit(0)` ends the program.

Example - SMSTio

68

```
import java.util.*;  
public class SMScost  
{  
    public static void main (String[] args)  
    {  
        Scanner console = new Scanner(System.in);  
  
        int count;  
        double cost;  
  
        System.out.print("Input No of Messages: ");  
        count = console.nextInt();  
        cost = 10 + 0.22 * count;  
        System.out.print("Total Cost is "+cost);  
    }  
}
```

input

output

Example - SMSGui

69

```
import javax.swing.*;

public class SMSGui
{
    public static void main (String[] args)
    {
        int count;
        double cost;
        String str;

        count = Integer.parseInt(JOptionPane.showInputDialog("Input no of
            messages: "));
        cost = 10 + 0.22 * count;
        str = "total cost = "+cost;
        JOptionPane.showMessageDialog(null, str, "SMS cost",
            JOptionPane.INFORMATION_MESSAGE);
    }
}
```

input

output

Mar-17
Dr. Regina Berretta



TIO and GUI

70

- Try to transform TIO to GUI in at least one of the examples in the computer lab this week.
- Ask demonstrators for help

Mar-17
Dr. Regina Berretta



Example - triangle

71

- A triangle has the following properties:
 - No side of a triangle can be greater than the sum of the other two sides.
 - An isosceles triangle has two equal sides.
 - An equilateral triangle has three equal sides.
 - An scalene triangle has three different sides.
- Write a java code that read the three sides of a triangle and check if is a triangle and which type is.
- Try different pseudocodes/Java codes and try to compare them.

Mar-17
Dr. Regina Berretta



Example - salary

72

- Work out in a pseudocode and Java code to calculate the salary in the end of two weeks. You know that:
 - The salary rate is A\$10/hour in the first 40 hours/week and A\$15/hour after 40 hours/week.
 - If the total salary is less than 500, the worker will receive 10% bonus. If the salary is between 500 and 1000, the worker will receive 5% bonus.
- You will do this exercise during your next computer lab

Mar-17
Dr. Regina Berretta



Your task

73

- Read
 - Chapter 3 of the text book
- Explore the Java API documentation
 - <http://docs.oracle.com/javase/8/docs/api/>
- Exercises
 - MyProgrammingLab
 - Implement/compile/run the examples from lecture slides
 - Complete the lab exercises

