

Computer Networks & Internet

A/PROF. DUY NGO

Learning Objectives

1.1 what is the Internet?

1.2 network edge

- end systems,
- access networks,
- Links
- delays

What's the Internet: “Nuts and Bolts” View (1 of 2)



billions of connected computing devices:

- **hosts = end systems**
- running **network apps**



communication links


- fiber, copper, radio, satellite
- transmission rate: **bandwidth**



packet switches: forward packets (chunks of data)

- **routers** and **switches**

What's the Internet: “Nuts and Bolts” View (2 of 2)



“Fun” Internet-Connected Devices



IP picture frame

<http://www.ceiva.com/>



Web-enabled toaster +
weather forecaster



Tweet-a-watt:
monitor energy use



Internet
refrigerator



Slingbox: watch,
control cable TV remotely



sensorized,
bed
mattress



Internet phones

What's the Internet: “Nuts and Bolts” View

Internet: “network of networks”


- Interconnected ISPs

protocols control sending, receiving of messages

- e.g., TCP, IP, HTTP, Skype, 802.11

Internet standards

- RFC: Request for comments
- IETF: Internet Engineering Task Force




What's the Internet: A Service View

infrastructure that provides services to applications:

- Web, VoIP, email, games, e-commerce, social nets, ...

provides programming interface to apps

- hooks that allow sending and receiving app programs to “connect” to Internet
- provides service options, analogous to postal service



What's a Protocol? (1 of 2)

human protocols:

“what’s the time?”

“I have a question”

introductions

... specific messages sent

... specific actions taken when messages received, or other events

network protocols:


machines rather than humans

all communication activity in Internet governed by protocols

protocols define **format, order of messages sent and received** among network entities, and **actions taken** on message transmission, receipt

What's a Protocol? (2 of 2)

A human protocol and a computer network protocol:



Q: other human protocols?

A Closer Look at Network Structure:


network edge:

- hosts: clients and servers
- servers often in data centers

access networks, physical media:
wired, wireless communication links

network core:

- interconnected routers
- network of networks




Access Networks

Q: How to connect end systems to edge router?


- residential access nets
- institutional access networks (school, company)
- mobile access networks

keep in mind:

- bandwidth (bits per second) of access network?
- shared or dedicated?




Access Network: Digital Subscriber Line (DSL) (1 of 2)



Access Network: Digital Subscriber Line (DSL) (2 of 2)


- use **existing** telephone line to central office DSLAM
 - data over DSL phone line goes to Internet
 - voice over DSL phone line goes to telephone net
- < 2.5 Mbps upstream transmission rate (typically < 1 Mbps)
- < 24 Mbps downstream transmission rate (typically < 10 Mbps)

Access Network: Cable Network (1 of 3)



frequency division multiplexing: different channels transmitted in different frequency bands

Access Network: Cable Network (2 of 3)



Access Network: Cable Network (3 of 3)


HFC: hybrid fiber coax

- asymmetric: up to 30Mbps downstream transmission rate, 2 Mbps upstream transmission rate


network of cable, fiber attaches homes to ISP router

- homes **share access network** to cable headend
- unlike DSL, which has dedicated access to central office

Access Network: Home Network



Enterprise Access Networks (Ethernet)



typically used in companies, universities, etc.

10 Mbps, 100Mbps, 1Gbps, 10Gbps transmission rates

today, end systems typically connect into Ethernet switch

Wireless Access Networks (1 of 2)

- shared **wireless** access network connects end system to router
 - via base station aka “access point”

wireless LANs:

- within building (100 meters.)
- 802.11b/g/n/ac (WiFi): 11, 54, 450, 700 Mbps transmission rate




Wireless Access Networks (2 of 2)

wide-area wireless access

provided by telco (cellular) operator, 10's km

between 1 and 100 Mbps

3G, 4G: LTE (Long Term Evolution)



Host: Sends Packets of Data


host sending function:

takes application message

breaks into smaller chunks, known as **packets**, of length **L** bits

transmits packet into access network at **transmission rate R**

- link transmission rate, aka link capacity, aka link bandwidth




$$\text{packet transmission delay} = \frac{\text{time needed to transmit } L\text{-bit packet into link}}{R} = \frac{L(\text{bits})}{R\left(\frac{\text{bits}}{\text{sec}}\right)}$$

The Network Core


mesh of interconnected routers

packet-switching: hosts break application-layer messages into packets

- forward packets from one router to the next, across links on path from source to destination
- each packet transmitted at full link capacity



Packet-Switching: Store-and-Forward (1 of 3)



Packet-Switching: Store-and-Forward (2 of 3)

takes $\frac{L}{R}$ seconds to transmit (push out) L -bit packet into
link at R bps

store and forward: entire packet must arrive at router before it can be
transmitted on next link

end-end delay = $\frac{2L}{R}$ (assuming } more on delay shortly ...
zero propagation delay)

Packet-Switching: Store-and-Forward (3 of 3)


one-hop numerical example:

$$L = 7.5 \text{ Mbits}$$

$$R = 1.5 \text{ Mbps}$$

$$\text{one-hop transmission delay} = L/R = 7.5 \text{ Mbits}/1.5 \text{ Mbps} = 5 \text{ sec}$$

Packet Switching: Queueing Delay, Loss



queueing and loss:

if arrival rate (in bits) to link exceeds transmission rate of link for a period of time:

- packets will queue, wait to be transmitted on link
- packets can be dropped (lost) if memory (buffer) fills up