


```
$ neutron port-create my-net --dns-name my-port
Created a new port:
```

Field	Value
admin_state_up	True
allowed_address_pairs	
binding:vnic_type	normal
device_id	
device_owner	
dns_assignment	{"hostname": "my-port", "ip_address": "192.0.2.67", "fqdn": "my-port.example.org."}
dns_name	my-port
fixed_ips	{"subnet_id": "6141b474-56cd-430f-b731-71660bb79b79", "ip_address": "192.0.2.67"}
id	fb3c10f4-017e-420c-9be1-8f8c557ae21f
mac_address	fa:16:3e:aa:9b:e1
name	
network_id	bf2802a0-99a0-4e8c-91e4-107d03f158ea
port_security_enabled	True
revision_number	1
security_groups	1f0ddd73-7e3c-48bd-a64c-7ded4fe0e635
status	DOWN
tenant_id	d5660cb1e6934612a01b4fb2fb630725

When this functionality is enabled, it is leveraged by the Compute service when creating instances. When allocating ports for an instance during boot, the Compute service populates the **dns_name** attributes of these ports with the **hostname** attribute of the instance, which is a DNS sanitized version of its display name. As a consequence, at the end of the boot process, the allocated ports will be known in the dnsmasq associated to their networks by their instance **hostname**.

The following is an example of an instance creation, showing how its **hostname** populates the **dns_name** attribute of the allocated port:

```
$ openstack server create --image cirros --flavor 42 \
  --nic net-id=37aaff3a-6047-45ac-bf4f-a825e56fd2b3 my_vm
```

Field	Value
OS-DCF:diskConfig	MANUAL
OS-EXT-AZ:availability_zone	
OS-EXT-STS:power_state	0
OS-EXT-STS:task_state	scheduling
OS-EXT-STS:vm_state	building
OS-SRV-USG:launched_at	-
OS-SRV-USG:terminated_at	-
accessIPv4	
accessIPv6	
adminPass	dB45Zvo8Jpfe
config_drive	
created	2016-02-05T21:35:04Z
flavor	m1.nano (42)
hostId	
id	66c13cb4-3002-4ab3-8400-7efc2659c363
image	cirros-0.3.5-x86_64-uec(b9d981eb-d21c-4ce2-9dbc-dd38f3d9015f)
key_name	-
locked	False
metadata	{}
name	my_vm
os-extended-volumes:volumes_attached	[]
progress	0
security_groups	default
status	BUILD
tenant_id	d5660cb1e6934612a01b4fb2fb630725
updated	2016-02-05T21:35:04Z
user_id	8bb6e578cba24e7db9d3810633124525

```
$ neutron port-list --device_id 66c13cb4-3002-4ab3-8400-7efc2659c363
```

id	name	mac_address	fixed_ips
b3ecc464-1263-44a7-8c38-2d8a52751773		fa:16:3e:a8:ce:b8	{"subnet_id": "277eca5d-9869-474b-960e-6da5951d09f7", "ip_address": "203.0.113.8"}, {"subnet_id": "eab47748-3f0a-4775-a09f-b0c24bb64bc4", "ip_address": "2001:db8:10::8"}

```
$ neutron port-show b3ecc464-1263-44a7-8c38-2d8a52751773
```


Field	Value
admin_state_up	True
allowed_address_pairs	
binding:vnic_type	normal
device_id	66c13cb4-3002-4ab3-8400-7efc2659c363
device_owner	compute:None
dns_assignment	{"hostname": "my-vm", "ip_address": "203.0.113.8", "fqdn": "my-vm.example.org."}, {"hostname": "my-vm", "ip_address": "2001:db8:10::8", "fqdn": "my-vm.example.org."}
dns_name	my-vm
extra_dhcp_opts	
fixed_ips	{"subnet_id": "277eca5d-9869-474b-960e-6da5951d09f7", "ip_address": "203.0.113.8"}, {"subnet_id": "eab47748-3f0a-4775-a09f-b0c24bb64bc4", "ip_address": "2001:db8:10::8"}
id	b3ecc464-1263-44a7-8c38-2d8a52751773
mac_address	fa:16:3e:a8:ce:b8
name	
network_id	37aaff3a-6047-45ac-bf4f-a825e56fd2b3
port_security_enabled	True
revision_number	1
security_groups	1f0ddd73-7e3c-48bd-a64c-7ded4fe0e635
status	ACTIVE
tags	[]
tenant_id	d5660cb1e6934612a01b4fb2fb630725


In the above example notice that:

- The name given to the instance by the user, **my_vm**, is sanitized by the Compute service and becomes **my-vm** as the port's **dns_name**.
- The port's **dns_assignment** attribute shows that its FQDN is **my-vm.example.org.** in the Networking service internal DNS, which is the result of concatenating the port's **dns_name** with the value configured in the **dns_domain** parameter in **neutron.conf**, as explained previously.
- The **dns_assignment** attribute also shows that the port's **hostname** in the Networking service internal DNS is **my-vm**.
- Instead of having the Compute service create the port for the instance, the user might have created it and assigned a value to its **dns_name** attribute. In this case, the value assigned to the **dns_name** attribute must be equal to the value that Compute service will assign to the instance's **hostname**, in this example **my-vm**. Otherwise, the instance boot will fail.



[\(https://creativecommons.org/licenses/by/3.0/\)](https://creativecommons.org/licenses/by/3.0/)
Except where otherwise noted, this document is licensed under [Creative Commons Attribution 3.0 License \(https://creativecommons.org/licenses/by/3.0/\)](https://creativecommons.org/licenses/by/3.0/). See all [OpenStack Legal Documents \(http://www.openstack.org/legal\)](http://www.openstack.org/legal).

 FOUND AN ERROR? REPORT A BUG (https://bugs.launchpad.net/neutron/+filebug?field.title=DNS%20integration%20in%20neutron&field.comment=%0A%0A%0Athis%20bug%20tracker%20is%20for%20errors%20with%20the%20documentation%2C%20use%20the%20following%20as%20a%20template%20and%20remove%20or%20add%20fields%20as%20you%20see%20fit.%20convert%20%5B%5D%20into%20%5BX%5D%20to%20check%20boxes.%0A%0A-%20%5B%5D%20this%20doc%20is%20inaccurate%20in%20this%20way%3A%20____%0A-%20%5B%5D%20this%20is%20a%20doc%20addition%20request.%0A%0A-%20%5B%5D%20i%20have%20a%20fix%20to%20the%20document%20that%20i%20can%20paste%20below%20including%20example%3A%20input%20and%20output.%20%0A%0Aif%20you%20have%20a%20troubleshooting%20or%20support%20issue%2C%20use%20the%20following%20resources.%0A%0A-%20ask%20openstack%3A%20http%3A%2F%2Fask.openstack.org%0A-%20the%20mailing%20list%3A%20http%3A%2F%2Flists.openstack.org%0A-%20irc%3A%20%27openstack%27%20channel%20on%20freenode%0A%0A-----%0ARELEASE%3A%202012.0.1.dev11%20on%202018-03-07%2021%3A05%0ASHA%3A%2043df2709acbdce86686a40b75fd34e96880427d0%0ASOURCE%3A%20https%3A%2F%2Fgit.openstack.org%2Fcg%2Fopenstack%2Fneutron%2Ftree%2Fdoc%2Fsource%2Fadmin%2Fconfig-dns-int.rst%0AURL%3A%20https%3A%2F%2Fdocs.openstack.org%2Fneutron%2Fqueens%2Fadmin%2Fconfig-dns-int.html&field.tags=doc)

 QUESTIONS? (<http://ask.openstack.org>)



OpenStack Documentation ▾

Neutron 12.0.1
(../index.html)
Installation Guide (../install/index.html)
OpenStack Networking Guide (index.html)
 Introduction (intro.html)
 Configuration (config.html)
 Deployment examples (deploy.html)
 Operations (ops.html)
 Migration (migration.html)
 Miscellaneous (misc.html)
 Archived Contents (archives/index.html)
Neutron Configuration Options (../configuration/index.html)
Command-Line Interface Reference (../cli/index.html)
Neutron Feature Classification (../feature_classification/index.html)
Contributor Guide (../contributor/index.html)

Page Contents
The Networking service internal DNS resolution

- OpenStack
- [Projects \(http://openstack.org/projects/\)](http://openstack.org/projects/)
 - [OpenStack Security \(http://openstack.org/projects/openstack-security/\)](http://openstack.org/projects/openstack-security/)
 - [Common Questions \(http://openstack.org/projects/openstack-faq/\)](http://openstack.org/projects/openstack-faq/)
 - [Blog \(http://openstack.org/blog/\)](http://openstack.org/blog/)
 - [News \(http://openstack.org/news/\)](http://openstack.org/news/)
- Community
- [User Groups \(http://openstack.org/community/\)](http://openstack.org/community/)
 - [Events \(http://openstack.org/community/events/\)](http://openstack.org/community/events/)
 - [Jobs \(http://openstack.org/community/jobs/\)](http://openstack.org/community/jobs/)
 - [Companies \(http://openstack.org/foundation/companies/\)](http://openstack.org/foundation/companies/)
 - [Contribute \(http://docs.openstack.org/infra/manual/developers.html\)](http://docs.openstack.org/infra/manual/developers.html)
- Documentation