HTML

Day 3

Marquee tag:

The <marquee> tag is used to create scrolling (moving) text or images inside a webpage.

Syntax:

<marquee attribute="value">Scrolling Text</marquee>

Attributes in marquee tag:

1.direction

- Defines the scrolling direction.
- Values: "left" (default), "right", "up", "down".

Example:

<marquee direction="right">Scrolling Right</marquee>

2.behavior

- Defines how the text should scroll.
- Values:
  - "scroll" → (default) scrolls continuously.
  - "slide" → scrolls once, then stops.
  - "alternate" → bounces back and forth.

Example:

```
<marquee behavior="alternate">Bouncing Text</marquee>
```

3.scrollamount

- Defines the speed of scrolling (number of pixels moved per step).

Example:

```
<marquee scrollamount="20">Fast Scrolling</marquee>
```

4.scrolldelay

- Defines the delay (in milliseconds) between each movement.

Example:

```
<marquee scrolldelay="200">Slow Scroll</marquee>
```

5.loop

Defines how many times the marquee should run.

Value: a number (3, 5, etc.) or "infinite" (default).

Example:

```
<marquee loop="3">Scrolls 3 times only</marquee>
```

```html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>
    <h1>Marquee tag</h1>
    <h1>Directions</h1>
    <h2><marquee style="color: white;background-color: red;">Andariki Namaskaram html classes yela unnay??</marquee></h2>
    <h2><marquee direction="right" style="color: white;background-color: orangered;">Students arevery busy with Ganesh chathurdhi celebrations</marquee></h2>
    <h2><marquee direction="left" style="color: white;background-color: orangered;">Students arevery busy with Ganesh chathurdhi celebrations</marquee></h2>
    <h2><marquee direction="up" style="color: white;background-color: orange;">Please concentrate on the topic</marquee></h2>
    <h2><marquee direction="down" style="color: white;background-color: orange;">Please concentrate on the topic</marquee></h2>

    <h1>Behaviours</h1>
    <h2><marquee behavior="alternate" direction="right" style="color: white;background-color: red;">marquee tag directions clear or not</marquee></h2>
    <h2><marquee behavior="scroll" direction="right" style="color: white;background-color: red;">marquee tag directions clear or not</marquee></h2>
    <h2><marquee behavior="slide" direction="right" style="color: white;background-color: red;">marquee tag directions clear or not</marquee></h2>

    <h2><marquee scrollamount="50" style="color: white;background-color: blue;"> this is all about scrollamount</marquee></h2>
    <h2><marquee scrolldelay="20" style="color: white;background-color: blue;"> this is all about scrolldelay</marquee></h2>

    <h2><marquee loop="2">This is only came two times only</marquee></h2>


    <h2><marquee behavior="" direction="left" style="background-color: orangered;color: white;">
        <img src="https://peachmode.com/cdn/shop/articles/bahubali-inspired-ethnics-for-your-traditional-closet-peachmode.jpg?v=1668999039&width=1024" alt="" height="100" widt
        <img src="https://peachmode.com/cdn/shop/articles/bahubali-inspired-ethnics-for-your-traditional-closet-peachmode.jpg?v=1668999039&width=1024" alt="" height="100" widt
        <img src="https://peachmode.com/cdn/shop/articles/bahubali-inspired-ethnics-for-your-traditional-closet-peachmode.jpg?v=1668999039&width=1024" alt="" height="100" widt
</body>
</html>
```

Elements:

Element is nothing but combination of open tag and closing tag along with content

Syntax:

<open tag>content</closing tag>

Example:

<h1>Valibasha Nabeesagari</h1>

Types of elements:

1.Inline elements

2.Block level elements

Inline elements:

- These elements take as much as width its necessary.
- They did not start in new line

- height and width are not affected except for img tag
- margin and padding are applicable only left and right not top and bottom

  ex: button , a , img , formatting tags, span

Block level elements:

- They always start in a new line
- They occupy 100% width
- height and width are affected
- Margin & padding → work in all directions (top, bottom, left, right).

Ex: div, heading tags, p tag, pre tag

Inline block elements:

- Behave like inline (stay in the same line)
- But you can set width and height like a block element

Ex: used in buttons, navigation menus, cards

```html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>
    <button>Login</button>
    <button>Signup</button><br><hr>
    <div>
        <img src="https://content.tupaki.com/en/feeds/2025/03/13/728177-3mpe7jhz.webp" alt="ram" height="120" width="200">
        <img src="https://content.tupaki.com/en/feeds/2025/03/13/728177-3mpe7jhz.webp" alt="ram" height="120" width="200">
    </div><br><hr>
    <a href="">Movies</a>
    <a href="">Webseries</a>
    <a href="">Dramas</a>
</body>
</html>
```

Difference between Div and Span:

Use for big blocks of content (layout/sections).

Use for small inline styling (highlight/word formatting).

Div:

div is a Block level element

Starts on a new line, takes full width

You can set width & height

Span:

Span is a inline element

Stays in the same line, takes only content width

For styling small parts of text or inline elements

Width/height not applied properly unless display:block or inline-block

```html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>
    <div>
        <h2>hii</h2>
        <h4>hello frnds</h4>
    </div>
    <p>he is my <span>friend</span></p>
</body>
</html>
```

hii

hello frnds

he is my friend