HTML

Day 4

HTML Lists:

A list in HTML is a way to group related items together in a structured format using special tags.

Types of Lists in HTML:

1.Ordered list

2.Un Ordered list

3.Definition/Description list

For list item we use <li>item</li> tag

1.Ordered List:

- An ordered list displays items with numbers/letters/roman numerals.
- For Ordered list we use <ol> tag

Attributes in ol tag:

- type
- start
- reversed

Attribute	Description	Example	Output
type	Defines numbering style	<ol type="A">	A, B, C…
	Possible values: "1" (default), "A", "a", "I", "i"		
start	Sets the starting value	<ol start="5">	5, 6, 7…
reversed	Boolean attribute, shows list in descending order	<ol reversed>	3, 2, 1…

```html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>
    <h1>Ordered list</h1>
    <ol>
        <li>Apple</li>
        <li>Banana</li>
        <li>Manago</li>
    </ol>
    <ol type="A">
        <li>Apple</li>
        <li>Banana</li>
        <li>Manago</li>
    </ol>
    <ol type="a">
        <li>Apple</li>
        <li>Banana</li>
        <li>Manago</li>
    </ol>
    <ol type="i">
        <li>Apple</li>
        <li>Banana</li>
        <li>Manago</li>
    </ol>
    <ol type="I">
        <li>Apple</li>
        <li>Banana</li>
        <li>Manago</li>
    </ol>
</body>
</html>
```

Ordered list

1. Apple
2. Banana
3. Manago

A. Apple
B. Banana
C. Manago

a. Apple
b. Banana
c. Manago

i. Apple
ii. Banana
iii. Manago

I. Apple
II. Banana
III. Manago

```html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>
    <h1>Ordered list</h1>
    <ol start="3">
        <li>Ram</li>
        <li>Sita</li>
        <li>Laxman</li>
    </ol>
</body>
</html>
```

Ordered list

3. Ram
4. Sita
5. Laxman

```html
<body>
    <h1>Ordered list</h1>
    <ol>
        <li value="10">Ram</li>
        <li>Sita</li>
        <li>Laxman</li>
    </ol>
</body>
```

Ordered list

10. Ram
11. Sita
12. Laxman

```html
<body>
    <h1>Ordered list</h1>
    <ol reversed>
        <li>Ram</li>
        <li>Sita</li>
        <li>Laxman</li>
    </ol>
</body>
```

Ordered list

3. Ram
2. Sita
1. Laxman

2.Unordered list:

- An unordered list displays items with bullets.
- For unordered list we use <ul> tag

Attributes in Unordered list:

- **type:** defines the list item style

```html
<body>
    <h1>Unordered list</h1>
    <ul>
        <li>Sam</li>
        <li>Ram</li>
        <li>Fam</li>
    </ul>
    <ul type="square">
        <li>Sam</li>
        <li>Ram</li>
        <li>Fam</li>
    </ul>

    <ul type="circle">
        <li>Sam</li>
        <li>Ram</li>
        <li>Fam</li>
    </ul>
</body>
```

Unordered list

- Sam
- Ram
- Fam

- Sam
- Ram
- Fam

- Sam
- Ram
- Fam

3.Definition/Description list:

Used for terms and their descriptions.

<dl> → Description list container

<dt> → Description term

<dd> → Description definition

```html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>
    <h1>Definition/Description list</h1>
    <dl>
        <dt>Html</dt>
        <dd>Hyper text markup language is used to build static structure of web page</dd>
    </dl>
</body>
</html>
```

Definition/Description list

Html

Hyper text markup language is used to build static structure of web page

Anchor tag:(<a>)

- The anchor tag in HTML is used to create hyperlinks.
- It connects one page to another, or one section of a page to another.
- It is written as <a> and closed with </a>.

Attributes in anchor tag:

- **href** → Specifies the URL (web address) or file path to link
  Ex: href=https://google.com
- **target** → Specifies where to open the link.
  - _self → same tab (default).
  - _blank → new tab/window.

title → Shows extra info when you hover the mouse over the link.

```html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Document</title>
</head>
<body>
    <center>
        <h1>Anchor tag</h1>
        <a href="./home.html" target="_self">Home</a>
        <a href="./about.html" target="_blank">About</a>
        <a href="./product.html" target="_parent">products</a>
        <a href="./signin.html" target="_top">Signin</a>

        <a href="" title="71RBatch">Html</a>
    </center>
</body>
</html>
```

Anchor tag

Home About products Signin Html