

git & golang book



Read golang book and work with git



golang book

AN INTRODUCTION TO
PROGRAMMING
IN **GO**



CALEB DOXSEY



git


github account:

[https://github.com/\[yourname\]](https://github.com/[yourname])

example:

<https://github.com/boyone>





Clone go-101

clone go-101 to your workspace:

```
>git clone https://github.com/boyone/go-101.git
```



golang book [1]

make working directory: [windows]

```
>md src\dojo\golang-book
```

make working directory: [linux/Mac]

```
>mkdir -p src/dojo/golang-book
```



golang book [2]

go to golang-book directory:

```
>cd src\dojo\golang-book
```


git init for golang-book directory:

```
>git init
```



golang book [3]

create github repository:



The screenshot shows the GitHub interface for creating a new repository. On the left, a dropdown menu is open, showing options: 'New repository', 'New gist', and 'New organization'. The main form is titled 'Create a new repository' with the subtitle 'A repository contains all the files for your project, including the revision history.' Below this, the 'Owner' is set to 'ajjammy' and the 'Repository name' is 'golang-book', which is marked with a green checkmark. A note below the name field says: 'Great repository names are short and memorable. Need inspiration? How about **refactored-waddle**.' At the bottom, there is a 'Description (optional)' text area.

add remote:

```
>git remote add origin https://github.com/<user>/golang-book.git  
>git remote -v
```



golang book [4]

create README.md file:

```
① README.md x
1  # Go Book
2
3  **Name:** *Chamnan Inta*
4
5  **Nickname:** *Jammy*
6
7  **Job Title:** *Programmer*
8
9  ## Chapter 2
10
11 ## Chapter 3
12
13 ## Chapter 4
```



golang book [5]

git add / git commit :

```
>git add README.md  
>git commit -m "Add README.md file"
```

git push

```
>git push -u origin master
```



golang book [6]

create .gitignore file:

```
.gitignore x
1 *.exe
2 *.DS_Store
```



golang book [7]

git add / git commit :

```
>git add .gitignore  
>git commit -m "Add .gitignore file"
```

git push

```
>git push
```



golang book [8]

1. Read book chapter 2
2. Update README.md
3. Create main.go file at directory golang-book/chapter2-1

```
1  # Go Book
2
3  **Name:** *Chamnan Inta*
4
5  **Nickname:** *Jammy*
6
7  **Job Title:** *Programmer*
8
9  ## Chapter 2
10
11  * chapter2-1 : My First Program
12
13  ## Chapter 3
```

```
1  package main
2
3  import "fmt"
4
5  // this is a comment
6  func main() {
7      fmt.Println("Hello World")
8  }
9
```



golang book [9]

git add / git commit :

```
>git add .  
>git commit -m "Add chapter2-1 My first program"
```

git push

```
>git push
```



add collaborators

ajjammy / golangbook

Unwatch 3 Star 0 Fork 0

Code Issues 0 Pull requests 0 Projects 0 Wiki Insights Settings

Options

- Collaborators**
- Branches
- Webhooks
- Integrations & services
- Deploy keys

Collaborators Push access to the repository

	Thawatchai Jongsuwanpaisan boyone	×
	ployploy	×

Search by username, full name or email address
You'll only be able to find a GitHub user by their email address if they've chosen to list it publicly. Otherwise, use their username instead.

ajjammy

ajjammy Jammy

Add collaborator



Exercise



Read book
Chapter 1 to 4



Create folder chapter<...>-...
Create file main.go
Update README.md file

```
git add  
git commit  
git push
```



Type



GO



golang : type Zero Value

```
package main

import "fmt"

func main() {
    fmt.Println("====Zero Value====")
    var number int
    var str string
    var boolean bool
    fmt.Printf("number: %v\n", number)
    fmt.Printf("str: '%v'\n", str)
    fmt.Printf("boolean: %v\n", boolean)
}
```



golang : type Strings

```
package main

import "fmt"

func main() {
    fmt.Println("====String====")
    backticks := `hello world!,
today's good day.`
    fmt.Println(backticks)

    doubleQuotes := "hello world!,\ntoday's good day."
    fmt.Println(doubleQuotes)
}
```



golang : type Floating point [1]

```
package main

import "fmt"

func main() {
    fmt.Println("====Floating point====")
    third := 1.0 / 3.0
    fmt.Printf("third = %v\n", third)
    fmt.Printf("third + third + third = %v\n", third+third+third)
}
```



golang : type Floating point [2]

```
package main

import "fmt"

func main() {
    fmt.Println("====Comparing floating point====")
    fmt.Println("0.1 + 0.2 == 0.3 is", 0.1+0.2 == 0.3)
    num := 0.1
    num += 0.2
    fmt.Println("num == 0.3 is", num == 0.3)
    fmt.Println("num is", num)
}
```



Variables



GO



golang : Variables [1]

create main.go in folder chapter4-1 :

```
package main

import "fmt"

func main() {

}
```

run -> no error -> push to your git repository



golang : Variables [2]

create main.go in folder chapter4-2 :

```
package main

import "fmt"

func main() {
    fmt.Print("Enter a number: ")
    var input float64
    fmt.Scanf("%f", &input)
    output := input * 2
    fmt.Println(output)
}
```


run -> no error -> push to your git repository




Exercise

Modify main.go in folder chapter4-2 for solve

Problem No.5 of Chapter 4 :




1



2



3



4


run -> no error -> push to your git repository




Exercise

Create main.go in folder chapter4-3 for solve

Problem No.6 of Chapter 4 :



1



2



3



4

run -> no error -> push to your git repository



Conditions



GO



golang : Conditions

create main.go in folder chapter5-1 :

```
package main

import "fmt"

func main() {
    fmt.Println("1")
    fmt.Println("2")
    fmt.Println("3")
    fmt.Println("4")
    fmt.Println("5")
    fmt.Println("6")
    fmt.Println("7")
    fmt.Println("8")
    fmt.Println("9")
    fmt.Println("10")
}
```



golang : Conditions [for]

```
package main

import "fmt"

func main() {
    number := 1
    for number <= 10 {
        fmt.Println(number)
        number = number + 1
    }
}
```



golang : Conditions [if]

create main.go in folder chapter5-2 :

```
package main

import "fmt"

func main() {
    for number := 1; number <= 100; number++ {
        if number%15 == 0 {
            fmt.Println(number, "FizzBuzz")
        } else if number%3 == 0 {
            fmt.Println(number, "Fizz")
        } else if number%5 == 0 {
            fmt.Println(number, "Buzz")
        } else {
            fmt.Println(number)
        }
    }
}
```



golang : Conditions [switch case]

create main.go in folder chapter5-3 :

```
package main

import "fmt"

func main() {
    switch i := 5 {
        case 0:
            fmt.Println("Zero")
        case 1:
            fmt.Println("One")
        case 2:
            fmt.Println("Two")
        case 3:
            fmt.Println("Three")
        case 4:
            fmt.Println("Four")
        case 5:
            fmt.Println("Five")
        default:
            fmt.Println("Unknown Number")
    }
}
```



Exercise

create exercise.go in folder chapter5-4 :

โปรแกรมจะให้ใส่ตัวเลขได้ไม่เกิน 5 ครั้ง

ถ้าเจอตัวเลขที่สุ่มมาจะแสดงคำว่า เจอแล้ว และจบการทำงาน

ถ้าเลขที่ใส่มากกว่าจะแสดงคำว่า มากไป

ถ้าเลขที่ใส่น้อยกว่าจะแสดงคำว่า น้อยไป

ถ้าใส่เกิน 5 ครั้งจะแสดงคำว่า เกินพอ และจบการทำงาน



1



2



3



4

run -> no error -> push to your git repository



function



GO



golang : function

```
package main

func main() {
}

func f() {
}

func fWithReturn(i int) int {
    return i
}

func fWithMultipleReturn(i int, s string) (int, error) {
    return i, nil
}
```



golang : function

create main.go in folder chapter6-1 :


```
package main

import "fmt"

func main() {
    fmt.Println(f1())
}

func f1() int {
    return f2()
}

func f2() int {
    return 1
}
```



golang : function

create main.go in folder chapter6-2 :

```
package main

import "fmt"

func main() {
    fmt.Println(f2())
}

func f2() (r int) {
    r = 1
    return
}
```

Return types can have names



golang : function

create main.go in folder chapter6-3 :

```
package main

import "fmt"

func main() {
    x, y := f()
    fmt.Println(x, y)
}

func f() (int, int) {
    return 5, 7
}
```

Multiple values can be returned



golang : function

create main.go in folder chapter6-4 :

```
package main

import "fmt"

func main() {
    fmt.Println(add(1,2,3))

    xs := []int{1,2,3}
    fmt.Println(add(xs...))
}

func add(args ...int) int {
    total := 0
    for _, v := range args {
        total += v
    }
    return total
}
```

Variadic Function




Exercise

create exercise.go in folder chapter6-5 :

REFACTOR FIZZBUZZ ใน CHAPTER5-2

ให้เรียกใช้งาน FUNCTION

แทนที่จะทำงานทุกอย่างใน FUNC MAIN



1



2



3



4

run -> no error -> push to your git repository




Collections:

Arrays, Slices, Map



golang : collections



```
func main() {  
    var x [5]int // array  
    var x []int // slice  
    var x map[string]int // map  
}
```



golang : arrays

create main.go in folder chapter7-1 :

```
package main

import "fmt"

func main() {
    var x [5]int
    x[3] = 4
    fmt.Println(x)

    x = [5]int{1, 2, 3, 4, 5}
    fmt.Println(x)

    y := [...]int{1, 2, 3, 4, 5, 6, 7, 8, 9, 0}
    fmt.Println(y)
}
```



golang : slice

create main.go in folder chapter7-2 :

```
package main

import "fmt"

func main() {
    slice := make([]int, 3)
    slice[0] = 1
    slice[1] = 2
    slice[2] = 3

    fmt.Println(slice)

    slice2 := []int{1, 2, 3, 4, 5}
    fmt.Println(slice2)

    fmt.Println("Slice with length and capacity")
    fmt.Printf("slice: length %v, capacity %v, %v\n", len(slice), cap(slice), slice)

    // append
    for i := 4; i < 15; i++ {
        slice = append(slice, i)
    }
    fmt.Printf("slice: length %v, capacity %v, %v\n", len(slice), cap(slice), slice)
}
```



golang : slice

create main.go in folder chapter7-3 :

```
package main

import "fmt"

func main() {
    arr := [5]int{1, 2, 3, 4, 5}
    fmt.Println(arr)

    slice := arr[0:3]
    fmt.Println(slice)
}
```

Create slice from array



golang : slice

create main.go in folder chapter7-4 :

```
package main

import "fmt"

func main() {
    slice := []int{1, 2, 3}
    fmt.Println(slice)
    newSlice := make([]int, 2)
    fmt.Println(newSlice)
    copy(slice, newSlice)
    fmt.Printf("slice: %v\n", slice)
    fmt.Printf("slice: %v\n", newSlice)
}
```

Copy slices



golang : map

create main.go in folder chapter7-5 :

```
package main

import "fmt"

func main() {
    var x map[string]int
    x = make(map[string]int)
    x["key"] = 10
    fmt.Println(x)
    fmt.Println(x["key"])

    y := map[string]int{
        "one": 1,
        "two": 2,
        "three": 3,
    }
    fmt.Println(y)
}
```



golang : map

create main.go in folder chapter7-6 :

```
package main

import "fmt"

func main() {
    x := map[string]int{
        "one": 1,
        "two": 2,
        "three": 3,
    }
    fmt.Println(x)

    delete(x, "two")
    fmt.Printf("After delete: %v\n", x)
}
```

Delete map



golang : map

create main.go in folder chapter7-7 :

```
package main

import "fmt"

func main() {
    mymap := make(map[int]int)
    mymap[1] = 1
    mymap[2] = 2

    fmt.Println(mymap[3])
    if mymap[3] != 0 {
        fmt.Println(mymap[3])
    }

    // ok?
    if value, ok := mymap[3]; ok {
        fmt.Println(value)
    }
}
```

Avoid to check zero value



golang : range and collections

create main.go in folder chapter7-8 :

```
package main

import "fmt"

func main() {
    numbers := [5]int{1, 2, 3, 4, 5}
    for i := 0; i < len(numbers); i++ {
        fmt.Println(i, numbers[i])
    }
    fmt.Println("With Range")
    for i, number := range numbers {
        fmt.Println(i, number)
    }
}
```

Range: Array



golang : range and collections

create main.go in folder chapter7-9 :

```
package main

import "fmt"

func main() {
    slice := []int{1, 2, 3, 4, 5}
    for i, number := range slice {
        fmt.Println(i, number)
    }
}
```

Range: Slice



golang : range and collections

create main.go in folder chapter7-10 :

```
package main

import "fmt"

func main() {
    maps := map[string]int{
        "one": 1,
        "two": 2,
        "three": 3,
    }

    for key, number := range maps {
        fmt.Println(key, number)
    }
}
```

Range: Map



golang : range and collections

create main.go in folder chapter7-11 :

```
package main

import "fmt"

func main() {
    for i, c := range "golang" {
        fmt.Println(i, c)
        fmt.Printf("%v\n", string(c))
    }
}
```

Range: String




Exercise

create exercise.go in folder chapter6-5 :

REFACTOR FIZZBUZZ ใน CHAPTER5-2

โดยใช้ TYPE ประเภท COLLECTION ของ GO
มาแทนที่เพื่อลด DUPLICATION ใน CODE



1



2



3



4

run -> no error -> push to your git repository



Sum up

Type: string, int, float, bool

Operation: string: +
int, float: +, -, *, /, %

convert: string: string(**rune**), string(**int**)
int: int(**rune**), int(**str**)
strconv.**Atoi(str)**, strconv.**Itoa(num)**

collection: array, slice, map

Operation: slice: append(slice, value)



Sum up

control structure: if, for

example: for {...}

for i:=0; i < len; i++ {...}

for index, value := **range** collection {...}

for index, value := **range** string {...}

fmt:

example: fmt.Printf("%v %t %d %f %s", num, num, num, float, str)

fmt.Println(num, num, num, float, str)

fmt.Sprintf("%v %t %d %f %s", num, num, num, float, str)



Exercise

create console-weather.go in folder exercise :

แสดงผลอุณหภูมิผ่าน TERMINAL โดยมีรูปแบบดังนี้

```
  _  _  
  ||  |  
  _  _ | c  
Bangkok few cloud  
  
  _  _ | c  
  ||  |  
  _  _ | c  
Tak sunny  
  
  _  _ | c  
  ||  |  
  _  _ | c  
Phuket rainy  
  
  _  _ | c  
  ||  |  
  _  _ | c  
Chiang-mai cold
```

```
func main() {  
    fmt.Println(weatherCelsius(25, "Bangkok few cloud"))  
    fmt.Println(weatherCelsius(34, "Tak sunny"))  
    fmt.Println(weatherCelsius(17, "Phuket rainy"))  
    fmt.Println(weatherCelsius(9, "Chiang-mai cold"))  
}
```

run -> no error -> push to your git repository



Pointers



Pointer

value , & and *

```
func foo(number int) {}  
func bar(number *int) {}
```

Parameters in Go are always passed by value,
and a copy of the value being passed is made.



golang : pass by copy value

create main.go in folder chapter8-1 :

```
func main() {  
    amount := 5  
    double(amount)  
    fmt.Printf("original %v\n", amount)  
}  
  
func double(number int) {  
    number *= 2  
    fmt.Println(number)  
}
```



golang : pass by pointer

create main.go in folder chapter8-2 :

```
func main() {  
    amount := 5  
    double(&amount)  
    fmt.Printf("original %v\n", amount)  
}  
  
func double(number *int) {  
    *number *= 2  
    fmt.Println(*number)  
}
```

When you pass a pointer, the pointer value will be copied and passed.



golang : pass by array value

create main.go in folder chapter8-3 :

```
func main() {  
    array := [3]int{1, 2, 3}  
    double(array)  
    fmt.Printf("origin addr %p\n", &array)  
    fmt.Printf("original %v\n", array)  
}  
  
func double(nums [3]int) {  
    fmt.Printf("double addr %p\n", &nums)  
    for i := range nums {  
        nums[i] *= 2  
    }  
    fmt.Println(nums)  
}
```



golang : pass by array pointer

create main.go in folder chapter8-4 :

```
func main() {  
    array := [3]int{1, 2, 3}  
    double(&array)  
    fmt.Printf("origin addr %p\n", &array)  
    fmt.Printf("original %v\n", array)  
}  
  
func double(nums *[3]int) {  
    fmt.Printf("double addr %p\n", nums)  
    fmt.Printf("double value %v\n", *nums)  
    for i := range *nums {  
        nums[i] *= 2  
    }  
    fmt.Println(*nums)  
}
```



golang : pass by slice value

create main.go in folder chapter8-5 :

```
func main() {  
    slice := []int{1, 2, 3}  
    double(slice)  
    fmt.Printf("origin addr %p\n", slice)  
    fmt.Printf("original %v\n", slice)  
}  
  
func double(nums []int) {  
    fmt.Printf("double addr %p\n", nums)  
    for i := 0; i < len(nums); i++ {  
        nums[i] *= 2  
    }  
    fmt.Println(nums)  
}
```



golang : pass by map value

create main.go in folder chapter8-6 :

```
func main() {  
    m := map[int]int{1:1, 2:2, 3:3,}  
    double(m)  
    fmt.Printf("origin addr %p\n", m)  
    fmt.Printf("original %v\n", m)  
}  
  
func double(nums map[int]int) {  
    fmt.Printf("double addr %p\n", nums)  
    for i := range nums {  
        nums[i] *= 2  
    }  
  
    fmt.Println(nums)  
}
```




Type



golang : struct type

create main.go in folder chapter9-1 :




```
type Circle struct {  
    x float64  
    y float64  
    r float64  
}  
  
func main() {  
    var c Circle  
    fmt.Printf("c type: %T\n", c)  
    fmt.Println(c.x, c.y, c.r)  
  
    c1 := new(Circle)  
    fmt.Printf("c1 type: %T\n", c1)  
    fmt.Println(c1.x, c1.y, c1.r)  
}
```



golang : struct type

create main.go in folder chapter9-1 :




```
func main() {  
    .  
    .  
  
    c2 := Circle{x: 0, y: 0, r: 5}  
    fmt.Printf("c2 type: %T\n", c2)  
    fmt.Println(c2.x, c2.y, c2.r)  
  
    c3 := NewCircle(1, 2, 3)  
    fmt.Printf("c3 type: %T\n", c3)  
    fmt.Println(c3.x, c3.y, c3.r)  
}  
  
func NewCircle(x, y, r float64) *Circle {  
    return &Circle{x, y, r}  
}
```



golang : specific type

create main.go in folder chapter9-2 :



```
type Zipcode string

func main() {
    zipcode := Zipcode("11000")
    if zipcode.valid() {
        fmt.Println(zipcode)
    }
}

func (z Zipcode) valid() bool{
    return true
}
```



Method




GO



golang : method

create main.go in folder chapter10-1 :




```
type Circle struct {  
    x float64  
    y float64  
    r float64  
}  
  
func (c Circle) area() float64 {  
    return math.Pi * c.r * c.r  
}  
  
func (c *Circle) changeRedius(r float64) {  
    c.r = r  
}
```



golang : method

create main.go in folder chapter10-1 :



```
func main() {  
    littleC := Circle{0, 0, 5}  
    fmt.Println("littleC", littleC.area())  
    littleC.changeRadius(10)  
    fmt.Println("littleC", littleC.area())  
  
    bigC := &Circle{0, 0, 5}  
    fmt.Println("bigC", bigC.area())  
    bigC.changeRadius(10)  
    fmt.Println("bigC", bigC.area())  
}
```



Interface



GO



golang : interface

create main.go in folder chapter11-1 :

```
type Rectangle struct {  
    w float64  
    h float64  
}  
  
func (r Rectangle) area() float64 {  
    return r.w * r.h  
}  
  
type Circle struct {  
    x float64  
    y float64  
    r float64  
}  
  
func (c *Circle) area() float64 {  
    return math.Pi * c.r * c.r  
}
```



golang : interface

create main.go in folder chapter11-1 :

```
type measure interface {  
    area() float64  
}  
  
func printArea(m measure) {  
    fmt.Println(m.area())  
}  
  
func main() {  
    c := &Circle{0, 0, 5}  
    printArea(c)  
  
    r := Rectangle{3, 4}  
    printArea(r)  
}
```



Exercise

create vending-machine.go in folder exercise :



Vending Machine

Coin: TEN(10), Five(5), TWO(2), ONE(1)
T F TW 0

Item: Soft Drink(18),
Canned Coffee(12),
Drinking Water(7)

Coin Return: returns all inserted money

#Criteria

Unlimited items

Unlimited change

Currently inserted money

run -> no error -> push to your git repository



Exercise

vending-machine: Test Cases



1. Buy SD(soft drink) with exact change

Insert: T, F, TW, 0

Currently inserted money: 18

Choose: Select SD

Return: SD

2. Start adding change but hit coin return

Insert: T, T, F

Currently inserted money: 25

Choose: Coin Return

Return: T, T, F

3. Buy CC(canned coffee) without exact change

Insert: T, T

Currently inserted money: 20

Choose: Select CC

Return: CC, F, TW, 0

run -> no error -> push to your git repository



Exercise

vending-machine:



```
func main() {  
    vm := NewVendingMachine(coins, items)  
  
    // Buy SD(soft drink) with exact change  
    vm.InsertCoin("T")  
    vm.InsertCoin("F")  
    vm.InsertCoin("TW")  
    vm.InsertCoin("O")  
    fmt.Println("Inserted Money:", vm.GetInsertedMoney())  
    // 18  
    can := vm.SelectSD()  
    fmt.Println(can) // SD  
    .  
    .  
    .  
}
```

run -> no error -> push to your git repository



Exercise

vending-machine:



```
func main() {  
    vm := NewVendingMachine(coins, items)
```

```
    .  
    .  
    .  
    // Buy CC(canned coffee) without exact change  
    vm.InsertCoin("T")  
    vm.InsertCoin("T")  
    fmt.Println("Inserted Money:", vm.GetInsertedMoney())  
    // 20  
    can = vm.SelectCC()  
    fmt.Println(can) // CC, F, TW, 0  
    .  
    .  
    .  
}
```

run -> no error -> push to your git repository



Exercise

vending-machine:



```
func main() {  
    vm := NewVendingMachine(coins, items)
```

```
    .  
    .  
    .  
    // Start adding change but hit coin return  
    vm.InsertCoin("T")  
    vm.InsertCoin("T")  
    vm.InsertCoin("F")  
    fmt.Println("Inserted Money:", vm.GetInsertedMoney())  
    // 25  
    change := vm.CoinReturn()  
    fmt.Println(change) // T, T, F  
}
```

run -> no error -> push to your git repository



Exercise

vending-machine:



```
func main() {  
    vm := NewVendingMachine(coins, items)
```

```
    // Buy SD(soft drink) with exact change
```

```
    vm.InsertCoin("T")
```

```
    vm.InsertCoin("F")
```

```
    vm.InsertCoin("TW")
```

```
    vm.InsertCoin("O")
```

```
    fmt.Println("Inserted Money:", vm.GetInsertedMoney()) // 18
```

```
    can := vm.SelectSD()
```

```
    fmt.Println(can) // SD
```

```
    // Buy CC(canned coffee) without exact change
```

```
    vm.InsertCoin("T")
```

```
    vm.InsertCoin("T")
```

```
    fmt.Println("Inserted Money:", vm.GetInsertedMoney()) // 20
```

```
    can = vm.SelectCC()
```

```
    fmt.Println(can) // CC, F, TW, O
```

```
    // Start adding change but hit coin return
```

```
    vm.InsertCoin("T")
```

```
    vm.InsertCoin("T")
```

```
    vm.InsertCoin("F")
```

```
    fmt.Println("Inserted Money:", vm.GetInsertedMoney()) // 25
```

```
    change := vm.CoinReturn()
```

```
    fmt.Println(change) // T, T, F
```

```
}
```

