Suica 2.0 for JavaScript

<script src="**suica.js**"></script>

boytchev.github.io/suica
version 1

BASIC OBJECTS

circle (center, size, color)
cone (center, size, color)
cube (center, size, color)
cylinder (center, size, color)
line (center/from, to, color)
point (center, size, color)
polygon (count, center, size, color)
prism (count, center, size, color)
pyramid (count, center, size, color)
sphere (center, size, color)
square (center, size, color)

BASIC PROPERTIES

.center = [**.x**, **.y**, **.z**]
.color = "colorname" / 0xFFFFFF / [r,g,b]$^{0...1}$
= **rgb** (r,g,b)^{255} / **hsl** (h^{360},s^{100},l^{100})
.count = count / [count, count]
.image = drawing / "filename" / **image** ("filename")
.images = .count / [count, count]
.size = width / [**.width**, **.height**, **.depth**]
.spin = spinH / [**.spinH**, **.spinV**, **.spinT**, **.spinS**]
.visible / **.hidden** = true / yes / false / no
.wireframe = true / yes / false / no

SUICA

background (color)
oxyz (size, color)
demo (distance, altitude, speed)
orbit (distance, altitude, speed)
lookAt (from, to, up)
perspective (near, far, fov)
orthographic (near, far)
fullWindow ()
fullScreen ()
stereo (distance)
anaglyph (distance)
vr ()
capture (filename, time, fps, format, skipframes)
SUICA_VERSION, SUICA_DATE

MISC

its
obj.**clone**
obj.**style** ({name: value, ...})
allObjects ()
findPosition (event)
findObject (event, interactive)
findObject (event, [object, ...])
findObjects (event, interactive)
findObjects (event, [object, ...])
objectPosition (local)
screenPosition (local, global)
radians (degrees)
degrees (radians)
random (from, to)
random ([value,...])
randomIn (object)
randomOn (object)

ADVANCED OBJECTS

construct (expression, size, color)
convex (src^{2}, size, color)
group (object, object, ...)
.add (object, object, ...)
model (filename, center, size)
model.save (filename, [object, object, ...])
surface (center, curve^{3}, count, size, color)
text3d (text, font$^{!}$, center, size, color)
tube (center, curve^{2}, radius, count, size, color)
extrude (shape, center, size, color)
.radius .offset .count$^{!,2}$
spline (src^{2}, closed, interpolating)
(src^{5}, param, param)
splane (src^{3}, closed$^{!,2}$, interpolating$^{!,2}$)
(src^{4}, param, param)

ADVANCED PROPERTIES

.closed = bool$^{!}$ / [bool, bool]^{2}
.curve^{2} = [point, ...] / spline / f(u)
^{3} = [[point, ...], ...] / splane / f(u,v)
.expression = "string" A+B, A-B, A*B, (...)
.font$^{!}$ = "fontname.json"
.interpolating = bool$^{!}$ / [bool, bool]^{2}
.src = [point, ... point]^{2} / f(u)^{5}
= [[point, ...], ... [point, ...]]^{3} / f(u,v)^{4}
.vertices
.threejs = THREE.Mesh
.material = THREE.Material
.geometry = THREE.BufferGeometry
.intersectData
.randomIn
.randomOn

EVENTS

onPointerEnter, **onPointerLeave**, **onPointerMove**, **onPointerDown**, **onPointerUp**, **onClick**, **onTime**, **onLoad**

obj.**addEventListener** (eventName, eventHandler)
obj.**removeEventListener** (eventName)
obj.eventName = eventHandler

function pointerEventHandler (event) { ... }
function timeEventHandler (time, dTime) { ... }
function loadEventHandler (object) { ... }

proactive ()

DRAWINGS & SHAPES

drawing (width, height, color)
shape (count)
moveTo (x, y, x, y, ...)
lineTo (x, y, x, y, ...)
curveTo (m$_x$, m$_y$, x, y)
arc (x, y, radius, from, to, cw)
shapes
stroke (color, width, closed)
fill (color)
fillText (x, y, text, color, font)
"bold 20px Courier"
clear (color)

LMS

scorm
.api, **.score**, **.studentName**, **.getValue** (value) **.setValue** (name, value), **.derandomize** (seed)

Suica 2.0 for HTML

<script src="**suica.js**"></script>

boytchev.github.io/suica
version 1

BASIC OBJECTS

<**circle** center size color ...>
<**cone** center size color ...>
<**cube** center size color ...>
<**cylinder** center size color ...>
<**line** center/from to color ...>
<**point** center size color ...>
<**polygon** count center size color ...>
<**prism** count center size color ...>
<**pyramid** count center size color ...>
<**sphere** center size color ...>
<**square** center size color ...>
<... id spin image images wireframe>

BASIC PROPERTIES

center = "**x**, **y**, **z**"
color = "colorname" / "0xFFFFFF", "r,g,b"[1]
= "**rgb** (r,g,b)"[255] / "**hsl** (h[360],s[100],l[100])"
count = "count" / "count, count"
id = "string"
image = "drawing" / "filename"
images = "count" / "count, count"
size = "width" / "**width**, **height**, **depth**"
spin = "spinH" / "**spinH**, **spinV**, **spinT**, **spinS**"
visible / **hidden** = "bool"
wireframe = "bool"

SUICA

<**suica** width height background orientation proactive perspective orthographic fullWindow fullScreen stereo anaglyph vr> ... </**suica**>
<**background** color>
<**oxyz** size color>
<**demo** distance altitude speed>
<**orbit** id distance altitude speed>
<**lookAt** from to up>
<**perspective** near far fov>
<**orthographic** near far>
<**fullWindow**>
<**fullScreen**>
<**stereo** distance>
<**anaglyph** distance>
<**vr**>
<**capture** filename time fps format skipframes>

DRAWINGS & SHAPES

<**drawing** size color>
<**shape** count>
<**moveTo** point>
<**lineTo** point>
<**curveTo** m point>
<**arc** point radius from to cw>
<**stroke** color width closed>
<**fill** color>
<**fillText** point text color font>
<**clear** color>

shapes

point="x, y" or **x**="x" **y**="y"
font="bold 20px Courier"

ADVANCED OBJECTS

<**clone** src[1] center size color ...>
<**construct** expression center size color>
<**convex** src[2] size color ...>
<**group** center size color ...> ... </**group**>
<**model** filename center size ...>
<**surface** center curve[3] count size color ...>
<**text3d** text font[1] center size color ...>
<**tube** center curve[2] radius count size color ...>
<**extrude** shape center size color radius offset count[1,2]>
<**splane** src[2,5] closed[1] interpolating[1]>
<**splane** src[3,4] closed[1,2] interpolating[1,2]>
<... id spin image images wireframe>

ADVANCED PROPERTIES

closed = "bool"[1] / "bool, bool"[2]
curve[2] = "point; ..." / "spline" / "func(u)"
[3] = "point; ... | ... " / "splane" / "func(u,v)"
expression = "string" A+B, A-B, A*B, (...)
font[1] = "fontname.json"
interpolating = "bool"[1] / "bool, bool"[2]
src = "id"[1] / "point; ..."[2] / "func(u)"[5]
= "point; ... | ..."[3] / "func(u,v)"[4]

interpolating vs **approximating**
closed vs **open**, **cw** vs **ccw**

EVENTS

onPointerEnter, **onPointerLeave**, **onPointerMove**, **onPointerDown**, **onPointerUp**, **onClick**, **onTime**, **onLoad**

<tag ... eventName="eventHandler">

<**proactive**>