

POWER OASIS™ CORE

Overbuilt. On purpose

- **4,800 Wh** — run a 1kW load for 3.5 hours
- **<20 ms UPS transfer** — equipment never sees the outage
- **35A built-in charger** — full recharge in under 3 hours
- **VRM cloud portal** — monitor your whole fleet remotely

4,800 Wh	3,000	<20	35	~220
Wh	VA / 120V	ms[1]	A built-in	lbs[2]
GROSS ENERGY	AC OUTPUT	UPS TRANSFER	CHARGER	CART WEIGHT

RUNTIME AT LOAD

Load	Runtime	Battery Stress (C-Rate)	Typical Application
250W	14h 17m	0.06C — minimal	LED lighting · laptops · phones
500W	7h 08m	0.11C — minimal	Workstation · monitors · networking
1,000W	3h 34m	0.22C — light	Construction tools · event AV
1,500W	2h 22m	0.34C — light	Heavy tools · broadcast
2,400W	1h 29m	0.54C — moderate	Rated continuous ceiling

At 80% depth of discharge · 92% inverter efficiency. The battery never exceeds 54% of its rated discharge limit — engineered for full cycle life.

KEY SPECIFICATIONS

Energy capacity	**4,800 / 4,320**	Wh	*Gross / usable AC (80% DoD × 93% eff)*
Inverter / charger	**48/3000**		*sine · UL 1741 listed*
AC output	**3,000 VA · 5,500 W surge**		*120V 60Hz ±0.1% · THD <3%*
UPS transfer	**<20 ms**		*Inverter synchronized to grid — no dropout*
Battery	**48V 100Ah LiFePO4**		*No thermal runaway · BMS protected*
Recharge	**~2.9 hrs**		*35A integrated charger · any 20A outlet*

Outlets	**4 positions (4 duplex)**		*NEMA 5-20R commercial grade[3]*
USB / 12V	**2× USB-C 100W PD · 2× USB-A · 12V**		*Max 1× USB-C 100W active*
Enclosure			
Display	**7" touchscreen**		*IP54 · VRM cloud · WiFi · BT · Ethernet*
Operating temp	**−20 to +40 °C**		*Derates above 40°C*
Protection	**125A DC breaker · 300A disconnect**		*Resettable · LOTO-capable*

ADDITIONAL SPECIFICATIONS

Complementing the key specifications on page 1

Surge capacity	**5,500**	W	*2-second peak*
AC input range	**90–140**	V AC	*Wall · generator · shore*
Charge voltages	**57.6 / 55.2**	V DC	*Absorption / float LiFePO4*
Efficiency	**~93**	%	*At rated load*
Max discharge rate	**0.46C**		*46% headroom · FN2010 EMI filter*

Battery weight	**~85**	lbs	*Estimated — vendor TBD*
Casters	**4× total-lock**		*Polyurethane · non-marking*
Cooling	**1× 120mm fan**		*Noctua IP52 · GX relay control*
Remote config	**VEConfigure**		*Via MK3-USB or VRM remote*
Communication	**VE.Bus + BMS-CAN**		*DVCC · <45 dBA est. noise*

CERTIFICATIONS & COMPLIANCE

Certification program in progress — status shown per standard

Standard	Scope	Status
UL 1741 · UL 1107	Inverter · DC disconnect	Components listed (MultiPlus-II · Blue Sea 6006)
UL 1973 · FCC 15	Battery · emissions	Targets — vendor confirmation and pre-compliance testing in progress
NEC 590.6 · NFPA 99	Site / medical use	Via optional Construction or Medical Modules

WARRANTY & SUPPORT

Coverage	Details
Warranty	
Support	VRM cloud diagnostics · field-serviceable by any qualified electrician · production timeline TBA

⚠ IMPORTANT NOTICES

• CONCEPT STAGE — specs preliminary · not for production · not for medical/OR use without Medical Module + NFPA 99 compliance · UPS Function factory-enabled.

Ready to see the Core in action?