

```
import keras
keras.__version__

'2.4.3'
```

```
from google.colab import drive
drive.mount('/content/gdrive')
```

Mounted at /content/gdrive

```
from keras.applications import VGG16
```

```
conv_base = VGG16(weights='imagenet',
                    include_top=False,
                    input_shape=(150, 150, 3))
```

📄 Downloading data from https://storage.googleapis.com/tensorflow/keras-applications/vgg16/vgg16_weights_tf_dim_ordering_tf_data_format.h5
58892288/58889256 [=====] - 0s 0us/step

```
conv_base.summary()
```

Model: "vgg16"

Layer (type)	Output Shape	Param #
input_1 (InputLayer)	[(None, 150, 150, 3)]	0
block1_conv1 (Conv2D)	(None, 150, 150, 64)	1792
block1_conv2 (Conv2D)	(None, 150, 150, 64)	36928
block1_pool (MaxPooling2D)	(None, 75, 75, 64)	0
block2_conv1 (Conv2D)	(None, 75, 75, 128)	73856
block2_conv2 (Conv2D)	(None, 75, 75, 128)	147584
block2_pool (MaxPooling2D)	(None, 37, 37, 128)	0
block3_conv1 (Conv2D)	(None, 37, 37, 256)	295168
block3_conv2 (Conv2D)	(None, 37, 37, 256)	590080
block3_conv3 (Conv2D)	(None, 37, 37, 256)	590080
block3_pool (MaxPooling2D)	(None, 18, 18, 256)	0

block4_conv1 (Conv2D)	(None, 18, 18, 512)	1180160
block4_conv2 (Conv2D)	(None, 18, 18, 512)	2359808
block4_conv3 (Conv2D)	(None, 18, 18, 512)	2359808
block4_pool (MaxPooling2D)	(None, 9, 9, 512)	0
block5_conv1 (Conv2D)	(None, 9, 9, 512)	2359808
block5_conv2 (Conv2D)	(None, 9, 9, 512)	2359808
block5_conv3 (Conv2D)	(None, 9, 9, 512)	2359808
block5_pool (MaxPooling2D)	(None, 4, 4, 512)	0
=====		
Total params: 14,714,688		
Trainable params: 14,714,688		
Non-trainable params: 0		

```

import os
import numpy as np
from keras.preprocessing.image import ImageDataGenerator

base_dir = '/content/gdrive/MyDrive/Colab Notebooks/64061/cats_and_dogs_small'

train_dir = os.path.join(base_dir, 'train')
validation_dir = os.path.join(base_dir, 'validation')
test_dir = os.path.join(base_dir, 'test')

datagen = ImageDataGenerator(rescale=1./255)
batch_size = 20

def extract_features(directory, sample_count):
    features = np.zeros(shape=(sample_count, 4, 4, 512))
    labels = np.zeros(shape=(sample_count))
    generator = datagen.flow_from_directory(
        directory,
        target_size=(150, 150),
        batch_size=batch_size,
        class_mode='binary')
    i = 0
    for inputs_batch, labels_batch in generator:
        features_batch = conv_base.predict(inputs_batch)
        features[i * batch_size : (i + 1) * batch_size] = features_batch
        labels[i * batch_size : (i + 1) * batch_size] = labels_batch
        i += 1
    if i * batch_size >= sample_count:
        # Note that since generators yield data indefinitely in a loop,
        # we must `break` after every image has been seen once.
        break
    return features, labels

```

```
train_features, train_labels = extract_features(train_dir, 2000)
validation_features, validation_labels = extract_features(validation_dir, 1000)
test_features, test_labels = extract_features(test_dir, 1000)
```

```
-----
KeyboardInterrupt                                Traceback (most recent call last)
<ipython-input-6-e489372cb3cc> in <module>()
----> 1 train_features, train_labels = extract_features(train_dir, 2000)
      2 validation_features, validation_labels = extract_features(validation_dir, 1000)
      3 test_features, test_labels = extract_features(test_dir, 1000)

-----
7 frames
/usr/lib/python3.7/threading.py in wait(self, timeout)
    294         try:             # restore state no matter what (e.g., KeyboardInterrupt)
    295             if timeout is None:
--> 296                 waiter.acquire()
    297                 gotit = True
    298             else:
```

KeyboardInterrupt:

SEARCH STACK OVERFLOW

```
train_features = np.reshape(train_features, (2000, 4 * 4 * 512))
validation_features = np.reshape(validation_features, (1000, 4 * 4 * 512))
test_features = np.reshape(test_features, (1000, 4 * 4 * 512))
```

```
-----
NameError                                Traceback (most recent call last)
<ipython-input-17-242630fb165b> in <module>()
      1
----> 2 train_features = np.reshape(train_features, (2000, 4 * 4 * 512))
      3 validation_features = np.reshape(validation_features, (1000, 4 * 4 * 512))
      4 test_features = np.reshape(test_features, (1000, 4 * 4 * 512))
```

NameError: name 'train_features' is not defined

SEARCH STACK OVERFLOW

```
from keras import models
from keras import layers
from keras import optimizers
```

```
model = models.Sequential()
model.add(layers.Dense(256, activation='relu', input_dim=4 * 4 * 512))
model.add(layers.Dropout(0.5))
model.add(layers.Dense(1, activation='sigmoid'))
```

```
model.add(layers.Dense(1, activation='sigmoid'))
```

```
model.compile(optimizer=optimizers.RMSprop(lr=2e-5),
              loss='binary_crossentropy',
              metrics=['acc'])
```

```
history = model.fit(train_features, train_labels,
                    epochs=30,
                    batch_size=20,
                    validation_data=(validation_features, validation_labels))
```

```
-----
NameError                                Traceback (most recent call last)
<ipython-input-8-0b1e89ced5ef> in <module>()
    12                 metrics=['acc'])
    13
--> 14 history = model.fit(train_features, train_labels,
    15                     epochs=30,
    16                     batch_size=20,
```

NameError: name 'train_features' is not defined

SEARCH STACK OVERFLOW

```
import matplotlib.pyplot as plt
```

```
acc = history.history['acc']
val_acc = history.history['val_acc']
loss = history.history['loss']
val_loss = history.history['val_loss']
```

```
epochs = range(len(acc))
```

```
plt.plot(epochs, acc, 'bo', label='Training acc')
plt.plot(epochs, val_acc, 'b', label='Validation acc')
plt.title('Training and validation accuracy')
plt.legend()
```

```
plt.figure()
```

```
plt.plot(epochs, loss, 'bo', label='Training loss')
plt.plot(epochs, val_loss, 'b', label='Validation loss')
plt.title('Training and validation loss')
plt.legend()
```

```
plt.show()
```

```

-----
NameError                                Traceback (most recent call last)
<ipython-input-9-ce9171dbf527> in <module>()
      1 import matplotlib.pyplot as plt
      2
----> 3 acc = history.history['acc']
      4 val_acc = history.history['val_acc']
      5

```

```

from keras import models
from keras import layers

```

```

model = models.Sequential()
model.add(conv_base)
model.add(layers.Flatten())
model.add(layers.Dense(256, activation='relu'))
model.add(layers.Dense(1, activation='sigmoid'))

```

```

-----
NameError                                Traceback (most recent call last)
<ipython-input-2-84e708839fb4> in <module>()
      3
      4 model = models.Sequential()
----> 5 model.add(conv_base)
      6 model.add(layers.Flatten())
      7 model.add(layers.Dense(256, activation='relu'))

```

NameError: name 'conv_base' is not defined

SEARCH STACK OVERFLOW

```
model.summary()
```

Model: "sequential_1"

Layer (type)	Output Shape	Param #
vgg16 (Functional)	(None, 4, 4, 512)	14714688
flatten (Flatten)	(None, 8192)	0
dense_2 (Dense)	(None, 256)	2097408
dense_3 (Dense)	(None, 1)	257
Total params: 16,812,353		
Trainable params: 16,812,353		
Non-trainable params: 0		

```

print('This is the number of trainable weights '
      'before freezing the conv base:', len(model.trainable_weights))

```

This is the number of trainable weights before freezing the conv base: 30

```
conv_base.trainable = False
```

```
print('This is the number of trainable weights '  
      'after freezing the conv base:', len(model.trainable_weights))
```

This is the number of trainable weights after freezing the conv base: 30

```
from keras.preprocessing.image import ImageDataGenerator
```

```
train_datagen = ImageDataGenerator(  
    rescale=1./255,  
    rotation_range=40,  
    width_shift_range=0.2,  
    height_shift_range=0.2,  
    shear_range=0.2,  
    zoom_range=0.2,  
    horizontal_flip=True,  
    fill_mode='nearest')
```

```
# Note that the validation data should not be augmented!
```

```
test_datagen = ImageDataGenerator(rescale=1./255)
```

```
train_generator = train_datagen.flow_from_directory(  
    # This is the target directory  
    train_dir,  
    # All images will be resized to 150x150  
    target_size=(150, 150),  
    batch_size=20,  
    # Since we use binary_crossentropy loss, we need binary labels  
    class_mode='binary')
```

```
validation_generator = test_datagen.flow_from_directory(  
    validation_dir,  
    target_size=(150, 150),  
    batch_size=20,  
    class_mode='binary')
```

```
model.compile(loss='binary_crossentropy',  
              optimizer=optimizers.RMSprop(lr=2e-5),  
              metrics=['acc'])
```

```
history = model.fit_generator(  
    train_generator,  
    steps_per_epoch=50,  
    epochs=10,  
    validation_data=validation_generator,  
    validation_steps=50,  
    verbose=2)
```

```

-----
NameError                                Traceback (most recent call last)
<ipython-input-1-9db6266e3974> in <module>()
    16 train_generator = train_datagen.flow_from_directory(
    17     # This is the target directory
---> 18     train_dir,
    19     # All images will be resized to 150x150
    20     target_size=(150, 150),

NameError: name 'train_dir' is not defined

```

SEARCH STACK OVERFLOW

```
model.save('cats_and_dogs_small_3.h5')
```

```
acc = history.history['acc']
val_acc = history.history['val_acc']
loss = history.history['loss']
val_loss = history.history['val_loss']
```

```
epochs = range(len(acc))
```

```
plt.plot(epochs, acc, 'bo', label='Training acc')
plt.plot(epochs, val_acc, 'b', label='Validation acc')
plt.title('Training and validation accuracy')
plt.legend()
```

```
plt.figure()
```

```
plt.plot(epochs, loss, 'bo', label='Training loss')
plt.plot(epochs, val_loss, 'b', label='Validation loss')
plt.title('Training and validation loss')
plt.legend()
```

```
plt.show()
```

```
conv_base.summary()
```

```
conv_base.trainable = True
```

```
set_trainable = False
for layer in conv_base.layers:
    if layer.name == 'block5_conv1':
        set_trainable = True
    if set_trainable:
        layer.trainable = True
    else:
        layer.trainable = False
```

```
model.compile(loss='binary_crossentropy',
              optimizer=optimizers.RMSprop(lr=1e-5),
              metrics=['acc'])

history = model.fit_generator(
    train_generator,
    steps_per_epoch=100,
    epochs=100,
    validation_data=validation_generator,
    validation_steps=50)

model.save('cats_and_dogs_small_4.h5')

acc = history.history['acc']
val_acc = history.history['val_acc']
loss = history.history['loss']
val_loss = history.history['val_loss']

epochs = range(len(acc))

plt.plot(epochs, acc, 'bo', label='Training acc')
plt.plot(epochs, val_acc, 'b', label='Validation acc')
plt.title('Training and validation accuracy')
plt.legend()

plt.figure()

plt.plot(epochs, loss, 'bo', label='Training loss')
plt.plot(epochs, val_loss, 'b', label='Validation loss')
plt.title('Training and validation loss')
plt.legend()

plt.show()

def smooth_curve(points, factor=0.8):
    smoothed_points = []
    for point in points:
        if smoothed_points:
            previous = smoothed_points[-1]
            smoothed_points.append(previous * factor + point * (1 - factor))
        else:
            smoothed_points.append(point)
    return smoothed_points

plt.plot(epochs,
         smooth_curve(acc), 'bo', label='Smoothed training acc')
plt.plot(epochs,
         smooth_curve(val_acc), 'b', label='Smoothed validation acc')
plt.title('Training and validation accuracy')
plt.legend()
```



```
plt.figure()

plt.plot(epochs,
         smooth_curve(loss), 'bo', label='Smoothed training loss')
plt.plot(epochs,
         smooth_curve(val_loss), 'b', label='Smoothed validation loss')
plt.title('Training and validation loss')
plt.legend()

plt.show()

test_generator = test_datagen.flow_from_directory(
    test_dir,
    target_size=(150, 150),
    batch_size=20,
    class_mode='binary')

test_loss, test_acc = model.evaluate_generator(test_generator, steps=50)
print('test acc:', test_acc)
```

