```
No.     Time            Source              Destination         Protocol Length Info
   1215 14:53:25.020765 128.61.88.199       128.119.245.12      TCP      66     50458 → 80 [SYN] Seq=0 Win=64240 Len=0 MSS=1460
WS=256 SACK_PERM=1
Frame 1215: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface 0
Ethernet II, Src: AsustekC_c7:e1:6d (08:62:66:c7:e1:6d), Dst: Cisco_eb:f1:80 (68:ef:bd:eb:f1:80)
Internet Protocol Version 4, Src: 128.61.88.199, Dst: 128.119.245.12
Transmission Control Protocol, Src Port: 50458, Dst Port: 80, Seq: 0, Len: 0
    Source Port: 50458
    Destination Port: 80
    [Stream index: 5]
    [TCP Segment Len: 0]
    Sequence number: 0    (relative sequence number)
    [Next sequence number: 0    (relative sequence number)]
    Acknowledgment number: 0
    1000 .... = Header Length: 32 bytes (8)
    Flags: 0x002 (SYN)
    Window size value: 64240
    [Calculated window size: 64240]
    Checksum: 0x4eaf [unverified]
    [Checksum Status: Unverified]
    Urgent pointer: 0
    Options: (12 bytes), Maximum segment size, No-Operation (NOP), Window scale, No-Operation (NOP), No-Operation (NOP), SACK permitted
    [Timestamps]
```