

```
apiVersion: apiextensions.k8s.io/v1
kind: CustomResourceDefinition
metadata:
  name: sample.cache.example.com
spec:
  group: cache.example.com
  names:
    kind: Sample
    plural: samples
    singular: sample
    shortNames:
      - sam
  scope: Namespaced
  versions:
    - name: v1
      served: true
      storage: true
      schema:
        openAPIV3Schema:
          type: object
          properties:
            spec:
              type: object
              properties:
                size:
                  type: integer
                  description: Number of Sample instances
            status:
              type: object
              properties:
                nodes:
                  type: array
                  items:
                    type: string
```

```
kubectl apply -f cache-crd.yaml
```

```
kubectl get crd
```

```
apiVersion: cache.example.com/v1
kind: Sample
metadata:
  name: my-sample
spec:
  size: 3
```

```
kubectl apply -f my-cache.yaml
```

```
kubectl get samples
```

```
kubectl describe Sample my-sample
```

```
kubectl delete Sample my-sample
```

```
kubectl get events --watch
```

```
kubectl apply -f operator-crd.yaml
```

```
kubectl apply -f operator-deployment.yaml
```

```
kubectl get pods -n <operator-namespace>
```

```
kubectl logs <operator-pod-name> -n <operator-namespace>
```