




Plucking strings and playing chords: percepts elicited from single and multiple cone stimulation

Brian P. Schmidt, Alexandra E. Boehm & Austin Roorda


INTRODUCTION

Incoming sensory information is often noisy and ambiguous. One strategy the brain uses to reduce uncertainty is to pool signals from multiple detectors. We studied the rules for combining signals from sensory receptors by targeting individual and pairs of cones with light and recording the associated percept.



METHODS

Two male and one female subject were enrolled in the study. Cone mosaics (at 1-3 degrees of eccentricity) were imaged and tracked with an adaptive optics scanning laser ophthalmoscope (AOSLO). Stimuli (543 nm; 0.35 arcmin; 500 ms) were delivered to cones of interest following established procedures (Harmening et al. 2014).





Procedure:

1. Thresholds for detecting 85% of flashes were found with an adaptive staircase procedure for both one- and two-cone conditions.

2. Appearance of flashes were recorded at the measured detection threshold. Subjects indicated the appearance of each stimulus with a hue and saturation scaling procedure (Gordon et al. 1994).

During each session groups of three cones were targeted both individually and in pairs; trials were randomly interleaved. The background in both experiments was a low photopic (~40 cd/m²) white. Separately, cone mosaics were classified with AOSLO densitometry (Sabesan et al. 2015).

RESULTS



6. Appearance of two-point stimuli is best predicted by a normalized summation model.

Model	Scale (a)	Exponent (n)	Variance (%)
Average	0.5	1	67
Winner-take-all	1	100	26
Scaled linear summation	Free: 0.61±0.22	1	69
Scaled power-law summation	Free: 0.49±0.34	Free: 0.66±0.48	72
Divisive normalization	Free: 0.68±0.26	0.5	72

CONCLUSIONS

Two-cone detection thresholds followed the expectations of a single detector that linearly summed signals from individual cones assuming each cone carried minimal noise. In comparison, two-cone appearance judgments were better predicted by a non-linear spatial summation model. Together these observations suggest that the detection and appearance judgments were mediated by different neural pathways; potentially implicating the magno- and parvocellular pathways, respectively.

FUNDING

National Eye Institute
National Institutes of Health

* NEI: F32EY027637, R01EY023591, T32EY7043-38
* Minnie Flaura Turner Memorial Fund for Impaired Vision Research
* Michael G. Harris Ezell Fellowship

Scan code to download poster