

Generative Models

CMPT 726

Mo Chen

SFU Computing Science

23 Nov., 2020

Outline

Generative Models

Autoencoders

Variational Auto Encoders

Generative Adversarial Networks

Outline

Generative Models

Autoencoders

Variational Auto Encoders

Generative Adversarial Networks

Generative Models


- Start with training data, with **unknown** distribution $p(x)$
 - No labels!
- Generate new samples from a similar distribution $\hat{p}(x)$
 - $\hat{p}(x)$ is learned from data

Generative Models



<https://arxiv.org/abs/1406.5298>

Generative Models



<https://junyanz.github.io/CycleGAN/>

Outline

Generative Models


Autoencoders

Variational Auto Encoders

Generative Adversarial Networks

Autoencoders


- Unsupervised learning method
 - Learns lower-dimensional features from unlabeled data
 - Labels can be expensive!



- Features z
 - Lower-dimensional
 - Can be useful for other tasks
 - How to learn?


Autoencoders

- Unsupervised learning method
 - Learn features that allow reconstruction of original data
 - Reconstruction (decoding) done by a decoder
 - Decoder: another neural network
 - Loss function: $\|x - \hat{x}\|^2$



After Training

- Replace decoder with another network (e.g. classifier)
 - Supervised learning can be more efficient when features are “pre-learned”
 - Example: train autoencoder on ImageNet dataset, and then train only classifier on bird classification (less data available)



Outline

Generative Models


Autoencoders

Variational Auto Encoders

Generative Adversarial Networks


Variational Autoencoders

- Make autoencoders probabilistic to allows us to generate a variety of new data
- New data generated from features z
 - Feature variations: $z \sim p_{\theta}(z) = \mathcal{N}(0, I)$ for simplicity
 - Synthetic data variations: $\hat{x} \sim p_{\theta}(x|z)$, represented by a neural network



Variational Autoencoders: Training

- We still need to learn features that allow reconstruction of original data
 - This time, since there is variation in z and x , we cannot simply minimize $\|x - \hat{x}\|^2$
- Instead, maximize the likelihood $p_\theta(\hat{x})$ that a training image will be generated
 - fit a distribution $p_\theta(\hat{x})$ to data, which has distribution $p(x)$



ELBO Loss

- How to maximize $p_\theta(x^{(i)})$?
 - Data sample $x^{(i)}$ is given; we are finding θ

$$\begin{aligned}
 \log p_\theta(x^{(i)}) &= \mathbb{E}_{z \sim q_\phi(z|x^{(i)})} [\log p_\theta(x^{(i)})] && (\mathbb{E}_b[a] = a \text{ if } a \text{ does not depend on } b) \\
 &= \mathbb{E}_{z \sim q_\phi(z|x^{(i)})} \left[\log \frac{p_\theta(x^{(i)}|z)p_\theta(z)}{p_\theta(z|x^{(i)})} \right] \\
 &= \mathbb{E}_{z \sim q_\phi(z|x^{(i)})} \left[\log \frac{p_\theta(x^{(i)}|z)p_\theta(z)}{p_\theta(z|x^{(i)})} \frac{q_\phi(z|x^{(i)})}{q_\phi(z|x^{(i)})} \right] && (\text{Bayes' rule: } p(a|b) = \frac{p(b|a)p(a)}{p(b)}) \\
 &= \mathbb{E}_{z \sim q_\phi(z|x^{(i)})} [\log p_\theta(x^{(i)}|z)] - \mathbb{E}_{z \sim q_\phi(z|x^{(i)})} \left[\log \frac{q_\phi(z|x^{(i)})}{p_\theta(z)} \right] + \mathbb{E}_{z \sim q_\phi(z|x^{(i)})} \left[\log \frac{q_\phi(z|x^{(i)})}{p_\theta(z|x^{(i)})} \right] \\
 &= \mathbb{E}_{z \sim q_\phi(z|x^{(i)})} [\log p_\theta(x^{(i)}|z)] - D_{\text{KL}}(q_\phi(z|x^{(i)}) \| p_\theta(z)) + D_{\text{KL}}(q_\phi(z|x^{(i)}) \| p_\theta(z|x^{(i)}))
 \end{aligned}$$

- D_{KL} is the **Kullback-Leibler divergence**
 - a measure of closeness of probability distributions
 - Always ≥ 0

ELBO Loss

- D_{KL} is the **Kullback-Leibler divergence**
 - a measure of closeness of probability distributions
 - Always ≥ 0

$$\begin{aligned} & \log p_{\theta}(x^{(i)}) \\ = & \mathbb{E}_{z \sim q_{\phi}(z|x^{(i)})} [\log p_{\theta}(x^{(i)}|z)] - D_{\text{KL}}(q_{\phi}(z|x^{(i)}) \| p_{\theta}(z)) + D_{\text{KL}}(q_{\phi}(z|x^{(i)}) \| p_{\theta}(z|x^{(i)})) \end{aligned}$$

- **First term**: Estimate by sampling from decoder (yet more Math tricks, see [1])
- **Second term**: Closed-form expression if we assume $p_{\theta}(z)$ is Gaussian
- **Third term**: intractable to compute but always ≥ 0 , so ignore...
- Maximize first two terms, the **evidence lower bound (ELBO)**

ELBO Loss


$$l(x^{(i)}, \theta, \phi) = \mathbb{E}_{z \sim q_{\phi}(z|x^{(i)})} [\log p_{\theta}(x^{(i)}|z)] - D_{\text{KL}}(q_{\phi}(z|x^{(i)}) \| p_{\theta}(z))$$

- **First term:** Estimate by sampling from decoder (yet more Math tricks, see [1])
 - Maximize data likelihood, given latent features
- **Second term:** Closed-form expression if we assume $p_{\theta}(z)$ is Gaussian
 - Make encoder $q_{\phi}(z|x^{(i)})$ close to $p_{\theta}(z) = \mathcal{N}(0, I)$
- Maximize first two terms, the **evidence lower bound (ELBO)**

ELBO Loss


$$l(x^{(i)}, \theta, \phi) = \mathbb{E}_{z \sim q_{\phi}(z|x^{(i)})} [\log p_{\theta}(x^{(i)}|z)] - D_{\text{KL}}(q_{\phi}(z|x^{(i)}) \| p_{\theta}(z))$$

- First term:** Estimate by sampling from decoder (yet more Math tricks, see [1])
 - Maximize data likelihood, given latent features
- Second term:** Closed-form expression if we assume $p_{\theta}(z)$ is Gaussian
 - Make encoder $q_{\phi}(z|x^{(i)})$ close to $p_{\theta}(z) = \mathcal{N}(0, I)$
- Maximize first two terms, the **evidence lower bound (ELBO)**





Test Time

- Throw away encoder
- Sample $z \sim \mathcal{N}(0, I)$
- Compute $p_{\theta}(x|z)$ using decoder
- Sample from decoder to generate new data \hat{x}



Test Time



“Auto-Encoding Variational Bayes.” <http://arxiv.org/abs/1312.6114>

Outline

Generative Models


Autoencoders

Variational Auto Encoders

Generative Adversarial Networks


Generative Adversarial Networks (GANs)

- No explicit representation of probability densities (mean and variance)
- Data generation can be thought of as sampling from data distribution a complex distribution
 - Sample from simple distribution (noise)
 - Transform the samples so that they become distributed according to a more complex distribution
- GANs: Learn this transformation




Generative Adversarial Networks (GANs)

- Generator network needs to output realistic images, i.e. those from the same distribution as some dataset
 - But need to learning the transformation *without labels*
 - Idea: learn to fool a discriminator network
- Discriminator network: discriminate between real and fake data
 - “Labels”: real or not real




Generative Adversarial Networks (GANs)

- Generator network needs to output realistic images, i.e. those from the same distribution as some dataset
 - But need to learning the transformation *without labels*
 - Idea: learn to fool a discriminator network
- Discriminator network: discriminate between real and fake data
 - “Labels”: real or not real




Discriminator Loss Function

- Maximize $l_d(x^{(i)}, z^{(i)}; \theta_d) = \log D_{\theta_d}(x^{(i)}) + \log \left(1 - D_{\theta_d}(G_{\theta_g}(z^{(i)})) \right)$
 - Fix generator parameters θ_g
- If the **input is real data** $x^{(i)}$, output something close to 1
- If the **input is fake data** $\hat{x}^{(i)}$, output something close to 0
 - Fake data is from generator: $\hat{x}^{(i)} = G_{\theta_g}(z^{(i)})$




Generator Loss Function

- Maximize $l_g(z^{(i)}; \theta_g) = \log \left(D_{\theta_d}(G_{\theta_g}(z^{(i)})) \right)$
 - Fix discriminator parameters θ_d
- Try to make discriminator output 1 when taking generated data as input




GANs: Training and Using

- For every training iteration
 - Perform k steps of discriminator updates
 - Sample $\{z^{(i)}\}_{i=1}^M$ (random noise), $\{x^{(i)}\}_{i=1}^M$ (from data)
 - Take ascent step in the $\nabla_{\theta_d} \sum_{i=1}^M l_d(x^{(i)}, z^{(i)}; \theta_d)$ direction
 - Perform a step of generator update
 - Sample $\{z^{(i)}\}_{i=1}^M$ (random noise)
 - Take ascent step in the $\nabla_{\theta_g} \sum_{i=1}^M l_g(z^{(i)}; \theta_g)$ direction
- After training, throw away discriminator




Generative Models



Goodfellow et al., 2014. "Generative Adversarial Networks."

<http://arxiv.org/abs/1406.2661>

Generative Models



<https://junyanz.github.io/CycleGAN/>