



diagonals: Fat Diagonals in R

Bastiaan Quast

The Graduate Institute, Geneva

Abstract

The abstract of the article.

Keywords: matrix, diagonal, block, R.

1. Introduction

Diagonals are an important matrix manipulation. We present the `diagonals` R package, which implements functions for dealing with **fat diagonals**. Fat diagonals are block matrix-diagonals that occur when two or more dimensions are mapped along a single edge of a matrix. For an asymmetric network graph (e.g. a dyadic social network) to be mapped to a matrix, we would need each node along each edge of matrix, however we would also need to map the direction of the tie, which is an additional dimension. Typically these would be represented as higher-order arrays (i.e. ≥ 3). In order to effectively visualise such arrays, it can be helpful to do so in a matrix. This could for instance be represented as in the following matrix (where the `i` and `o` suffices represent incoming and outgoing respectively).

	Ai	Ao	Bi	Bo	Ci	Co	Di	Do
A	1	1	0	0	1	0	1	0
B	0	1	1	1	0	1	0	1
C	1	0	0	0	1	1	0	0
D	1	0	1	0	1	1	1	1

Sometimes the ties of a node to itself are not particularly meaningful (e.g. feeling of amiability towards oneself) and can be removed. For a symmetric network this can simply be done using the function `diag()` in R's `base` package, e.g.

```
sm <- matrix(1, nrow=4, ncol=4)
```

```
diag(sm) <- NA
sm
```

```
      [,1] [,2] [,3] [,4]
[1,]    NA     1     1     1
[2,]     1    NA     1     1
[3,]     1     1    NA     1
[4,]     1     1     1    NA
```

However, for higher-order matrices this does not work well.

```
diag(m) <- NA
m
```

```
      Ai Ao Bi Bo Ci Co Di Do
A NA  1  0  0  1  0  1  0
B  0 NA  1  1  0  1  0  1
C  1  0 NA  0  1  1  0  0
D  1  0  1 NA  1  1  1  1
```

In comes the **diagonals** package and its workhorse **fatdiag()** function. The function is designed to mimick the behaviour of the **diag()** as closely as possible, but with then for **fat diagonals**.

```
# the matrix m was restored to its original state
library(diagonals)
```

```
D I
A G
  O N
  A L
    S
```

```
fatdiag(m, steps=4) <- NA
m
```

```
      Ai Ao Bi Bo Ci Co Di Do
A NA NA  0  0  1  0  1  0
B  0  1 NA NA  0  1  0  1
C  1  0  0  0 NA NA  0  0
D  1  0  1  0  1  1 NA NA
```

Note that the **steps** argument defines the number of steps on the diagonal ladder. Alternatively we could set the **size** of the step, more on this later.

2. Design

The implementation of fat diagonals in the `diagonals` package is intended to be as close as possible to the functions dealing with diagonals included in the `base` package. As such, the package includes two functions.

- `fatdiag()`
- `fatdiag()<-`

These functions offer a very similar syntax to the `base` functions:

- `diag()`
- `diag()<-`

With the exception that the fat diagonal functions generally need more information in terms of the number of `steps` on the diagonal ladder, or the `size` of these steps.

3. Usage

In the introduction we briefly demonstrate the usage of the `fatdiag()` function for assigning new values to the fat diagonal. Here we take a closer look at some of the additional options which are available.

```
fatdiag(m, size=c(1,2) ) <- 881:888
m
```

	Ai	Ao	Bi	Bo	Ci	Co	Di	Do
A	881	882	0	0	1	0	1	0
B	0	1	883	884	0	1	0	1
C	1	0	0	0	885	886	0	0
D	1	0	1	0	1	1	887	888

So far we have been using the set `fatdiag()`, i.e. `fatdiag()<-`. However, we can also use the `fatdiag()` function either for diagonal extraction, or diagonal matrix creation.

```
fatdiag(m, steps = 4)
```

```
[1] 881 882 883 884 885 886 887 888
```

Fat diagonal matrices can be created using a scalar:

```
fatdiag(9, steps=3)
```

	[,1]	[,2]	[,3]	[,4]	[,5]	[,6]	[,7]	[,8]	[,9]
[1,]	1	1	1	0	0	0	0	0	0
[2,]	1	1	1	0	0	0	0	0	0
[3,]	1	1	1	0	0	0	0	0	0
[4,]	0	0	0	1	1	1	0	0	0
[5,]	0	0	0	1	1	1	0	0	0
[6,]	0	0	0	1	1	1	0	0	0
[7,]	0	0	0	0	0	0	1	1	1
[8,]	0	0	0	0	0	0	1	1	1
[9,]	0	0	0	0	0	0	1	1	1

or using a vector:

```
fatdiag(1:27, steps=3)
```

	[,1]	[,2]	[,3]	[,4]	[,5]	[,6]	[,7]	[,8]	[,9]
[1,]	1	4	7	0	0	0	0	0	0
[2,]	2	5	8	0	0	0	0	0	0
[3,]	3	6	9	0	0	0	0	0	0
[4,]	0	0	0	10	13	16	0	0	0
[5,]	0	0	0	11	14	17	0	0	0
[6,]	0	0	0	12	15	18	0	0	0
[7,]	0	0	0	0	0	0	19	22	25
[8,]	0	0	0	0	0	0	20	23	26
[9,]	0	0	0	0	0	0	21	24	27

We can extract a fat diagonal and diagonalise it again.

```
m <- matrix(801:881, nrow=9, ncol=9)
fatdiag(fatdiag(m, steps=3), steps=3)
```

	[,1]	[,2]	[,3]	[,4]	[,5]	[,6]	[,7]	[,8]	[,9]
[1,]	801	810	819	0	0	0	0	0	0
[2,]	802	811	820	0	0	0	0	0	0
[3,]	803	812	821	0	0	0	0	0	0
[4,]	0	0	0	831	840	849	0	0	0
[5,]	0	0	0	832	841	850	0	0	0
[6,]	0	0	0	833	842	851	0	0	0
[7,]	0	0	0	0	0	0	861	870	879
[8,]	0	0	0	0	0	0	862	871	880
[9,]	0	0	0	0	0	0	863	872	881

4. Conclusion

Higher-order arrays can sometimes be mapped to a matrix, which enables us to visualise these arrays in a intuitive manner. However, the standard matrix manipulations relating

to diagonals become more complex when we do so. The `diagonals` package provides the `fatdiag()` function family, which enables the manipulation of fat diagonals in R, using a syntax that is very close to the `diag()` function family from R's `base` package.

Affiliation:

Bastiaan Quast

The Graduate Institute, Geneva

Maison de la paix Geneva, Switzerland

E-mail: bquast@gmail.com

URL: <http://qua.st/>