rnn: RNN, GRU, and LSTM in native R

Bastiaan Quast
The Graduate Institute

Dimitri Fichou
University of Giessen

Abstract

The abstract of the article. The abstract of the article.The abstract of the article.The abstract of the article.The abstract of the article.The abstract of the article.The abstract of the article.The abstract of the article.The abstract of the article.The abstract of the article.The abstract of the article.The abstract of the article.The abstract of the article.The abstract of the article.The abstract of the article.The abstract of the article.The abstract of the article.The abstract of the article.The abstract of the article.

1. About package foo in R

The special JSS style commands related to software and mathematical formulas are written as follows in LYX: R or R for the names of programming languages, **foo** or **foo** for software packages, and `some code` or **some code** for code; E for expectations, VAR for variances, COV for covariances, and P for probabilities.

Writing several lines of code:

```
first line of code
second line of code
third line of code
```

Alternatively, you can distinguish between input and output code:

```
first line of input code
second line of input code
```

```
first line of output code
```

```
second line of output code
third line of output code
```

Acknowledgments

Here you can write some acknowledgments.

A. This is the first appendix section

A.1. A subsection

A subsubsection

some text

Affiliation:

Bastiaan Quast
Department of International Economics
The Graduate Institute, Geneva
Maison de la paix
1201 Geneva
E-mail: bastiaan.quast@graduateinstitute.ch
URL: http://qua.st/