



THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DOD/SS SPECIFIED IN THE SOLICITATION: MIL-C-38999

Previous editions are obsolete

SPECIFICATION SHEET NUMBER	
MS27503C (USAF)	4 May 50
SUPERSEEDING MS27503B (USAF)	13 August 1974
AMSC N/A	FSC 5935
Unlimited.	Page 1 of 2

C DIA 3 PROJECT CDS

⊕	E	A	(M)	GG	(M)	.012	CIA	⊕
---	---	---	-----	----	-----	------	-----	---



SHELL SIZE	A +.001 -.005 DIA	B +.000 -.016 DIA	C +.006 -.002 DIA	D +.005 -.001 DIA	XX MAX	N +.005 -.006 DIA	Q +.011 -.010 DIA	V +.001 -.005 DIA	CC	ZE MIN DIA	FOR INSERT ARR SEE DWG MS
OVER PROJ.											
8	.473	.563		.362		.412	.687	.562	.004	.463	27343,27516
10	.590	.690		.490		.540	.797	.672		.515	27344,27517
12	.755	.859	.076	.607	.125	.689	.906	.781		.629	27345,27518
14	.875	.954		.732		.814	1.031	.906		.754	27346,27519
16	1.000	1.109		.857		.939	1.156	1.031	.010	.879	27347,27520
18	1.125	1.233		.962		1.039	1.261	1.156		.950	27348,27521
20	1.250	1.358		1.087		1.164	1.375	1.250		1.105	27349,27522
22	1.375	1.483	.125	1.212	.156	1.289	1.500	1.375		1.230	27350,27523
24	1.500	1.610		1.337		1.414	1.625	1.500		1.355	27351,27524

1. DIMENSIONS IN INCHES.
2. DIAMETERS A AND D SHALL BE CONCENTRIC WITHIN .015 TIR.
3. DIAMETER A WITH RESPECT TO DIAMETER B, AND DIAMETER D WITH RESPECT TO DIAMETER N, SHALL BE CONCENTRIC AT MMC.
4. NORMAL KEYWAY POSITION. FOR OTHER KEYWAY POSITIONS SEE FIGURE 4 OF PROCUREMENT SPECIFICATION.
5. THE GAGE FEATURES FOR GG SHALL BE CC SMALLER THAN THEIR MMC AT BASIC LOCATION.

© CANCELED 6 MONTHS FROM THE DATE OF THIS DOCUMENT. USE MS27478

THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REF DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

EXAMPLE OF PART NUMBER

MS27503 Y 24 E 61 P A

MS NO.	CLASS	SHELL SIZE	FINISH (COLOR)	INSERT ARR. NUMBER	STYLE (P OR S)	POLARIZATION NO LETTER REQUIRED FOR NORMAL

Form Approved
OMB NO. 0704-0188

THIS SPECIFICATION IS APPROVED FOR USE BY the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DODISS SPECIFIED IN THE SOLICITATION: MIL-C-38399


DD Form 672, MAY 88

Previous editions are obsolete.

PREPARING ACTIVITY: AF - 85
CUSTOMERS: ARMY -
NAVY -
AIR FORCE -
DLA -

TITLE
MILITARY SPECIFICATION SHEET
CONNECTOR, RECEPTACLE, ELECTRIC,
SOLDER MOUNTING, SOLDER TYPE,
HERMETIC SEAL, SERIES II


SPECIFICATION SHEET NUMBER
MS27503C (USAF)
SUPERSEDING
MS27503B (USAF)
AMSC N/A
FSC 5935



SHELL SIZE	A +.000 -.005 DIA	B +.000 -.016 DIA OVER PROJ.	C +.006 -.002 DIA	D +.005 -.001 DIA	I ±.005 DIA	XX MAX	N +.005 -.005 DIA	Q +.011 -.010 DIA	V +.001 -.005 DIA	CC	ZZ MIN DIA	FOR INSERT ARR SEE DWG MS
8	.473	.563	.078	.362	.296	.125	.412	.667	.562	.010	.403	27343, 27516
10	.590	.680		.490	.413		.540	.797	.672		.515	27344, 27517
12	.750	.859		.507	.527		.689	.906	.781		.629	27345, 27518
14	.875	.954		.732	.652		.814	1.031	.906		.754	27346, 27519
16	1.000	1.108		.857	.777		.939	1.156	1.031		.879	27347, 27520
18	1.125	1.233	.125	.962	.865	.156	1.039	1.281	1.156		.980	27348, 27521
20	1.250	1.358		1.087	.991		1.164	1.375	1.250		1.105	27349, 27522
22	1.375	1.483		1.212	1.116		1.289	1.500	1.375		1.230	27350, 27523
24	1.500	1.610		1.337	1.241		1.414	1.625	1.500		1.355	27351, 27524

NOTES:

1. INSERT FRONT SURFACE SHALL BE FLAT WITHIN .005 TIR.
2. DIMENSIONS IN INCHES.
3. THE POINT AT WHICH A GAGE PIN, HAVING THE SAME BASIC DIAMETER AS THE MATING CONTACT AND A SQUARE FACE, TOUCHES SOCKET CONTACT SPRING.
4. NORMAL KEYWAY POSITION. FOR OTHER KEYWAY POSITIONS SEE FIGURE 4 OF PROCUREMENT SPECIFICATION.
5. DIAMETERS A AND D SHALL BE CONCENTRIC WITHIN .015 TIR.
6. DIAMETER A WITH RESPECT TO DIAMETER B, AND DIAMETER D WITH RESPECT TO DIAMETER N, SHALL BE CONCENTRIC AT MMC.
7. DIAMETERS D AND I SHALL BE CONCENTRIC WITHIN .005 TIR AT MMC.
8. THE GAGE FEATURES FOR GG SHALL BE CC SMALLER THAN THEIR MMC SIZE AT BASIC LOCATION.



EXAMPLE OF PART NUMBER

THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REF DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

Form Approved
OMB No 0704-0188