

METRIC


MIL-DTL-38999/52B
w/AMENDMENT 2
2 July 2024
SUPERSEDING
MIL-DTL-38999/52B
w/AMENDMENT 1
8 August 2017

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, CIRCULAR, COVER, PROTECTIVE, RECEPTACLE, MIL-DTL-38999, SERIES IV

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein
shall consist of this specification sheet and MIL-DTL-38999.



mm	Inches	mm	Inches	mm	Inches
4.80	.189	27.64	1.088	34.93	1.375
6.35	.25	27.79	1.094	127.00	5.00

STYLE R (WITH ROPE)

FIGURE 1. Protective cover, receptacle, all classes.

MSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FSC 5935



A

Dimensions			
Shell size	A dia max	B dia max	C BSC
11	26.59 (1.047)	19.18 (.775)	2.84 (.112)
13	30.99 (1.220)	22.86 (.900)	2.87 (.113)
15	34.19 (1.346)	26.42 (1.040)	3.37 (.133)
17	37.39 (1.472)	29.21 (1.150)	3.37 (.133)
19	40.21 (1.583)	32.39 (1.275)	3.89 (.153)
21	43.31 (1.705)	35.56 (1.400)	3.89 (.153)
23	46.50 (1.831)	38.74 (1.525)	4.39 (.173)
25	49.71 (1.957)	41.91 (1.650)	4.39 (.173)


Dimensions				
Shell size	D° BSC REF	E° BSC REF	F° BSC REF	G° BSC REF
11	47° 21'	148° 21'	211° 47'	312° 39'
13	46° 34'	148° 22'	211° 38'	313° 26'
15	46° 23'	148° 35'	211° 25'	313° 37'
17	46° 11'	148° 47'	211° 13'	313° 49'
19	45° 33'	149° 27'	210° 33'	314° 27'
21	45° 28'	149° 29'	210° 31'	314° 32'
23	45° 25'	149° 29'	210° 31'	314° 35'
25	45° 30'	149° 34'	210° 26'	314° 30'

NOTES:

1. Dimensions are in millimeters. Inch equivalents are given for information only.
2. Method of attachment to cover and / or ring is optional.
3. Protective covers shall fit receptacles with pin or socket contacts configured in any polarization position.

FIGURE 1. Protective cover, receptacle, all classes – Continued.

MIL-DTL-38999/52B
w/AMENDMENT 2



STYLE N (WITH ROPE AND RING)

Shell size	K dia max (class H, N and Y)	K dia max (see note 4 for classes)	L dia min (class H, N and Y)	L dia min (see note 4 for classes)	M (class H, N and Y)	M (see note 4 for classes)	N
11	32.0 (1.26)	35.0 (1.38)	21.97 (.86)	25.12 (.99)	21.00 / 18.00 (.83/.71)	22.50 / 19.50 (.89/.76)	127.00 (5.00)
13	37.0 (1.46)	37.0 (1.46)	25.12 (.99)	29.92 (1.18)	22.50 / 18.50 (.89/.73)	25.00 / 23.50 (.98/.93)	127.00 (5.00)
15	40.0 (1.57)	42 (1.65)	29.92 (1.18)	31.50 (1.24)	25.00 / 23.50 (.98/.93)	27.00 / 24.50 (1.06/.96)	127.00 (5.00)
17	44.0 (1.73)	46 (1.81)	32.00 (1.26)	34.75 (1.37)	31.00 / 25.00 (1.22/.98)	32.00 / 26.00 (1.26/1.02)	127.00 (5.00)
19	46.0 (1.81)	49.0 (1.93)	36.27 (1.43)	38.05 (1.50)	32.50 / 26.50 (1.28/1.04)	34.00 / 28.00 (1.34/1.10)	127.00 (5.00)
21	49.0 (1.93)	54.0 (2.13)	38.25 (1.51)	42.55 (1.68)	34.00 / 28.00 (1.34/1.10)	36.50 / 30.50 (1.44/1.20)	127.00 (5.00)
23	54.0 (2.13)	56.0 (2.20)	42.62 (1.68)	44.35 (1.75)	35.50 / 30.00 (1.40/1.18)	36.50 / 31.00 (1.44/1.22)	127.00 (5.00)
25	56.0 (2.20)	59.0 (2.32)	44.45 (1.75)	47.55 (1.87)	37.50 / 31.50 (1.48/1.24)	39.00 / 33.00 (1.54/1.30)	127.00 (5.00)

FIGURE 2. Protective cover, receptacle, rope and ring assembly, all classes.

NOTES:

1. Dimensions are in millimeters. Inch equivalents are given for information only.
2. Method of attachment to cover and/or ring is optional.
3. Protective covers shall fit receptacles configured in any polarization position.
4. Applicable connector classes: Environmental classes C, F, G, J, K, L, M, R, S, T, W and Z.

FIGURE 2. Protective cover, receptacle, rope and ring assembly, all classes – Continued.

REQUIREMENTS:

Dimensions and configurations: See figures 1 and 2.

Materials:

- Cover
 - Classes C, F, G, R, T, W and Z: Impact extruded or machined aluminum alloy.
 - Classes H, K, N, S and Y: Corrosion resistant steel.
 - Classes J and M: High performance virgin resin in accordance with MIL-DTL-38999.
 - Class F: Impact extruded or machined aluminum alloy.
 - (Cover base materials listed. For finishes or surface treatments, see MIL-DTL-38999.)
- Gasket
 - Silicone elastomer.
- Ring
 - Corrosion resistant steel, passivated, 1.020 mm (0.04 inches) maximum thickness.
- Rope
 - Insulated stainless steel, passivated. Passivation or proof of passive finish using ASTM-A967/A967M or equivalent is permissible. Insulation shall withstand 200°C.
- Fastener
 - Stainless steel, passivated.
 - Option: Aluminum integral to cover.

Mating connectors: MIL-DTL-38999, series IV.

Gasket shall be bonded to cover, or mechanically retained.

Rope shall rotate freely on fastener.

Fastener tensile strength: The protective cover and rope assembly shall withstand a dead weight tensile load of 11.33 kg (25 pounds) applied to both axial and longitudinal directions. The load shall be applied at the end of the rope assembly and held for 5 minutes. There shall be no separation of the rope assembly from the protective cover or damage to the rope assembly. Both axial and longitudinal directions shall be 11.33 kg (25 pounds). The load shall be applied to the end of the rope.

Air Leakage: Testing shall be in accordance with EIA-364-02, except the minimum period of measurement shall be 10 seconds. The air leakage rate shall be no greater than 1 atmospheric cubic inch per hour (4.55×10^{-3} cm³/s). Protective covers shall be mated to connectors having either contacts or inserts removed so that a pressure of 10 lbft/in² (.703 Kg/cm²) can be applied against the insides of the protective covers or stowage receptacles.

Qualification (all classes): Qualification shall be in accordance with MIL-DTL-38999, except only the following tests shall be required:

MIL-DTL-38999/52B
w/AMENDMENT 2

Examination of product
Coupling torque
Humidity
Salt spray (corrosion)
Fastener tensile strength (see requirement)
Air leakage

Qualification (classes J and M only): Qualification shall be in accordance with MIL-DTL-38999, except that in addition to the test sequence specified for all classes above, the additional following tests shall be required:


Temperature cycling
Hydrolytic stability

Group A sampling inspection. Sampling for group A inspection shall be as specified in table I.

TABLE I. Group A sampling plan.

Lot size	Sampling size
1 to 13	100 percent
14 to 150	13 units
151 to 280	20 units
281 to 500	29 units
501 to 1,200	34 units
1,201 to 3,200	42 units
3,201 and up	54 units

Part or Identifying Number (PIN) example:



Class F is not for Navy use and is inactive for use in Air Force new design.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government

MIL-DTL-38999/52B
w/AMENDMENT 2

assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-DTL-38999, this document references the following:

EIA-364-02
ASTM-A967/A967M

CONCLUDING MATERIAL

Custodians:

Army - CR
Navy - AS
Air Force – 85
DLA - CC

Preparing activity:

DLA - CC

(Project 5935-2024-151)

Review activities:

Army - MI
Navy - EC, MC, OS
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.dla.mil>.