

INCH-POUND

MS27512H
w/AMENDMENT 1
27 June 2025
SUPERSEDING
MS27512H
12 May 2015

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, CIRCULAR, NUT, HEXAGON,
CONNECTOR MOUNTING, FOR MIL-DTL-38999, SERIES II, AND MIL-DTL-27599, SERIES II

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the connectors described herein
shall consist of this specification sheet and MIL-DTL-38999.

Reactivated after 10 June 2005, and may be
used for new and existing designs and acquisitions.




FIGURE 1. Nut, hexagon.

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FSC 5935



MS27512H
w/AMENDMENT 1

Shell size	A Thread size, class 2B	P +.017 -.016 hex
-8	.8750 – 20 UNEF	1.062
-10	1.0000 – 20 UNEF	1.188
-12	1.1250 – 18 UNEF	1.312
-14	1.2500 – 18 UNEF	1.438
-16	1.3750 – 18 UNEF	1.562
-18	1.5000 – 18 UNEF	1.688
-20	1.6250 – 18 UNEF	1.812
-22	1.7500 – 18 UNS	2.000
-24	1.8750 – 16 UN	2.125

Inches	mm	Inches	mm
.016	0.41	1.312	33.32
.017	0.43	1.438	36.53
.0295	0.750	1.562	39.67
.059	1.50	1.688	42.88
.125	3.18	2.000	50.80
1.062	26.97	2.125	53.98
1.188	30.18		

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Threads shall be in accordance with MIL-S-7742.
4. Remove all burrs and sharp edges.
5. Standard safety wire holes are drilled. The safety wire openings depicted in the alternate design are crimped. The alternate hex nut with a crimped edge is specified by adding “-C” to the Part or Identifying Number (PIN).

FIGURE 1. Nut, hexagon – Continued.

REQUIREMENTS:

Dimensions and configurations: See figure 1.

Material: See table I.

Finish: See table I and MIL-DTL-38999.

Applicable jam-nut connectors: See MIL-DTL-38999, series II, and MIL-DTL-27599, series II.

MS27512H
w/AMENDMENT 1

TABLE I. Material and finish. 1/

Code	Material	Finish <u>3/</u>
A	Impact extruded or machined aluminum alloy	A and D
B		B
C		C
F		F
E	Corrosion resistant steel <u>2/</u>	E

1/ See MIL-DTL-38999.

2/ Shall be cleaned, descaled and passivated in accordance with ASTM A380.

3/ Applicable to MIL-DTL-38999 series II and MIL-DTL-275999, series II connectors.

Qualification. Qualification shall be in accordance with MIL-DTL-38999, except only the following tests shall be required:

Examination of product.

Safety wire hole pull-out (see requirement below).

Salt spray (corrosion).

Safety wire pull-out: Safety wire shall not pull out of hex nut with crimped edges when safety wire NI-CU alloy (MONEL™) (UNS NO4400) or NI-CR alloy (INCONEL™) (UNS NO6600) .020 inch (0.51 mm) diameter in accordance with NASM20995 is threaded through a hole and a pull of 30 pounds (133.5 Newton) minimum is applied. Nine pulls total shall be applied. Pulls shall be applied in three directions. Pulling forces shall be applied parallel with the axis of the nut and also perpendicular to the axis of the nut. Three pulls shall be applied parallel to the axis in one direction and three pulls shall be applied parallel to the axis in the opposite direction. An additional three pulls shall be applied perpendicular to axis of nut.

Group A inspection shall consist of examination of product and safety wire pull out. Sampling for group A inspection shall be as specified in table II.

TABLE II. Group A sampling plan.

Lot size	Sampling size
1 to 13	100 percent
14 to 150	13 units
151 to 280	20 units
281 to 500	29 units
501 to 1,200	34 units
1,201 to 3,200	42 units
3,201 and up	54 units

MS27512H
w/AMENDMENT 1

Part or Identifying Number (PIN) example:

<u>MS27512</u>	<u>-10</u>	<u>E</u>	<u>-C</u>
MS number	Shell size	Material and finish code	Alternative crimped edge (see note)

NOTE: Standard safety wire holes are drilled. No PIN designator code is used when hex nuts with drilled safety wire holes are specified. When a hex nut with crimped edges is required, a "-C" designator shall be added to the end of the PIN to indicate a crimped design.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-DTL-38999 and MIL-DTL-27599, this document references the following:

MIL-S-7742
ASTM A380
NASM20995

CONCLUDING MATERIAL

Custodians:

Army – CR
Navy – AS
Air Force – 85
DLA – CC

Preparing activity:

DLA – CC

(Project 5935-2025-051)

Review activities:

Army – AR, MI
Navy – EC, MC, OS
Air Force – 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.dla.mil>.