




TABLE I. Dimensions.

Shell size	A Thread size class 2B	J max	P $\pm .017$ $-.016$ hex	S min no. of slots
9	.6875-24 UNEF	.135	.875	1
11	.8125-20 UNEF	"	1.000	"
13	1.0000-20 UNEF	"	1.188	"
15	1.1250-18 UNEF	"	1.312	"
17	1.2500-18 UNEF	.135	1.438	"
19	1.3750-18 UNEF	.192	1.562	"
21	1.5000-18 UNEF	"	1.688	"
23	1.6250-18 UNEF	"	1.812	"
25	1.7500-18 UNS	"	2.000	"

EXAMPLE OF PART NUMBER

MS27514 11 E
MS NO. SHELL SIZE MATERIAL AND FINISH CODE

(E) CANCELED; FOR PROCUREMENT USE MS 3186

(E) denotes changes

PREPARING ACTIVITY: Air Force - 85
CUSTODIANS: ARMY CR NAVY AS
AIR FORCE 85 DLA
Navy - EC, MC, OS
REVIEW: Air Force-11, 15, 17, 99
USER: Army-AR, MI; DLA - CS
PROJECT NUMBER: 5935-3757

MILITARY SPECIFICATION SHEET
TITLE NUT, SLOTTED, HEXAGON CONNECTOR MOUNTING, SERIES I

SPECIFICATION SHEET NUMBER
MS27514E 26 July 1990
SUPERSEDING
MS27514D 20 February 1978
AMSC N/A FSC 5935

DISTRIBUTION STATEMENT

A: Approved for public release; distribution is unlimited.

Inches	mm	Inches	mm
.016	.41	.875	22.23
.017	.43	1.000	25.40
.0295	7.50	1.188	30.18
.045	1.14	1.312	33.32
.059	1.50	1.438	36.53
.125	3.18	1.562	39.67
.135	3.43	1.688	42.88
.192	4.88	2.000	50.80

TABLE II. Material and finish codes.

Code	Material	Finish 1/	Applicable connectors
A	Aluminum: QQ-A-200/8, condition T-6; QQ-A-225/5, condition T-4 or QQ-A-225/8, condition T-6	A	Series I, finishes A and D
B		B	Series I, finish B
C		C	Series I, finish C
F		F	Series I, finish F
E	Corrosion resisting steel: QQ-S-764, type 303 or 303 SE	E	Series I, finish E

1/ In accordance with MIL-C-38999.

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Safety wire holes shall not pull out when safety wire NI-CU alloy (MONEL) or NI-CR alloy (INCONEL) .020 (0.51 mm) diameter in accordance with MS20995 is threaded through a hole and a pull of 30 pounds minimum is applied. Two pulls shall be made, one parallel with axis of nut and one perpendicular to axis of nut.
4. If more than one slot is used, they shall be 120° apart. Orientation optional in respect to hexagon configuration. Slot width shall provide sufficient clearance for use on applicable jam nut receptacles.
5. Threads to be in accordance with MIL-S-7742.
6. Remove all burrs and sharp edges.
7. For design feature purposes, this standard takes precedence over acquisition documents referenced herein.
8. Referenced documents shall be of the issue in effect on date of invitation for bid.

PREPARING ACTIVITY Air Force - GS CUSTODIANS. ARMY - CR NAVY - AS AIR FORCE - 85 DLA Navy - EC, MC, CS Air Force - 11, 15, 17, 99 REVIEW USER Army - AR, AF, OLA - ES PROJECT NUMBER 5035-745	MILITARY SPECIFICATION SHEET TITLE NUT, SLOTTED, HEXAGON CONNECTOR MOUNTING, SERIES I	SPECIFICATION SHEET NUMBER MS27514E SUPERSIDING MS27514D 20 February 1978 AMSC N/A FSC 5935
DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.		Page 2 of 2