

PRODUCT : CT256
DESCRIPTION : polyurethane hardener

PHYSICAL AND CHEMICAL PROPERTIES

SPECIFIC WEIGHT : $0,938 \pm 0,020$ (gr./cc. a 20° C.)
DRY RESIDUE: $22\% \pm 1$
NCO : $3,40\% \pm 0,3$

GENERAL PROPERTIES

Hardener for polyurethane sealers with quite good coverage and elasticity properties and high rapidity

EXPIRY : 12 months
The data refer to products preserved in original, sealed containers.

STORAGE : keep in a fresh and well ventilated place; do not exceed 25°-28° C. Polyisocyanic catalysts should be kept away from humidity; if partially used, re-seal the containers perfectly and use up the remaining product within a short period.

Company Information: SIRCA S.p.A. has a quality system certified by DNV according to standard UNI EN ISO 9001/2008

□□□□□□□□□□

The information given in this technical sheet is based on the best of our knowledge and experience.
Sirca guarantees the consistency of the chemical/physical characteristics of its products within the tolerances indicated above.
The final result is the full responsibility of the user who, before using the product, must check that it meets his requirements in terms of safety, application equipment, support material to paint, and environmental conditions.
Sirca's technical and commercial network is at your complete disposal to deal with any questions regarding how to correctly apply and use our products

REV. 0 02.04.2011

SIRCA s.p.a.

Sede legale: 35010 San Dono di Massanzago (Pd) – Viale Roma, 85 – Italy – Stabilimenti: San Dono di Massanzago (Pd) – Viale Roma, 85 –
Tel. 049/9322311 – Fax 049/5797262 – San Giovanni al Natisone (Ud) – Via Comunale del Rovere, 4 – Tel. 0432/747411 – Fax 0432/747411 –
Internet: www.sirca.it – E-mail: info@sirca.it