

Technical Data Sheet

ES1013S40

14/12/2022

Version 2

SIRCA S.p.A. - Offices and plant: Viale Roma, 85-35010 Sandono di Massanzago (PD) - Italy - Tel. 049/9322311 ra - 049/5797262 Fax - Internet: www.sirca.it.

S.p.A. has a quality system certified by DNV according to standard UNI EN ISO 9001.

Name and Code

ES1013S40 Rich gold Antique Patina .

Chemical Nature

Acrylic paint.

Description and performances

This patina is suitable for special antique effects, it is applied by cloth and eventually removed with steel wool pad. It's suitable for those painting systems where special effect are required (i.e. decapè effect) and it is suggested for furniture and accessories for furniture.

Colour shade is indicated in product description.

Additional description of the product

Chemical - Technical Properties

Description	Method	Unit of measure	Value - Range
Specific gravity	I.O. 309	g/cm3	0,950±0,010
Solid content	I.O. 371	%	10±2
Viscosity DIN 2 @20°C	I.O. 301	seconds	60±5

The solid content may vary according to the color shade of the specific product.

Technical Data Sheet

ES1013S40

14/12/2022

Version 2

Field of application

ES1013S40: ready to use.

General properties

Generally this kind of patina are applied by spray on open grain (transparent or pigmented painting system) and after drying any excess is removed by cloth. It is good practice not to wait more than 24 hours. We recommend to overcoat this effect after using the cloth and not exceeding the application amount, otherwise it is possible to have adhesion problems. According to the drying properties of the product low thinner are used..

Storage instructions

Keep the product in a ventilated area; do not exceed 25-28°C. Polyisocyanic hardeners should be protected from frost and humidity. If they have been partially used please close the can tight and use the residual amount in a short time.

EXPIRATION DATE 12 months

The data refers to the product stored in original sealed packaging.

The information supplied are correct to the best of our knowledge. However, as the coating process depends on many variables and the present application takes place without our supervision, we cannot assume any responsibility for the final result. Sirca guarantees that chemical and physical characteristics of the products are within the reported range. Due to the large variety of substrates and application devices, the purchaser/user should test our products in his own application conditions and safety and environment circumstances. Sirca's technical and sales departments are at customer's disposal for any further information regarding correct application of our products