

SET A

```
import java.util.Scanner;

public class ConditionalMajorityOdd {

    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int n = sc.nextInt();
        int[] votes = new int[n];

        for (int i = 0; i < n; i++) {
            votes[i] = sc.nextInt();
        }

        int validCount = 0;

        // Count valid votes (odd indices)
        for (int i = 1; i < n; i += 2) {
            validCount++;
        }

        // Check majority among valid votes
        for (int i = 1; i < n; i += 2) {
            int count = 0;

            for (int j = 1; j < n; j += 2) {
                if (votes[i] == votes[j]) {
                    count++;
                }
            }

            if (count > validCount / 2) {
                System.out.println(votes[i]);
                break;
            }
        }

        System.out.println(-1);
    }
}
```

SET B

```
import java.util.Scanner;

public class ConditionalMajority {

    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int n = sc.nextInt();
        int[] votes = new int[n];

        for (int i = 0; i < n; i++) {
            votes[i] = sc.nextInt();
        }

        int validCount = 0;

        // Count valid votes (even indices)
        for (int i = 0; i < n; i += 2) {
            validCount++;
        }

        // Check majority among valid votes
        for (int i = 0; i < n; i += 2) {
            int count = 0;

            for (int j = 0; j < n; j += 2) {
                if (votes[i] == votes[j]) {
                    count++;
                }
            }

            if (count > validCount / 2) {
                System.out.println(votes[i]);
                return;
            }
        }

        System.out.println(-1);
    }
}
```

Set X

```
import java.util.Scanner;
public class DominantRating {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        int[] arr = new int[n];
        for (int i = 0; i < n; i++) {
            arr[i] = sc.nextInt();
        }
        // Step 1: Extract verified (even-position) ratings
        int candidate = -1;
        int count = 0;
        int verifiedCount = 0;

        for (int i = 0; i < n; i += 2) {
            verifiedCount++;
            if (count == 0) {
                candidate = arr[i];
                count = 1;
            } else if (arr[i] == candidate) {
                count++;
            } else {
                count--;
            }
        }
        // Step 2: Verify the candidate actually appears more than half the time
        int actualCount = 0;
        for (int i = 0; i < n; i += 2) {
            if (arr[i] == candidate) {
                actualCount++;
            }
        }

        if (actualCount > verifiedCount / 2) {
            System.out.println(candidate);
        } else {
            System.out.println(-1);
        }
    }
}
```