

Solutions

SET A			SET B			General Marking instructions:
25	48	9	31	54	11	1. Each output yields 1 mark, with a total of 9 marks.
103	156	39	117	172	43	2. A complete table yields 1 mark.
275	100	10	309	114	16	3. If the trace table is not found $\Rightarrow$ 0 marks.
9+1 = 10 marks						

Questions

SetA

1	class Test {	18	class Exam extends Test {
2	static int[] x = {2, 7};	19	int x = 4, y = 1;
3	int y = 5;	20	Exam(Test z){
4	Test(){	21	z.methodA(6, z);
5	int z = x[0] + Test.x[1];	22	methodA(Test.x, y);
6	methodA(z, this);	23	}
7	System.out.println(x[0]+" "+y+" "+z);	24	int addNum(int t){
8	}	25	return t + x + Test.x[1];
9	void methodA(int z, Test t) {	26	}
10	x[0] += t.x[0] + addNum(z);	27	void methodA(int[] t, int y) {
11	Test.x[1] = 3 + t.y + (++y);	28	y += x + this.y + this.x;
12	y = z + x[0] + x[1];	29	super.y = (super.x[0]++) + addNum(y);
13	}	30	System.out.println(t[0]+" "+t[1]+" "+y);
14	int addNum(int t){	31	}
15	return t + x[1] + y;	32	}
16	}	Write your Outputs here:	
17	}		

Following the given classes, find the outputs of the driver code below:

```
Test one = new Test();
Exam two = new Exam(one);
```


SetB

1	class Test {	18	class Exam extends Test {
2	static int[] x = {6, 5};	19	int x = 2, y = 6;
3	int y = 3;	20	Exam(Test z){
4	Test(){	21	z.methodA(8, z);
5	int z = x[0] + Test.x[1];	22	methodA(Test.x, y);
6	methodA(z, this);	23	}
7	System.out.println(x[0]+" "+y+" "+z);	24	int addNum(int t){
8	}	25	return t + x + Test.x[1];
9	void methodA(int z, Test t) {	26	}
10	x[0] += t.x[0] + addNum(z);	27	void methodA(int[] t, int y) {
11	Test.x[1] = 5 + t.y + (++y);	28	y += x + this.y + this.x;
12	y = z + x[0] + x[1];	29	super.y = (super.x[0]++) + addNum(y);
13	}	30	System.out.println(t[0]+" "+t[1]+" "+y);
14	int addNum(int t){	31	}
15	return t + x[1] + y;	32	}
16	}	Write your Outputs here:	
17	}		

Following the given classes, find the outputs of the driver code below:

Test one = new Test();
Exam two = new Exam(one);