

Name:	ID:	Section:
-------	-----	----------

Question 1 [C03] [9+1 Points]

1	public class P {
2	public static int temp = 3;
3	public int a = 2;
4	public int sum = 5;
5	public P() {
6	a = temp + 1;
7	sum = a + temp;
8	temp += 2;
9	}
10	public P(int x){
11	methodQ(x, temp);
12	}
13	public void methodP(int x, int y) {
14	int z = 1;
15	a = a + x + (temp++);
16	z = z + y + a;
17	sum = sum + z + a;
18	System.out.println(z + " " + a + " " + sum);
19	}
20	public void methodQ(int x, int y){
21	a = a + (++temp);
22	sum = sum + x;
23	System.out.println(a+" "+temp+" "+sum);
24	}
25	}

Write the output of the following code:

```
Q q1 = new Q();
Q q2 = new Q(q1);
```

Output:

26	public class Q extends P {
27	public int a = 4;
28	public int sum = 6;
29	public static int temp = 3;
30	public Q() {
31	a = super.a + temp;
32	sum = sum + a;
33	temp--;
34	}
35	public Q(Q q) {
36	super(2);
37	a = q.a;
38	sum = q.sum+temp;
39	methodP(a,sum);
40	}
41	public void methodP(int x, int y) {
42	int z = -1;
43	z = z + y + (a++);
44	sum = sum + z + a;
45	System.out.println(z + " " + a + " " + sum);
46	}
47	public void methodQ(int x, int y) {
48	int a = 1;
49	a = super.a + this.a+temp;
50	temp = super.temp + x;
51	methodP(temp, a);
52	sum = a + sum + super.sum;
53	System.out.println(a + " " + temp + " " + sum);
54	}
55	}

Name:	ID:	Section:
-------	-----	----------

Question 1 [C03] [9+1 Points]

1	public class P {
2	public static int temp = 5;
3	public int a = 2;
4	public int sum = 3;
5	public P() {
6	a = temp + 1;
7	sum = a + temp;
8	temp += 2;
9	}
10	public P(int x){
11	methodQ(x, temp);
12	}
13	public void methodP(int x, int y) {
14	int z = 1;
15	a = a + x + (temp++);
16	z = z + y + a;
17	sum = sum + z + a;
18	System.out.println(z + " " + a + " " + sum);
19	}
20	public void methodQ(int x, int y){
21	a = a + (++temp);
22	sum = sum + x;
23	System.out.println(a+" "+temp+" "+sum);
24	}
25	}

Write the output of the following code:

```
Q q1 = new Q();
Q q2 = new Q(q1);
```

Output:

26	public class Q extends P {
27	public int a = 4;
28	public int sum = 6;
29	public static int temp = 3;
30	public Q() {
31	a = super.a + temp;
32	sum = sum + a;
33	temp--;
34	}
35	public Q(Q q) {
36	super(2);
37	a = q.a;
38	sum = q.sum+temp;
39	methodP(sum, a);
40	}
41	public void methodP(int x, int y) {
42	int z = -1;
43	z = z + y + (a++);
44	sum = sum + z + a;
45	System.out.println(z + " " + a + " " + sum);
46	}
47	public void methodQ(int x, int y) {
48	int a = 2;
49	a = super.a + this.a+temp;
50	temp = super.temp + x;
51	methodP(a, temp);
52	sum = a + sum + super.sum;
53	System.out.println(a + " " + temp + " " + sum);
54	}
55	}