

CSE111 - Quiz 4 (Set A) [Time: 25 minutes]

NAME:

ID:

SECTION:

Design the **Quiz** class derived from the **Exam** class to generate the given output. For simplicity, assume that a quiz can contain max 2 questions. The **Quiz** class can't have more than one instance array. [Marks: 10]

Parent class & Driver Class	Output
<pre>public class Exam{ public int marks; public Exam(int m){ marks = m; } public String toString(){ return "Marks: "+marks+", "; } } public class Tester{ public static void main(String [] args){ Quiz q1 = new Quiz(25, 40); Quiz q2 = new Quiz(10, 15); System.out.println(q1); System.out.println(q2); System.out.println("1-----"); q1.setQuestion(new String[] {"Coding", "Tracing"}, new int [] {10, 15}); System.out.println("2-----"); System.out.println(q1); System.out.println("3-----"); q2.setQuestion(new String[] {"Debugging"}, new int [] {15}); System.out.println("4-----"); System.out.println(q2); System.out.println("5-----"); q2.setQuestion(new String[] {"Debugging"}, new int [] {10}); System.out.println("6-----"); System.out.println(q2); } }</pre>	<pre>ID: QZ1, Marks: 25, Time: 40 min No questions set yet ID: QZ2, Marks: 10, Time: 15 min No questions set yet 1----- 2----- ID: QZ1, Marks: 25, Time: 40 min Coding-10 Marks Tracing-15 Marks 3----- Total question marks exceeded quiz marks. 4----- ID: QZ2, Marks: 10, Time: 15 min No questions set yet 5----- 6----- ID: QZ2, Marks: 10, Time: 15 min Debugging-10 Marks</pre>

CSE111 - Quiz 5 (Set A) [Time: 25 minutes]

NAME:

ID:

SECTION:

Illustrate the output of the following statements written in the main method of a tester class. [Answers without workings on the script will be rejected]

[Marks: 10]

1	public class A{
2	public int sum = 13, y = -2, temp = 15;
3	public A(){
4	B.temp = temp + this.temp + 4;
5	}
6	public A(B a2){
7	a2.y = a2.temp - 19;
8	sum = ++this.temp + 14;
9	}
10	public void methodA(int m){
11	y = y + m + (this.sum);
12	this.methodB(10);
13	sum = sum + B.x + y;
14	System.out.println(temp + " " + y+ " " + this.sum);
15	}
16	public void methodB(int m){
17	y = y + m + (this.sum++);
18	System.out.println(B.x + " " + y+ " " + sum);
19	}
20	}
21	class B extends A{
22	public static int x = 4, temp = 12;
23	public int sum = 11, y = 3;
24	public B(int p){
25	temp = temp + p + sum++;
26	}
27	public B(B a2){
28	super(a2);
29	sum = a2.sum;
30	x = a2.x + 2;
31	System.out.println(a2.sum+" "+this.x+" "+super.y);
32	}
33	public void methodB(int m){
34	y = y + this.y + m;
35	sum = x + y + super.sum;
36	System.out.println(super.y + " " + B.temp+ " " + sum);
37	}
38	}

Driver code:

```
B a1 = new B(8);  
B a2 = new B(a1);  
a2.methodA(16);
```

Output:
