

CSE111 - Quiz 4 (Set B) [Time: 25 minutes]

NAME:

ID:

SECTION:

Design the **Trip** class derived from the **Travel** class to generate the given output. For simplicity, assume that a trip can contain max 2 places. The **Trip** class can't have more than one instance array. [Marks: 10]

Parent class & Driver Class	Output
<pre>public class Travel{ public int budget; public Travel(int b){ budget = b; } public String toString(){ return "Budget: " + budget + "L, "; } } public class Tester2{ public static void main(String [] args){ Trip t1 = new Trip(50, 8); Trip t2 = new Trip(20, 3); System.out.println(t1); System.out.println(t2); System.out.println("1-----"); t1.setPlaces(new String[]{"China", "UK"}, new int[]{20, 25}); System.out.println("2-----"); System.out.println(t1); System.out.println("3-----"); t2.setPlaces(new String[]{"UK", "Japan"}, new int[]{15, 10}); System.out.println("4-----"); System.out.println(t2); System.out.println("5-----"); t2.setPlaces(new String[]{"Japan"}, new int[]{10}); System.out.println("6-----"); System.out.println(t2); } }</pre>	<pre>ID: TR1, Budget: 50L, Duration: 8 month No destinations set yet ID: TR2, Budget: 20L, Duration: 3 month No destinations set yet 1----- 2----- ID: TR1, Budget: 50L, Duration: 8 month China-20L UK-25L 3----- Budget exceeded for trip. 4----- ID: TR2, Budget: 20L, Duration: 3 month No destinations set yet 5----- 6----- ID: TR2, Budget: 20L, Duration: 3 month Japan-10L</pre>

CSE111 - Quiz 5 (Set B) [Time: 25 minutes]

NAME:

ID:

SECTION:

Illustrate the output of the following statements written in the main method of a tester class. [Answers without workings on the script will be rejected] [Marks: 10]

1	public class A{
2	public int sum = 11, y = 2, temp = 5;
3	public A(){
4	B.temp = temp + this.temp + 4;
5	}
6	public A(B a2){
7	a2.y = a2.temp - 19;
8	sum = ++this.temp + 14;
9	}
10	public void methodA(int m){
11	y = y + m + (this.sum);
12	this.methodB(10);
13	sum = sum + B.x + y;
14	System.out.println(temp + " " + y + " " + this.sum);
15	}
16	public void methodB(int m){
17	y = y + m + (this.sum++);
18	System.out.println(B.x + " " + y + " " + sum);
19	}
20	}
21	class B extends A{
22	public static int x = 5, temp = -2;
23	public int sum = 16, y = 2;
24	public B(int p){
25	temp = temp + p + sum++;
26	}
27	public B(B a2){
28	super(a2);
29	sum = a2.sum;
30	x = a2.x + 2;
31	System.out.println(a2.sum+" "+this.x+" "+super.y);
32	}
33	public void methodB(int m){
34	y = y + this.y + m;
35	sum = x + y + super.sum;
36	System.out.println(super.y + " " + B.temp + " " + sum);
37	}
38	}

Driver code:

```
B a1 = new B(7);  
B a2 = new B(a1);  
a2.methodA(11);
```

Output:
