

There are a total of six problems. You have to solve all of them.

Problem 1 (CO5): Pumping Lemma (5 points)

Let $\Sigma = \{0, 1\}$. Consider the following language.

$$L = \{w \in \Sigma^* : w = 0^a 1^b 1^c 0^d, \text{ where } a + b = c + d \text{ and } a, b, c, d \geq 0\}$$

Use the pumping lemma to demonstrate that L is not regular language.

Problem 2 (CO3): Designing Context-Free Grammars (10 points)

Let $\Sigma = \{0, 1\}$. Consider the following languages. Recall that for a string w , $|w|$ denotes the length of w .

$$L_1 = \{w \in \Sigma^* : w \text{ is an even length palindrome}\}$$

$$L_2 = \{w \in \Sigma^* : \text{length of } w \text{ is even}\}$$

$$L_3 = \{x11y : x, y \in L_2, |x| = |y|\}$$

$$L_4 = L_1 \cap L_3$$

Now solve the following problems.

- Give a context-free grammar for the language L_1 . (3 points)
- Give a context-free grammar for the language L_3 . (4 points)
- Give a context-free grammar for the language L_4 . (3 point)

Problem 3 (CO4): The CYK Algorithm (5 points)

Apply the CYK algorithm to fill up the table for the string $aaaba$ using the following grammar. Here a and b are terminals, and the rest are variables.

$$\begin{aligned} S &\rightarrow BA \mid BC \\ A &\rightarrow AB \mid AC \mid a \\ B &\rightarrow CB \mid CC \mid b \\ C &\rightarrow CA \mid a \end{aligned}$$

1,5 {?}				
1,4 {S, A, B, C}	2,5 {?}			
1,3 {?}	2,4 {A, B, C}	3,5 {?}		
1,2 {A, B, C}	2,3 {A, B, C}	3,4 {?}	4,5 {S}	
1,1 {A, C}	2,2 {A, C}	3,3 {A, C}	4,4 {B}	5,5 {A, C}
a	a	a	b	a

Problem 4 (CO3): Constructing Pushdown Automata (10 points)

Let $\Sigma = \{0, 1\}$. Consider the following languages.

$$L_1 = \{w \mid w \text{ starts and ends with the same character}\}$$

$$L_2 = \{w \mid \text{the number of 0s in } w \text{ is not same as the number of 1s}\}$$

- (a) Give the state diagram of a pushdown automaton that recognizes L_1 . (4 points)
- (b) Give the state diagram of a pushdown automaton that recognizes L_2 . (6 points)

Problem 5 (CO3): Derivations, Parse Trees and Ambiguity (10 points)

Take a look at the grammar below and solve the following problems.

$$A \rightarrow 1A \mid 1C \mid 0B \mid 00A$$

$$B \rightarrow 0A \mid 1B \mid 00B$$

$$C \rightarrow 0C0 \mid 0C1 \mid 1C0 \mid 1C1 \mid \epsilon$$

- (a) Give a leftmost derivation for the string 01011001. (3 points)
- (b) Sketch the parse tree corresponding to the derivation you gave in (a). (2 points)
- (c) Demonstrate that the given grammar is ambiguous by showing two more parse trees (apart from the one you already found in (b)) for the same string. (3 points)
- (d) Find a string w of length six such that w has exactly one parse tree in the grammar above. (1 point)
- (e) Design an unambiguous Context Free Grammar for the language represented by the given ambiguous grammar. (1 point)

Problem 6 (CO4): Chomsky Normal Form (10 points)

Answer the following questions.

- (a) List the productions that violate the conditions of the Chomsky Normal Form (CNF) in the following grammar. (5 points)

$$M \rightarrow \epsilon \mid x \mid MN$$

$$N \rightarrow NC \mid yy \mid P$$

$$P \rightarrow QQ \mid z$$

$$Q \rightarrow yQ \mid \epsilon$$

- (b) Write down the additional rules that need to be added to the following grammar if the production $B \rightarrow \epsilon$ is removed. (3 points)

$$S \rightarrow Aa \mid BB$$

$$A \rightarrow CA \mid BaB \mid \epsilon$$

$$B \rightarrow AB \mid b \mid \epsilon$$

- (c) Write down the additional rules that need to be added to the following grammar if all the unit productions are removed. (2 points)

$$X \rightarrow 0X1Y1 \mid Y$$

$$Y \rightarrow XY \mid YY \mid Z$$

$$Z \rightarrow 1Z \mid Z$$

There are a total of six problems. You have to solve all of them.

Problem 1 (CO5): Pumping Lemma (5 points)

Let $\Sigma = \{0, 1\}$. Consider the following language.

$$L = \{w \in \Sigma^* : w = 1^a 0^b 0^c 1^d, \text{ where } a + d = b + c \text{ and } a, b, c, d \geq 0\}$$

Use the pumping lemma to demonstrate that L is not regular language.

Problem 2 (CO3): Designing Context-Free Grammars (10 points)

Let $\Sigma = \{0, 1\}$. Consider the following languages. Recall that for a string w , $|w|$ denotes the length of w .

$$L_1 = \{w \in \Sigma^* : w \text{ is a odd length palindrome}\}$$

$$L_2 = \{w \in \Sigma^* : \text{length of } w \text{ is multiple of two}\}$$

$$L_3 = \{x000y : x, y \in L_2, |x| = |y|\}$$

$$L_4 = L_1 \cap L_3$$

Now solve the following problems.

- Give a context-free grammar for the language L_1 . (3 points)
- Give a context-free grammar for the language L_3 . (4 points)
- Give a context-free grammar for the language L_4 . (3 point)

Problem 3 (CO4): The CYK Algorithm (5 points)

Apply the CYK algorithm to fill up the table for the string aabaa using the following grammar. Here a and b are terminals, and the rest are variables.

$$\begin{aligned} S &\rightarrow BA \mid BC \\ A &\rightarrow AB \mid AC \mid a \\ B &\rightarrow CB \mid CC \mid b \\ C &\rightarrow CA \mid a \end{aligned}$$

1,5 {?}				
1,4 {?}	2,5 {S,A}			
1,3 {?}	2,4 {S,A}	3,5 {?}		
1,2 {A,B,C}	2,3 {?}	3,4 {S}	4,5 {A,B,C}	
1,1 {A,C}	2,2 {A,C}	3,3 {B}	4,4 {A,C}	5,5 {A,C}
a	a	b	a	a

Problem 4 (CO3): Constructing Pushdown Automata (10 points)

Let $\Sigma = \{0, 1\}$. Consider the following languages.

$$L_1 = \{w \mid w \text{ starts and ends with the different character}\}$$

$$L_2 = \{w \mid \text{the number of 0s in } w \text{ is not same as the number of 1s}\}$$

- (a) Give the state diagram of a pushdown automaton that recognizes L_1 . (4 points)
- (b) Give the state diagram of a pushdown automaton that recognizes L_2 . (6 points)

Problem 5 (CO3): Derivations, Parse Trees and Ambiguity (10 points)

Take a look at the grammar below and solve the following problems.

$$A \rightarrow 1A \mid 0B \mid 00A$$

$$B \rightarrow 1B \mid 1C \mid 0A \mid 00B$$

$$C \rightarrow 0C0 \mid 0C1 \mid 1C0 \mid 1C1 \mid 0 \mid 1$$

- (a) Give a leftmost derivation for the string 10110010. (3 points)
- (b) Sketch the parse tree corresponding to the derivation you gave in (a). (2 points)
- (c) Demonstrate that the given grammar is ambiguous by showing two more parse trees (apart from the one you already found in (b)) for the same string. (3 points)
- (d) Find a string w of length six such that w has exactly one parse tree in the grammar above. (1 point)
- (e) Design an unambiguous Context Free Grammar for the language represented by the given ambiguous grammar. (1 point)

Problem 6 (CO4): Chomsky Normal Form (10 points)

Answer the following questions.

- (a) List the productions that violate the conditions of the Chomsky Normal Form (CNF) in the following grammar. (5 points)

$$P \rightarrow a \mid PR \mid \epsilon$$

$$Q \rightarrow bP \mid R$$

$$R \rightarrow QQ \mid aT$$

$$T \rightarrow QT \mid \epsilon$$

- (b) Write down the additional rules that need to be added to the following grammar if the production $A \rightarrow \epsilon$ is removed. (3 points)

$$S \rightarrow AA \mid bB$$

$$A \rightarrow CB \mid aA \mid \epsilon$$

$$B \rightarrow ABA \mid b \mid \epsilon$$

- (c) Write down the additional rules that need to be added to the following grammar if all the unit productions are removed. (2 points)

$$A \rightarrow 0A1B1 \mid C$$

$$B \rightarrow 1B \mid B$$

$$C \rightarrow BC \mid A \mid B$$