Lab 6 Setup Guide

Adding the OpenAI Agents SDK to your existing environment

1. Open the project folder

Open the folder containing Lab 6. If you are continuing in the same folder you used for Lab 3, Lab 4, or Lab 5, you can reuse its virtual environment and skip straight to Step 4.

2. Create a virtual environment with uv

If this is a fresh folder, open a terminal in Cursor (Ctrl+`) and run:

```
uv venv .venv
```

3. Activate the virtual environment

```
# macOS/Linux
source .venv/bin/activate

# Windows
.venv\Scripts\activate
```

4. Install the required packages

Lab 6 needs one new package on top of everything you have already installed: openai-agents, the OpenAI Agents SDK itself. requests and gradio are both carried over from Lab 5 and Lab 4, needed again here for the bonus trivia question tool and the chat interface.

```
uv pip install --upgrade openai openai-agents pypdf python-dotenv requests gradio
ipykernel
```

- **openai** the client library (includes AsyncAzureOpenAI, which this lab uses)
- **openai-agents** new this module — the OpenAI Agents SDK, imported in Python as agents
- **pypdf** reads your notes.pdf, same as Lab 3 and Lab 4
- **python-dotenv** loads your .env file
- **requests** calls the trivia API behind fetch_bonus_question_tool, same as Lab 5
- **gradio** the chat interface, same as Lab 4 and Lab 5
- **ipykernel** lets Cursor run the notebook using this venv

5. Select the notebook kernel

Open Lab 6.ipynb, click the kernel picker (top-right of the notebook), and choose the Python interpreter inside .venv.

6. Reuse (or create) your .env file

If you already have a .env file from an earlier lab in this same folder, you do not need a new one: Lab 6 only reads the same two Azure values you have been using all along.

```
AZURE_OPENAI_ENDPOINT=https://apim-azr-ue2-bgpt-prd-ucin.azure-api.net
AZURE_OPENAI_API_KEY=your-apim-subscription-key-here
```

Get these two values from your instructor or APIM admin if you do not already have them from an earlier lab.

Never commit this file.

7. Understand the one new setting: tracing

Unlike earlier labs, Lab 6 also calls set_tracing_disabled(True) before it builds the agent. The OpenAI Agents SDK's built-in tracing tries to send step-by-step data to OpenAI's own platform using a real OPENAI_API_KEY, and this course only ever provides Azure OpenAI credentials. This is not something you configure in .env: it is one line of Python already included in the Lab 6 notebook, and it is why Lab 6 does not need an OPENAI_API_KEY value at all.

8. Run the notebook

Run the cells top to bottom (▶ or Shift+Enter). The credential-loading cell should print that your endpoint and API key were both found, before any agent is built or run.

9. Confirm the SDK installed correctly

As a quick sanity check before you open the notebook, you can confirm the package imports cleanly from your activated environment:

```
python -c "import agents; print('openai-agents OK')"
```

If that prints openai-agents OK, you are ready to start Lab 6.