

DRAFT OGC API - Records - Part 1

Core

Open Geospatial Consortium

Submission Date: <yyyy-mm-dd>

Approval Date: <yyyy-mm-dd>

Publication Date: 2020-01-13

External identifier of this OGC® document: <http://www.opengis.net/doc/is/ogcapi-records-1/1.0>

Internal reference number of this OGC® document: 20-004

Version: 0.0.1

Category: OGC® Implementation Specification

Editors: Charles Heazel, Tom Kralidis, Panagiotis (Peter) A. Vretanos

DRAFT OGC API - Records - Part 1: Core

Copyright notice

Copyright © 2020 Open Geospatial Consortium

To obtain additional rights of use, visit <http://www.opengeospatial.org/legal/>

Warning

The OGC API - Records specification is still a work in progress. Please be aware that the specification document that is in this repository is not yet in a state that could be useful to anyone who has not been attending the bi-weekly standards working group (SWG) meetings and/or who is not actively working on the document. The SWG is working diligently to update the specification so please refer back to this readme periodically for any status updates.

This document is not an OGC Standard. This document is distributed for review and comment. This document is subject to change without notice and may not be referred to as an OGC Standard.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Document type: OGC® Implementation
Specification

Document stage: Draft

Document language: English

License Agreement

Permission is hereby granted by the Open Geospatial Consortium, ("Licensor"), free of charge and subject to the terms set forth below, to any person obtaining a copy of this Intellectual Property and any associated documentation, to deal in the Intellectual Property without restriction (except as set forth below), including without limitation the rights to implement, use, copy, modify, merge, publish, distribute, and/or sublicense copies of the Intellectual Property, and to permit persons to whom the Intellectual Property is furnished to do so, provided that all copyright notices on the intellectual property are retained intact and that each person to whom the Intellectual Property is furnished agrees to the terms of this Agreement.

If you modify the Intellectual Property, all copies of the modified Intellectual Property must include, in addition to the above copyright notice, a notice that the Intellectual Property includes modifications that have not been approved or adopted by LICENSOR.

THIS LICENSE IS A COPYRIGHT LICENSE ONLY, AND DOES NOT CONVEY ANY RIGHTS UNDER ANY PATENTS THAT MAY BE IN FORCE ANYWHERE IN THE WORLD.

THE INTELLECTUAL PROPERTY IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE DO NOT WARRANT THAT THE FUNCTIONS CONTAINED IN THE INTELLECTUAL PROPERTY WILL MEET YOUR REQUIREMENTS OR THAT THE OPERATION OF THE INTELLECTUAL PROPERTY WILL BE UNINTERRUPTED OR ERROR FREE. ANY USE OF THE INTELLECTUAL PROPERTY SHALL BE MADE ENTIRELY AT THE USER'S OWN RISK. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR ANY CONTRIBUTOR OF INTELLECTUAL PROPERTY RIGHTS TO THE INTELLECTUAL PROPERTY BE LIABLE FOR ANY CLAIM, OR ANY DIRECT, SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM ANY ALLEGED INFRINGEMENT OR ANY LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR UNDER ANY OTHER LEGAL THEORY, ARISING OUT OF OR IN CONNECTION WITH THE IMPLEMENTATION, USE, COMMERCIALIZATION OR PERFORMANCE OF THIS INTELLECTUAL PROPERTY.

This license is effective until terminated. You may terminate it at any time by destroying the Intellectual Property together with all copies in any form. The license will also terminate if you fail to comply with any term or condition of this Agreement. Except as provided in the following sentence, no such termination of this license shall require the termination of any third party end-user sublicense to the Intellectual Property which is in force as of the date of notice of such termination. In addition, should the Intellectual Property, or the operation of the Intellectual Property, infringe, or in LICENSOR's sole opinion be likely to infringe, any patent, copyright, trademark or other right of a third party, you agree that LICENSOR, in its sole discretion, may terminate this license without any compensation or liability to you, your licensees or any other party. You agree upon termination of any kind to destroy or cause to be destroyed the Intellectual Property together with all copies in any form, whether held by you or by any third party.

Except as contained in this notice, the name of LICENSOR or of any other holder of a copyright in all or part of the Intellectual Property shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Intellectual Property without prior written authorization of LICENSOR or such copyright holder. LICENSOR is and shall at all times be the sole entity that may authorize you or any third party to use certification marks, trademarks or other special designations to indicate compliance with any LICENSOR standards or specifications. This Agreement is governed by the laws of the Commonwealth of Massachusetts. The application to this Agreement of the United Nations Convention on Contracts for the International Sale of Goods is hereby expressly excluded. In the event any provision of this Agreement shall be deemed unenforceable, void or invalid, such provision shall be modified so as to make it valid and enforceable, and as so modified the entire Agreement shall remain in full force and effect. No decision, action or inaction by LICENSOR shall be construed to be a waiver of any rights or remedies available to it.

Table of Contents

1. Scope	8
2. Conformance	9
3. References	10
4. Terms and Definitions	12
4.1. Conformance Module; Conformance Test Module	12
4.2. Conformance Class; Conformance Test Class	12
4.3. dataset	12
4.4. Distribution	12
4.5. Executable Test Suite (ETS)	12
4.6. Recommendation	13
4.7. Requirement	13
4.8. Requirements Class	13
4.9. Requirements Module	13
4.10. Standardization Target	13
5. Conventions	14
5.1. Identifiers	14
5.2. Examples	14
5.3. Schema	14
5.4. UML Notation	14
5.5. Namespace Prefix Conventions	15
6. Overview	16
6.1. General	16
6.2. Record Schema	17
6.3. API Behavior Model	17
6.4. Search	17
6.5. Dependencies	18
7. Requirements Class "Core"	19
7.1. Overview	19
7.2. Dependencies	19
7.3. Platform	19
7.3.1. API landing page	20
7.3.1.1. Operation	20
7.3.1.2. Response	20
7.3.1.3. Error situations	21
7.3.2. API definition	21
7.3.2.1. Operation	21
7.3.2.2. Response	21
7.3.2.3. Error situations	22

7.3.3. Declaration of conformance classes	22
7.3.3.1. Operation	22
7.3.3.2. Response	22
7.3.3.3. Error situations	23
7.4. Collection Access	24
7.4.1. Record Collections	24
7.4.1.1. Operation	24
7.4.1.2. Response	24
7.4.1.3. Error situations	26
7.4.2. Collection Information	26
7.4.2.1. Operation	26
7.4.2.2. Response	26
7.4.2.3. Error situations	28
7.5. Records Access	28
7.5.1. Operation	28
7.5.2. Parameters	28
7.5.2.1. Overview	28
7.5.2.2. Parameter bbox	29
7.5.2.3. Parameter datetime	29
7.5.2.4. Parameter limit	30
7.5.2.5. Parameter type	30
7.5.2.6. Parameter q	31
7.5.2.7. Parameter externalids	32
7.5.2.8. Parameter sortby	33
7.5.2.9. Combinations of Filtering Parameters	35
7.5.3. Response	35
7.5.4. Paged Response	36
7.6. Record Access	37
7.6.1. Operation	37
7.6.2. Response	37
7.7. General	37
7.7.1. HTTP Response	37
7.7.2. HTTP status codes	38
8. Requirements Class "Collections"	40
8.1. Overview	40
8.2. Collections Metadata	40
8.3. Collection information	41
8.4. Examples	45
9. Requirements Class "OpenSearch"	46
9.1. Overview	46
9.2. Heading	46

10. Requirements Class JSON	47
10.1. Common	47
10.2. Record	48
11. Requirements Class HTML	49
11.1. Common	49
11.2. Record	50
12. Requirements Class XML	51
12.1. Common	51
12.2. Record	52
13. Requirements class "OpenAPI 3.0"	53
14. Media Types	54
14.1. HTML Encoding	54
14.2. JSON Encoding	54
14.2.1. GeoJSON	54
14.3. Media Types	54
14.4. Default Encodings	55
15. Security Considerations	56

i. Abstract

Blah, blah, blah, simple access API, blah, blah, blah, making resources discoverable , blah, blah, blah, associations, blah, blah, blah, core queryables, blah, blah, core query parameters, blah, blah, blah, OpenAPI to support developers, blah, blah, blah.

Table 1. Overview of resources, applicable HTTP methods and links to the document sections

Resource	Path	HTTP method	Document reference
Landing page	/	GET	API landing page
Conformance declaration	/conformance	GET	Declaration of Conformance Classes
Record collections	/collections	GET	Collection Access
Record collection	/collections/{catalogueId}	GET	Collection Information
Records	/collections/{catalogueId}/items	GET	Records Access
Record	/collections/{catalogueId}/items/{recordId}	GET	Record Access

ii. Keywords

The following are keywords to be used by search engines and document catalogues.

ogcdoc, OGC document, <tags separated by commas>

iii. Preface

NOTE

Insert Preface Text here. Give OGC specific commentary: describe the technical content, reason for document, history of the document and precursors, and plans for future work. > Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. The Open Geospatial Consortium shall not be held responsible for identifying any or all such patent rights.

Recipients of this document are requested to submit, with their comments, notification of any relevant patent claims or other intellectual property rights of which they may be aware that might be infringed by any implementation of the standard set forth in this document, and to provide supporting documentation.

iv. Submitting organizations

The following organizations submitted this Document to the Open Geospatial Consortium (OGC):

Organization name(s)

- CubeWerx Inc.

v. Submitters

All questions regarding this submission should be directed to the editor or the submitters:

Name	Affiliation
Panagiotis (Peter) A. Vretanos (editor)	CubeWerx Inc.
Tom Kralidis (editor)	Meteorological Service of Canada

Chapter 1. Scope

This document specifies the behaviour of an API that supports the ability to search collections of descriptive information, called records, about resources such as data collections, services, processes, styles, code lists and other related resources. Records represent resource characteristics that can be queried and presented for evaluation and further processing by both humans and software.

This specification defines a list of core queryables and a set of core query parameter organized into X conformance classes.

Chapter 2. Conformance

Conformance with this standard shall be checked using the tests specified in Annex A (normative) of this document. The framework, concepts, and methodology for testing, and the criteria to claim conformance, are specified in the OGC Compliance Testing Policies and Procedures and the OGC Compliance Testing web site.

The one Standardization Target for this standard is Web APIs.

OGC API - Common provides a common foundation for OGC API standards. Therefore, this standard should be viewed as an extension to API - Common. Conformance to this standard requires demonstrated conformance to the applicable Conformance Classes of API - Common.

This standard identifies eleven (11) Conformance Classes. The Conformance Classes implemented by an API are advertised through the [/conformance](#) path on the landing page. Each Conformance Class has an associated Requirements Class. The Requirements Classes define the functional requirements which will be tested through the associated Conformance Class.

The Requirements Classes for OGC API - Records are:

- **Core**
- **Collections**
- **OpenSearch**
- **JSON-Record**
- **ATOM-Record**
- **HTML-Record**

The *Core* Requirements Class is the minimal useful service interface for the OGC Records API. The requirements specified in this Requirements Class are mandatory for all implementations of API - Records. The core defines a set of mandatory properties (core queryables) that every record must contain, a set of core query parameters that support bounding box spatial queries, temporal queries, full text searching, parameters for sorting responses.

The *OpenSearch* Requirements Class defines the requirements to support query by OpenSearch clients.

The *Collections* Requirements Class defines requirements for making the [/collections](#) endpoint of any OGC Web API searchable.

The *JSON* Requirements Class defines the requirements for a GeoJSON (see RFC 7946) representation of a standard catalogue record.

The *ATOM* Requirements Class defines the requirements for an ATOM representation of a standard catalogue record.

The *HTML* Requirements Class defines the requirements for an HTML representation of a standard catalogue record.

Chapter 3. References

The following normative documents contain provisions that, through reference in this text, constitute provisions of this document. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. For undated references, the latest edition of the normative document referred to applies.

- Fielding, R., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., Berners-Lee, T.: IETF RFC 2616, **HTTP/1.1**, [RFC 2616](#)
- Rescorla, E.: IETF RFC 2818, **HTTP Over TLS**, [RFC 2818](#)
- Klyne, G., Newman, C.: IETF RFC 3339, **Date and Time on the Internet: Timestamps**, [RFC 3339](#)
- Berners-Lee, T., Fielding, R., Masinter, L.: IETF RFC 3986, **Uniform Resource Identifier (URI): Generic Syntax**, [RFC 3986](#)
- Duerst, M., Suignard, M.: IETF RFC 3987, **Internationalized Resource Identifiers (IRIs)**, [RFC 3987](#)
- Gregorio, J., Fielding, R., Hadley, M., Nottingham, M., Orchard, D.: IETF RFC 6570, **URI Template**, [RFC 6570](#)
- IETF RFC 7946: **The GeoJSON Format**, [eoJSON](#)
- Nottingham, M.: IETF RFC 8288, **Web Linking**, [RFC 8288](#)
- OGC 19-072: **OGC API (OAPI) Common Specification**, (Draft) [API Common](#)
- Open API Initiative: **OpenAPI Specification 3.0.2**, [OpenAPI](#)
- **Schema.org**: [Schema.org](#)
- W3C: **HTML5**, W3C Recommendation, [HTML5](#)
- W3C, **RDF 1.1 Semantics**, February 2014, <https://www.w3.org/TR/rdf11-mt/>
- W3C, **Extensible Markup Language (XML) 1.0 (Fifth Edition)**, November 2008, <https://www.w3.org/TR/xml/>
- OGC: OGC 07-036, Geography Markup Language (GML) Encoding Standard, version 3.2.1, 2007
- OGC: OGC 10-129r1, OGC® Geography Markup Language (GML) – Extended schemas and encoding rules (GML 3.3), version 3.3, 2012
- W3C: W3C Recommendation, XML Path Language (XPath), version 2, 2007
- W3C: W3C Recommendation, XML Linking Language (XLink), version 1, 2001
- W3C: W3C Working Draft, The app: URI scheme, 2013
- ISO/IEC: ISO/IEC 19757-3:2006 Information technology – Document Schema Definition Languages (DSDL) – Part 3: Rule-based validation – Schematron, 2006
- IETF: RFC 2183, 1997
- IETF: RFC 2387, 1998
- IETF: RFC 2392, 1998 [18] IETF: RFC 3986, 2005 [19] IETF: RFC 7159, The JavaScript Object Notation (JSON) Data Interchange Format <https://www.ietf.org/rfc/rfc7159.txt>, 2014

- W3C: W3C JSON-LD 1.0, A JSON-based Serialization for Linked Data. <http://www.w3.org/TR/json-ld/>, 2014
- W3C: W3C JSON-LD 1.0 Processing Algorithms and API. <http://www.w3.org/TR/json-ld-api>, 2014
- W3C: W3C RDF 1.1 Concepts and Abstract Syntax. <https://www.w3.org/TR/2014/REC-rdf11-concepts-20140225/>, 2014

Chapter 4. Terms and Definitions

This document uses the terms defined in Sub-clause 5 of [OGC API - Common Part 1](#) (OGC 19-072), which is based on the ISO/IEC Directives, Part 2, Rules for the structure and drafting of International Standards. In particular, the word “shall” (not “must”) is the verb form used to indicate a requirement to be strictly followed to conform to this standard.

For the purposes of this document, the following additional terms and definitions apply.

4.1. Conformance Module; Conformance Test Module

set of related tests, all within a single conformance test class ([OGC 08-131](#))

NOTE: When no ambiguity is possible, the word ‘test’ may be omitted. i.e. conformance test module is the same as conformance module. Conformance modules may be nested in a hierarchical way.

4.2. Conformance Class; Conformance Test Class

set of conformance test modules that must be applied to receive a single certificate of conformance ([OGC 08-131](#))

NOTE: When no ambiguity is possible, the word _test_ may be left out, so conformance test class maybe called a conformance class.

4.3. dataset

collection of data, published or curated by a single agent, and available for access or download in one or more formats (DCAT)

4.4. Distribution

represents an accessible form of a **dataset** (DCAT)

EXAMPLE: a downloadable file, an RSS feed or a web service that provides the data.

4.5. Executable Test Suite (ETS)

A set of code (e.g. Java and CTL) that provides runtime tests for the assertions defined by the ATS. Test data required to do the tests are part of the ETS ([OGC 08-134](#))

4.6. Recommendation

expression in the content of a document conveying that among several possibilities one is recommended as particularly suitable, without mentioning or excluding others, or that a certain course of action is preferred but not necessarily required, or that (in the negative form) a certain possibility or course of action is deprecated but not prohibited ([OGC 08-131](#))

4.7. Requirement

expression in the content of a document conveying criteria to be fulfilled if compliance with the document is to be claimed and from which no deviation is permitted ([OGC 08-131](#))

4.8. Requirements Class

aggregate of all requirement modules that must all be satisfied to satisfy a conformance test class ([OGC 08-131](#))

4.9. Requirements Module

aggregate of requirements and recommendations of a specification against a single standardization target type ([OGC 08-131](#))

4.10. Standardization Target

entity to which some requirements of a standard apply ([OGC 08-131](#))

NOTE: The standardization target is the entity which may receive a certificate of conformance for a requirements class.

Chapter 5. Conventions

The following conventions will be used in this document. Examples of conventions are symbols, abbreviations, use of XML schema, or special notes regarding how to read the document.

5.1. Identifiers

The normative provisions in this standard are denoted by the URI

<http://www.opengis.net/spec/ogcapi-records-1/1.0>

All requirements and conformance tests that appear in this document are denoted by partial URIs which are relative to this base.

5.2. Examples

Most of the examples provided in this standard are encoded in JSON. JSON was chosen because it is widely understood by implementers and easy to include in a text document. This convention should NOT be interpreted as a requirement that JSON must be used. Implementors are free to use any format they desire as long as there is a Conformance Class for that format and the API advertises its support for that Conformance Class.

5.3. Schema

JSON Schema is used throughout this standard to define the structure of resources. These schema are typically represented using YAML encoding. This convention is for the ease of the user. It does not prohibit the use of another schema language or encoding. Nor does it indicate that JSON schema is required. Implementations should use a schema language and encoding appropriate for the format of the resource.

5.4. UML Notation

Diagrams using the Unified Modeling Language (UML) adhere to the following conventions:

- UML elements having a package name of “GML” are those defined in the UML model of GML 3.2.1
- UML elements having a package name of “SWE Common” are those defined in the UML model of SWE Common 2.0
- UML elements not qualified with a package name, or with “CIS”, are those defined in this standard.

Further, in any class where an attribute name or association role name is identical to a name in some superclass the local definition overrides the superclass definition.

5.5. Namespace Prefix Conventions

UML diagrams and XML code fragments adhere to the namespace conventions shown in [Table 2](#). The namespace prefixes used in this document are not normative and are merely chosen for convenience. The namespaces to which the prefixes correspond are normative, however.

Table 2. Namespace mapping conventions

UML prefix	GML prefix	Namespace URL	Description
GML	gml	http://www.opengis.net/gml/3.2	GML 3.2.1
GML33	gml33	http://www.opengis.net/gml/3.3	GML 3.3

Chapter 6. Overview

6.1. General

The OGC API family of standards enable access to resources using the HTTP protocol and its' associated operations (GET, PUT, POST, etc.). OGC API - Common defines a set of features which are applicable to all OGC APIs. Other OGC standards extend API - Common with features specific to a resource type. This OGC API - Records standard defines an API with two goals:

1. Provide modern API patterns and encodings to facilitate further lowering the barrier to finding the existence of spatial resources on the Web.
2. Provide functionality comparable to that of the [OGC Catalogue Service \(CSW\) standard](#).

Resources exposed through an OGC API may be accessed through a Universal Resource Identifier (URI). URIs are composed of three sections:

- Service Offering: The service endpoint (subsequently referred to as Base URI or {root})
- Access Paths: Unique paths to Resources
- Query: Parameters to adjust the representation of a Resource or Resources like encoding format or subsetting

Some resources are also accessible through links on previously accessed resources. Unique relation types are used for each resource.

[Table 3](#) summarizes the access paths and relation types defined in this standard.

Table 3. Record API Paths

Path Template	Relation	Resource
Common		
{root}/	none	Landing page
{root}/api	service-desc or service-doc	API Description (optional)
{root}/conformance	conformance	Conformance Classes
{root}/collections	data	Metadata describing the spatial collections available from this API.
{root}/collections/{collectionid}		Metadata describing the collection which has the unique identifier {collectionid}
Records		
{root}/collections/{collectionid}/items	items	Search results based on querying the service for records satisfying 0..n query parameters.

Path Template	Relation	Resource
{root}/collections/{collectionid}/items/{recordid}	item	Record of metadata which has the unique identifier {recordid} .

Where:

- {root} = Base URI for the API server
- {collectionid} = an identifier for a specific collection
- {recordid} = an identifier for a specific record within a collection

6.2. Record Schema

6.3. API Behavior Model

The Record API is designed to be compatible but not conformant with the OGC Catalogue Service for the Web (CSW). This allows API - Record and CSW implementations to co-exist in a single processing environment.

NOTE Replace the following with a discussion of CSW and API - Record

[OGC Catalogue Service standard version 3](#) provides an abstract core model of metadata (data about data) describing a number of different information types (data, services, styles, processes, etc.) on which the classic operations GetCapabilities, DescribeRecord, GetRecords, and GetRecordById can be explained naturally. This model consists of a 1..n catalogue collections residing in a CSW backend repository. It holds service metadata describing service qualities (identification, contact, operations, filtering capabilities, etc.). At its heart, a catalogue may provide discovery services to any number of metadata repositories. The core catalogue model is based on an extension of Dublin Core (CSW Record). Application profiles can be developed to target specific metadata information models (such as ISO 19115/19139, etc.).

Discussion has shown that the API model also assumes underlying service and object descriptions, so a convergence seems possible. In any case, it will be advantageous to have a similar "mental model" of the server store organization on hand to explain the various functionalities introduced below.

6.4. Search

TBD: Want to include a discussion about the levels of search that a catalogue might offer.

- Level 1: bbox, datetime, q, type, externalIds
- Level 2: OpenSearch
- Level 3: CQL

6.5. Dependencies

The OGC API - Records standard is an extension of the OGC API - Common standard. Therefore, an implementation of OGC API - Records must first satisfy the appropriate Requirements Classes from API - Common. [Table 4](#) Identifies the OGC API - Common Requirements Classes which are applicable to each section of this Standard. Instructions on when and how to apply these Requirements Classes are provided in each section.

Table 4. Mapping API - Records Sections to API - Common Requirements Classes

API - Record Section	API - Common Requirements Class
API Landing Page	http://www.opengis.net/spec/ogcapi_common-1/1.0/req/core
API Definition	http://www.opengis.net/spec/ogcapi_common-1/1.0/req/core
Declaration of Conformance Classes	http://www.opengis.net/spec/ogcapi_common-1/1.0/req/core
Collections	http://www.opengis.net/spec/ogcapi_common-1/1.0/req/collections
OpenAPI 3.0	http://www.opengis.net/spec/ogcapi_common-1/1.0/req/oas30
JSON	http://www.opengis.net/spec/ogcapi_common-1/1.0/req/geojson
HTML	http://www.opengis.net/spec/ogcapi_common-1/1.0/req/html

Chapter 7. Requirements Class "Core"

7.1. Overview

Requirements Class	
http://www.opengis.net/spec/ogcapi-records-1/1.0/req/core	
Target type	Web API
Dependency	http://www.opengis.net/spec/ogcapi_common-1/1.0/req/core
Dependency	http://www.opengis.net/spec/ogcapi_common-1/1.0/req/collections

The **Core** Requirements Class defines the requirements for locating, understanding, and accessing Record resources. The **Core** Requirements Class is presented in five sections:

1. **API Platform**: a set of common capabilities
2. **Collection Access**: operations for accessing information about collections of records
3. **Records Access**: operations for accessing record resources
4. **Record Access**: operations for accessing a single record
5. **General**: general principles for use with this standard

7.2. Dependencies

The OGC API - Records standard is an extension of the OGC API - Common standard. Therefore, an implementation of API - Records must first satisfy the appropriate Requirements Classes from API - Common.

Requirement 1	/req/core/api-common
The API implementation SHALL demonstrate conformance with the following Requirements Classes of the OGC API - Common version 1.0 Standard.	
A	http://www.opengis.net/spec/ogcapi_common-1/1.0/req/core
B	http://www.opengis.net/spec/ogcapi_common-1/1.0/req/collections

7.3. Platform

API - Common defines a set of common capabilities which are applicable to any OGC Web API. Those capabilities provide the platform upon which resource-specific APIs can be built. This section describes those capabilities and any modifications needed to better support Record resources.

7.3.1. API landing page

The landing page provides links to start exploration of the resources offered by an API. Its most important component is a list of links. OGC API - Common already requires some common links. Those links are sufficient for this standard.

Table 5. Dependencies

http://www.opengis.net/spec/ogcapi_common-1/1.0/req/core

7.3.1.1. Operation

The **Landing Page** operation is defined in the **Core** conformance class of API - Common. No modifications are needed to support **Record** resources. The **Core** conformance class specifies only one way of performing this operation:

1. Issue a **GET** request on the **{root}/** path

Support for **GET** on the **{root}/** path is required by API - Common.

7.3.1.2. Response

A successful response to the **Landing Page** operation is defined in API - Common. The schema for this resource is provided in **Landing Page Response Schema**.

Landing Page Response Schema

```
type: object
required:
  - links
properties:
  title:
    description: The title of the API
    type: string
  description:
    description: A textual description of the API
    type: string
  links:
    description: Links to the resources exposed through this API.
    type: array
    items:
      $ref: link.yaml
```

The following JSON fragment is an example of a response to an OGC API - Records Landing Page operation.

```
{
  "links": [
    { "href": "http://data.example.org/",
      "rel": "self", "type": "application/json", "title": "this document" },
    { "href": "http://data.example.org/api",
      "rel": "service-desc", "type": "application/openapi+json;version=3.0", "title":
"the API definition" },
    { "href": "http://data.example.org/conformance",
      "rel": "conformance", "type": "application/json", "title": "OGC conformance
classes implemented by this API" },
    { "href": "http://data.example.org/collections",
      "rel": "data", "type": "application/json", "title": "Metadata about the resource
collections" }
  ]
}
```

7.3.1.3. Error situations

The requirements for handling unsuccessful requests are provided in [HTTP Response](#). General guidance on HTTP status codes and how they should be handled is provided in [HTTP status codes](#).

7.3.2. API definition

Every API is required to provide a definition document that describes the capabilities of that API. This definition document can be used by developers to understand the API, by software clients to connect to the server, or by development tools to support the implementation of servers and clients.

Table 6. Dependencies

http://www.opengis.net/spec/ogcapi_common-1/1.0/req/core

7.3.2.1. Operation

This operation is defined in the **Core** conformance class of API - Common. No modifications are needed to support **Records** resources. The **Core** conformance class describes two ways of performing this operation:

1. Issue a **GET** request on the **{root}/api** path
2. Follow the **service-desc** or **service-doc** link on the landing page

Only the link is required by API - Common.

7.3.2.2. Response

A successful response to the API Definition request is a resource which documents the design of the API. API - Common leaves the selection of format for the API Definition response to the API implementor. However, the options are limited to those which have been defined in the API - Common standard. At this time OpenAPI 3.0 is the only option provided.

7.3.2.3. Error situations

The requirements for handling unsuccessful requests are provided in [HTTP Response](#). General guidance on HTTP status codes and how they should be handled is provided in [HTTP status codes](#).

7.3.3. Declaration of conformance classes

To support "generic" clients that want to access multiple OGC API standards and extensions - and not "just" a specific API / server, the API has to declare the conformance classes it claims to have implemented.

Table 7. Dependencies

http://www.opengis.net/spec/ogcapi_common-1/1.0/req/core

7.3.3.1. Operation

This operation is defined in the **Core** conformance class of API - Common. No modifications are needed to support **Records** resources. The **Core** conformance class describes two ways of performing this operation:

1. Issue a **GET** request on the **{root}/conformance** path
2. Follow the **conformance** link on the landing page

Both techniques are required by API - Common.

7.3.3.2. Response

A successful response to the Conformance operation is a list of URLs. Each URL identifies an OGC Conformance Class for which this API claims conformance. The schema for this resource is defined in API - Common and provided for reference in [Conformance Response Schema](#).

Requirement 2	/req/core/conformance
The list of Conformance Classes advertised by the API SHALL include:	
A	http://www.opengis.net/spec/ogcapi-common-1/1.0/conf/core
B	http://www.opengis.net/spec/ogcapi-common-1/1.0/conf/collections
C	http://www.opengis.net/spec/ogcapi-records-1/1.0/conf/core

Permission 1	/per/core/additional-conformance
The list of Conformance Classes advertised by the API may additionally include:	
A	http://www.opengis.net/spec/ogcapi-records-1/1.0/req/html

B	http://www.opengis.net/spec/ogcapi-records-1/1.0/req/json
C	http://www.opengis.net/spec/ogcapi-records-1/1.0/req/opensearch
D	http://www.opengis.net/spec/ogcapi-records-1/1.0/req/atom
E	http://www.opengis.net/spec/ogcapi-records-1/1.0/req/collections
F	http://www.opengis.net/spec/ogcapi-records/1.0/req/oas30

Conformance Response Schema

```

type: object
required:
  - conformsTo
properties:
  conformsTo:
    type: array
    items:
      type: string
      example: "http://www.opengis.net/spec/ogcapi-common-1/1.0/conf/core"

```

The following JSON fragment is an example of a response to an OGC API - Records conformance operation.

Conformance Information Example

```

{
  "conformsTo": [
    "http://www.opengis.net/spec/ogcapi-common-1/1.0/conf/core",
    "http://www.opengis.net/spec/ogcapi-common-1/1.0/conf/collections",
    "http://www.opengis.net/spec/ogcapi-common-1/1.0/conf/oas3",
    "http://www.opengis.net/spec/ogcapi-records-1/1.0/conf/core",
    "http://www.opengis.net/spec/ogcapi-records-1/1.0/req/oas30",
    "http://www.opengis.net/spec/ogcapi-records-1/1.0/req/html",
    "http://www.opengis.net/spec/ogcapi-records-1/1.0/req/json",
    "http://www.opengis.net/spec/ogcapi-records-1/1.0/req/opensearch",
    "http://www.opengis.net/spec/ogcapi-records-1/1.0/req/atom"
  ]
}

```

7.3.3.3. Error situations

The requirements for handling unsuccessful requests are provided in [HTTP Response](#). General guidance on HTTP status codes and how they should be handled is provided in [HTTP status codes](#).

7.4. Collection Access

API - Common starts with the assumption that spatial resources are organized into collections. An API will expose one or more collections. The API - Common Collections Conformance Class defines how to organize and provide access to a collection of collections.

This standard extends the API - Common **Collections** conformance class to support collections of records, then extends that class to support **Record** unique capabilities.

7.4.1. Record Collections

The **Collections** operation returns a set of metadata which describes the collections available from this API.

Table 8. Dependencies

http://www.opengis.net/spec/ogcapi_common-1/1.0/req/collections

7.4.1.1. Operation

This operation is defined in the **Collections** conformance class of API - Common. No modifications are needed to support **Record** resources. The **Collections** conformance class describes two ways of performing this operation:

1. Issue a **GET** request on **{root}/collections** path
2. Follow the **data** link on the landing page

Support for both the **{root}/collections** path and the **data** link is required by API - Common.

7.4.1.2. Response

A successful response to the **Collections Operation** is a document which includes summary metadata for each collection accessible through the API.

Collections Response Schema

```
type: object
required:
  - links
  - collections
properties:
  links:
    type: array
    items:
      $ref: link.yaml
  collections:
    type: array
    items:
      $ref: collectionInfo.yaml
```

The following JSON fragment is an example of a response to an OGC API - Records Collections operation.

Collections Example

```
{
  "links": [
    {
      "href":
"http://www.pvretano.com/cubewerx/cubeserv/default/wrs/4.0/collections?f=application%2Fjson",
      "rel": "self",
      "type": "application/json",
      "title": "this document"
    },
    {
      "href":
"http://www.pvretano.com/cubewerx/cubeserv/default/wrs/4.0/collections?f=text%2Fxml",
      "rel": "alternate",
      "type": "text/xml",
      "title": "this document as XML"
    },
    {
      "href":
"http://www.pvretano.com/cubewerx/cubeserv/default/wrs/4.0/collections?f=text%2Fhtml",
      "rel": "alternate",
      "type": "text/html",
      "title": "this document as HTML"
    }
  ],
  "collections": [
    {
      "id": "radarsat2cat",
      "type": "catalogue",
      "title": "CubeWerx RADARSAT-2 Catalogue",
      "description": "A sample catalogue of RADARSAT-2 products stored in S3 on AWS.",
      "links": [
        {
          "href":
"http://www.pvretano.com/cubewerx/cubeserv/default/csw/4.0/collections/s1tepcat",
          "rel": "collection",
          "title": "Root URL for this record collection. At this endpoint you can retrieve a description of this catalogue as well as hypermedia controls that allow you to query the catalogue."
        }
      ]
    },
    {
      "id": "sentinel1cat",
      "type": "catalogue",
      "title": "CubeWerx Sentinel-1 Catalogue",

```

```

    "description": "A sample catalogue of Sentinel-1 products stored in S3 on AWS.",
    "links": [
      {
        "href":
"http://www.pvretano.com/cubewerx/cubeserv/default/csw/4.0/collections/sentinel1cat",
        "rel": "collection",
        "title": "Root URL for this record collection. At this endpoint you can
retrieve a description of this catalogue as well as hypermedia controls that allow you
to query the catalogue."
      }
    ]
  }
]
}

```

7.4.1.3. Error situations

The requirements for handling unsuccessful requests are provided in [HTTP Response](#). General guidance on HTTP status codes and how they should be handled is provided in [HTTP status codes](#).

7.4.2. Collection Information

Collection Information is the set of metadata which describes a single collection. An abbreviated copy of this information is returned for each Collection in the `/collections` response.

Table 9. Dependencies

http://www.opengis.net/spec/ogcapi_common-1/1.0/req/collections

7.4.2.1. Operation

This operation is defined in the `Collections` conformance class of API - Common. No modifications are required to support `Records` resources.

1. Issue a `GET` request on the `{root}/collections/{collectionid}` path

The `{collectionid}` parameter is the unique identifier for a single collection on the API. The list of valid values for `{collectionid}` is provided in the `/collections` response.

Support for the `/collections/{collectionid}` path is required by API - Common.

7.4.2.2. Response

A successful response to the Collection Operation is a set of metadata which describes the collection identified by the `{collectionid}` parameter.

```
type: object
required:
  - id
  - links
properties:
  id:
    type: string
    example: address
  title:
    type: string
    example: address
  description:
    type: string
    example: An address.
  links:
    type: array
    items:
      $ref: link.yaml
    example:
      - href: http://data.example.com/buildings
        rel: item
      - href: http://example.com/concepts/buildings.html
        rel: describedBy
        type: text/html
  extent:
    $ref: extent.yaml
  itemType:
    description: indicator about the type of the items in the collection (the default
value is 'unknown').
    type: string
    default: unknown
  crs:
    description: the list of coordinate reference systems supported by the API; the
first item is the default coordinate reference system
    type: array
    items:
      type: string
    default:
      - http://www.opengis.net/def/crs/OGC/1.3/CRS84
    example:
      - http://www.opengis.net/def/crs/OGC/1.3/CRS84
      - http://www.opengis.net/def/crs/EPSG/0/4326
```

The following JSON fragment is an example of a response to an OGC API - Records Collection Information operation.

```
{
  "recordid": "sentinel1cat",
  "type": "catalogue",
  "title": "CubeWerx Sentinel-1 Catalogue",
  "description": "A sample catalogue of Sentinel-1 products stored in S3 on AWS.",
  "links": [
    {
      "href":
"http://www.pvretano.com/cubewerx/cubeserv/default/csw/4.0/collections/sentinel1cat",
      "rel": "collection",
      "title": "Root URL for this record collection.  At this endpoint you can
retrieve a description of this catalogue as well as hypermedia controls that allow you
to query the catalogue."
    }
  ]
}
```

7.4.2.3. Error situations

The requirements for handling unsuccessful requests are provided in [HTTP Response](#). General guidance on HTTP status codes and how they should be handled is provided in [HTTP status codes](#).

7.5. Records Access

7.5.1. Operation

Requirement 3	/req/core/rc-op
A	A Records API implementation SHALL comply with the API - Common requirement /req/collections/rc-op .
B	For API - Records, the API - Common /req/collections/rc-op requirement SHALL only apply to collections where the <code>itemType</code> is specified as <code>records</code> .

7.5.2. Parameters

7.5.2.1. Overview

The following tables list the set mandatory query parameters.

Table 10. Table of Query Parameters

bbox	A bounding box. If the spatial extent of the record intersects the specified bounding box then the record shall be presented in the response document.
datetime	A time instance or time period. If the temporal extent of the record intersects the specified data/time value then the record shall be presented in the response document.
limit	The number of records to be presented in a response document.
type	A resource type. Only records of the specified type shall be presented in the response document.
q	A space-separated list of search terms. If any server-chosen text field in the record contains 1 or more of the terms listed then this records hall appear in the response set.
externalIds	A comma-separated list of external identifiers. Only records with the specified names shall appear in the response document.
sortby	A comma-separated list of queryables specifying how the records in the response shall be ordered for presentation.

The query parameters **bbox**, **datetime** and **limit** are inherited from API -Common. All requirements and recommendations in API - Common regarding these parameters also apply for API - Records.

The query parameters **type**, **q**, **externalids** and **sortby** are specific to API - Records.

This clause provides a brief description of the query parameters inherited from API - Common and requirements for the API - Records-specific parameters.

7.5.2.2. Parameter **bbox**

The Bounding Box (bbox) parameter is defined in API - Common. The following requirement governs use of that parameter in a Records API.

Requirement 4	/req/core/rc-bbox-parameter
A	A Records API SHALL support the Bounding Box (bbox) parameter for /collections/{catalogueId} requests.
B	Requests which include the Bounding Box parameter SHALL comply with API - Common requirement /req/core/rc-bbox-definition .
C	Responses to Bounding Box requests SHALL comply with API - Common requirement /req/core/rc-bbox-response .

7.5.2.3. Parameter **datetime**

The Date-Time (datetime) parameter is defined in API - Common. The following requirement governs use of that parameter in a Records API.

Requirement 5	/req/core/rc-datetime-parameter
A	A Records API SHALL support the Date-Time (datetime) parameter for <code>/collections</code> and <code>/collections/{collectionid}</code> requests.
B	Requests which include the Date-Time parameter SHALL comply with API - Common requirement <code>/req/core/rc-time-definition</code> .
C	Responses to Date-Time requests SHALL comply with API - Common requirement <code>/req/core/rc-time-response</code> .

7.5.2.4. Parameter limit

The limit parameter is defined in API - Common. The following requirement governs use of that parameter in a Records API.

Requirement 6	/req/core/rc-limit-parameter
A	A Records API SHALL support the Limit (limit) parameter for <code>/collections</code> and <code>/collections/{collectionid}</code> requests.
B	Requests which include the Limit parameter SHALL comply with API - Common requirement <code>/req/core/rc-limit-definition</code> .
C	Responses to Limit requests SHALL comply with API - Common requirements: <ul style="list-style-type: none"> • <code>/req/core/rc-limit-response</code> • <code>/req/core/rc-numberReturned</code> • <code>/req/core/rc-numberMatched</code>

7.5.2.5. Parameter type

Requirement 7	/req/core/rc-type-definition
----------------------	-------------------------------------

A	<p>The operation SHALL support a parameter type with the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: type in: query required: false schema: type: string style: form explode: false </pre>
---	--

Requirement 8	/req/core/rc-type-response
A	If the type parameter is provided by the client, only records where type of the resource (i.e. record property type) exactly matches the specified value SHALL be included in the result set.

7.5.2.6. Parameter q

Requirement 9	/req/core/rc-q-definition
A	<p>The operation SHALL support a parameter q with the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: q in: query required: false schema: type: array minItems: 1 maxItems: 10 items: type: string style: spaceDelimited explode: false </pre>
B	The query parameter req_core_rc-q-case-definition may be used concurrently with the q parameter to qualify the search as case sensitive or case in-sensitive.
Requirement 10	/req/core/rc-q-case-definition

A	<p>The operation SHALL support a parameter q-case with the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: q-case in: query required: false schema: type: boolean default: false style: form explode: false </pre>
B	<p>A value of true indicates that the search SHALL be case sensitive; a value of false indicates that the search shall be case insensitive.</p>

Requirement 11	/req/core/rc-q-response
A	<p>If the q parameter is provided by the client, only records whose text fields contains one or more of the specified search terms SHALL be in the result set.</p>
B	<p>The specific set of text keys/fields/properties of a record to which the q operator be applied is left to the discretion of the implementation.</p>

7.5.2.7. Parameter externalids

Requirement 12	/req/core/rc-extids-definition
-----------------------	---------------------------------------

A	<p>The operation SHALL support a parameter externalids with the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: externalids in: query required: false schema: type: array minItems: 1 maxItems: 10 items: type: string style: form explode: false </pre>
---	--

Requirement 13	/req/core/rc-extids-response
A	<p>If the externalids parameter is provided by the client, only records whose external identifiers (i.e. record property externalId) exactly match one of the values specified for this parameter SHALL be included in the result set.</p>

7.5.2.8. Parameter sortby

Requirement 14	/req/core/rc-sortby-definition
A	<p>The operation SHALL support a parameter sortby with the following characteristics (using an OpenAPI Specification 3.0 fragment):</p> <pre> name: sortby in: query required: false schema: type: array minItems: 1 items: type: string pattern: [A-Za-z_][A-Za-z_0-9]*[:]?([Aa][Ss][Cc] [Dd][Ee][Ss][Cc])? style: form explode: false </pre>

B	The default sort order SHALL be ascending.
---	--

Requirement 15	/req/core/rc-sortby-response
A	If the sortby parameter is specified, then the records in a response SHALL be ordered by the keys and sort directions (i.e. asc or desc) specified.
B	The specific set of keys that may used for sorting SHALL be specified by the /collections/{catalogueId}/sortables resource.

Requirement 16	/req/core/sortables-op
A	For every collection (path /collections/{catalogueId}), the server SHALL support the HTTP GET operation at the path /collections/{catalogueId}/sortables .
B	The parameter catalogue is each id property in the collections response (JSONPath: \$.collections[*].id) where the item type is specified as record .

Requirement 17	/req/core/sortables-success
A	A successful execution of the operation SHALL be reported as a response with a HTTP status code 200 .
B	<p>The content of that response SHALL be based upon the following OpenAPI 3.0 schema:</p> <pre> type: array items: type: object required: - name properties: name: type: string title: type: string description: type: string </pre>

sortBy Example

```
.../collections/mycat/items?...&sortBy=modified:desc,recordid&...
```

sortBy Extent Example

```
.../collections/mycat/items?...&sortBy=extent:asc&...
```

7.5.2.9. Combinations of Filtering Parameters

Any combination of query parameters from the [Table of Query Parameters](#) may be specified for filtering.

Any combination of **bbox**, **datetime**, **q** and **limit** parameters for filtering on Record properties is allowed. Note that the requirements on these parameters imply that only records matching all the predicates are in the result set; i.e., the logical operator between the predicates is 'AND' (exclusive).

7.5.3. Response

Requirement 18	/req/core/rc-response
A	Each record in the response SHALL contain the mandatory properties listed in the Table of Core Queryables .

Permission 2	/per/core/additional-properties
A	Each record in the response MAY contain zero or more of the optional properties listed in the Table of Core Queryables .
B	Each record in the response MAY contain any number of additional domain-specific properties but the meaning of those properties is not specified in this document.

Table 11. Table of Core Queryables

Queryables	Requirement	Description
id	M	A unique record identifier assigned by the server.
created	M	The date this record was created in the server.
changed	M	The most recent date on which the record was changed.
title	M	A human-readable name given to the resource.

Queryables	Requirement	Description
description	M	A free-text description of the resource.
keywords	M	A list of keywords or tag associated with the resource.
type	M	The nature or genre of the resource.
language	O	This refers to the natural language used for textual values (i.e. titles, descriptions, etc) of a resource.
externalid	O	An identifier for the resource assigned by an external entity.
modified	O	The more recent date on which the resource was changed.
publisher	O	The entity making the resource available.
themes	O	A knowledge organization system used to classify the resource.
formats	O	A list of available distributions for the resource.
contactpoint	O	An entity to contact about the resource.
license	O	A legal document under which the resource is made available.
rights	O	A statement that concerns all rights not addressed by the license such as a copyright statement.
extent	O	The spatio-temporal coverage of the resource.
links	O	A list of links for navigating the API.
associations	O	A list of links for accessing the resource or links to other resources associated with this resource.

7.5.4. Paged Response

One consequence of the Limit parameter is that the full result set is not delivered to the user. However, users frequently want to know how big the result set is and how to access the rest of it. The following requirement add information to the response to address that need.

Requirement 19	/req/core/rc-paged-response
-----------------------	------------------------------------

A	<p>Responses to a filtered operation that only return a portion of the full selected resource set SHALL comply with API - Common requirements:</p> <ul style="list-style-type: none"> • <code>/req/core/rc-response</code> • <code>/req/core/rc-links</code> • <code>/req/core/rc-rel-type</code> • <code>/req/core/rc-timestamp</code> • <code>/req/core/rc-numberMatched</code> • <code>/req/core/rc-numberReturned</code>
---	--

7.6. Record Access

7.6.1. Operation

Requirement 20	<code>/req/core/record-op</code>
A	For every record in a record collection (path <code>/collections/{catalogueId}</code>), the server SHALL support the HTTP GET operation at the path <code>/collections/{catalogueId}/items/{recordId}</code> .
B	The parameter <code>catalogueId</code> is each <code>id</code> property in the collections response (JSONPath: <code>\$.collections[*].id</code>) where the item type is specified as <code>record</code> . <code>recordId</code> is a local identifier of the record.

7.6.2. Response

Requirement 21	<code>/req/core/record-success</code>
A	A successful execution of the operation SHALL be reported as a response with a HTTP status code <code>200</code> .

7.7. General

7.7.1. HTTP Response

Each HTTP request shall result in a response that meets the following requirement.

Requirement 22	<code>/req/core/http-response</code>
----------------	--------------------------------------

A	An HTTP operation SHALL return a response which includes a status code and an optional description elements.
B	If the status code is not equal to 200, then the description element SHALL be populated.

The YAML schema for these results is provided in [HTTP Response Schema](#).

HTTP Response Schema

```

type: object
required:
  - code
properties:
  code:
    type: string
  description:
    type: string

```

7.7.2. HTTP status codes

The **Status Codes** listed in [Table 7](#) are of particular relevance to implementors of this standard. Status codes 200, 400, and 404 are called out in API requirements. Therefore, support for these status codes is mandatory for all compliant implementations. The remainder of the status codes in [Table 7](#) are not mandatory, but are important for the implementation of a well functioning API. Support for these status codes is strongly encouraged for both client and server implementations.

Table 12. Typical HTTP status codes

Status code	Description
200	A successful request.
304	An entity tag was provided in the request and the resource has not been changed since the previous request.
400	The server cannot or will not process the request due to an apparent client error. For example, a query parameter had an incorrect value.
401	The request requires user authentication. The response includes a WWW-Authenticate header field containing a challenge applicable to the requested resource.
403	The server understood the request, but is refusing to fulfill it. While status code 401 indicates missing or bad authentication, status code 403 indicates that authentication is not the issue, but the client is not authorised to perform the requested operation on the resource.
404	The requested resource does not exist on the server. For example, a path parameter had an incorrect value.
405	The request method is not supported. For example, a POST request was submitted, but the resource only supports GET requests.

Status code	Description
406	The Accept header submitted in the request did not support any of the media types supported by the server for the requested resource.
500	An internal error occurred in the server.

More specific guidance is provided for each resource, where applicable.

The API Description Document describes the HTTP status codes generated by that API. This should not be an exhaustive list of all possible status codes. It is not reasonable to expect an API designer to control the use of HTTP status codes which are not generated by their software. Therefore, it is recommended that the API Description Document limit itself to describing HTTP status codes relevant to the proper operation of the API application logic. Client implementations should be prepared to receive HTTP status codes in addition to those described in the API Description Document.

Permission 3	/per/core/additional-status-codes
A	Servers MAY support other capabilities of the HTTP protocol and, therefore, MAY return other status codes than those listed in Table 7 , too.

Chapter 8. Requirements Class "Collections"

8.1. Overview

Requirements Class	
http://www.opengis.net/spec/ogcapi-records-1/1.0/req/collections	
Target type	Web API
Dependency	http://www.opengis.net/spec/ogcapi_common-1/1.0/req/core
Dependency	http://www.opengis.net/spec/ogcapi_common-1/1.0/req/collections

The purpose of the conformance class is to specify requirements that extend the behaviour at the [/collections](#) endpoint to make it queryable by OGC API Records clients.

The conformance class defines the following extensions:

1. It extends the set of query parameters defined in the [Collections Metadata](#) section to support the richer set of query parameters defined in the [Parameters](#) clause of this specification.
2. It extends the schema of the collection information object defined in the [Collection Information](#) clause of the [OGC API - Common - Part 2: Geospatial Data](#) extension to add additional keys/properties that are required by OGC API Records.

8.2. Collections Metadata

The [Collections Metadata](#) clause of the [OGC API - Common - Part 2: Geospatial Data](#) extension defines the [bbox](#), [datetime](#) and 'limit' query parameters for the [/collections](#) resource.

Requirement 23	/req/collections/query-params
A	<p>The HTTP GET operation at the /collections path shall support the following additional query parameters defined in the Parameters section:</p> <ul style="list-style-type: none">• type• q• sortby

The collections metadata (i.e. HTTP GET on the [/collections](#) path) is defined in the [Collections Metadata](#) clause of the [OGC API - Common - Part 2: Geospatial Data](#) extension.

Requirement 24	/req/collections/query-response
----------------	---

A	The response shall only contain those collection information objects that satisfy all the query parameters specified with the HTTP GET operation (i.e. one or more of bbox, datetime, limit, type, q, sortby).
---	--

8.3. Collection information

The collection information object is defined in the [Collection Information](#) clause of the [OGC API - Common - Part 2: Geospatial Data](#) extension.

The following table cross-walks the properties of the collection information object with the core queryables.

Table 13. Crosswalk of core queryables with collection information object properties

Collection property	Requirement	Core Queryable	Requirement
id	M	id	M
title	O	title	M
description	O	description	M
itemType	O	—	—
extent	O	extent	O
links	M	links	O
crs	O	—	—

The following requirements specify additional properties that a compliant implementation of this conformance class must add to the collection information object.

Requirement 25	/req/collections/title
A	The title property shall be present in the collection information object.

Requirement 26	/req/collections/description
A	The description property shall be present in the collection information object.

No additional requirements are necessary for the **extent** property.

No additional requirements are necessary to the **links** property. Since the **links** property is mandatory for the collection information object, it will always be present but because it is an optional core queryables, catalogue clients will either know how to handle it or they will ignore it.

Requirement 27	/req/collections/type
A	The type property shall be present in the collection information object.
B	The value of the type property shall be the same as the value of the itemType property if the later is present.
C	Otherwise, the value of the type property shall denote the resource type of the collection (e.g. feature, coverage, map, etc.).

Requirement 28	/req/collections/created
A	The created property shall be present in the collection information object.
B	The value of the created property shall conform to the date-time production of RFC 3339 .
C	The value of the created property shall indicate the date-time the collection was created.

Requirement 29	/req/collections/created
A	The changed property shall be present in the collection information object.
B	The value of the changed property shall conform to the date-time production of RFC 3339 .
B	The value of the changed property shall indicate the most recent date on which the collection was changed.

NOTE Adding, modifying, or deleting items from a collections are all examples of changes to that collection.

Requirement 30	/req/collections/keywords
A	The keywords property shall be present in the collection information object.

B	The value of the keywords property shall be a list of keywords or tags associated with the collection.
Recommendation 1	/rec/collections/additional-properties
A	The Table 9 table contains a list of recommended additional properties that may be added to a collection information object to enhance the searchability of the collections offered at an OGC API endpoint.

Table 14. Additional collection information properties

Property	Description
language	This refers to the natural language used for textual values (i.e. titles, descriptions, etc) of a resource.
publisher	The entity making the resource available.
themes	A knowledge organization system used to classify the resource.
formats	A list of available distributions for the resource.
contactpoint	An entity to contact about the resource.
license	A legal document under which the resource is made available.
rights	A statement that concerns all rights not addressed by the license such as a copyright statement.
associations	A list of links for accessing the resource or links to other resources associated with this resource.

The collections metadata response is defined in the [Collections Metadata](#) clause on the [OGC API - Common - Part 2: Geospatial Data](#) extension.

Requirement 31	/req/collections/response
-----------------------	----------------------------------

A

The content of that response shall be based upon the following OpenAPI 3.0 schema that extends the schema of the collection information object as defined in the [Collection Information](#) clause of the [OGC API - Common - Part 2: Geospatial Data](#) specification:

```
collection:
  type: object
  required:
    - id
    - created
    - changed
    - title
    - description
    - keywords
    - type
  properties:
    id:
      description: identifier of the collection
      type: string
    created:
      description: the date this collection was
created in the server
      type: string
      format: date-time
    changed:
      description: the most recent date on which the
collection was changed
      type: string
      format: date-time
    title:
      description: human readable title of the
collection
      type: string
    description:
      description: a description of the features in
the collection
      type: string
    keywords:
      description: A list of keywords or tag
associated with the collection
      type: array
      items:
        type: string
    type:
      description: the nature or genre of the items
of the collections (e.g. feature, coverage)
      type: string

    itemType:
      description: indicator about the type of the
items in the collection (the default value is
'feature').
```

8.4. Examples

Example 1: List all the collections that lie within a specific bounding box and contains the the keyword **weather**.

```
type: string
default: feature
language:
description: refers to the natural language
used for textual values (i.e. titles, descriptions, etc)
of items in the collection
type: string
```

Client

Server

```
GET /collections?bbox=[41.875315,-96.767601,56.732861,-73.47|
6586&q=weather HTTP/1.1
```

```
Accept: application/json
```

```
HTTP/1.1 200 OK
```

```
Content-Type: application/json
```

```
Need example output here...
```

```
description: List of available distributions
for the collection
type: array
items:
  type: string
contactpoint:
  description: entity to contact about the
collection
  type: object
license:
  description: legal document under which the
collection is made available.
  type: string
rights:
  description: a statement that concerns all
rights not addressed by the license such as a copyright
statement.
  type: string
links:
  type: array
  items:
    $ref: "#/components/schemas/link"
associations:
  type: array
  items:
    $ref: "#/components/schemas/link"
extent:
  $ref: "#/components/schemas/extent"
crs:
  description: the list of coordinate reference
systems supported by the service
  type: array
  items:
```

Chapter 9. Requirements Class

"OpenSearch"

9.1. Overview

Requirements Class	
http://www.opengis.net/spec/ogcapi-records-1/1.0/req/opensearch	
Target type	Web API
Dependency	http://www.opengis.net/spec/ogcapi_common-1/1.0/req/core
Dependency	http://www.opengis.net/spec/ogcapi_common-1/1.0/req/collections

9.2. Heading

Chapter 10. Requirements Class JSON

The following requirements apply to an OGC API - Records implementation when the following conditions apply:

1. The API advertises conformance to the JSON Conformance Class
2. The client negotiates a JSON or GeoJSON format

The JSON Requirements Class restricts requirements defined in the **Core** Requirements Class by imposing encoding-specific requirements. At this time, these additional requirements only apply to the HTTP response payloads. The sections below identify the scope of each new requirement and the **Core** requirements which lay within each scope.

Requirements Class	
http://www.opengis.net/spec/ogcapi-records-1/1.0/req/json	
Target type	Web API
Dependency	Requirements Class "API - Common Core"
Dependency	API - Common GeoJSON
Dependency	GeoJSON
Pre-conditions	1) The API advertises conformance to the JSON Conformance Class 2) The client negotiates use of the JSON or GeoJSON encoding.

10.1. Common

This section covers the requirements inherited from the API - Common standard. Its scope includes responses for the following operations:

- **{root}/**: Landing Page
- **{root}/api**: API Description
- **{root}/conformance**: Conformance Classes
- **{root}/collections**: Collections
- **{root}/collections/{collectionid}**: Collection Information

Requirement 32	/req/json/api-common
Extends	/req/core/api-common
The API SHALL demonstrate conformance with the following Requirements Class of the OGC API - Common version 1.0 Standard.	
A	http://www.opengis.net/spec/ogcapi_common-1/1.0/req/geojson

It is also necessary to advertise conformance with this Requirements Class.

Requirement 33	/req/json/conformance
The list of Conformance Classes advertised by the API SHALL include:	
A	http://www.opengis.net/spec/ogcapi-records-1/1.0/conf/json

10.2. Record

TBD: Requirements for the GeoJSON encoding of a record.

Chapter 11. Requirements Class HTML

The following requirements apply to an OGC API - Records implementation when the following conditions apply:

1. The API advertises conformance to the HTML Conformance Class
2. The client negotiates an HTML format

The HTML Requirements Class restricts requirements defined in the **Core** Requirements Class by imposing encoding-specific requirements. At this time, these additional requirements only apply to the HTTP response payloads. The sections below identify the scope of each new requirement and the **Core** requirements which lay within each scope.

Requirements Class	
http://www.opengis.net/spec/ogcapi-records-1/1.0/req/html	
Target type	Web API
Dependency	Conformance Class "Core"
Dependency	API - Common HTML
Dependency	HTML5
Dependency	Schema.org

11.1. Common

This section covers the requirements inherited from the API - Common standard. Its scope includes responses for the following operations:

- **{root}/**: Landing Page
- **{root}/api**: API Description
- **{root}/conformance**: Conformance Classes
- **{root}/collections**: Collections
- **{root}/collections/{collectionid}**: Collection Information

Requirement 34	/req/html/api-common
Extends	/req/core/api-common
The API SHALL demonstrate conformance with the following Requirements Class of the OGC API - Common version 1.0 Standard.	
A	http://www.opengis.net/spec/ogcapi_common-1/1.0/req/html

It is also necessary to advertise conformance with this Requirements Class.

Requirement 35	/req/html/conformance
The list of Conformance Classes advertised by the API SHALL include:	
A	http://www.opengis.net/spec/ogcapi-records-1/1.0/conf/html

11.2. Record

RBDL Requirements for the HTML encoding of a record.

Chapter 12. Requirements Class XML

The following requirements apply to an OGC API - Records implementation when the following conditions apply:

1. The API advertises conformance to the XML Conformance Class
2. The client negotiates a XML format

The XML Requirements Class restricts requirements defined in the **Core** Requirements Class by imposing encoding-specific requirements. At this time, these additional requirements only apply to the HTTP response payloads. The sections below identify the scope of each new requirement and the **Core** requirements which lay within each scope.

Requirements Class	
http://www.opengis.net/spec/ogcapi-records-1/1.0/req/atom	
Target type	Web API
Dependency	Requirements Class "API - Common Core"
Dependency	The Atom Publishing Protocol
Pre-conditions	1) The API advertises conformance to the ATOM Conformance Class 2) The client negotiates use of the ATOM encoding.

12.1. Common

This section covers the requirements inherited from the API - Common standard. Its scope includes responses for the following operations:

- **{root}/**: Landing Page
- **{root}/api**: API Description
- **{root}/conformance**: Conformance Classes
- **{root}/collections**: Collections
- **{root}/collections/{collectionid}**: Collection Information

Requirement 36	/req/xml/api-common
Extends	/req/core/api-common
The API SHALL demonstrate conformance with the following Requirements Class of the OGC API - Common version 1.0 Standard.	
A	http://www.opengis.net/spec/ogcapi_common-1/1.0/req/xml

It is also necessary to advertise conformance with this Requirements Class.

Requirement 37	/req/xml/conformance
The list of Conformance Classes advertised by the API SHALL include:	
A	http://www.opengis.net/spec/ogcapi-records-1/1.0/conf/xml

12.2. Record

TBD: Requirements for the ATOM encoding of a record.

Chapter 13. Requirements class "OpenAPI 3.0"

Requirements Class	
http://www.opengis.net/spec/ogcapi-records/1.0/req/oas30	
Target type	Web API
Dependency	Conformance Class "Core"
Dependency	OGC API - Common Standard 1.0
Dependency	OpenAPI Specification 3.0.2

The OpenAPI 3.0 Requirements Class is applicable to API - Records as well. So an implementation of API - Records which supports OpenAPI 3.0 as an API Description format must also comply with the API - Common oas30 Conformance Class.

Requirement 38	/req/oas30/oas-common
Extends	/req/core/api-common
A	The API SHALL demonstrate conformance with the following Requirements Class of the OGC API - Common version 1.0 Standard. http://www.opengis.net/spec/ogcapi-common-1/1.0/req/oas30 .

Implementations must also advertise conformance with this Requirements Class.

Requirement 39	/req/oas30/conformance
The list of Conformance Classes advertised by the API SHALL include:	
A	http://www.opengis.net/spec/ogcapi-records-1/1.0/conf/oas30

Chapter 14. Media Types

This standard does not mandate any particular encoding or format. However, it does provide extensions for encodings which are commonly used in OGC APIs. These extensions include:

- [JSON](#)
- [HTML](#)

Neither of these encodings are mandatory. An implementor of this standard may choose to implement neither of them, selecting different encodings instead.

14.1. HTML Encoding

Support for HTML is recommended. HTML is the core language of the World Wide Web. An API that supports HTML will support browsing the spatial resources with a web browser and will also enable search engines to crawl and index those resources.

14.2. JSON Encoding

Support for JSON is recommended. JSON is a commonly used format that is simple to understand and well supported by tools and software libraries.

JSON structures documented in this standard are defined using JSON Schema. These schema are available in JSON and YAML formats from <http://schemas.opengis.net/tbd>

14.2.1. GeoJSON

"GeoJSON is a geospatial data interchange format based on JavaScript Object Notation (JSON). It defines several types of JSON objects and the manner in which they are combined to represent data about geographic features, their properties, and their spatial extents. GeoJSON uses a geographic coordinate reference system, World Geodetic System 1984, and units of decimal degrees." [IETF RFC 7946](#)

GeoJSON provides a simple way of representing OGC Features in JSON. Due to its simplicity, however, it is not suitable for all feature data. It is best used for content which has a spatial extent that can be used with the World Geodetic System 1984 Coordinate Reference System.

14.3. Media Types

A description of the MIME-types is mandatory for any OGC standard which involves data encodings. The list of suitable MIME-types for the API - Records standard is provided in [Table 10](#).

Table 15. API - Records MIME Types

Encoding	MIME Type
HTML	text/html
JSON	application/json

GeoJSON	application/geo+json
ATOM	application/atom+xml

14.4. Default Encodings

The media type used to encode a response to a request shall be determined through the HTTP content negotiation protocol as specified in API - Common. However, content negotiation is not required by the HTTP standard. So default encodings must be established.

Requirement 40	/req/core/rc-mediatype-default
A	IF the JSON Conformance Class is advertised, then the default media type for content SHALL be JSON or GeoJSON.
C	IF the JSON Conformance Class is not advertised, then the default media type for content SHALL be HTML.

Chapter 15. Security Considerations

TBD: Discuss any security considerations.

See:

- https://github.com/opengeospatial/oapi_common/blob/master/core/clause_12_security_considerations.adoc
- https://github.com/opengeospatial/ogcapi-features/blob/master/core/standard/clause_11_security_considerations.adoc