

NetFront

StatManager

React Native UI Component Specification

Document Version	v2.4.1
Date	August 25, 2026
Prepared For	NetFront Hockey Club Development Team
Platform	React Native (Expo)
Category	UI Component Specification — Technical Reference

CONFIDENTIAL — For internal NetFront HC development use only. Do not distribute.

Table of Contents

Section	Title	Topics Covered
§ 1	Design Tokens	Colors, typography, spacing, shadows, animation
§ 2	Navigation Architecture	Tab navigator, screen hierarchy, modal stack
§ 3	Global Components	AppBarHeader, ClockModeSelector, shared controls
§ 4	Game Screen	GameStatusBar, RinkInteraction, ZoneTimeCards, EventLog
§ 5	Modals	LogEvent, EditEvent,

Section	Title	Topics Covered
		PeriodSummary, EndOfGame, PlayerDetail
§ 6	Setup Screen	Form groups, game configuration, CTAs
§ 7	Roster Screen	Player cards, search, filters, AddPlayerModal
§ 8	Settings Screen	Preference groups, toggles, export, about
§ 9	Global State Model	UI-layer state keys, types, defaults, driven components
§ 10	Interaction Flows	Log event, zone timer, clock mode switch, side toggle
§ 11	Component Checklist	Priority matrix for MVP development
§ 12	Accessibility Notes	Touch targets, contrast, focus management, ARIA
§ 13	RN / Expo Implementation Notes	Recommended libraries, patterns, state, SVG, timers

§ 1 Design Tokens

All design tokens should be centralized in `constants/colors.ts`, `constants/typography.ts`, and `constants/spacing.ts`. Components must import from these files — no hardcoded values in component files.

1.1 Color Palette

Export all tokens from `constants/colors.ts`. Token names should match the `NF_*` naming convention exactly.

Token Name	Hex Value	Usage
NF_BLUE	#0A1A3F	Primary background, headers, nav bar, app shell
NF_ORANGE	#FF7A00	Accent, active states, CTA

Token Name	Hex Value	Usage
		buttons, highlights, active tab indicator
NF_WHITE	#FFFFFF	Primary text on dark surfaces, icon fill
NF_SURFACE	#111E3F	Card backgrounds, list row backgrounds
NF_SURFACE_LIGHT	#1A2B55	Elevated cards, active/selected rows
NF_BORDER	#1F3366	Card borders, dividers, input outlines
NF_TEXT_MUTED	#8A9BBE	Secondary labels, hints, placeholders, inactive tab text
NF_RED	#E03B3B	Away indicator, penalty, destructive actions, DZone label
NF_GREEN	#2ECC71	Active timers, goal dots, connected status indicator
NF_YELLOW	#FFD700	Shot dots on rink chart SVG
NF_BLUE_ACCENT	#1565C0	Take Away dots, Clock Sync mode indicator badge
NF_BLACK_DOT	#1C1C1C	Give Away dots (always rendered with white stroke)
NF_WARNING_YELLOW	#F1C40F	Connecting/warning status indicator, pulse animation target

1.2 Typography

Export all typography specs from `constants/typography.ts`. Use React Native's `StyleSheet.create()` to define named text styles. All font-family values fall back to system defaults where Inter is unavailable.

Role	Font Family	Weight	Size	Color
App Brand "NetFront"	System-ui / Inter	Bold	16px	#FF7A00
App Brand "StatManager"	System-ui / Inter	Bold	16px	#FFFFFF
Screen Title	System-ui /	Bold	22px	#FFFFFF

Role	Font Family	Weight	Size	Color
	Inter			
Section Header	System-ui / Inter	Bold	18-20px	#FFFFFF
Card Label	System-ui / Inter	SemiBold (600)	14-16px	#8A9BBE
Body / Row Text	System-ui / Inter	Regular (400)	14px	#FFFFFF
Event Log	Courier / Monospace	Regular (400)	10-11px	#FFFFFF
Stat Number (large)	System-ui / Inter	Bold	22-28px	#FF7A00
Mode Badge	System-ui / Inter	Bold	10px	#FFFFFF
Version Tag	System-ui / Inter	Regular (400)	10px	#8A9BBE

1.3 Spacing & Layout

Export from `constants/spacing.ts`. All values are in `px` / React Native unitless numbers. Components should reference these tokens, not inline numbers.

Token	Value	Usage
OUTER_PADDING	16px	Screen edge padding on all main screens
SECTION_GAP	12px	Vertical gap between top-level sections on GameScreen
CARD_PADDING	12px	Internal padding for all card components
CARD_BORDER_RADIUS	10px	borderRadius on all card and modal surfaces
PILL_BORDER_RADIUS	20px	borderRadius on all pill/badge elements
CTA_BUTTON_HEIGHT	50px	Height of all full-width CTA buttons
NAV_BAR_HEIGHT	60px	Bottom navigation bar height
HEADER_BAR_HEIGHT	38px	AppBar brand bar height

Token	Value	Usage
MODE_BAR_HEIGHT	36px	ClockModeSelector bar height
STATUS_BAR_HEIGHT	~56px	GameStatusBar base height; expands when GameControlsPanel is visible
ZONE_CARD_GAP	8px	Horizontal gap between the three ZoneTimeCards

1.4 Shadow & Elevation

Level	CSS / RN Shadow Value	Usage
Default Card	elevation: 4 / box-shadow: 0 2px 8px rgba(0,0,0,0.4)	All card components (ZoneCards, GameControlsPanel, etc.)
Active / Glow	box-shadow: 0 0 10px rgba(255,122,0,0.5)	Orange glow on active ZoneCard, active SegmentedControl option
Modal Overlay	backdrop-filter: blur(4px) + rgba(0,0,0,0.7) overlay	All full-screen modals (PeriodSummary, EndOfGame)

1.5 Animation Tokens

Name	Value	Usage
TRANSITION_DEFAULT	0.2s ease	All interactive color/opacity changes across the app
TRANSITION_SWAP	0.3s opacity	Zone card reorder animation, rink label flip on side toggle
PULSE_ACTIVE_DOT	@keyframes: opacity 1 ↔ 0.4, 1.2s infinite	Zone timer active pulsing green dot
CLOCK_GLOW	@keyframes: glow on/off, 1.5s infinite	ClockDisplay glow animation in CLK and SYNC modes when running
SLIDE_UP_MODAL	translateY: 100% → 0, 0.3s ease	All bottom sheet modals (LogEvent, EditEvent, PlayerDetail)

§ 2 Navigation Architecture

2.1 Bottom Tab Navigator

Component: `BottomTabNavigator`. Implemented via `@react-navigation/bottom-tabs`.
Four tabs always visible. Tab bar persists across all screens.

Index	Icon	Label	Screen Component	Notes
0		Game	<code>GameScreen</code>	Main 4-section tracking screen. Hosts <code>AppBar</code> and <code>ClockModeSelector</code> .
1		Setup	<code>SetupScreen</code>	Game configuration before and during play.
2		Roster	<code>RosterScreen</code>	Player management and stats lookup.
3		Settings	<code>SettingsScreen</code>	App-wide preferences and export configuration.

Tab bar style notes:

- Background: `#0A1A3F`
- Active tab: `#FF7A00` icon + label + 2px orange underline indicator
- Inactive tab: `#8A9BBE` icon + label
- Height: 60px. Icon size: 22px. Label size: 12px
- **Game tab only:** a sub-toolbar row (36px tall) sits immediately above the nav bar, containing [Period Summary] and [End of Game] modal trigger buttons

2.2 Screen Hierarchy

AppRoot |— BottomTabNavigator | | |— GameScreen | | |—
AppBar (static, 38px) | | |— ClockModeSelector (static, 36px, Game
tab only) | | |— Section1_GameStatus | | |— GameControlsPanel
(Away only, collapsible) | | |— Section2_RinkInteraction | | |—
RinkSVG (tappable, tap → LogEventModal) | | |— TapHintLabel | | |
|— StatSummaryTable | | |— Section3_ZoneTimeCards | | |—
OZoneCard | | |— NZoneCard (always center) | | |— DZoneCard
| | |— Section4_EventLog | | |— EventLog rows (tap →
EditEventModal) | |— SetupScreen | |— RosterScreen | |—
SettingsScreen |— Modals (rendered at root level, above navigator) |—
LogEventModal (bottom sheet, trigger: RinkSVG tap) |— EditEventModal
(bottom sheet, trigger: EventLog row tap) |— PeriodSummaryModal (full
screen, trigger: Game tab sub-toolbar) |— EndOfGameModal (full screen,
trigger: Game tab sub-toolbar) |— PlayerDetailSheet (bottom sheet, trigger:
RosterScreen player row)

⚙️ IMPLEMENTATION NOTE — Modal Rendering

All modals must be rendered at the root-level navigator scope (above BottomTabNavigator), not inside individual screen components. This ensures modals visually overlay the nav bar and all screen content. Use a shared ModalProvider context or Zustand modal state to trigger renders from screen-level events.

§ 3 Global Components

3.1 AppHeaderBar

Component: AppHeaderBar | **Position:** Top of GameScreen, above ClockModeSelector | **Height:** 38px | **Background:** #0A1A3F | **Bottom border:** 1px #FF7A00

Prop	Type	Default	Description
appName	string	"NetFront StatManager"	Brand name — split into orange/white rendering
version	string	"v2.4.1"	Displayed right-aligned in muted style

✂ IMPLEMENTATION NOTE

"NetFront" renders in #FF7A00 bold. "StatManager" renders in #FFFFFF bold. These must be two separate `<Text>` spans within one `<View>` row — not a single string. Version tag right-aligned: #8A9BBE, 10px. Use `flexDirection: 'row'` with `justifyContent: 'space-between'` at the outer container level.

3.2 ClockModeSelector

Component: ClockModeSelector | **Position:** Below AppHeaderBar, above Section 1 | **Height:** 36px | **Background:** #0A1A3F | **Bottom border:** 1px #FF7A00

Modes (stored in global state key `clockMode`):

- `'manual'` → label "Manual", badge MAN (gray)
- `'clock'` → label "Clock", badge CLK (orange)
- `'clocksync'` → label "Clock Sync", badge SYNC (blue #1565C0)

Prop	Type	Default	Description
clockMode	'manual' 'clock' 'clocksync'	'clock'	Currently active mode; drives badge, controls, and modal note
onModeChange	(mode: ClockMode) => void	required	Callback fired on mode switch; updates global state

Sub-components:

- SegmentedControl: three pills [Manual][Clock][Clock Sync]. Active = orange fill. Inactive = transparent + muted text.
- ModeDescription: italic muted 10px label to the right of pills describing the current mode behavior.

3.3 ConnectionIndicator

Component: ConnectionIndicator | **Displayed:** Top-right of Section 1 status bar.
In Manual mode, shows "MANUAL" badge with no dot.

State	Dot Color	Label	Animation
connected	#2ECC71	Connected	None (static dot)
connecting	#F1C40F	Connecting	Pulse opacity 1 ↔ 0.4, infinite, 1.2s
not_connected	#E03B3B	Not Connected	None (static dot)
manual	N/A — no dot	"MANUAL" badge (#8A9BBE)	None

 SYNC MODE NOTE

In clocksync mode, ConnectionIndicator state must be synchronized with the syncStatus indicator inside GameControlsPanel. Both components read from the same connectionStatus and syncStatus global state keys. Do not maintain separate local state for these.

3.4 ToggleSwitch

Standard iOS-style toggle. Used throughout Settings and Setup screens.

- Active track: #FF7A00
- Inactive track: #1F3366
- Thumb: #FFFFFF

3.5 SegmentedControl

Pill group — only one option active at a time. Reused across all screens.

- Active: #FF7A00 fill + #FFFFFF text
- Inactive: transparent + #8A9BBE text
- Border radius: 20px
- Font: 12px bold

3.6 StepperControl

`[-] value [+]` layout. Used in Setup (Periods) and GameControlsPanel (period control).

- Buttons: 32px square, orange outline, 6px border-radius
- Value: bold white 18px, centered

3.7 PillButton (Outline)

Used for zone time Start/Stop, game controls.

- Height: 32px. Border radius: 16px
- Inactive: orange outline + orange text
- Active: orange fill + white text
- Font: 13px bold white

3.8 PlayerRosterPicker

Inline scrollable list used inside `LogEventModal` and `EditEventModal`.

- Max height: 160px. Overflow: scroll (FlatList in RN)
- Row: jersey number badge (orange, 28px square) + player name bold white 14px + position pill
- Selected row: #FF7A00 background highlight
- Top row: "No Player" option for clearing selection
- Only Active (non-Injured) players displayed
- On selection: list collapses to single-line — e.g., #11 Mikko Virtanen · F

✂ IMPLEMENTATION NOTE

`PlayerRosterPicker` is a shared component. It must accept an `onSelect` callback and a `selectedPlayerId` prop. It should never own its own state — always controlled by the parent modal. Filter source array to `status === 'active'` before rendering. Injured players must be excluded entirely from the list.

§ 4 Game Screen (GameScreen)

The primary tracking screen. Composed of four vertically stacked sections preceded by `AppBar` and `ClockModeSelector`. All sections are scrollable together in a `ScrollView`. The header bars are fixed and do not scroll.

4.1 Section 1 — GameStatusBar

Component: `GameStatusBar`

4.1.1 Main Status Row

Layout: Horizontal row, 16px horizontal padding, space-between. **Background:** #0A1A3F. **Bottom border:** 1px #1F3366 (inner) + 1px #FF7A00 (outer, below game controls panel).

Sub-Component	Content	Style Notes
PeriodBadge	"1st" / "2nd" / "3rd" / "OT"	Orange pill, bold 14px white text. Reads from <code>currentPeriod</code> state.
ClockDisplay	"14:22" countdown or static	Bold mono 22px white. Glow animation when running in CLK/SYNC.  edit icon in MAN mode. Mode badge (MAN/CLK/SYNC) shown below clock label.
ScoreDisplay	"HOME 2 — 3 AWAY"	"HOME" in #FF7A00, numbers bold 22px white, "AWAY" in #8A9BBE.
StrengthBadge	"ES" / "PP" / "PK"	Orange pill badge with abbreviated label + full text label below in muted 12px. Reads from <code>currentStrength</code> state.
ConnectionIndicator	See § 3.3	Top-right of row. Mode-aware state.

4.1.2 Clock Display — Mode Behavior

Mode	Editable?	Runs?	Badge	Edit Hint / Visual
manual	Yes — tap to type MM:SS	No (static value)	Gray "MAN"	 pencil icon alongside clock value
clock	Via  Set Time button only	Yes (Start/Stop)	Orange "CLK"	None
clocksync	No (scorekeeper-driven)	Yes (synced)	Blue "SYNC"	 sync icon when synced; red border when sync lost

4.1.3 GameControlsPanel (Away Games Only)

Visibility: Rendered only when `gameIsAway === true`. Hidden entirely for home games. **Collapse:** Chevron button "▲ Hide" / "▼ Show" toggles open/closed. Default state: open.

Card style: #111E3F background, 10px radius, 12px padding, 1px #1F3366 border.

ROW A — Clock + Period (mode-sensitive):

Component	Manual Mode	Clock Mode	Sync Mode
Start/Stop Button	Hidden — shows "Manual Entry" italic muted label instead	Orange pill "► Start" / "■ Stop"	Green "■ Synced-Stop" or orange "► Sync Start"
SyncStatus	Hidden	Hidden	●●● dot + label + "Scorekeeper-driven" sublabel
PeriodControl	< PREV / badge / NEXT >	< PREV / badge / NEXT >	< PREV / badge / NEXT >

ROW B — Scores + Strength (always visible in all modes):

- `HomeScoreControl`: Label "HOME" orange 11px + ▲ number ▼ stepper (32px square orange outline buttons, bold white 22px value)
- `AwayScoreControl`: Label "AWAY" muted 11px + same stepper layout
- `StrengthSelector`: Label "Strength" muted 11px + three stacked pill buttons: [Even Strength][Power Play][Penalty Kill]. One active (orange fill) at a time. Default: Even Strength. Selection immediately updates `StrengthBadge` and `currentStrength` global state ('ES' | 'PP' | 'PK').

✂ IMPLEMENTATION NOTE — `StrengthSelector`

Selecting a strength value in Row B immediately updates both the `StrengthBadge` in the main `GameStatusBar` and the `currentStrength` global state key. This ensures all newly logged events inherit the correct strength. Store as 'ES' | 'PP' | 'PK'. Default: 'ES'.

4.2 Section 2 — `RinkInteraction`

Component: `RinkInteraction`

4.2.1 Header Row

- "RINK" bold white 18px, left-aligned

- `offensiveSideToggle` right-aligned: "Offensive Side: Left ◀ | Right ▶" — pill toggle, active side in orange. State: `offensiveSide: 'left' | 'right'`. Default: `'left'`.
- On toggle: (1) RinkSVG zone labels fade out 0.15s → swap → fade in 0.15s. (2) ZoneCards row reorders OZone↔DZone. (3) Zone derivation logic updates immediately.

4.2.2 RinkSVG Component

Full-width SVG. Aspect ratio ~2:1 (width:height). ViewBox: `"0 0 400 200"`.

SVG Layers (bottom to top):

1. Ice surface — white fill rectangle, `rx=12` rounded corners
2. Goal lines — red (`#CC0000`) horizontal lines, `y≈20` and `y≈180`
3. Blue lines — blue (`#0033CC`) vertical lines at `x≈133` and `x≈267`
4. Center line — red vertical line at `x=200`
5. Face-off circles — 6 total: center (`r=30`), 2 neutral zone dots, 2 end-zone pairs
6. Goal creases — red semi-circles at each end (`r≈18`)
7. Net icons — small rectangles at each goal
8. Referee crease — small semi-circle at center bottom
9. Zone labels — "OZone" left third, "NZone" center, "DZone" right third (swap on toggle)
10. Event dots layer — dynamic `<Circle>` elements placed on tap
11. Tap capture overlay — transparent `<Rect>` `width="100%" height="100%", pointerEvents="all"`

4.2.3 Rink Tap Interaction

On tap sequence:

12. Calculate SVG coordinate from tap: `svgX = (clientX - rect.left) / rect.width * viewBoxWidth` and `svgY = (clientY - rect.top) / rect.height * viewBoxHeight`
13. Place a "pending" dot at (`svgX`, `svgY`) with color based on current `selectedEventType`
14. Open `LogEventModal`

15. On modal Cancel → remove pending dot from `rinkDots` state

16. On modal Confirm → finalize dot, derive zone, append to `eventLog`

Event dot visual specs:

Event Type	Fill	Radius	Stroke	Stroke Width
Shot	#FFD700	6	none	—
Goal	#2ECC71	8	#FFFFFF	1.5px
Hit	#E03B3B	6	none	—
Give Away	#1C1C1C	6	#FFFFFF	1px
Take Away	#1565C0	6	none	—
Blocked Shot	#FFFFFF	6	#0A1A3F	1.5px

REAL-TIME DOT COLOR

All dots persist on the rink across the full game session. When a pending dot is placed and the modal is open, switching event type pills inside the modal must update the pending dot color in real time — immediately re-render the dot with the new event type's fill color. Do not wait for Confirm.

Zone derivation from tap x-coordinate:

- `offensiveSide='left'`: $x < 33\% \rightarrow \text{OZone}$, $33\text{--}66\% \rightarrow \text{NZone}$, $x > 66\% \rightarrow \text{DZone}$
- `offensiveSide='right'`: $x < 33\% \rightarrow \text{DZone}$, $33\text{--}66\% \rightarrow \text{NZone}$, $x > 66\% \rightarrow \text{OZone}$

4.2.4 Tap Hint Label

Text: " Tap rink to log event". Position: below `RinkSVG`, outside SVG container. Style: centered, italic, #8A9BBE, 11px. Margin-top: 6px.

4.2.5 StatSummaryTable

Positioned below the tap hint label. Displays cumulative period-by-period totals.

Period	Shots	Goals	Hits	GA	TA	BLK
1st	—	—	—	—	—	—
2nd	—	—	—	—	—	—
3rd	—	—	—	—	—	—
TOTAL	—	—	—	—	—	—

Table style notes: Header row: #FF7A00 background, white bold 11px monospace. Data rows: alternating #111E3F / #1A2B55, white 11px monospace. TOTAL row: bold white, #0A1A3F background.

4.3 Section 3 — ZoneTimeCards

Component: ZoneTimeCards. Layout: horizontal row, 8px gap, equal-width cards (flex: 1 each).

Card reorder logic (based on offensiveSide state):

- offensiveSide='left': [OZoneCard][NZoneCard][DZoneCard]
- offensiveSide='right': [DZoneCard][NZoneCard][OZoneCard]
- NZoneCard always remains in the center position. OZone and DZone swap. 0.3s CSS transition.

4.3.1 ZoneCard Component

Prop	Type	Description
zoneName	'OZone' 'NZone' 'DZone'	Determines header color and zone identity
isActive	boolean	Whether the timer is currently running
elapsed	string (MM:SS)	Current elapsed time for the active interval
longest	string	Longest recorded zone interval this game
shortest	string	Shortest recorded zone interval this game

Prop	Type	Description
average	string	Average zone interval time this game
onToggle	() => void	Fires on Start/Stop button press

Internal structure:

- Header: zone name bold 14px — OZone: #FF7A00, NZone: #FFFFFF, DZone: #E03B3B
- Timer display: bold 24px — active: #2ECC71 with 8px pulsing green dot; inactive: muted
- StartStop button: PillButton — "► Start" (outline) / "■ Stop" (orange fill)
- Stats rows: "Longest:" / "Shortest:" / "Avg:" — label muted 10px + value white 11px monospace

Card style: #111E3F background, 12px padding, 8px border-radius, 1px #1F3366 border. Default shadow: 0 2px 8px rgba(0,0,0,0.4). Active card: orange glow shadow 0 0 10px rgba(255,122,0,0.5).

4.4 Section 4 — EventLog

Component: EventLog. Max height: 220px. Overflow: scroll. Custom scrollbar: thin, #FF7A00 thumb.

4.4.1 Header Row

- "EVENT LOG" bold white 18px, left-aligned
- Filter pill right: "Logging: [TeamName]" — small orange pill showing active logging team

4.4.2 EventLog Table

Period (×1)	Clock (×1.5)	Event (×2)	PLYR (×1)	Zone (×1.5)	STR (×1)
2nd	14:22	Shot	#11	OZone	ES

Period (×1)	Clock (×1.5)	Event (×2)	PLYR (×1)	Zone (×1.5)	STR (×1)
2nd	13:48	Zone Start	—	OZone	—
2nd	12:30	Goal	#7	OZone	PP

Style notes: Font 10–11px monospace. Header: #FF7A00 background, white bold. Data rows: alternating #111E3F / #1A2B55.

Left-border row accents (2px solid):

- Goal: #FF7A00 orange
- Zone Start: #2ECC71 green
- Zone Stop: #E03B3B red
- Give Away: #333333 dark
- Take Away: #1565C0 blue
- Blocked Shot: #CCCCCC light gray
- Period End: full-width gray separator, centered italic muted text, no border accent

Column value notes: STR values: ES | PP | PK | – (dash for zone/period events). PLYR values: #11 (bold orange mono) or —. Event abbreviation: "Blk Shot" for Blocked Shot.

4.4.3 Row Tap → EditEventModal

Tapping any event row opens `EditEventModal` with that event's data pre-filled. Highlight the tapped row with #FF7A00 background for 200ms before the modal opens (flash feedback).

§ 5 Modals

5.1 LogEventModal

Type: Bottom sheet (slides up from bottom, 0.3s ease). **Trigger:** Tap on RinkSVG surface.

Visual: #111E3F card, rounded top corners 16px. Drag handle: 4px × 36px #1F3366 pill centered at top.

Content layout (top to bottom):

17. Title: "Log Event" bold white 18px

18. Event type selector grid (3+3, two rows):

- Row 1: [Shot] [Goal] [Hit]
- Row 2: [Give Away] [Take Away] [Blocked Shot]

19. Contextual note (11px muted italic) — varies by clockMode + event type:

- Manual + Shot/Hit/GA/TA/BLK: "Period only — clock not tracked for this event"
- Manual + Goal: "Clock time will be recorded from current display"
- Clock/Sync + any: "Clock time captured: [currentClockValue]" (adds "(Synced)" in SYNC mode)

20. Player selector — "Select Player" placeholder → expands to PlayerRosterPicker on tap → collapses to "#11 Mikko Virtanen · F" on selection

21. Action buttons row: [Confirm] orange fill 48px + [Cancel] orange outline 48px, equal flex width

Active pill styles per event type:

Event Type	Active Fill	Text Color	Border
Shot	#FF7A00	#FFFFFF	None
Goal	#2ECC71	#FFFFFF	None
Hit	#E03B3B	#FFFFFF	None
Give Away	#1a1a1a (near-black)	#FFFFFF	White 1.5px
Take Away	#1565C0	#FFFFFF	None

Event Type	Active Fill	Text Color	Border
Blocked Shot	#FFFFFF	#0A1A3F (dark)	Dark 1.5px

⚙ INACTIVE PILL STYLES

Inactive pills use transparent fill + orange outline + orange text, with exceptions: Give Away inactive uses its own near-black outline, and Blocked Shot inactive uses a white/light outline. These two pill types maintain a distinct inactive visual to prevent ambiguity with the orange default inactive style.

5.2 EditEventModal

Type: Bottom sheet (same visual style as LogEventModal). **Trigger:** Tap on EventLog row. **Title:** "Edit Event" bold white 18px.

Editable fields:

- Period: `SegmentedControl` [1st][2nd][3rd][OT]
- Clock: text input (MM:SS, monospace, #1A2B55 background)
- Event Type: same 3+3 pill grid as LogEventModal, pre-selected
- Zone: `SegmentedControl` [OZone][NZone][DZone]
- Strength: `SegmentedControl` [ES][PP][PK]
- Player: `PlayerRosterPicker` pre-selects matching player (or "No Player")

Action buttons: [Save Changes] orange fill 48px + [Delete Event] #E03B3B outline 48px.

5.3 PeriodSummaryModal

Type: Full-screen overlay (backdrop blur 4px, dark overlay). **Trigger:** "Period Summary" button in Game tab sub-toolbar. **Title:** "Period [N] Summary" bold white 24px.

Content sections (top to bottom):

22. Stat Cards grid (3+2+1 layout): Shots | Goals | Hits | Give Away | Take Away | Blocked Shot. Each card: #1A2B55 background, bold orange stat number 28px, muted label 12px.
23. MiniRinkSVG with event dot clusters — same geometry as main rink, ~200px tall, full modal width. Dots use same color spec as Section 4.2.3.
24. Legend: inline row —  Shots  Goals  Hits  Give Away  Take Away  Blocked. Centered, 11px muted. Wraps to two lines if needed.
25. Zone Time section: title + three horizontal progress bars (OZone/NZone/DZone) — colored fills, percentage label left, time string right.
26. Strength Breakdown table: Strength | Shots | Goals (rows: ES / PP / PK).
27. CTA: "Return to Game →" full-width orange button 50px.

5.4 EndOfGameModal

Type: Full-screen overlay (same style as PeriodSummaryModal). **Trigger:** "End of Game" button in Game tab sub-toolbar. **Title:** "Final Game Summary" bold white 24px.

Content sections (top to bottom):

28. Score display: "HOME 2 — 3 AWAY" — HOME in orange, AWAY in muted, numbers bold white 36px.
29. Period Breakdown Table: Period | Shots | Goals | Hits | GA | TA | BLK. Rows: 1st / 2nd / 3rd / TOTAL. TOTAL row: bold, orange background. Alternating #111E3F / #1A2B55, orange header, mono 12px.
30. MiniRinkSVG with full-game dot clusters (same spec as PeriodSummaryModal, denser dots).
31. Legend: same as PeriodSummaryModal.
32. Zone Time section: same horizontal bars layout as PeriodSummaryModal.
33. Strength Breakdown table: same as PeriodSummaryModal.
34. CTA: " Email Report to Coaches" full-width orange button 50px.

5.5 PlayerDetailSheet

Type: Bottom sheet (~75% screen height). **Trigger:** Tap on player row in RosterScreen. Drag handle at top.

Content layout:

- Jersey number badge (60px, orange bg, white bold 24px) + Name bold white 20px + Position pill + Status pill (Active / Inactive / Injured)
- Stat grid (2×4): GP | G | A | PTS | SOG | +/- | PIM | TOI — each cell: label muted 10px, value bold white 18px
- "On Ice This Game" toggle with label
- Buttons row: [Edit Player] orange outline + [Remove from Roster] red outline

§ 6 Setup Screen (SetupScreen)

Form group card style: #111E3F background, 12px padding, 10px border-radius, 1px #1F3366 border. 12px gap between groups. Row style: horizontal flex, label left (white 14px), control right (orange value or control component).

6.1 Groups and Fields

Group / Field	Control Type	Default / Notes
GROUP — TEAMS		
Your Team	Inline editable label	"NetFront HC" in orange — tap to edit inline
Opponent	Text input	Placeholder: "Enter opponent name"
GROUP — VENUE & TIME		
Date	Tappable date value → date picker	"Aug 19, 2026" in orange
Time	Tappable time value → time picker	"7:00 PM" in orange
Arena	Text input	—

Group / Field	Control Type	Default / Notes
Location	Text input	Placeholder: "City, State"
GROUP — GAME FORMAT		
Home / Away	Large two-state toggle	HOME (orange, left) / AWAY (right). Drives <code>gameIsAway</code> global state and <code>GameControlsPanel</code> visibility.
Periods	<code>StepperControl</code>	Default: 3
Period Length	<code>SegmentedControl</code>	[15 min][17 min][20 min]. Default: 20 min
Overtime	<code>ToggleSwitch</code>	Default: off
Shootout	<code>ToggleSwitch</code>	Default: off. Grayed out when Overtime = off.
GROUP — TRACKING PREFERENCES		
Track Zone Time	<code>ToggleSwitch</code>	Default: ON
Track Hits	<code>ToggleSwitch</code>	Default: ON
Auto-Flip Rink	<code>ToggleSwitch</code>	Default: ON. Sublabel: "Flips rink orientation each period" muted 11px.

Bottom CTAs:

- "🏒 Start Game" — full-width orange button 50px, white bold 18px → navigates to Game tab and initializes game state
- "← Return to Existing Game" — small muted text link. Visible only when a game is already in progress.

§ 7 Roster Screen (`RosterScreen`)

7.1 Header Row

- Title: "Roster" bold white 22px, left-aligned
- "+ Add Player" orange outline pill button, right-aligned → opens `AddPlayerModal`
- Subtitle: "[TeamName] — [N] players" muted 13px below title

7.2 SearchBar

Full-width.  icon left. Placeholder: "Search by name or number...". Background: #1A2B55. Border: 1px #1F3366. Radius: 10px. White text 14px.

7.3 Position Filter Tabs

Horizontal scrollable pill row: [All][Forwards][Defense][Goalie][Active][Inactive].
Active: orange fill. Inactive: #1A2B55 + muted text.

7.4 PlayerCard Component

Card style: #111E3F background, 12px padding, 8px radius, 1px #1F3366 border, 8px gap between cards.

Zone	Content	Style
LEFT — Jersey badge	Jersey number	36px square, #0A1A3F background, orange border 1.5px, bold orange 18px number
CENTER — Player info	Name, position, status, mini stats	Name: bold white 15px. Position pill (muted) + Status pill (Active=green / Inactive=gray / Injured=orange). Mini stats: "G: 3 A: 7 PTS: 10 SOG: 22" mono 11px muted.
RIGHT — Actions	Chevron + menu icon	">" muted chevron + "⋮" vertical menu icon



INJURED PLAYER DISPLAY

Injured player rows render at reduced opacity (0.65). The "Active" status pill is replaced with an orange " Injured" badge. These players are excluded from PlayerRosterPicker in the event logging modals.

7.5 AddPlayerModal

Simple form modal (bottom sheet). Fields: Jersey # (number input) | Full Name (text input) | Position (SegmentedControl [F][D][G]). Buttons: [Save Player] orange fill + [Cancel] orange outline.

§ 8 Settings Screen (SettingsScreen)

User Profile Card (top): Avatar 60px circle, #FF7A00 background, white initials bold 20px. Name bold white 16px. Role muted 13px. [Edit Profile] orange outline button right.

All groups use the same card style as SetupScreen.

Group / Field	Control Type	Default / Notes
GROUP — APP APPEARANCE		
Theme	SegmentedControl	[Dark ✓][Light][System]. Default: Dark
Accent Color	Color swatch dots	Orange selected (✓), then blue/green/purple options
Font Size	SegmentedControl	[S][M ✓][L]. Default: M
Screen Brightness	Slider 0-100%	Orange thumb. Default: 80%
GROUP — SOUND & HAPTICS		
Haptic Feedback	ToggleSwitch	Default: ON
Button Sounds	ToggleSwitch	Default: OFF
GROUP — GAME DEFAULTS		
Default Period Length	Tappable orange value	"20 min"
Default Periods	Tappable orange value	"3"
Auto-Start Clock	ToggleSwitch	Default: OFF
Clock Direction	SegmentedControl	[Count Down ✓][Count Up]. Default: Count Down
Offensive Side Reminder	ToggleSwitch	Default: ON. Sublabel: "Prompt at start of each period"

Group / Field	Control Type	Default / Notes
GROUP — DATA & EXPORT		
Export Format	SegmentedControl	[PDF ✓][CSV][Both]. Default: PDF
Email Reports To	Tappable orange value	"coaches@netfronthc.com"
Auto-Save Events	ToggleSwitch	Default: ON
Sync to Cloud	ToggleSwitch	Default: OFF. "Coming soon" muted badge shown alongside toggle.
GROUP — NOTIFICATIONS		
Game Reminders	ToggleSwitch	Default: ON
Reminder Lead Time	Tappable orange value	"2 hours before"
GROUP — ABOUT & SUPPORT		
App Version	Static muted label	"NetFront SM v2.4.1" — not tappable
View Changelog	Row + ">" chevron	—
Privacy Policy	Row + ">" chevron	—
Contact Support	Row + ">" chevron	Sublabel: "support@netfront.app"
Reset All Settings	Destructive tap row	Label in #E03B3B red. Tap → confirmation alert dialog before executing.

§ 9 Global State Model (UI-Layer)

All state below should be managed by a single `Zustand` store (recommended) or a React Context provider. No component should own game-critical state locally. State keys are exported from `store/gameStore.ts`.

State Key	Type / Values	Default	Drives
<code>clockMode</code>	<code>'manual' 'clock' 'clocksync'</code>	<code>'clock'</code>	ClockModeSelector, ClockDisplay, GameControlsPanel, LogEventModal note

State Key	Type / Values	Default	Drives
gameIsAway	boolean	true	GameControlsPanel visibility, SetupScreen Home/Away toggle
currentPeriod	'1st' '2nd' '3rd' 'OT'	'2nd'	PeriodBadge, GameControlsPanel period control
currentClock	string (MM:SS)	'14:22'	ClockDisplay, event timestamp capture in LogEventModal
clockRunning	boolean	false	ClockDisplay glow animation, Start/Stop button label
currentStrength	'ES' 'PP' 'PK'	'ES'	StrengthBadge, new event log rows
offensiveSide	'left' 'right'	'left'	RinkSVG labels, ZoneCards order, zone derivation on tap
connectionStatus	'connected' 'connecting' 'not_connected'	'connected'	ConnectionIndicator dot and label
syncStatus	'synced' 'waiting' 'lost'	'waiting'	SyncStatus component in GameControlsPanel (SYNC mode only)
selectedEventType	'shot' 'goal' 'hit' 'giveaway' 'takeaway' 'blockedshot'	'shot'	LogEventModal pills, pending rink dot color (real-time)
selectedPlayer	{ number, name, position } null	null	PlayerRosterPicker selected state, event log PLYR column
rinkDots	Array<{ x, y, type, period, clock, isPending }>	[]	RinkSVG dot layer — all persistent and pending dots
eventLog	Array<EventObject>	(sample events)	EventLog table rows, StatSummaryTable aggregates
homeScore	number	2	ScoreDisplay, GameControlsPanel HomeScoreControl
awayScore	number	3	ScoreDisplay,

State Key	Type / Values	Default	Drives
			GameControlsPanel AwayScoreControl
ozoneDuration	{ running, elapsed, longest, shortest, average }	—	OZoneCard timer display and stats
nzoneDuration	{ running, elapsed, longest, shortest, average }	—	NZoneCard timer display and stats
dzoneDuration	{ running, elapsed, longest, shortest, average }	—	DZoneCard timer display and stats

§ 10 Interaction Flows

10.1 Log Event Flow

35. Stat manager taps rink surface
36. App calculates SVG coordinates from tap position
37. Pending dot placed at (svgX, svgY) — color from selectedEventType default ('shot' = yellow)
38. LogEventModal slides up
39. Modal displays contextual clock note based on clockMode + selectedEventType
40. Stat manager selects event type pill → pending dot color updates in real time, immediately
41. Stat manager taps "Select Player" → PlayerRosterPicker expands → player selected → picker collapses to summary line
42. Stat manager taps Confirm:
 - (a) Pending dot becomes permanent (isPending: false)
 - (b) Zone derived from x-coordinate + offensiveSide
 - (c) Clock captured based on clockMode rules

- (d) New row prepended to eventLog: period | clock | event | player # | zone | strength
- (e) StatSummaryTable increments appropriate column for current period
- (f) Modal closes

43. OR stat manager taps Cancel:

- (a) Pending dot removed from rinkDots array
- (b) Modal closes

10.2 Zone Timer Flow

44. Stat manager taps Start on a ZoneCard

45. Card starts elapsed timer, `isActive=true`, button changes to "■ Stop", pulsing green dot appears

46. Stat manager taps Stop

47. Timer freezes, `isActive=false`, button reverts to "▶ Start"

48. Card updates Longest / Shortest / Average stats from interval history

49. Zone Start and Zone Stop events appended to `eventLog` with current period/clock/zone

10.3 Clock Mode Switching Flow

Transition	UI Changes
Manual → Clock	Freeze clock value. Show Start/Stop button. Remove ⇌ pencil hint. Remove MANUAL badge. Show CLK badge.
Clock → Sync	Pause clock. Show "Waiting..." yellow SyncStatus. Show ↺ sync icon on clock. Update badge to SYNC (blue).
Sync → Manual	Freeze clock at current synced value. Hide all sync UI. Show ⇌ pencil hint. Show MAN badge (gray).

⚠️ **CLOCK MODE SAFETY**

When switching away from `clocksync` mode during an active game, confirm with the user if the clock is currently running. Abruptly cutting the sync connection mid-period can cause timestamp inconsistencies in the event log. Display a confirmation dialog before allowing the switch.

10.4 Offensive Side Toggle Flow

50. Stat manager taps Left/Right on `OffensiveSideToggle`

51. `offensiveSide` state updates immediately

52. RinkSVG zone labels fade out (0.15s opacity) → label values swap → fade in (0.15s)

53. ZoneCards row reorders: OZone ↔ DZone position swap; NZone stays center; 0.3s transition

54. Zone derivation logic for all future tap events updates immediately via `offensiveSide` state

§ 11 Component Checklist (Developer Reference)

Priority legend: **P0** = Must-have for MVP | **P1** = Required before launch | **P2** = Can defer to v2

Component	Screen / Location	Priority	Notes
<code>AppBarHeader</code>	GameScreen top	P0	Static, always visible on Game tab
<code>ClockModeSelector</code>	GameScreen	P0	Three modes; drives most Section 1 behavior
<code>GameStatusBar</code>	GameScreen S1	P0	Period, clock, score, strength, connection
<code>GameControlsPanel</code>	GameScreen S1	P0	Away only,

Component	Screen / Location	Priority	Notes
			collapsible, mode-sensitive rows
ConnectionIndicator	GameScreen S1	P1	Cycle states for mockup; real BLE/WebSocket in production
RinkSVG	GameScreen S2	P0	Tap-to-place dots, zone labels, flip on offensiveSide
LogEventModal	GameScreen S2	P0	6 event types, real-time dot update, roster picker
StatSummaryTable	GameScreen S2	P1	7 columns including GA/TA/BLK
ZoneTimeCards	GameScreen S3	P0	Live timers, reorder on offensiveSide toggle
EventLog	GameScreen S4	P0	6 columns, colored row accents, tap to edit
EditEventModal	GameScreen S4	P1	Pre-filled from tapped row, all fields editable
PeriodSummaryModal	Game tab toolbar	P1	Mini rink dot chart, stat cards, zone bars
EndOfGameModal	Game tab toolbar	P1	Full game table, mini rink, email CTA
SetupScreen	Tab 2	P0	Form groups, Start Game CTA, drives gamelsAway
RosterScreen	Tab 3	P1	Player cards, search, filters, AddPlayerModal
PlayerDetailSheet	RosterScreen	P2	Stat grid, on-ice toggle, edit/remove
SettingsScreen	Tab 4	P2	All toggle/segmented preference groups
PlayerRosterPicker	LogEvent + EditEvent	P0	Shared inline component, Active players only
SegmentedControl	Multiple screens	P0	Shared, reused across all screens

Component	Screen / Location	Priority	Notes
ToggleSwitch	Multiple screens	P0	Shared, standard iOS-style toggle
PillButton	Multiple screens	P0	Start/Stop zones, CTAs, mode pills
StepperControl	Setup, GameControls	P1	Shared $\pm$ stepper for period/score controls

§ 12 Accessibility Notes

- Minimum touch target:** All interactive elements must meet 44×44px minimum (Apple HIG + Android Material guidelines). This includes PillButtons, ZoneCard Start/Stop, StepperControl buttons, and all modal action buttons.
- State communicated beyond color:** All status indicators (ConnectionIndicator, SyncStatus, ZoneCard active) include a text label alongside the colored dot. Color alone must never be the sole indicator of state.
- Large text support:** ClockDisplay and all stat numbers must use React Native's scalable font units. Do not fix font sizes in ways that prevent system-level text scaling.
- Event log contrast:** Monospace font in the EventLog must maintain a minimum contrast ratio of 4.5:1 against all row background colors (#111E3F and #1A2B55). White (#FFFFFF) text on these backgrounds meets this standard.
- Modal focus trapping:** Bottom sheet and full-screen modals must trap keyboard/screen reader focus when open. Focus must be restored to the triggering element when the modal closes.
- Toggle and control labels:** All ToggleSwitch and SegmentedControl instances must expose accessibilityLabel and accessibilityRole props. Do not rely on visual proximity to label text alone.

- **Drag handle accessibility:** All bottom sheet drag handles must include `accessibilityHint="Drag down to close"` and `accessibilityRole="button"`.
- **RinkSVG tap target:** The invisible tap capture rect over the SVG must be fully keyboard and switch-control accessible via alternative logging entry (e.g., a fallback text-based event entry button).

§ 13 React Native / Expo Implementation Notes

Feature	Recommended Approach
SVG Rink	<code>react-native-svg</code> — use <code>Svg</code> , <code>Rect</code> , <code>Circle</code> , <code>Line</code> , <code>Text</code> components. <code>ViewBox</code> coordinate mapping required for accurate dot placement from touch events.
Bottom Sheets	<code>@gorhom/bottom-sheet</code> (preferred) or custom <code>Animated.View</code> + <code>PanResponder</code> . Use <code>snapPoints</code> for consistent sizing.
Full Screen Modals	React Native <code>Modal</code> component with <code>animationType="slide"</code> and <code>transparent={true}</code> . Apply dark overlay and blur manually behind the modal card.
Live Timers	<code>setInterval</code> in <code>useEffect</code> with proper cleanup on unmount. Persist interval timestamps (not accumulated seconds) in Zustand so the timer survives re-renders.
Scrollable Event Log	<code>FlatList</code> with <code>keyExtractor</code> . Fixed-height container (220px). Set <code>inverted={false}</code> — newest events are prepended so natural scroll order is newest-first.
Zone Card Reorder	Use <code>Animated.View</code> with <code>LayoutAnimation</code> (RN) or a keyed array reorder to animate the <code>OZone</code> ↔ <code>DZone</code> position swap. 0.3s duration.
SVG Dot Persistence	Store the <code>rinkDots</code> array in Zustand. Map each dot to a <code><Circle></code> inside the <code><Svg></code> . Pending dot has <code>isPending: true</code> — remove on Cancel, update to false on Confirm.
Segmented Control	Build a fully custom component. Do not use <code>@react-native-segmented-control/segmented-control</code> — it does not support the app's

Feature	Recommended Approach
	dark color scheme and custom pill styles.
Color Tokens	Centralize all color values in <code>constants/colors.ts</code> . Export as a typed <code>const</code> object. Import directly into <code>StyleSheet</code> definitions — never as inline style strings.
Typography	Centralize all font specs in <code>constants/typography.ts</code> . Define named <code>StyleSheet</code> text styles (e.g., <code>TEXT_STAT_LARGE</code> , <code>TEXT_MONO_ROW</code>) and reuse across components.
State Management	<code>Zustand</code> strongly recommended for all global game state. Use slices for <code>gameStore</code> , <code>rosterStore</code> , and <code>settingsStore</code> . Avoids prop drilling and simplifies modal triggers.
Navigation	<code>@react-navigation/bottom-tabs</code> for tab navigator. Root navigator wraps the tab navigator to allow root-level modal rendering above the tab bar.
Clock Countdown	Use <code>useRef</code> for the interval ID to avoid stale closure issues. Store clock as total seconds (number), convert to <code>MM:SS</code> string for display only. Subtract 1 per tick.
Offline Support	<code>AsyncStorage</code> (or <code>expo-secure-store</code> for sensitive data) for auto-saving event log between sessions. Persist <code>eventLog</code> and <code>rinkDots</code> on every event append.

RECOMMENDED FILE STRUCTURE

```
constants/colors.ts · constants/typography.ts · constants/spacing.ts ·
store/gameStore.ts · store/rosterStore.ts · store/settingsStore.ts ·
components/global/ · components/game/ · components/modals/ · screens/GameScreen.tsx ·
screens/SetupScreen.tsx · screens/RosterScreen.tsx · screens/SettingsScreen.tsx ·
navigation/RootNavigator.tsx · navigation/BottomTabNavigator.tsx
```

