

WARM-UPS

Enough chit-chatting, time to code!



PRIMARY DATA TYPES

What are the primary data types most often used in data analysis and in R?

PRIMARY DATA TYPES

What are the primary data types most often used in data analysis and in R?

Character

Numeric

- double
- integer


Dates

Factors

Logical

PRIMARY DATA TYPES

What are the primary data types most often used in data analysis and in R?



DATA TYPE EXERCISES

Create these vectors:

- `dbl_var <- c(1, 2.5, 4.5, NaN, Inf)`
- `int_var <- c(1L, 6L, 10L, NA)`
- `log_var <- c(TRUE, FALSE, T, F)`
- `chr_var <- c("these are", "some strings")`
- `fct_var <- factor(c("male", "female", "male", "female"))`

Brainstorm with your neighbors all the ways to test for the type of contents in these vectors

SOLUTIONS

```
typeof      -> be careful, what happens when you apply this to a factor?  
class       -> be careful, what happens when you apply this to a double?  
is.numeric  
is.double  
is.integer  
is.logical  
is.character  
is.factor  
  
# Bonus  
is.na  
is.nan  
is.infinite
```

*Plenty more, just type **is.** + tab for a full list*

COERCION EXERCISES

Discuss with your neighbor ...what happens when you do the following? Use your mind not your computer to answer:

- `typeof(c(int_var, dbl_var))`
- `typeof(c(int_var, log_var))`
- `typeof(c(log_var, chr_var))`
- `typeof(c(chr_var, int_var))`
- `typeof(c(chr_var, fct_var))`

SOLUTIONS

```
> typeof(c(int_var, dbl_var))
```

```
[1] "double"
```

```
> typeof(c(int_var, log_var))
```

```
[1] "integer"
```

```
> typeof(c(log_var, chr_var))
```

```
[1] "character"
```

```
> typeof(c(chr_var, int_var))
```

```
[1] "character"
```

```
> typeof(c(chr_var, fct_var))
```

```
[1] "character"
```


COERCION EXERCISES

Now, how would you make these conversions:

- *convert `int_var` to a double*
- *convert `log_var` to a character*
- *convert `fct_var` to a character*
- *convert `log_car` to a factor*

SOLUTIONS

```
as.double(int_var)  
as.character(log_var)  
as.character(fct_var)  
as.factor(log_var)
```

EXERCISES

How would you apply the following function to compute the sum of squares for each list item?

```
sum_of_squares <- function(x) {  
  sum(x ^ 2)  
}
```

```
lst <- list(c(3, 4, 8), c(4, 7, 1))
```

SOLUTIONS

```
library(tidyverse)

sum_of_squares <- function(x) {
  sum(x ^ 2)
}

lst <- list(c(3, 4, 8), c(4, 7, 1))

map_dbl(lst, sum_of_squares)
[1] 89 66
```

EXERCISES

What is the output of the following code?

```
c(25, 10, 15, 12) %>% rank()
```

SOLUTIONS

```
c(25, 10, 15, 12) %>% rank()  
[1] 4 1 3 2
```

EXERCISES

id is the primary key in df1. Examine the data frame df2 . Which variable is the secondary key? How would you join by these keys?

```
> df1
```

	id	name	phone
1	4	Jane	03566658397
2	5	John	05521214979
3	6	Joe	06334794646

```
> df2
```

	customer_id	order_id	paid
1	4	A10	Yes
2	5	A11	Yes
3	4	A12	No
4	6	A13	No

SOLUTIONS

```
> df1
```

	id	name	phone
1	4	Jane	03566658397
2	5	John	05521214979
3	6	Joe	06334794646

```
> df2
```

	customer_id	order_id	paid
1	4	A10	Yes
2	5	A11	Yes
3	4	A12	No
4	6	A13	No

```
df1 %>% left_join(df2, by = c("id" = "customer_id"))
```


LET'S GET STARTED!

