

Simulation

Discrete event systems

Discrete event simulation 1

- Consider systems with finitely many components.
- Each component has only finitely many states.
- Components interact through events.
- Event takes place at a particular time (it has no duration).

Discrete event simulation 2

- Event can change states, generate other events (for the same or later time).
- Typical structural components
 - "machine resources" (busy/free)
 - "human resources" (busy/free)
 - "raw materials" (availability/quantity)
 - "products" (stage of production/availability)
- Events are beginnings and endings of actions

Wash machine

- Components of car wash
 - Wash machine (free/busy)
 - Queuing space (M available slots)
 - Clients (unwashed/washed)
- Events
 - Client arrival/departure
 - Wash start/end
 - Entering/leaving the queue
- Some events occur always together

Main simulation functionalities 1

- Simulation software has 5 main functionalities
 - Description of model structure
 - System parts -> state variables
 - Interaction logic -> "flow chart"
 - Event logic-> "code"
 - Random processes
 - Random numbers from desired distribution
 - Collecting and reporting statistics
 - Visualisation, confidence intervals, analysis

Main simulation functionalities 2

- Time management
 - Advancing the clock event by event
 - Activating events in right order
- Management of simulation experiment
 - Starting/ending simulation
 - Adding/removing events
 - Controlled replication of experiments

Main simulation functionalities 3

- Some functions are common to all models and experiments
 - Time management
 - Random numbers
 - Data collection and reporting
- Some are model and case dependent
 - Model structure and logic
 - Control flow in (series of) experiment(s)

Simulation paradigms

- Three approaches to simulation
 - Event based
 - State changes linked to certain time
 - Process based
 - Life cycle of events related to a system component.
 - Activity based
 - Activities that tie up resources of system components
- These lead to different model/code structures
 - Fit to different modelling situations

Event based simulation

- Event routines have central role
 - One routine for each type of event
 - Model logic is in the event routines
 - Event routine can change state variables and create event notices.
 - Scheduler manages event notices (time, event)
- One routine at a time is active.

Process/object based s.

- Subprocesses as objects with own state variables and event routines.
 - All actions related to a system component are within a single object
- Specific methods to communicate with scheduler and other objects.
 - No separate event notices
- Several processes active simultaneously (threads, coroutines).

Activity based s.

- Logic within activity routines
 - Each routine is linked to some resource
 - Two interfaces
 - Activation (if conditions are true, then reserve the resource and fix ending time)
 - Passivation: free the resource at given time
- All activities are scanned systematically
 - If conditions are true, routine is activated .
 - If no routine activates, time is incremented to next known ending time.

Simulation

Event based simulation

Event based simulation

- Historically oldest approach
- Logic is within sequentially executed routines
 - Easy to implement with any procedural language
 - Logic gets easily fragmented
 - Successive/dependent events are in separate routines

Wash machine (event b.)

- At least two types of events (arrival and departure (see introduction))
 - Both events can reserve the machine and generate departure
 - Potential maintainability problem
- Use 4 atomic events
 - Arrival (generates the client)
 - Start (reserve the resource and start service)
 - End (end service, free resource)
 - Departure (exits the client)


Wash machine 2

- Arrival
 - If queue not full
 - Create new client and put to the queue
 - Create a Start-event
 - Create new Arrival event (for later time)
- Start
 - If machine is free and clients in the queue
 - Take client from queue
 - Set machine busy
 - Create an End-event (for later time)

Wash machine 3

- End
 - Set machine free
 - Create Departure-event (for same time)
 - Create Start-event (for same time)
- Departure
 - Collect needed information from the client (if any)
 - Remove client

Wash machine



Wash machine - implementation

- 4 event (sub)routines
- For events `EventType` (Arrival, Start, End, Departure)
- For bookkeeping `EventNotice` (Time, Event)
- Event list to keep `EventNotice`
 - Methods
 - `NextEvent`
 - `AddEvent` (Time, Event)
 - `(RemoveEvent` (Event))
- Queue
 - Contains instances of `Client` -type
 - Methods `Add`, `Next`, `Length`
 - Serves Start-event
 - Another queue (or like) is needed for Departure

Wash machine - main

```
Initialize
T=0;
AddEvent(ArrivalTimeDistribution(),Arrival);
While (T< TMax)  \\ (ending condition)
    Notice=NextEvent();
    T=Notice.Time;
    Type=Notice.Event;
    CASE Type of
        ...
        \\ call for corresponding event routine
    END CASE
End While
```

Arrival

```
Arrival_Event()  
    ClientTypePointer :: Car  
    {  
        AddEvent(ArrivalTimeDisribution(),Arrival);  
        If Queue.Length() < M then  
            Car= New Client();  
            Queue.Add(Car)  
            AddEvent(0.,Start)  
        EndIf  
    }
```

Start

```
Start_Event()  
  ClientTypePointer :: Car  
  {  
    If (Machine.Free() and Queue.Length() > 0) then  
      Car = Queue.Next();  
      Machine.Reserve(Car);  
      AddEvent(ServiceTimeDistribution(), End)  
    Endif  
  }
```

End

```
End_Event()  
    ClientTypePointer :: Car  
    {  
        Car= Machine.Free()  
        Departure.Reserve(Car)  \ \  To keep track of  
        the client pointer  
        AddEvent(0.,Departure)  
        AddEvent(0.,Start)  
    }
```

Departure

```
Departure_Event()  
    ClientTypePointer :: Car  
    {  
        Car=Departure.Free()  
        // Collect statistics  
        RemoveClient(Car)  
    }  
// Reserve-Free for departure is a hack to keep the  
   client pointer in absence of a real queue.
```

Observations

- Different queuing strategies can be hidden within Queue
- In case of several services, routing, client types etc requires replication or parametrization of events.
- In practice the service and its queue can be modeled as one entity where to the client is routed.

Simulation

Event based harbour network

Container harbours

- Main events
 - Ship i arrives to harbour j
 - Ship i to queue of harbour j at time t
 - Try to start loading (if queue empty)
 - Loading begins at dock
 - Ship i from queue, dock k reserved, loading end event for time t_2

Container harbours

- Main events
 - Unloading of the ship ends
 - Dock k becomes free at t_3
 - Try to start loading (if ships in queue)
 - Ship leaves for the next harbour
 - Ship i is scheduled to arrive to harbour j' at t_4

Questions ?

- Main events
 - Ship i arrives to harbour j
 - Ship i enters the queue of j at time t
 - What information is contained in the event notice.
How the rest is communicated.
 - Unloading begins
 - Ship i taken from the queue, dock k reserved, end unloading –event for time t_1
 - Is reference to dock k needed, where to keep link to ship i

Questions?

- Main events
 - Unloading ends
 - Dock k becomes free at time t_3
 - Where is knowledge about the dock, about the ship
 - Ship leaves for next harbour
 - Arrival of ship i to harbour j' is scheduled at time t_4
 - Who knows the value of j' for ship i

Event notices

- For traditional languages event notices are problematic
 - Static data types
 - Limited amount of information can be communicated
- Use of objects and inheritance helps
 - Inherited notice class for each type of event