Product spec sheets

Your Security Company

QA msedge 20261015T1631 Main workflow · QA Customer (disposable)

4MP Turret

Qty 4 · GEN-TUR-4

Type	Turret camera
Resolution	4.1 MP (2688×1520)
Lens	2.8 mm
Field of view	103°
Night (IR) reach	100 ft
Identify faces to	14.0 ft
Recognise people to	28.1 ft
Detect people to	140 ft
Indoor / outdoor	Outdoor
PoE	Class 2 · 6 W
Specs	Typical values

4MP Varifocal Dome

Qty 1 · GEN-DOME-4

Type	Dome camera
Resolution	4.1 MP (2688×1520)
Lens	2.8–12 mm
Field of view	100° (zoom 33–100°)
Night (IR) reach	100 ft
Identify faces to	14.8 ft
Recognise people to	29.6 ft
Detect people to	148 ft
Indoor / outdoor	Outdoor
PoE	Class 3 · 8 W
Specs	Typical values

Avigilon H5A Bullet 2MP IR

Qty 2 · 2.0C-H5A-BO1-IR

Type	Bullet camera
Resolution	2.1 MP (1920×1080)
Lens	3.3–9 mm
Field of view	99° (zoom 34–99°)
Night (IR) reach	164 ft
Identify faces to	10.8 ft
Recognise people to	21.5 ft
Detect people to	108 ft
Indoor / outdoor	Outdoor
PoE	Class 3 · 13 W
Specs	Checked against maker

Uniview IPC3614SB 4MP Turret

Qty 2 · IPC3614SB-ADF28KM-I0

Type	Turret camera
Resolution	3.7 MP (2560×1440)
Lens	2.8 mm
Field of view	101°
Night (IR) reach	98.0 ft
Identify faces to	13.8 ft
Recognise people to	27.6 ft
Detect people to	138 ft
Indoor / outdoor	Outdoor
PoE	4 W
Specs	Checked against maker

AXIS M4308-PLE Panoramic

Qty 2 · 02100-001

Type	Fisheye camera
Resolution	8.3 MP (2880×2880)
Lens	1.3 mm
Field of view	360°
Night (IR) reach	49.0 ft
Identify faces to	6.0 ft
Recognise people to	12.0 ft
Detect people to	60.2 ft
Indoor / outdoor	Outdoor
PoE	Class 4 · 15.5 W
Specs	Checked against maker

16-ch NVR

Qty 1 · GEN-NVR16

Type	NVR
Part number	GEN-NVR16
Channels	16
Storage	16 TB
Specs	Typical values

16-port PoE+ Switch

Qty 1 · GEN-SW16P

Type	PoE switch
Part number	GEN-SW16P
Ports	16 · 250 W PoE
Specs	Typical values

Confirm final specs on the manufacturer datasheet before ordering.