

Independent calculations of fault valving: interim results

Reproducibility study of Zhu, Allison, Dunham, and Yang (2020)

2026-10-09 00:47 UTC

This is an interim scientific report. The full study remains incomplete. At this snapshot, 9 of 12 configured cases have completed, and 30 of 49 panel packages are available. Of these, 2 are independently reproduced constitutive-law panels and 28 are partial comparisons, including one newly drawn schematic. The 19 pending panels are labeled as not reproduced (pending) in the inventory; this describes their current availability, not a failed physical behavior. Pending runs are `baseline`, `baseline_fine`, `baseline_tight`. Their configured durations remain unchanged.

1 Scope and independence

Fault slip increases permeability, while healing between earthquakes restricts drainage. The resulting pore-pressure changes alter frictional strength. We independently implemented the coupled earthquake-cycle and fluid-flow model of Zhu et al. [1] in C++. The scientific inputs are the published article, its supplement, and comparable written model documentation. The earlier project attempt used authors' archived outputs; that attempt and all its simulation inputs are excluded here. No authors' code, simulation output, source dataset, digitized output curve, or published image supplies a numerical result or figure in this report. The schematic is newly drawn and is not a reproduced simulation.

Every displayed numerical panel comes from independent arrays in `data/panels`. Its JSON sidecar records parameters, source hashes, selection window, and provenance. A constitutive-law check establishes a narrower result than recovery of an earthquake sequence. All displayed cycle calculations remain partial comparisons because timing, event patterns, assumed inputs, or spatial convergence remain unresolved. Published cycle durations below are approximate visual readings used only as comparison targets, never computational inputs.

2 Physical model and declared assumptions

The elastic domain occupies $0 \leq y \leq L_y$ and $0 \leq z \leq L_z$, with depth z positive downward. Both dimensions are 500 km. Antiplane displacement u is half the fault slip on $y = 0$; the remote side is displaced at half the plate rate. The top and bottom are traction free. The shear modulus is 32.4 GPa, $V_p = 10^{-9} \text{ m s}^{-1}$, and the radiation-damping coefficient is $\eta_{\text{rad}} = 4.68 \times 10^6 \text{ Pa s m}^{-1}$.

The regularized friction law and aging law are

$$f(V, \psi) = a \operatorname{asinh} \left[\frac{V}{2V_0} \exp \left(\frac{\psi}{a} \right) \right], \quad (1)$$

$$\dot{\psi} = \frac{b}{d_c} \left[V_0 \exp \left(\frac{f_0 - \psi}{b} \right) - |V| \right], \quad (2)$$

$$\tau_{\text{qs}} - \eta_{\text{rad}} V = (\sigma - p) f(V, \psi). \quad (3)$$

Here $V_0 = 10^{-6} \text{ m s}^{-1}$, $f_0 = 0.6$, and $d_c = 2 \text{ mm}$. Friction is signed; slip speed is used in state and permeability evolution if reverse slip occurs. This extends the paper's positive-sliding

convention and is documented explicitly. Radiation damping limits rapid slip within the quasi-dynamic approximation; it does not reproduce propagating elastic waves.

Fault-zone fluid storage, Darcy flux, and permeability obey

$$n\beta \partial_t p = \partial_z q, \quad q = \frac{k}{\eta} (\partial_z p - \rho g), \quad (4)$$

$$k = k_{\min} + (k_* - k_{\min}) \exp[-(\sigma - p)/\sigma_*], \quad (5)$$

$$\dot{k}_* = \frac{|V|}{L} (k_{\max} - k_*) - \frac{k_* - k_{\min}}{T}. \quad (6)$$

Positive q denotes upward flow. The surface pressure is zero and the bottom influx is fixed. We use $n\beta = 10^{-11} \text{ Pa}^{-1}$, $\eta = 10^{-4} \text{ Pa s}$, $\rho = 1000 \text{ kg m}^{-3}$, $g = 9.8 \text{ m s}^{-2}$, $\sigma_* = 30 \text{ MPa}$, $L = 1 \text{ m}$, $k_{\min} = 10^{-19} \text{ m}^2$, and $k_{\max} = 10^{-15} \text{ m}^2$. The healing times are 10^7 , 10^8 , 10^9 , and 10^{10} s . Bottom influx is $3 \times 10^{-9} \text{ m s}^{-1}$ except for $T = 10^7 \text{ s}$, where it is $3.3 \times 10^{-10} \text{ m s}^{-1}$. Porosity changes, thermal pressurization, and bulk poroelastic stress changes are omitted as in the published model.

Several inputs needed for an executable model are not fully specified in the article or supplement. We assume $\sigma(z) = (22 \text{ MPa km}^{-1})z$, consistent with the displayed normal-stress line in the original Fig. 1d. We prescribe $a = 0.01$ at the surface, increasing linearly to 0.03 at 15 km, then increasing at 0.003 km^{-1} . We set $a - b = -0.01$ above 13.5 km and increase it linearly below that depth, crossing zero at 17 km. These profiles continue to the bottom boundary. They approximate a parameter diagram, not a digitized simulation result, and their exact agreement with the authors' inputs cannot be established from the written record.

Initially k_* has its steady-sliding value at V_p , and pressure is the discrete steady solution with flux q_0 at every face. State is initialized at its steady-sliding value at V_p . Initial velocity varies from $10^{-4}V_p$ above 17 km to V_p below, through a hyperbolic tangent of width 1.5 km. Elastic prestress balances that initial velocity. A Gaussian reduction of 10^{-4} in ψ , centered at 12 km with width 1 km, perturbs the fault. Earthquake times, rupture footprints, and subsequent slip are not prescribed. These initial conditions are independent choices; no published restart is used.

An exploratory all-depth steady-sliding initialization was also tested. Shallow elastic stiffness imposed a severe explicit time-step restriction. The nearly locked shallow start is therefore used for the production runs; its influence is assessed separately from numerical resolution. Full parameter files and all choices are included in the repository.

3 Independent numerical method

The elastic boundary-value problem can be reduced analytically to a fault stiffness operator. A cosine mode with $\kappa_j = j\pi/L_z$ has stiffness

$$K_0 = \frac{\mu}{2L_y}, \quad K_j = \frac{\mu\kappa_j}{2} \coth(\kappa_j L_y), \quad j > 0. \quad (7)$$

The factor one-half converts fault slip to one-sided displacement. These eigenvalues retain the finite side and bottom boundaries. FFTW cosine transforms apply this operator on cell centers, with $\tau_{qs} = \tau_{\text{initial}} - Kd$ and d equal to accumulated slip minus $V_p t$.

Physical fault nodes form a graded subset of this auxiliary grid. If P linearly interpolates physical slip to the cosine grid, the physical operator is $W^{-1}P^T h K P$, where W contains control-volume widths and h is the auxiliary spacing. This weighted Galerkin projection preserves constant traction, elastic reciprocity, and positive elastic energy. It retains the fine grid through the rupture region while reducing the number of far-depth unknowns.

Pressure is discretized by conservative finite volumes, using excess pressure $p - \rho g z$ and harmonic face permeability. Gradients use actual node distances; surface pressure is imposed at the surface and

bottom flux enters storage directly. This scheme differs from the paper’s fourth-order summation-by-parts method. The production cosine grid has 131,072 points, giving a minimum fault spacing of 3.815 m. Spacing is finest through the rupture depths and down to 30 km; it increases at greater depths toward a 1 km target. The final interval can reach about 1.5 times that target to avoid an undersized boundary interval. The surface spacing is about eight times the minimum and decreases to the minimum over the upper 2 km. Both the minimum and maximum spacings halve or double in refinement cases. The number of physical nodes and the resolved frictional length scales are recorded in the completed-case audit files. No stress or velocity floor replaces spatial resolution.

We use the fourth-order additive Runge–Kutta method ARK4(3)6L[2]SA [3], treating fluid flow implicitly and slip, state, and k_* explicitly. The nonlinear pressure solve iterates permeability and a tridiagonal solve to an absolute pressure-update tolerance of 0.001 Pa. An embedded third-order estimate controls errors in slip, state, permeability, and pressure. The fourth-order solution is accepted. Production tolerance is 10^{-5} in the scaled maximum norm; the time-accuracy case uses 2.5×10^{-6} . A controlled interseismic benchmark showed that this tighter tolerance reduced accumulated errors without substantially increasing the cost of the graded calculation. The maximum step is 10^6 s. Detailed coefficients, scales, boundary formulas, and data formats are given in `documentation/numerics.md`.

4 Completed runs and quantitative comparisons

Every completed case passed an audit of all accepted history rows and saved field profiles, including samples outside the figure windows. The audit checks finite values, positive effective stress, permeability bounds, accepted error estimates, consecutive steps, field/history consistency, and source and parameter hashes. Fixed-pressure cases also retain pressure throughout their saved profiles. These checks establish internal consistency; they do not establish sequence convergence or agreement with the paper. The audit files are `data/<case>/output_verification.json`.

Case	Duration (yr)	Accepted steps	Profiles	Large events
reference	400	164586	14041	5
short	200	272347	8873	4
long	350	306854	17162	6
long_reference	350	209873	12897	4
verylong	500	216379	18414	3
verylong_reference	500	334274	19194	4
baseline_coarse	200	438564	14838	7
initialization	100	282753	7219	4
normal_stress	100	287400	7227	4

A seismic interval is a whole-fault maximum speed excursion above 10^{-3} m s^{-1} . A resolved rupture accumulates at least 1 cm of slip in a connected depth interval. A large event has a connected footprint reaching above 2 km and spanning more than 10 km. Slip is measured between the saved first-above and first-below threshold profiles. Incomplete events cannot define cycles. Velocity maps use the last complete large-event cycle; cumulative-slip profiles use the last two complete cycles. All available recurrence intervals are retained in each analysis file. Neither event selection nor time windows are fitted to the published images.

Case	Last cycle (yr)	All-cycle median (yr)	Paper (yr)	Difference (%)
reference	64	66	50	27.9
long_reference	88.4	88.4	160	-44.8
long	70.5	63.6	65	8.4
verylong_reference	95.1	95.2	160	-40.6
verylong	174	179	150	16.3

The reference target is main Fig. 2a; the long-healing targets are supplementary Figs. 3a,c and 5a,c. The differences describe the selected final cycles and do not imply stationary recurrence. In particular, the two long-healing fixed-pressure references differ substantially from their approximately 160-year targets. Uncertain friction profiles and initialization, finite simulated duration, and unestablished spatial convergence prevent assigning these discrepancies to one cause. No high-healing-time mesh study has been completed.

Case	T (s)	$\Delta(\sigma - p)$ at 10 km (MPa)	Leading front (m/yr)	Deepest front (m/yr)
short	1e+07	4.57	1.84e+03	1.53e+03
long	1e+09	16.5	187	242
verylong	1e+10	6.82	168	168

The stress range uses the nearest saved depth, about 10.004 km. Front rates are medians of all retained upward segments of the $|V| = V_p$ contour, with $R^2 \geq 0.8$, at 13–20 km depth. The leading and deepest branches are contour extrema, not tracked identities of individual pulses. Their definitions need not coincide with the paper’s reported migration speeds of 2500, 120, and 30 m/yr for these three cases. The discrepancies are retained rather than selecting the branch closest to the published rate.

The short-healing case produces aseismic pulses. The following medians compare with the article’s approximate one-year duration, few-year recurrence, and few-centimeter slip scales. Pulse widths depend on our declared threshold, $|V| \geq 1.1V_p$. Each counted episode lasts at least 0.01 yr, lies within the selected window, and remains below the seismic threshold at every accepted whole-fault history sample. All qualifying episodes are retained in the case analysis. The depth dependence limits any claim of agreement.

Depth (km)	Episodes	Duration (yr)	Recurrence (yr)	Slip (cm)
15	14	0.302	3.04	4.72
18	11	0.611	3.17	2.46
20	2	0.894	8.64	3.19

The final model assessment requires the baseline, mesh-refined case, and tighter time-tolerance case together. This interim report does not treat completed coarse-grid, normal-stress, or initialization runs as a completed sensitivity comparison. Software fixtures and exploratory short calculations are excluded from all scientific figures here.

5 Panel inventory and provenance

Each row specifies the original label, quantity, documentation, independent-data command, plotting command, status, and discrepancy. Data paths follow `data/panels/<label>.npz`, with parameters and provenance in the adjacent JSON file. Commands are intended for a clean checkout or completed cases; do not start a duplicate simulation in a directory containing a live run. Supplementary Fig. 2 visibly labels rows a and b; its caption also mentions c and d, which are not separately visible. The inventory therefore includes the two displayed rows and records that inconsistency.

Panel	Quantity	Documentation	Data command	Plot command	Status	Discrepancy
F1a	Geometry schematic and assumed friction profiles	Main Fig. 1a; Eqs. (7)-(9); Table 1; $a(z)$, $b(z)$ are assumed	<code>python3 scripts/panel.py F1a --data</code>	<code>python3 scripts/plot.py F1a</code>	partial	New schematic, not a simulation reproduction; friction profiles are declared approximations.
F1b	Permeability versus effective normal stress	Main Eq. (3), Fig. 1b; Table 1	<code>python3 scripts/panel.py F1b --data</code>	<code>python3 scripts/plot.py F1b</code>	independently reproduced	Analytic laws agree with numerical limiting-case verification.
F1c	Healing and slip-enhancement limiting solutions	Main Eq. (4), Fig. 1c; Table 1	<code>python3 scripts/panel.py F1c --data</code>	<code>python3 scripts/plot.py F1c</code>	independently reproduced	Analytic laws agree with numerical limiting-case verification.
F1d	Steady pressure, stress, and permeability profiles	Main Eqs. (2)-(4), Fig. 1d; assumed normal-stress gradient	<code>python3 scripts/panel.py F1d --data</code>	<code>python3 scripts/plot.py F1d</code>	partial	Normal stress gradient is assumed; steady Darcy balance is independently verified.
F2a	Slip velocity in time and step coordinates	Main Fig. 2; main Eqs. (1)-(9), Table 1	<code>python3 scripts/panel.py F2a --data</code>	<code>python3 scripts/plot.py F2a</code>	partial	Last complete interval 64 yr versus approximately 50 yr in Main Fig. 2a (+28%). All-interval median 66 yr. Initial state and friction profiles remain uncertain.
F2b	Cumulative slip profiles	Main Fig. 2; main Eqs. (1)-(9), Table 1	<code>python3 scripts/panel.py F2b --data</code>	<code>python3 scripts/plot.py F2b</code>	partial	Last complete interval 64 yr versus approximately 50 yr in Main Fig. 2a (+28%). All-interval median 66 yr. Initial state and friction profiles remain uncertain.
F2c	Slip velocity in time and step coordinates	Main Fig. 2; main Eqs. (1)-(9), Table 1	<code>python3 scripts/panel.py F2c --data</code>	<code>python3 scripts/plot.py F2c</code>	not reproduced (pending)	Pending completed baseline calculation and final extraction; no result supplied in this snapshot.
F2d	Cumulative slip profiles	Main Fig. 2; main Eqs. (1)-(9), Table 1	<code>python3 scripts/panel.py F2d --data</code>	<code>python3 scripts/plot.py F2d</code>	not reproduced (pending)	Pending completed baseline calculation and final extraction; no result supplied in this snapshot.
F3a	Effective normal stress history	Main Fig. 3; main Eqs. (1)-(4), Table 1	<code>python3 scripts/panel.py F3a --data</code>	<code>python3 scripts/plot.py F3a</code>	not reproduced (pending)	Pending completed baseline calculation and final extraction; no result supplied in this snapshot.
F3b	Effective normal stress depth profiles	Main Fig. 3; main Eqs. (1)-(4), Table 1	<code>python3 scripts/panel.py F3b --data</code>	<code>python3 scripts/plot.py F3b</code>	not reproduced (pending)	Pending completed baseline calculation and final extraction; no result supplied in this snapshot.
F3c	Permeability history	Main Fig. 3; main Eqs. (1)-(4), Table 1	<code>python3 scripts/panel.py F3c --data</code>	<code>python3 scripts/plot.py F3c</code>	not reproduced (pending)	Pending completed baseline calculation and final extraction; no result supplied in this snapshot.
F3d	Permeability depth profiles	Main Fig. 3; main Eqs. (1)-(4), Table 1	<code>python3 scripts/panel.py F3d --data</code>	<code>python3 scripts/plot.py F3d</code>	not reproduced (pending)	Pending completed baseline calculation and final extraction; no result supplied in this snapshot.
F3e	Upward fluid flux history	Main Fig. 3; main Eqs. (1)-(4), Table 1	<code>python3 scripts/panel.py F3e --data</code>	<code>python3 scripts/plot.py F3e</code>	not reproduced (pending)	Pending completed baseline calculation and final extraction; no result supplied in this snapshot.
F3f	Upward fluid flux depth profiles	Main Fig. 3; main Eqs. (1)-(4), Table 1	<code>python3 scripts/panel.py F3f --data</code>	<code>python3 scripts/plot.py F3f</code>	not reproduced (pending)	Pending completed baseline calculation and final extraction; no result supplied in this snapshot.
F4a	Slip velocity versus time	Main Fig. 4; Eqs. (1)-(9); Table 1	<code>python3 scripts/panel.py F4a --data</code>	<code>python3 scripts/plot.py F4a</code>	not reproduced (pending)	Pending completed baseline calculation and final extraction; no result supplied in this snapshot.
F4b	Slip velocity versus accepted step	Main Fig. 4; Eqs. (1)-(9); Table 1	<code>python3 scripts/panel.py F4b --data</code>	<code>python3 scripts/plot.py F4b</code>	not reproduced (pending)	Pending completed baseline calculation and final extraction; no result supplied in this snapshot.

Panel	Quantity	Documentation	Data command	Plot command	Status	Discrepancy
F4c	Effective normal stress	Main Fig. 4; Eqs. (1)-(9); Table 1	<code>python3 scripts/panel.py F4c --data</code>	<code>python3 scripts/plot.py F4c</code>	not reproduced (pending)	Pending completed baseline calculation and final extraction; no result supplied in this snapshot.
F4d	Permeability	Main Fig. 4; Eqs. (1)-(9); Table 1	<code>python3 scripts/panel.py F4d --data</code>	<code>python3 scripts/plot.py F4d</code>	not reproduced (pending)	Pending completed baseline calculation and final extraction; no result supplied in this snapshot.
F5a	Slip velocity versus time	Main Fig. 5; Eqs. (1)-(9); Table 1; $T=1e7$ s, $q_0=3.3e-10$ m/s	<code>python3 scripts/panel.py F5a --data</code>	<code>python3 scripts/plot.py F5a</code>	partial	Complete aseismic episodes above 1.1 Vp at 15/18/20 km: 14/11/2. Median intervals: 3.04, 3.17, 8.64 yr. Durations and slip are tabulated in the report; exact pulse sequence is not recovered.
F5b	Slip velocity versus accepted step	Main Fig. 5; Eqs. (1)-(9); Table 1; $T=1e7$ s, $q_0=3.3e-10$ m/s	<code>python3 scripts/panel.py F5b --data</code>	<code>python3 scripts/plot.py F5b</code>	partial	Complete aseismic episodes above 1.1 Vp at 15/18/20 km: 14/11/2. Median intervals: 3.04, 3.17, 8.64 yr. Durations and slip are tabulated in the report; exact pulse sequence is not recovered.
F5c	Effective normal stress	Main Fig. 5; Eqs. (1)-(9); Table 1; $T=1e7$ s, $q_0=3.3e-10$ m/s	<code>python3 scripts/panel.py F5c --data</code>	<code>python3 scripts/plot.py F5c</code>	partial	Complete aseismic episodes above 1.1 Vp at 15/18/20 km: 14/11/2. Median intervals: 3.04, 3.17, 8.64 yr. Durations and slip are tabulated in the report; exact pulse sequence is not recovered.
F5d	Permeability	Main Fig. 5; Eqs. (1)-(9); Table 1; $T=1e7$ s, $q_0=3.3e-10$ m/s	<code>python3 scripts/panel.py F5d --data</code>	<code>python3 scripts/plot.py F5d</code>	partial	Complete aseismic episodes above 1.1 Vp at 15/18/20 km: 14/11/2. Median intervals: 3.04, 3.17, 8.64 yr. Durations and slip are tabulated in the report; exact pulse sequence is not recovered.
F6	Upward migration of the $ V =V_p$ contour	Main Fig. 6 and Discussion; reported rates 2.50, 0.38, 0.12, 0.03 km/year	<code>python3 scripts/panel.py F6 --data</code>	<code>python3 scripts/plot.py F6</code>	not reproduced (pending)	Pending completed baseline calculation and final extraction; no result supplied in this snapshot.
S1a	Slip velocity at 5, 10, 15, and 20 km	Supplementary Fig. 1; main Eqs. (1)-(9)	<code>python3 scripts/panel.py S1a --data</code>	<code>python3 scripts/plot.py S1a</code>	not reproduced (pending)	Pending completed baseline calculation and final extraction; no result supplied in this snapshot.
S1b	Permeability at 5, 10, 15, and 20 km	Supplementary Fig. 1; main Eqs. (1)-(9)	<code>python3 scripts/panel.py S1b --data</code>	<code>python3 scripts/plot.py S1b</code>	not reproduced (pending)	Pending completed baseline calculation and final extraction; no result supplied in this snapshot.
S1c	Upward flux at 5, 10, 15, and 20 km	Supplementary Fig. 1; main Eqs. (1)-(9)	<code>python3 scripts/panel.py S1c --data</code>	<code>python3 scripts/plot.py S1c</code>	not reproduced (pending)	Pending completed baseline calculation and final extraction; no result supplied in this snapshot.
S1d	Effective stress at 5, 10, 15, and 20 km	Supplementary Fig. 1; main Eqs. (1)-(9)	<code>python3 scripts/panel.py S1d --data</code>	<code>python3 scripts/plot.py S1d</code>	not reproduced (pending)	Pending completed baseline calculation and final extraction; no result supplied in this snapshot.
S2a	Alternative cycle: slip velocity in time and step coordinates	Visible panels a,b of Supplementary Fig. 2; caption additionally mentions absent c,d	<code>python3 scripts/panel.py S2a --data</code>	<code>python3 scripts/plot.py S2a</code>	not reproduced (pending)	Pending completed baseline calculation and final extraction; no result supplied in this snapshot.
S2b	Alternative cycle: slip velocity in time and step coordinates	Visible panels a,b of Supplementary Fig. 2; caption additionally mentions absent c,d	<code>python3 scripts/panel.py S2b --data</code>	<code>python3 scripts/plot.py S2b</code>	not reproduced (pending)	Pending completed baseline calculation and final extraction; no result supplied in this snapshot.

Panel	Quantity	Documentation	Data command	Plot command	Status	Discrepancy
S3a	Slip velocity in time and step coordinates	Supplementary Fig. 3; main Eqs. (1)-(9), Table 1	<code>python3 scripts/panel.py S3a --data</code>	<code>python3 scripts/plot.py S3a</code>	partial	Last complete interval 88.4 yr versus approximately 160 yr in Supplementary Fig. 3a (-45%). All-interval median 88.4 yr. Initial state and friction profiles remain uncertain.
S3b	Cumulative slip profiles	Supplementary Fig. 3; main Eqs. (1)-(9), Table 1	<code>python3 scripts/panel.py S3b --data</code>	<code>python3 scripts/plot.py S3b</code>	partial	Last complete interval 88.4 yr versus approximately 160 yr in Supplementary Fig. 3a (-45%). All-interval median 88.4 yr. Initial state and friction profiles remain uncertain.
S3c	Slip velocity in time and step coordinates	Supplementary Fig. 3; main Eqs. (1)-(9), Table 1	<code>python3 scripts/panel.py S3c --data</code>	<code>python3 scripts/plot.py S3c</code>	partial	Last complete interval 70.5 yr versus approximately 65 yr in Supplementary Fig. 3c (+8%). All-interval median 63.6 yr. Initial state and friction profiles remain uncertain.
S3d	Cumulative slip profiles	Supplementary Fig. 3; main Eqs. (1)-(9), Table 1	<code>python3 scripts/panel.py S3d --data</code>	<code>python3 scripts/plot.py S3d</code>	partial	Last complete interval 70.5 yr versus approximately 65 yr in Supplementary Fig. 3c (+8%). All-interval median 63.6 yr. Initial state and friction profiles remain uncertain.
S4a	Effective normal stress history	Supplementary Fig. 4; main Eqs. (1)-(4), Table 1	<code>python3 scripts/panel.py S4a --data</code>	<code>python3 scripts/plot.py S4a</code>	partial	At 10 km, stress range 16.5 MPa and permeability ratio 9.64. The target is reduced valving with long healing; event sequence and mesh convergence remain uncertain.
S4b	Effective normal stress depth profiles	Supplementary Fig. 4; main Eqs. (1)-(4), Table 1	<code>python3 scripts/panel.py S4b --data</code>	<code>python3 scripts/plot.py S4b</code>	partial	At 10 km, stress range 16.5 MPa and permeability ratio 9.64. The target is reduced valving with long healing; event sequence and mesh convergence remain uncertain.
S4c	Permeability history	Supplementary Fig. 4; main Eqs. (1)-(4), Table 1	<code>python3 scripts/panel.py S4c --data</code>	<code>python3 scripts/plot.py S4c</code>	partial	At 10 km, stress range 16.5 MPa and permeability ratio 9.64. The target is reduced valving with long healing; event sequence and mesh convergence remain uncertain.
S4d	Permeability depth profiles	Supplementary Fig. 4; main Eqs. (1)-(4), Table 1	<code>python3 scripts/panel.py S4d --data</code>	<code>python3 scripts/plot.py S4d</code>	partial	At 10 km, stress range 16.5 MPa and permeability ratio 9.64. The target is reduced valving with long healing; event sequence and mesh convergence remain uncertain.
S4e	Upward fluid flux history	Supplementary Fig. 4; main Eqs. (1)-(4), Table 1	<code>python3 scripts/panel.py S4e --data</code>	<code>python3 scripts/plot.py S4e</code>	partial	At 10 km, stress range 16.5 MPa and permeability ratio 9.64. The target is reduced valving with long healing; event sequence and mesh convergence remain uncertain.
S4f	Upward fluid flux depth profiles	Supplementary Fig. 4; main Eqs. (1)-(4), Table 1	<code>python3 scripts/panel.py S4f --data</code>	<code>python3 scripts/plot.py S4f</code>	partial	At 10 km, stress range 16.5 MPa and permeability ratio 9.64. The target is reduced valving with long healing; event sequence and mesh convergence remain uncertain.

Panel	Quantity	Documentation	Data command	Plot command	Status	Discrepancy
S5a	Slip velocity in time and step coordinates	Supplementary Fig. 5; main Eqs. (1)-(9), Table 1	<code>python3 scripts/panel.py S5a --data</code>	<code>python3 scripts/plot.py S5a</code>	partial	Last complete interval 95.1 yr versus approximately 160 yr in Supplementary Fig. 5a (-41%). All-interval median 95.2 yr. Initial state and friction profiles remain uncertain.
S5b	Cumulative slip profiles	Supplementary Fig. 5; main Eqs. (1)-(9), Table 1	<code>python3 scripts/panel.py S5b --data</code>	<code>python3 scripts/plot.py S5b</code>	partial	Last complete interval 95.1 yr versus approximately 160 yr in Supplementary Fig. 5a (-41%). All-interval median 95.2 yr. Initial state and friction profiles remain uncertain.
S5c	Slip velocity in time and step coordinates	Supplementary Fig. 5; main Eqs. (1)-(9), Table 1	<code>python3 scripts/panel.py S5c --data</code>	<code>python3 scripts/plot.py S5c</code>	partial	Last complete interval 174 yr versus approximately 150 yr in Supplementary Fig. 5c (+16%). All-interval median 179 yr. Initial state and friction profiles remain uncertain.
S5d	Cumulative slip profiles	Supplementary Fig. 5; main Eqs. (1)-(9), Table 1	<code>python3 scripts/panel.py S5d --data</code>	<code>python3 scripts/plot.py S5d</code>	partial	Last complete interval 174 yr versus approximately 150 yr in Supplementary Fig. 5c (+16%). All-interval median 179 yr. Initial state and friction profiles remain uncertain.
S6a	Effective normal stress history	Supplementary Fig. 6; main Eqs. (1)-(4), Table 1	<code>python3 scripts/panel.py S6a --data</code>	<code>python3 scripts/plot.py S6a</code>	partial	At 10 km, stress range 6.82 MPa and permeability ratio 1.77. The target is reduced valving with long healing; event sequence and mesh convergence remain uncertain.
S6b	Effective normal stress depth profiles	Supplementary Fig. 6; main Eqs. (1)-(4), Table 1	<code>python3 scripts/panel.py S6b --data</code>	<code>python3 scripts/plot.py S6b</code>	partial	At 10 km, stress range 6.82 MPa and permeability ratio 1.77. The target is reduced valving with long healing; event sequence and mesh convergence remain uncertain.
S6c	Permeability history	Supplementary Fig. 6; main Eqs. (1)-(4), Table 1	<code>python3 scripts/panel.py S6c --data</code>	<code>python3 scripts/plot.py S6c</code>	partial	At 10 km, stress range 6.82 MPa and permeability ratio 1.77. The target is reduced valving with long healing; event sequence and mesh convergence remain uncertain.
S6d	Permeability depth profiles	Supplementary Fig. 6; main Eqs. (1)-(4), Table 1	<code>python3 scripts/panel.py S6d --data</code>	<code>python3 scripts/plot.py S6d</code>	partial	At 10 km, stress range 6.82 MPa and permeability ratio 1.77. The target is reduced valving with long healing; event sequence and mesh convergence remain uncertain.
S6e	Upward fluid flux history	Supplementary Fig. 6; main Eqs. (1)-(4), Table 1	<code>python3 scripts/panel.py S6e --data</code>	<code>python3 scripts/plot.py S6e</code>	partial	At 10 km, stress range 6.82 MPa and permeability ratio 1.77. The target is reduced valving with long healing; event sequence and mesh convergence remain uncertain.
S6f	Upward fluid flux depth profiles	Supplementary Fig. 6; main Eqs. (1)-(4), Table 1	<code>python3 scripts/panel.py S6f --data</code>	<code>python3 scripts/plot.py S6f</code>	partial	At 10 km, stress range 6.82 MPa and permeability ratio 1.77. The target is reduced valving with long healing; event sequence and mesh convergence remain uncertain.




Figure 1: Independent outputs corresponding to F1. F1a: Geometry schematic and assumed friction profiles; F1b: Permeability versus effective normal stress; F1c: Healing and slip-enhancement limiting solutions; F1d: Steady pressure, stress, and permeability profiles. Units and color scales are shown on the panels. Parameter files and selection rules are specified in the provenance sidecars. Panel F1a is a new schematic, not a simulated reproduction. Comparison target: Zhu et al. [1].




Figure 2: Independent outputs corresponding to F2. F2a: Slip velocity in time and step coordinates; F2b: Cumulative slip profiles. Units and color scales are shown on the panels. Parameter files and selection rules are specified in the provenance sidecars. Pending and absent here: F2c, F2d. Cases: reference ($T=1e+08$ s; fixed pressure). These panels are partial comparisons. Comparison target: Zhu et al. [1].




Figure 3: Independent outputs corresponding to F5. F5a: Slip velocity versus time; F5b: Slip velocity versus accepted step; F5c: Effective normal stress; F5d: Permeability. Units and color scales are shown on the panels. Parameter files and selection rules are specified in the provenance sidecars. Cases: short ($T=1\text{e}+07$ s; coupled pressure). These panels are partial comparisons. Comparison target: Zhu et al. [1].




Figure 4: Independent outputs corresponding to S3. S3a: Slip velocity in time and step coordinates; S3b: Cumulative slip profiles; S3c: Slip velocity in time and step coordinates; S3d: Cumulative slip profiles. Units and color scales are shown on the panels. Parameter files and selection rules are specified in the provenance sidecars. Cases: long ($T=1e+09$ s; coupled pressure), long_reference ($T=1e+09$ s; fixed pressure). These panels are partial comparisons. Comparison target: Zhu et al. [1].




Figure 5: Independent outputs corresponding to S4. S4a: Effective normal stress history; S4b: Effective normal stress depth profiles; S4c: Permeability history; S4d: Permeability depth profiles; S4e: Upward fluid flux history; S4f: Upward fluid flux depth profiles. Units and color scales are shown on the panels. Parameter files and selection rules are specified in the provenance sidecars. Cases: long ($T=1\text{e}+09$ s; coupled pressure). These panels are partial comparisons. Comparison target: Zhu et al. [1].




Figure 6: Independent outputs corresponding to S5. S5a: Slip velocity in time and step coordinates; S5b: Cumulative slip profiles; S5c: Slip velocity in time and step coordinates; S5d: Cumulative slip profiles. Units and color scales are shown on the panels. Parameter files and selection rules are specified in the provenance sidecars. Cases: verylong ($T=1e+10$ s; coupled pressure), verylong_reference ($T=1e+10$ s; fixed pressure). These panels are partial comparisons. Comparison target: Zhu et al. [1].




Figure 7: Independent outputs corresponding to S6. S6a: Effective normal stress history; S6b: Effective normal stress depth profiles; S6c: Permeability history; S6d: Permeability depth profiles; S6e: Upward fluid flux history; S6f: Upward fluid flux depth profiles. Units and color scales are shown on the panels. Parameter files and selection rules are specified in the provenance sidecars. Cases: verylong ($T=1e+10$ s; coupled pressure). These panels are partial comparisons. Comparison target: Zhu et al. [1].

6 Reproduction and remaining work

The full project command builds and tests the C++ solver, runs all twelve cases, extracts every panel, compiles the final report, and verifies its source bundle:

```
python3 -m pip install -r requirements.txt
python3 scripts/reproduce.py
```

That full-duration run is ongoing at this snapshot. This interim report is regenerated from completed, audited case metadata and generated panel packages:

```
python3 scripts/interim_report.py
```

The command compiles `report/interim.pdf`, packages its standalone LaTeX source and all included figures, and verifies compilation of the extracted bundle. It records commands, exit codes, input hashes, and output hashes in `data/interim_report_verification.json`. The source archive is `report/interim-latex-source.zip`; the unexpanded source is already a single file, `report/interim.tex`. All scientific arrays and their independent generation commands are available in the repository.

Completion still requires the remaining calculations, the pending panels, common-duration validation comparisons, the full scientific report, visual and numerical artifact review, execution of the final regeneration procedure, and publication of those final deliverables. This snapshot makes the completed scientific results reviewable without declaring that work finished.

References

- [1] Zhu, W., K. L. Allison, E. M. Dunham, and Y. Yang (2020). Fault valving and pore pressure evolution in simulations of earthquake sequences and aseismic slip. *Nature Communications*, 11, 4833. doi:10.1038/s41467-020-18598-z. Includes the published Supplementary Information.
- [2] Allison, K. L., and E. M. Dunham (2018). Earthquake cycle simulations with rate-and-state friction and power-law viscoelasticity. *Tectonophysics*, 733, 232–256. doi:10.1016/j.tecto.2017.10.021.
- [3] Kennedy, C. A., and M. H. Carpenter (2001). Additive Runge–Kutta schemes for convection–diffusion–reaction equations. NASA/TM-2001-211038, Appendix C. [NASA technical report](#).