

Lecture 7 Further Edge Detection

COMP3204 & COMP6223 Computer Vision

What better ways are there to detect edges?




Book
pp
153 -
172

Department of
Electronics and
Computer Science

UNIVERSITY OF
Southampton
School of Electronics
and Computer Science



(a) original image



(b) Sobel edge magnitude



(c) thresholded magnitude

Applying the Sobel Operator



(a) Gaussian
smoothing



(b) Sobel edge
detection




(c) non-maximum
suppression




(d) hysteresis
thresholding


Stages in Canny Edge Detection



Interpolation in Non-Maximum Suppression



Hysteresis Thresholding Transfer Function



Action of Non-Maximum Suppression and Hysteresis Thresholding



(a) hysteresis thresholding,
upper level = 40,
lower level = 10




(b) uniform thresholding,
level = 40



(c) uniform thresholding,
level = 10

Comparing Hysteresis Thresholding with Uniform Thresholding



(a) original image




(b) Canny




(c) Sobel

Comparing Canny with Sobel



| | | | | | | | | | |
|--|----|----|---|----|---|----|---|----|---|
| <table><tr><td>0</td><td>-1</td><td>0</td></tr><tr><td>-1</td><td>4</td><td>-1</td></tr><tr><td>0</td><td>-1</td><td>0</td></tr></table> | 0 | -1 | 0 | -1 | 4 | -1 | 0 | -1 | 0 |
| 0 | -1 | 0 | | | | | | | |
| -1 | 4 | -1 | | | | | | | |
| 0 | -1 | 0 | | | | | | | |
| Laplacian Edge Detection Operator | | | | | | | | | |

| | |
|--|---|
| $p = \begin{bmatrix} 1 & 2 & 3 & 4 & 1 & 1 & 2 & 1 \\ 2 & 2 & 3 & 0 & 1 & 2 & 2 & 1 \\ 3 & 0 & 38 & 39 & 37 & 36 & 3 & 0 \\ 4 & 1 & 40 & 44 & 41 & 42 & 2 & 1 \\ 1 & 2 & 43 & 44 & 40 & 39 & 1 & 3 \\ 2 & 0 & 39 & 41 & 42 & 40 & 2 & 0 \\ 1 & 2 & 0 & 2 & 2 & 3 & 1 & 1 \\ 0 & 2 & 1 & 3 & 1 & 0 & 4 & 2 \end{bmatrix}$ <p>(a) image data</p> | $L = \begin{bmatrix} 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & -31 & -47 & -36 & -32 & 0 & 0 \\ 0 & -44 & 70 & 37 & 31 & 60 & -28 & 0 \\ 0 & -42 & 34 & 12 & 1 & 50 & -39 & 0 \\ 0 & -37 & 47 & 8 & -6 & 33 & -42 & 0 \\ 0 & -45 & 72 & 37 & 45 & 74 & -34 & 0 \\ 0 & 5 & -44 & -38 & -40 & -31 & -6 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix}$ <p>(b) after Laplacian operator</p> |
| Edge Detection via the Laplacian Operator | |




LoG(4, 31)




Shape of Laplacian of Gaussian Operator


Zero Crossing Detection

- Basic – straight comparison
- Advanced




$IF \left(\max(1, 2, 3, 4) > 0 \wedge \min(1, 2, 3, 4) < 0 \right) \quad THEN \quad f(x, y) = \text{edge}$


| | | |
|---|---|---|
|  |  |  |
| (a) face image | (b) 11×11 LoG | (c) 15×15 LoG |
| Marr-Hildreth Edge Detection | | |




(a) original image



(b) first order



(c) Prewitt




(d) Sobel



(e) Laplacian



(f) Marr-Hildreth



(g) Canny



(h) Spacek

Comparison of Edge Detection Operators