

Columns

.col-xs-	Always	Full
.col-sm-	> 768px	750 wide
.col-md-	> 992px	970 wide
.col-lg-	> 1200px	1170 wide

List classes

.list-inline

.list-unstyled

.dl-horizontal

.list-group

.list-group-item

.list-group-item-heading

.list-group-item-text

.list-group-item-info

.list-group-item-warning

.list-group-item-danger

.list-group-item-success

```
<dl class="dl-horizontal">...</dl>
```

```
<ul class="list-unstyled">...</ul>
```

```
<ul class="list-inline">...</ul>
```

```
<ul class="list-group">
```

```
<li class="list-group-item">...</li>
```

```
<li class="list-group-item">...</li>
```

```
</ul>
```

Nav classes

.nav .nav-tabs

.nav-pills .nav-tabs-justified

.nav-divider .nav-stacked

```
<ul class="nav nav-tabs" role="tablist">
```

```
<li class="active">*</li>
```

```
<li><a href="#">...</a></li>
```

```
<li><a href="#">...</a></li>
```

```
</ul>
```

```
*<a href="#" data-toggle="tab">...</a>
```

Navbar classes

.navbar .navbar-left

.navbar-brand .navbar-right

.navbar-default .navbar-btn

.navbar-fixed-top .navbar-nav

.navbar-static-top .navbar-link

.navbar-fixed-bottom .navbar-text

.navbar-collapse .navbar-form

.navbar-inverse .navbar-toggle

```
<div class="navbar-header">
  <button class="navbar-toggle">
    <span class="sr-only">...</span>
  </button>
  <a class="navbar-brand" ...>...</a>
</div>
```

Nav Utility classes

.pagination .breadcrumb

.pagination-sm .pager

.pagination-lg .fade

.active .in

```
<ol class="breadcrumb">
  <li><a href="#">...</a></li>
  <li><a href="#">...</a></li>
  <li class="active">...</li>
</ol>
```

```
<ul class="pagination">
  <li><a href="#">1</a></li>
  <li><a href="#">2</a></li>
  <li><a href="#">3</a></li>
  <li><a href="#">4</a></li>
  <li><a href="#">5</a></li>
</ul>
```

Tab classes

.tab-content

```
<div class="tab-content">
  <div class="tab-pane active">...</div>
  <div class="tab-pane">...</div>
  <div class="tab-pane">...</div>
</div>
```

Media classes

.media .media-list

.media-heading .media-body

.media-object

```
<div class="media">
  <a class="pull-left" href="#">
    <img class="media-object" ... >
  </a>
  <div class="media-body">
    <h4 class="media-heading">...</h4>
  </div>
</div>
```

Progress classes

.progress

.progress-bar

.progress-striped

.progress-bar-striped

.progress-bar-info

.progress-bar-warning

.progress-bar-danger

.progress-bar-success

```
<div class="progress">
  <div class="progress-bar"
    role="progressbar"
    aria-valuenow="60"
    aria-valuemin="0"
    aria-valuemax="100">

    <span class="sr-only">...</span>
  </div>
</div>
```

General Offset classes

.margin-[xs|sm|md|lg]-0

.margin-[xs|sm|md|lg]-6

.margin-[xs|sm|md|lg]-9

.margin-[xs|sm|md|lg]-12

.margin-[xs|sm|md|lg]-15

.margin-[xs|sm|md|lg]-18



By Aurelius Wendelken

(hamburg)

cheatography.com/hamburg/

twitter.com/webtobesocial

Published 28th July, 2014.

Last updated 27th November, 2014.

Page 1 of 7.

Sponsored by **Readability-Score.com**

Measure your website readability!

<https://readability-score.com>

General Offset classes (cont)

.margin-[xs|sm|md|lg]-24

```
<div class="margin-xs-24">
  <p>...</p>
</div>
```

Top Offset classes

.margin-top-[xs|sm|md|lg]-0

.margin-top-[xs|sm|md|lg]-6

.margin-top-[xs|sm|md|lg]-9

.margin-top-[xs|sm|md|lg]-12

.margin-top-[xs|sm|md|lg]-15

.margin-top-[xs|sm|md|lg]-18

.margin-top-[xs|sm|md|lg]-24

```
<div class="margin-top-xs-24">
  <p>...</p>
</div>
```

Right Offset classes

.margin-right-[xs|sm|md|lg]-0

.margin-right-[xs|sm|md|lg]-6

.margin-right-[xs|sm|md|lg]-9

.margin-right-[xs|sm|md|lg]-12

.margin-right-[xs|sm|md|lg]-15

.margin-right-[xs|sm|md|lg]-18

.margin-right-[xs|sm|md|lg]-24

```
<div class="margin-right-xs-24">
  <p>...</p>
</div>
```

Bottom Offset classes

.margin-bottom-[xs|sm|md|lg]-0

.margin-bottom-[xs|sm|md|lg]-6

.margin-bottom-[xs|sm|md|lg]-9

.margin-bottom-[xs|sm|md|lg]-12

.margin-bottom-[xs|sm|md|lg]-15

.margin-bottom-[xs|sm|md|lg]-18

.margin-bottom-[xs|sm|md|lg]-24

```
<div class="margin-bottom-xs-24">
  <p>...</p>
</div>
```

Left Offset classes

.margin-left-[xs|sm|md|lg]-0

.margin-left-[xs|sm|md|lg]-6

.margin-left-[xs|sm|md|lg]-9

.margin-left-[xs|sm|md|lg]-12

.margin-left-[xs|sm|md|lg]-15

.margin-left-[xs|sm|md|lg]-18

.margin-left-[xs|sm|md|lg]-24

```
<div class="margin-left-xs-24">
  <p>...</p>
</div>
```

General Padding classes

.padding-[xs|sm|md|lg]-0

.padding-[xs|sm|md|lg]-6

.padding-[xs|sm|md|lg]-9

.padding-[xs|sm|md|lg]-12

General Padding classes (cont)

.padding-[xs|sm|md|lg]-15

.padding-[xs|sm|md|lg]-18

.padding-[xs|sm|md|lg]-24

```
<div class="col-xs-12">
  <p class="padding-xs-24">...</p>
</div>
```

Top Padding classes

.padding-top-[xs|sm|md|lg]-0

.padding-top-[xs|sm|md|lg]-6

.padding-top-[xs|sm|md|lg]-9

.padding-top-[xs|sm|md|lg]-12

.padding-top-[xs|sm|md|lg]-15

.padding-top-[xs|sm|md|lg]-18

.padding-top-[xs|sm|md|lg]-24

```
<div class="col-xs-12">
  <p class="padding-top-xs-24">...</p>
</div>
```

Right Padding classes

.padding-right-[xs|sm|md|lg]-0

.padding-right-[xs|sm|md|lg]-6

.padding-right-[xs|sm|md|lg]-9

.padding-right-[xs|sm|md|lg]-12

.padding-right-[xs|sm|md|lg]-15

.padding-right-[xs|sm|md|lg]-18

.padding-right-[xs|sm|md|lg]-24

```
<div class="col-xs-12">
  <p class="padding-right-xs-24">...</p>
</div>
```



By **Aurelius Wendelken**
(hamburg)
cheatography.com/hamburg/
twitter.com/webtobesocial

Published 28th July, 2014.
Last updated 27th November, 2014.
Page 2 of 7.

Sponsored by **Readability-Score.com**
Measure your website readability!
<https://readability-score.com>

Bottom Padding classes

.padding-bottom-[xs|sm|md|lg]-0

.padding-bottom-[xs|sm|md|lg]-6

.padding-bottom-[xs|sm|md|lg]-9

.padding-bottom-[xs|sm|md|lg]-12

.padding-bottom-[xs|sm|md|lg]-15

.padding-bottom-[xs|sm|md|lg]-18

.padding-bottom-[xs|sm|md|lg]-24

```
<div class="col-xs-12">
  <p class="padding-bottom-xs-6"></p>
</div>
```

Left Padding classes

.padding-left-[xs|sm|md|lg]-0

.padding-left-[xs|sm|md|lg]-6

.padding-left-[xs|sm|md|lg]-9

.padding-left-[xs|sm|md|lg]-12

.padding-left-[xs|sm|md|lg]-15

.padding-left-[xs|sm|md|lg]-18

.padding-left-[xs|sm|md|lg]-24

```
<div class="col-xs-12">
  <p class="padding-left-xs-24">...</p>
</div>
```

Wrapper classes

.container **.container-fluid**

.row

```
<div class="container">
  <div class="row">
    <div class="col-xs-4">...</div>
    <div class="col-xs-8">...</div>
  </div>
</div>
```

```
<div class="container-fluid">
  <div class="row">
    <div class="col-sm-12">...</div>
  </div>
</div>
```

Position classes

.pos-static-[xs|sm|md|lg]

.pos-relative-[xs|sm|md|lg]

.pos-absolute-[xs|sm|md|lg]

.pos-fixed-[xs|sm|md|lg]

```
<div class="pos-relative-xs">
  <div class="pos-absolute-xs">...</div>
</div>
```

Text Weight classes

.text-normal-[xs|sm|md|lg]

.text-strong-[xs|sm|md|lg]

```
<p class="text-normal">...</p>
<li class="text-strong">...</li>
```

Header classes and Tags

.h1, <h1> **.h2**, <h2>

.h3, <h3> **.h4**, <h4>

.h5, <h5> **.h6**, <h6>

```
<h1>...</h1>
<p class="h3">...</p>
```

Layout Helper classes

.pull-left-[xs|sm|md|lg]

.pull-right-[xs|sm|md|lg]

```
<div class="pull-left">...</div>
<div class="pull-right-sm">...</div>
```

Table classes

.table **.table-responsive**

.table-condensed **.table-striped**

.table-bordered **.table-hover**

```
<table class="table">...</table>
```

```
<div class="table-responsive">
  <table class="table">...</table>
</div>
```

Table Helper classes

.active **.info**

.warning **.danger**

.success

```
<tr class="info">
  <th class="active">...</th>
  <th class="success">...</th>
  <td class="warning">...</td>
  <td class="danger">...</td>
</tr>
```

Text Utility classes

.text-info **.text-lowercase**

.text-muted **.text-uppercase**

.text-warning **.text-capitalize**

.text-danger **.text-nowrap**

.text-success **.text-primary**

.lead **.mark**

```
<p class="text-info">...</p>
<p class="text-muted">...</p>
<p class="text-primary">...</p>
<p class="text-success">...</p>
<p class="text-warning">...</p>
<p class="text-danger">...</p>
<p class="text-lowercase">...</p>
<p class="text-uppercase">...</p>
<p class="text-capitalize">...</p>
```



By **Aurelius Wendelken**

(hamburg)

cheatography.com/hamburg/

twitter.com/webtobesocial

Published 28th July, 2014.

Last updated 27th November, 2014.

Page 3 of 7.

Sponsored by **Readability-Score.com**

Measure your website readability!

<https://readability-score.com>

Text Helper classes

.text-left .text-right
.text-center .text-justify

```
<p class="text-left">...</p>
<p class="text-right">...</p>
<p class="text-center">...</p>
<p class="text-justify">...</p>
```

Label classes

.label .label-default
.label-info .label-warning
.label-success .label-danger
.label-primary

```
<span class="label label-info" ... />
<span class="label label-default" ... />
```

Modal classes

.modal
.modal-open
.modal-dialog
.modal-header
.modal-content
.modal-footer
.modal-title
.modal-body
.modal-sm
.modal-lg
.modal-backdrop
.modal-scrollbar-measure

```
<div id="target" class="modal fade">
  <div class="modal-dialog">
    <div class="modal-content">...</div>
  </div>
</div>
```

```
<div class="modal-header">...</div>
<div class="modal-body">...</div>
<div class="modal-footer">...</div>
```

Carousel classes

.carousel .carousel-control
.carousel-inner .carousel-indicators

```
.carousel-caption
<div class="carousel-inner">
  <div class="item active">
    
    <div class="carousel-caption" ... />
  </div>
</div>
```

Carousel Helper classes

.left .right
.prev .next
.item .active
.icon-prev .icon-next

```
<a class="left carousel-control">...</a>
<a class="right carousel-control">...</a>
```

Modal Helper classes

.fade .in
.close
<button class="close" ... />
<button class="btn btn-primary" data-toggle="modal" data-target="#target">...</button>

Embed classes

.embed-responsive
.embed-responsive-item
.embed-responsive-4by3
.embed-responsive-16by9
tbd

Img classes

.img-responsive .caption
.img-rounded .jumbotron
.img-thumbnail .thumbnail
.img-circle

```
<img class="img-responsive" ... >
<img class="img-rounded" ... >
<img class="img-circle" ... >
<img class="img-thumbnail" ... >
```

Popover classes

.popover .popover-content
.popover-title

```
<div class="popover" role="tooltip">
  <div class="arrow">...</div>
  <h3 class="popover-title">...</h3>
  <div class="popover-content">...</div>
</div>
```

Popover Helper classes

.top .right .bottom
.left .arrow

```
<button type="button"
  class="btn btn-lg btn-danger"
  data-toggle="popover" title="..."
  data-content="...">...</button>
```

Tooltip classes

.tooltip .tooltip-inner
.tooltip-arrow

```
<div class="tooltip top" role="tooltip">
  <div class="tooltip-arrow"></div>
  <div class="tooltip-inner">...</div>
</div>
```

Tooltip Helper classes

.in .top .right
.bottom .left .top-left
.top-right .bottom-left .bottom-right

```
<button type="button"
  class="btn btn-default"
  data-toggle="tooltip" title="..."
  data-placement="left">...</button>
```



Screenreader classes

.sr-only .sr-only-focusable

Cite classes

.blockquote-reverse

```
<blockquote class="blockquote-reverse">
  <p>...</p>
</blockquote>
```

Well classes

.well .well-sm

.well-lg .close

```
<div class="well">...</div>
<div class="well well-sm">...</div>
<div class="well well-lg">...</div>
```

Column Visibility classes

.hidden-[xs|sm|md|lg]

.visible-[xs|sm|md|lg]

.visible-[xs|sm|md|lg]-block

.visible-[xs|sm|md|lg]-inline

.visible-[xs|sm|md|lg]-inline-block

```
<div class="visible-xs-block"> ...</div>
<div class="visible-lg-block">...</div >
<div class="hidden-lg">...</div >
```

Column Helper classes

.col-[xs|sm|md|lg]-[push|pull|offset]-0

.col-[xs|sm|md|lg]-[push|pull|offset]-1

.col-[xs|sm|md|lg]-[push|pull|offset]-2

.col-[xs|sm|md|lg]-[push|pull|offset]-3

.col-[xs|sm|md|lg]-[push|pull|offset]-4

Column Helper classes (cont)

.col-[xs|sm|md|lg]-[push|pull|offset]-5

.col-[xs|sm|md|lg]-[push|pull|offset]-6

.col-[xs|sm|md|lg]-[push|pull|offset]-7

.col-[xs|sm|md|lg]-[push|pull|offset]-8

.col-[xs|sm|md|lg]-[push|pull|offset]-9

.col-[xs|sm|md|lg]-[push|pull|offset]-10

.col-[xs|sm|md|lg]-[push|pull|offset]-11

.col-[xs|sm|md|lg]-[push|pull|offset]-12

```
<div class="col-md-9 col-md-push-3" ... />
<div class="col-md-3 col-md-pull-9" ... />
```

Grid classes

.col-[xs|sm|md|lg]-1

.col-[xs|sm|md|lg]-2

.col-[xs|sm|md|lg]-3

.col-[xs|sm|md|lg]-4

.col-[xs|sm|md|lg]-5

.col-[xs|sm|md|lg]-6

.col-[xs|sm|md|lg]-7

.col-[xs|sm|md|lg]-8

.col-[xs|sm|md|lg]-9

.col-[xs|sm|md|lg]-10

.col-[xs|sm|md|lg]-11

.col-[xs|sm|md|lg]-12

```
<div class="col-xs-6 col-md-4">...</div>
<div class="col-xs-6 col-md-4">...</div>
<div class="col-xs-6 col-md-4">...</div>
```

Default Background classes

.bg-info .bg-search

.bg-warning .bg-default

.bg-danger .bg-primary

.bg-success .bg-secondary

```
<p class="bg-primary">...</p>
<p class="bg-success">...</p>
<p class="bg-info">...</p>
<p class="bg-warning">...</p>
<p class="bg-danger">...</p>
```

Background Color classes

.bg-white-[xs|sm|md|lg]

.bg-default-[xs|sm|md|lg]

.bg-secondary-[xs|sm|md|lg]

<div class="bg-white-xs">...</div>

Button classes

.btn .btn-toolbar

.btn-warning .btn-secondary

.btn-info .btn-primary

.btn-danger .btn-default

.btn-success .btn-link

```
<button class="btn btn-info">...</button>
<button class="btn btn-link">...</button>
```

```
<div class="btn-toolbar" role="toolbar">
  <div class="btn-group">...</div>
  <div class="btn-group">...</div>
  <div class="btn-group">...</div>
</div>
```



By **Aurelius Wendelken**
(hamburg)
cheatography.com/hamburg/
twitter.com/webtobesocial

Published 28th July, 2014.
Last updated 27th November, 2014.
Page 5 of 7.

Sponsored by **Readability-Score.com**
Measure your website readability!
<https://readability-score.com>

Button Helper classes

<code>.btn-xs</code>	<code>.btn-group-xs</code>
<code>.btn-sm</code>	<code>.btn-group-sm</code>
<code>.btn-lg</code>	<code>.btn-group-lg</code>
<code>.btn-block</code>	<code>.btn-group-justified</code>
<code>.btn-group</code>	<code>.btn-group-vertical</code>
<code>.disabled</code>	

```
<a class="btn btn-primary btn-lg">...</a>
<a class="btn btn-default btn-sm">...</a>
```

Visibility classes

<code>.hide</code>	<code>.show</code>
<code>.hidden</code>	<code>.invisible</code>
<code>.text-hide</code>	<code>.center-block</code>

```
<h1 class="text-hide">...</h1>
<div class="show">...</div>
<div class="hidden">...</div>
<div class="center-block">...</div>
```

Print classes

<code>.hidden-print</code>
<code>.visible-print-block</code>
<code>.visible-print-inline</code>
<code>.visible-print-inline-block</code>

```
<div class="hidden-print">...</div>
<div class="visible-print-block">...</div>
```

Form classes

<code>.form-control</code>
<code>.form-control-static</code>
<code>.form-control-feedback</code>
<code>.form-horizontal</code>
<code>.form-inline</code>
<code>.input-group-addon</code>
<code>.input-group-btn</code>
<code>.form-group</code>
<code>.input-group</code>

```
<form class="form-inline" role="form">
  <div class="form-group">
    <label class="sr-only">...</label>
    <input ... class="form-control">
  </div>
</form>
```

Form Helper classes

<code>.has-feedback</code>	<code>.has-error</code>
<code>.has-warning</code>	<code>.has-success</code>
<code>.help-block</code>	<code>.sr-only</code>

```
<div class="form-group has-success">
  <label class="control-label">...</label>
  <input ... class="form-control">
</div>
```

Form Utility classes

<code>.input-sm</code>	<code>.input-lg</code>
<code>.form-group-sm</code>	<code>.form-group-lg</code>
<code>.checkbox</code>	<code>.checkbox-inline</code>
<code>.radio</code>	<code>.radio-inline</code>
<code>.disabled</code>	

```
<div class="form-group form-group-lg">
  <label class="control-label">...</label>
  <input ... class="form-control">
</div>
```

Alert classes

<code>.alert</code>	<code>.alert-link</code>
<code>.alert-info</code>	<code>.alert-danger</code>
<code>.alert-warning</code>	<code>.alert-success</code>
<code>.alert-dismissible</code>	

```
<div class="alert alert-info">...</div>
<div class="alert alert-success">...</div>
<div class="alert alert-warning">...</div>
<div class="alert alert-danger">...</div>

<button type="button" class="close"
  data-dismiss="alert">
  <span aria-hidden="true">...</span>
  <span class="sr-only">...</span>
</button>
```

Dropdown classes

<code>.dropdown</code>
<code>.dropdown-menu</code>
<code>.dropdown-menu-left</code>
<code>.dropdown-menu-right</code>
<code>.dropdown-backdrop</code>
<code>.dropdown-toggle</code>
<code>.dropdown-header</code>
<code>.dropup</code>

```
<ul class="dropdown-menu" role="menu">
  <li class="dropdown ">
    <a href="#target"
      data-toggle="dropdown">...</a>
    <ul class="dropdown-menu"
      id="target" role="menu">...</ul>
  </li>
</ul>
```

Panel classes

<code>.panel</code>	<code>.panel-title</code>
<code>.panel-info</code>	<code>.panel-body</code>
<code>.panel-heading</code>	<code>.panel-footer</code>
<code>.panel-collapse</code>	<code>.panel-default</code>
<code>.panel-group</code>	<code>.panel-primary</code>
<code>.panel-warning</code>	<code>.panel-danger</code>



Panel classes (cont)

.panel-success

```
<div id="..." class="panel panel-default">
  <div class="panel-heading">
    <h3 class="panel-title">...</h3>
  </div>
  <div class="panel-body">...</div>
  <div class="panel-footer">...</div>
</div>

<div class="panel panel-info">...</div>
<div class="panel panel-primary">...</div>
<div class="collapse in">...</div>
```

Panel Helper classes

.collapse

.in

collapsing

.fade

```
<button class="btn btn-danger"
  data-toggle="collapse"
  data-target="#target">...</button>

<div id="target">...</div>
```

Code classes

.pre-scrollable

```
<pre class="pre-scrollable">...</pre>
```

Page classes

.page-header

```
<div class="page-header">
  <h1>...</h1>
</div>
```



By **Aurelius Wendelken**
(hamburg)
cheatography.com/hamburg/
twitter.com/webtobesocial

Published 28th July, 2014.
Last updated 27th November, 2014.
Page 7 of 7.

Sponsored by **Readability-Score.com**
Measure your website readability!
<https://readability-score.com>